

milchstore@colts.dreamhost.com's password:

```
  | |
 _| _ \ | _|(_-<
 \_| \_/_| \_| \_/_
```

Welcome to colts.dreamhost.com

Any malicious and/or unauthorized activity is strictly forbidden.
All activity may be logged by DreamHost Web Hosting.

```
[colts]$ ls
Maildir  backup-20100225100813.sql      logs          milchstore.tar
__MACOSX backup-20100225100813.sql.zip milchstore.com
[colts]$ vim installscript
[colts]$ ls
Maildir  backup-20100225100813.sql      installscript milchstore.com
__MACOSX backup-20100225100813.sql.zip logs          milchstore.tar
[colts]$ chmod +x installscript
[colts]$ ./installscript
--07:39:03-- http://ca3.php.net/get/php-5.2.10.tar.gz/from/us2.php.net/mirror
              => `mirror'
Resolving ca3.php.net... 216.235.13.26
Connecting to ca3.php.net|216.235.13.26|:80... connected.
HTTP request sent, awaiting response... 302 Found
Location: http://us2.php.net/distributions/php-5.2.10.tar.gz [following]
--07:39:03-- http://us2.php.net/distributions/php-5.2.10.tar.gz
              => `php-5.2.10.tar.gz'
Resolving us2.php.net... 64.71.164.5, 2001:470:0:b9::4047:a405
Connecting to us2.php.net|64.71.164.5|:80... connected.
HTTP request sent, awaiting response... 200 OK
Length: 11,433,921 (11M) [application/x-gzip]

100%[=====>] 11,433,921      3.61M/s      ETA 00:00

07:39:07 (3.60 MB/s) - `php-5.2.10.tar.gz' saved [11433921/11433921]

--07:39:07-- http://mirrors.usc.edu/pub/gnu/libiconv/libiconv-1.13.tar.gz
              => `libiconv-1.13.tar.gz'
Resolving mirrors.usc.edu... 68.181.195.4
Connecting to mirrors.usc.edu|68.181.195.4|:80... connected.
HTTP request sent, awaiting response... 200 OK
Length: 4,731,530 (4.5M) [application/x-gzip]

100%[=====>] 4,731,530      7.04M/s

07:39:08 (7.03 MB/s) - `libiconv-1.13.tar.gz' saved [4731530/4731530]

--07:39:08-- http://easynews.dl.sourceforge.net/sourceforge/mcrypt/libmccrypt-2.5.8.tar.gz
              => `libmccrypt-2.5.8.tar.gz'
```

Connecting to easynews.dl.sourceforge.net|69.16.168.245|:80... connected.
HTTP request sent, awaiting response... 302 Found
Location: http://prdownloads.sourceforge.net/mcrypt/libmcrypt-2.5.8.tar.gz?download&failedmirror=easynews.dl.sourceforge.net [following]
--07:39:08-- http://prdownloads.sourceforge.net/mcrypt/libmcrypt-2.5.8.tar.gz?download&failedmirror=easynews.dl.sourceforge.net
=> `libmcrypt-2.5.8.tar.gz?download&failedmirror=easynews.dl.sourceforge.net'
Resolving prdownloads.sourceforge.net... 216.34.181.59
Connecting to prdownloads.sourceforge.net|216.34.181.59|:80... connected.
HTTP request sent, awaiting response... 302 Found
Location: http://cdnetworks-us-1.dl.sourceforge.net/project/mcrypt/Libmcrypt/2.5.8/libmcrypt-2.5.8.tar.gz [following]
--07:39:08-- http://cdnetworks-us-1.dl.sourceforge.net/project/mcrypt/Libmcrypt/2.5.8/libmcrypt-2.5.8.tar.gz
=> `libmcrypt-2.5.8.tar.gz'
Resolving cdnetworks-us-1.dl.sourceforge.net... 65.49.46.187
Connecting to cdnetworks-us-1.dl.sourceforge.net|65.49.46.187|:80... connected.
HTTP request sent, awaiting response... 200 OK
Length: 1,335,178 (1.3M) [application/x-gzip]

100%[=====>] 1,335,178 1.76M/s

07:39:09 (1.76 MB/s) - `libmcrypt-2.5.8.tar.gz' saved [1335178/1335178]

--07:39:09-- ftp://xmlsoft.org/libxml2/libxml2-2.7.3.tar.gz
=> `libxml2-2.7.3.tar.gz'

Resolving xmlsoft.org... 194.199.20.115
Connecting to xmlsoft.org|194.199.20.115|:21... connected.
Logging in as anonymous ... Logged in!
==> SYST ... done. ==> PWD ... done.
==> TYPE I ... done. ==> CWD /libxml2 ... done.
==> PASV ... done. ==> RETR libxml2-2.7.3.tar.gz ... done.
Length: 4,789,450 (4.6M) (unauthoritative)

100%[=====>] 4,789,450 1.23M/s ETA 00:00

07:39:16 (995.16 KB/s) - `libxml2-2.7.3.tar.gz' saved [4789450]

--07:39:16-- ftp://xmlsoft.org/libxml2/libxslt-1.1.24.tar.gz
=> `libxslt-1.1.24.tar.gz'

Resolving xmlsoft.org... 194.199.20.115
Connecting to xmlsoft.org|194.199.20.115|:21... connected.
Logging in as anonymous ... Logged in!
==> SYST ... done. ==> PWD ... done.
==> TYPE I ... done. ==> CWD /libxml2 ... done.
==> PASV ... done. ==> RETR libxslt-1.1.24.tar.gz ... done.
Length: 3,363,961 (3.2M) (unauthoritative)

100%[=====>] 3,363,961 897.67K/s ETA 00:00

07:39:23 (787.45 KB/s) - `libxslt-1.1.24.tar.gz' saved [3363961]

--07:39:23-- http://internap.dl.sourceforge.net/sourceforge/mhash/mhash-0.9.9.9.tar.gz

=> `mhash-0.9.9.9.tar.gz'

Resolving internap.dl.sourceforge.net... 74.201.26.4

Connecting to internap.dl.sourceforge.net|74.201.26.4|:80... connected.

HTTP request sent, awaiting response... 302 Moved Temporarily

Location: http://prdownloads.sourceforge.net/mhash/mhash-0.9.9.9.tar.gz?download&failedmirror=internap.dl.sourceforge.net [following]

--07:39:24-- http://prdownloads.sourceforge.net/mhash/mhash-0.9.9.9.tar.gz?download&failedmirror=internap.dl.sourceforge.net

=> `mhash-0.9.9.9.tar.gz?download&failedmirror=internap.dl.sourceforge.net'

Resolving prdownloads.sourceforge.net... 216.34.181.59

Connecting to prdownloads.sourceforge.net|216.34.181.59|:80... connected.

HTTP request sent, awaiting response... 302 Found

Location: http://hivelocity.dl.sourceforge.net/project/mhash/mhash/0.9.9.9/mhash-0.9.9.9.tar.gz [following]

--07:39:24-- http://hivelocity.dl.sourceforge.net/project/mhash/mhash/0.9.9.9/mhash-0.9.9.9.tar.gz

=> `mhash-0.9.9.9.tar.gz'

Resolving hivelocity.dl.sourceforge.net... 74.50.111.26

Connecting to hivelocity.dl.sourceforge.net|74.50.111.26|:80... connected.

HTTP request sent, awaiting response... 200 OK

Length: 931,437 (910K) [application/x-gzip]

100%[=====>] 931,437 248.06K/s ETA 00:00

07:39:34 (235.39 KB/s) - `mhash-0.9.9.9.tar.gz' saved [931437/931437]

--07:39:34-- http://www.zlib.net/zlib-1.2.3.tar.gz

=> `zlib-1.2.3.tar.gz'

Resolving www.zlib.net... 69.73.181.135

Connecting to www.zlib.net|69.73.181.135|:80... connected.

HTTP request sent, awaiting response... 200 OK

Length: 496,597 (485K) [application/x-tar]

100%[=====>] 496,597 466.51K/s

07:39:35 (465.80 KB/s) - `zlib-1.2.3.tar.gz' saved [496597/496597]

--07:39:35-- http://curl.haxx.se/download/curl-7.18.2.tar.gz

=> `curl-7.18.2.tar.gz'

Resolving curl.haxx.se... 83.168.254.42

Connecting to curl.haxx.se|83.168.254.42|:80... connected.

HTTP request sent, awaiting response... 200 OK

Length: 2,273,077 (2.2M) [application/x-gzip]

100%[=====>] 2,273,077 899.44K/s

07:39:39 (896.95 KB/s) - `curl-7.18.2.tar.gz' saved [2273077/2273077]

--07:39:39-- http://kent.dl.sourceforge.net/sourceforge/freetype/freetype-2.3.9.tar.gz

=> `freetype-2.3.9.tar.gz'

Resolving kent.dl.sourceforge.net... 212.219.56.167

Connecting to kent.dl.sourceforge.net|212.219.56.167|:80... connected.

HTTP request sent, awaiting response... 302 Found

Location: http://downloads.sourceforge.net/sourceforge/freetype/freetype-2.3.9.tar.gz?download&failedmirror=kent.dl.sourceforge.net [following]

--07:39:39-- http://downloads.sourceforge.net/sourceforge/freetype/freetype-2.3.9.tar.gz?download&failedmirror=kent.dl.sourceforge.net

=> `freetype-2.3.9.tar.gz?download&failedmirror=kent.dl.sourceforge.net'

Resolving downloads.sourceforge.net... 216.34.181.59

Connecting to downloads.sourceforge.net|216.34.181.59|:80... connected.

HTTP request sent, awaiting response... 302 Found

Location: http://voxel.dl.sourceforge.net/project/freetype/freetype2/2.3.9/freetype-2.3.9.tar.gz [following]

--07:39:40-- http://voxel.dl.sourceforge.net/project/freetype/freetype2/2.3.9/freetype-2.3.9.tar.gz

=> `freetype-2.3.9.tar.gz'

Resolving voxel.dl.sourceforge.net... 208.122.62.226

Connecting to voxel.dl.sourceforge.net|208.122.62.226|:80... connected.

HTTP request sent, awaiting response... 200 OK

Length: 1,809,558 (1.7M) [application/x-gzip]

100%[=====>] 1,809,558 1.33M/s

07:39:42 (1.33 MB/s) - `freetype-2.3.9.tar.gz' saved [1809558/1809558]

--07:39:42-- ftp://alpha.gnu.org/pub/gnu/libidn/libidn-0.6.14.tar.gz

=> `libidn-0.6.14.tar.gz'

Resolving alpha.gnu.org... 140.186.70.21

Connecting to alpha.gnu.org|140.186.70.21|:21... connected.

Logging in as anonymous ... Logged in!

==> SYST ... done. ==> PWD ... done.

==> TYPE I ... done. ==> CWD /pub/gnu/libidn ... done.

==> PASV ... done. ==> RETR libidn-0.6.14.tar.gz ... done.

Length: 2,321,402 (2.2M) (unauthoritative)

100%[=====>] 2,321,402 1.29M/s

07:39:50 (1.29 MB/s) - `libidn-0.6.14.tar.gz' saved [2321402]

--07:39:50-- ftp://ftp.cac.washington.edu/imap/old/imap-2004g.tar.Z

=> `imap-2004g.tar.Z'

Resolving ftp.cac.washington.edu... 140.142.11.20

Connecting to ftp.cac.washington.edu|140.142.11.20|:21... connected.

Logging in as anonymous ... Logged in!

==> TYPE I ... done. ==> CWD /imap/old ... done.
==> PASV ... done. ==> RETR imap-2004g.tar.Z ... done.
Length: 2,246,713 (2.1M) (unauthoritative)

100%[=====>] 2,246,713 2.08M/s

07:39:52 (2.08 MB/s) - `imap-2004g.tar.Z' saved [2246713]

--07:39:52-- http://www.openssl.org/source/openssl-0.9.8k.tar.gz
=> `openssl-0.9.8k.tar.gz'

Resolving www.openssl.org... 195.30.6.166
Connecting to www.openssl.org|195.30.6.166|:80... connected.
HTTP request sent, awaiting response... 200 OK
Length: 3,852,259 (3.7M) [application/x-tar]

100%[=====>] 3,852,259 185.19K/s ETA 00:00

07:40:15 (177.98 KB/s) - `openssl-0.9.8k.tar.gz' saved [3852259/3852259]

--07:40:15-- ftp://ftp.openldap.org/pub/OpenLDAP/openldap-release/openldap-2.4.17.tgz
=> `openldap-2.4.17.tgz'

Resolving ftp.openldap.org... 204.152.186.57, 2001:4f8:3:ba:219:21ff:fe2f:68d5
Connecting to ftp.openldap.org|204.152.186.57|:21... connected.
Logging in as anonymous ... Logged in!
==> SYST ... done. ==> PWD ... done.
==> TYPE I ... done. ==> CWD /pub/OpenLDAP/openldap-release ... done.
==> PASV ... done. ==> RETR openldap-2.4.17.tgz ... done.
Length: 5,423,027 (5.2M) (unauthoritative)

100%[=====>] 5,423,027 3.91M/s

07:40:17 (3.91 MB/s) - `openldap-2.4.17.tgz' saved [5423027]

----- Unpacking downloaded archives. This process may take several minutes!

Extracting php-5.2.10...

Done.

Extracting libiconv-1.13...

Done.

Extracting libmcrypt-2.5.8...

Done.

Extracting libxml2-2.7.3...

Done.

Extracting libxslt-1.1.24...

Done.

Extracting mhash-0.9.9.9...

Done.

Extracting zlib-1.2.3...

Done.

Done.
Extracting libidn-0.6.14...
Done.
Extracting imap-2004g...
Done.
Extracting openssl-0.9.8k...
Done.
Extracting freetype-2.3.9...
Done.
Extracting openldap-2.4.17...
Done.
checking for a BSD-compatible install... /usr/bin/install -c
checking whether build environment is sane... yes
checking for a thread-safe mkdir -p... /bin/mkdir -p
checking for gawk... gawk
checking whether make sets \$(MAKE)... yes
checking whether make sets \$(MAKE)... (cached) yes
checking for gcc... gcc
checking for C compiler default output file name... a.out
checking whether the C compiler works... yes
checking whether we are cross compiling... no
checking for suffix of executables...
checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ISO C89... none needed
checking for style of include used by make... GNU
checking dependency style of gcc... none
checking how to run the C preprocessor... gcc -E
checking for a BSD-compatible install... /usr/bin/install -c
checking for strip... /usr/bin/strip
checking build system type... x86_64-unknown-linux-gnu
checking host system type... x86_64-unknown-linux-gnu
checking for ranlib... ranlib
checking whether gcc and cc understand -c and -o together... yes
checking for grep that handles long lines and -e... /bin/grep
checking for egrep... /bin/grep -E
checking for ANSI C header files... yes
checking for sys/types.h... yes
checking for sys/stat.h... yes
checking for stdlib.h... yes
checking for string.h... yes
checking for memory.h... yes
checking for strings.h... yes
checking for inttypes.h... yes
checking for stdint.h... yes
checking for unistd.h... yes
checking minix/config.h usability... no
checking minix/config.h presence... no
checking for minix/config.h... no

checking for ld used by GCC... /usr/bin/ld
checking if the linker (/usr/bin/ld) is GNU ld... yes
checking for shared library path variable... LD_LIBRARY_PATH
checking whether to activate relocatable installation... no
checking how to copy files... cp -p
checking how to make hard links... ln
checking whether ln -s works... yes
checking for a sed that does not truncate output... /bin/sed
checking for fgrep... /bin/grep -F
checking for ld used by gcc... /usr/bin/ld
checking if the linker (/usr/bin/ld) is GNU ld... yes
checking for BSD- or MS-compatible name lister (nm)... /usr/bin/nm -B
checking the name lister (/usr/bin/nm -B) interface... BSD nm
checking the maximum length of command line arguments... 98304
checking whether the shell understands some XSI constructs... yes
checking whether the shell understands "+="... yes
checking for /usr/bin/ld option to reload object files... -r
checking for objdump... objdump
checking how to recognize dependent libraries... pass_all
checking for ar... ar
checking for strip... /usr/bin/strip
checking for ranlib... (cached) ranlib
checking command to parse /usr/bin/nm -B output from gcc object... ok
checking for dlfcn.h... yes
checking for objdir... .libs
checking if gcc supports -fno-rtti -fno-exceptions... no
checking for gcc option to produce PIC... -fPIC -DPIC
checking if gcc PIC flag -fPIC -DPIC works... yes
checking if gcc static flag -static works... yes
checking if gcc supports -c -o file.o... yes
checking if gcc supports -c -o file.o... (cached) yes
checking whether the gcc linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking whether -lc should be explicitly linked in... no
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
checking whether stripping libraries is possible... yes
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries... no
checking for windres... no
checking for simple visibility declarations... yes
checking for shared library run path origin... done
checking for iconv... yes
checking for working iconv... yes
checking for iconv declaration...
extern size_t iconv (iconv_t cd, char * *inbuf, size_t *inbytesleft, char * *outbuf, size_t *outbytesleft);
checking whether NLS is requested... yes
checking for msgfmt... /usr/bin/msgfmt

checking for xgettext... /usr/bin/xgettext
checking for msgmerge... /usr/bin/msgmerge
checking for CFPreferencesCopyAppValue... no
checking for CFLocaleCopyCurrent... no
checking for GNU gettext in libc... yes
checking whether to use NLS... yes
checking where the gettext function comes from... libc
checking for mbstate_t... yes
checking for wchar_t... yes
checking for getc_unlocked... yes
checking for mbrtowc... yes
checking for wcrctomb... yes
checking for mbsinit... yes
checking for setlocale... yes
checking whether <wchar.h> is standalone... yes
checking for memmove... yes
checking for nl_langinfo and CODESET... yes
checking wchar.h usability... yes
checking wchar.h presence... yes
checking for wchar.h... yes
checking for EILSEQ... yes
checking byte ordering... little endian
checking for working alloca.h... yes
checking for alloca... yes
checking for stdlib.h... (cached) yes
checking for string.h... (cached) yes
checking sys/param.h usability... yes
checking sys/param.h presence... yes
checking for sys/param.h... yes
checking for unistd.h... (cached) yes
checking errno.h usability... yes
checking errno.h presence... yes
checking for errno.h... yes
checking sys/socket.h usability... yes
checking sys/socket.h presence... yes
checking for sys/socket.h... yes
checking signal.h usability... yes
checking signal.h presence... yes
checking for signal.h... yes
checking for stdint.h... (cached) yes
checking for wchar.h... (cached) yes
checking stdio.h usability... yes
checking stdio.h presence... yes
checking for stdio.h... yes
checking whether canonicalize_file_name is declared... yes
checking for canonicalize_file_name... yes
checking for getcwd... yes
checking for readlink... yes
checking for pathconf... yes
checking for setenv... yes

checking for complete errno.h... yes
checking whether strerror_r is declared... yes
checking for strerror_r... yes
checking whether strerror_r returns char *... yes
checking whether malloc, realloc, calloc are POSIX compliant... yes
checking for stdlib.h... (cached) yes
checking for GNU libc compatible malloc... yes
checking for long long int... yes
checking for SIGPIPE... yes
checking for stdbool.h that conforms to C99... yes
checking for _Bool... yes
checking for unsigned long long int... yes
checking for C/C++ restrict keyword... __restrict
checking whether clearerr_unlocked is declared... yes
checking whether feof_unlocked is declared... yes
checking whether ferror_unlocked is declared... yes
checking whether fflush_unlocked is declared... yes
checking whether fgets_unlocked is declared... yes
checking whether fputc_unlocked is declared... yes
checking whether fputs_unlocked is declared... yes
checking whether fread_unlocked is declared... yes
checking whether fwrite_unlocked is declared... yes
checking whether getc_unlocked is declared... yes
checking whether getchar_unlocked is declared... yes
checking whether putchar_unlocked is declared... yes
checking for wint_t... yes
checking if environ is properly declared... yes
checking for error_at_line... yes
checking for mbstate_t... (cached) yes
checking for memmove... (cached) yes
checking search.h usability... yes
checking search.h presence... yes
checking for search.h... yes
checking for tsearch... yes
checking for working strerror function... yes
checking for volatile sig_atomic_t... yes
checking for sigprocmask... yes
checking for ssize_t... yes
checking whether stdint.h conforms to C99... no
checking sys/inttypes.h usability... no
checking sys/inttypes.h presence... no
checking for sys/inttypes.h... no
checking sys/bittypes.h usability... yes
checking sys/bittypes.h presence... yes
checking for sys/bittypes.h... yes
checking for bit size of ptrdiff_t... 64
checking for bit size of size_t... 64
checking for bit size of sig_atomic_t... 32
checking for bit size of wchar_t... 32

```
checking whether sig_atomic_t is signed... yes
checking whether wchar_t is signed... yes
checking whether wint_t is signed... no
checking for ptrdiff_t integer literal suffix... l
checking for size_t integer literal suffix... ul
checking for sig_atomic_t integer literal suffix...
checking for wchar_t integer literal suffix...
checking for wint_t integer literal suffix... u
checking for random.h... no
checking for struct random_data... yes
checking whether <wchar.h> is standalone... (cached) yes
configure: creating ./config.status
config.status: creating Makefile
config.status: creating lib/Makefile
config.status: creating srclib/Makefile
config.status: creating src/Makefile
config.status: creating po/Makefile.in
config.status: creating man/Makefile
config.status: creating tests/Makefile
config.status: creating include/iconv.h
config.status: creating include/iconv.h.inst
config.status: creating config.h
config.status: creating lib/config.h
config.status: executing depfiles commands
config.status: executing libtool commands
config.status: executing po-directories commands
config.status: creating po/POTFILES
config.status: creating po/Makefile
=== configuring in libcharset (/home/milchstore/source/libiconv-1.13/libcharset)
configure: running /bin/sh ./configure --disable-option-checking '--prefix=/home/milchstore/php5' '--enable-extra-encodings' --cache-file=/dev/null --srcdir=.
checking whether make sets $(MAKE)... yes
checking for gcc... gcc
checking for C compiler default output file name... a.out
checking whether the C compiler works... yes
checking whether we are cross compiling... no
checking for suffix of executables...
checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ISO C89... none needed
checking how to run the C preprocessor... gcc -E
checking for a BSD-compatible install... /usr/bin/install -c
checking build system type... x86_64-unknown-linux-gnu
checking host system type... x86_64-unknown-linux-gnu
checking whether to activate relocatable installation... no
checking for grep that handles long lines and -e... /bin/grep
checking for egrep... /bin/grep -E
checking for ANSI C header files... yes
checking for sys/types.h... yes
```

checking for stdlib.h... yes
checking for string.h... yes
checking for memory.h... yes
checking for strings.h... yes
checking for inttypes.h... yes
checking for stdint.h... yes
checking for unistd.h... yes
checking minix/config.h usability... no
checking minix/config.h presence... no
checking for minix/config.h... no
checking whether it is safe to define __EXTENSIONS__... yes
checking for a sed that does not truncate output... /bin/sed
checking for fgrep... /bin/grep -F
checking for ld used by gcc... /usr/bin/ld
checking if the linker (/usr/bin/ld) is GNU ld... yes
checking for BSD- or MS-compatible name lister (nm)... /usr/bin/nm -B
checking the name lister (/usr/bin/nm -B) interface... BSD nm
checking whether ln -s works... yes
checking the maximum length of command line arguments... 98304
checking whether the shell understands some XSI constructs... yes
checking whether the shell understands "+="... yes
checking for /usr/bin/ld option to reload object files... -r
checking for objdump... objdump
checking how to recognize dependent libraries... pass_all
checking for ar... ar
checking for strip... strip
checking for ranlib... ranlib
checking command to parse /usr/bin/nm -B output from gcc object... ok
checking for dlfcn.h... yes
checking for objdir... .libs
checking if gcc supports -fno-rtti -fno-exceptions... no
checking for gcc option to produce PIC... -fPIC -DPIC
checking if gcc PIC flag -fPIC -DPIC works... yes
checking if gcc static flag -static works... yes
checking if gcc supports -c -o file.o... yes
checking if gcc supports -c -o file.o... (cached) yes
checking whether the gcc linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking whether -lc should be explicitly linked in... no
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
checking whether stripping libraries is possible... yes
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries... yes
checking for simple visibility declarations... yes
checking for nl_langinfo and CODESET... yes
checking whether we are using the GNU C Library 2.1 or newer... yes
checking for setlocale... yes
configure: creating ./config.status

```
config.status: creating lib/Makefile
config.status: creating include/localcharset.h
config.status: creating include/localcharset.h.inst
config.status: creating config.h
config.status: executing libtool commands
=== configuring in preload (/home/milchstore/source/libiconv-1.13/preload)
configure: running /bin/sh ./configure --disable-option-checking '--prefix=/home
/milchstore/php5' '--enable-extra-encodings' --cache-file=/dev/null --srcdir=.
checking whether make sets $(MAKE)... yes
checking for gcc... gcc
checking for C compiler default output file name... a.out
checking whether the C compiler works... yes
checking whether we are cross compiling... no
checking for suffix of executables...
checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ISO C89... none needed
checking how to run the C preprocessor... gcc -E
checking for a BSD-compatible install... /usr/bin/install -c
checking build system type... x86_64-unknown-linux-gnu
checking host system type... x86_64-unknown-linux-gnu
checking whether to activate relocatable installation... no
checking whether ln -s works... yes
checking for grep that handles long lines and -e... /bin/grep
checking for egrep... /bin/grep -E
checking for ANSI C header files... yes
checking for sys/types.h... yes
checking for sys/stat.h... yes
checking for stdlib.h... yes
checking for string.h... yes
checking for memory.h... yes
checking for strings.h... yes
checking for inttypes.h... yes
checking for stdint.h... yes
checking for unistd.h... yes
checking minix/config.h usability... no
checking minix/config.h presence... no
checking for minix/config.h... no
checking whether it is safe to define __EXTENSIONS__... yes
checking for a sed that does not truncate output... /bin/sed
checking for fgrep... /bin/grep -F
checking for ld used by gcc... /usr/bin/ld
checking if the linker (/usr/bin/ld) is GNU ld... yes
checking for BSD- or MS-compatible name lister (nm)... /usr/bin/nm -B
checking the name lister (/usr/bin/nm -B) interface... BSD nm
checking the maximum length of command line arguments... 98304
checking whether the shell understands some XSI constructs... yes
checking whether the shell understands "+="... yes
checking for /usr/bin/ld option to reload object files... -r
```

```
checking how to recognize dependent libraries... pass_all
checking for ar... ar
checking for strip... strip
checking for ranlib... ranlib
checking command to parse /usr/bin/nm -B output from gcc object... ok
checking for dlfcn.h... yes
checking for objdir... .libs
checking if gcc supports -fno-rtti -fno-exceptions... no
checking for gcc option to produce PIC... -fPIC -DPIC
checking if gcc PIC flag -fPIC -DPIC works... yes
checking if gcc static flag -static works... yes
checking if gcc supports -c -o file.o... yes
checking if gcc supports -c -o file.o... (cached) yes
checking whether the gcc linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking whether -lc should be explicitly linked in... no
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
checking whether stripping libraries is possible... yes
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries... no
checking for simple visibility declarations... yes
configure: creating ./config.status
config.status: creating Makefile
config.status: executing libtool commands
builddir="`pwd`"; cd libcharset && make all && make install-lib libdir="$builddir/lib" includedir="$builddir/lib"
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/libcharset'
if [ ! -d include ] ; then mkdir include ; fi
cp ./include/libcharset.h.in include/libcharset.h
cd lib && make all
make[2]: Entering directory `/home/milchstore/source/libiconv-1.13/libcharset/lib'
/bin/sh ../libtool --mode=compile gcc -I. -I. -I.. -I./.. -I../include -g -O2 -fvisibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_LIBCHARSET -DBUILDING_DLL -DENABLE_RELOCATABLE=1 -DIN_LIBRARIES -DINSTALLDIR=\"/home/milchstore/php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libcharset_set_relocation_prefix -Drelocate=libcharset_relocate -DHAVE_CONFIG_H -c ./localcharset.c
libtool: compile: gcc -I. -I. -I.. -I./.. -I../include -g -O2 -fvisibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_LIBCHARSET -DBUILDING_DLL -DENABLE_RELOCATABLE=1 -DIN_LIBRARIES -DINSTALLDIR=\"/home/milchstore/php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libcharset_set_relocation_prefix -Drelocate=libcharset_relocate -DHAVE_CONFIG_H -c ./localcharset.c -fPIC -DPIC -o .libs/localcharset.o
libtool: compile: gcc -I. -I. -I.. -I./.. -I../include -g -O2 -fvisibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_LIBCHARSET -DBUILDING_DLL -DENABLE_RELOCATABLE=1 -DIN_LIBRARIES -DINSTALLDIR=\"/home/milchstore/php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libcharset_set_relocation_prefix -Drelocate=libcharset_relocate -DHAVE_CONFIG_H -c ./localcharset.c -o localcharset.o >/dev/n
```

```

/bin/sh ../libtool --mode=compile gcc -I. -I. -I.. -I./.. -I../include -g -O2 -f
visibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_LIBCHARSET
-DBUILDING_DLL -DENABLE_RELOCATABLE=1 -DIN_LIBRARY -DINSTALLDIR=\"/home/milchsto
re/php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libcharset_set_relocation_pre
fix -Drelocate=libcharset_relocate -DHAVE_CONFIG_H -c ./relocatable.c
libtool: compile: gcc -I. -I. -I.. -I./.. -I../include -g -O2 -fvisibility=hidd
en -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_LIBCHARSET -DBUILDING_DLL -
DENABLE_RELOCATABLE=1 -DIN_LIBRARY -DINSTALLDIR=\"/home/milchstore/php5/lib\" -D
NO_XMALLOC -Dset_relocation_prefix=libcharset_set_relocation_prefix -Drelocate=l
ibcharset_relocate -DHAVE_CONFIG_H -c ./relocatable.c -fPIC -DPIC -o .libs/relo
catable.o
libtool: compile: gcc -I. -I. -I.. -I./.. -I../include -g -O2 -fvisibility=hidd
en -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_LIBCHARSET -DBUILDING_DLL -
DENABLE_RELOCATABLE=1 -DIN_LIBRARY -DINSTALLDIR=\"/home/milchstore/php5/lib\" -D
NO_XMALLOC -Dset_relocation_prefix=libcharset_set_relocation_prefix -Drelocate=l
ibcharset_relocate -DHAVE_CONFIG_H -c ./relocatable.c -o relocatable.o >/dev/nul
l 2>&1
/bin/sh ../libtool --mode=link gcc -g -O2 -fvisibility=hidden -o libcharset.la
-rpath /home/milchstore/php5/lib -version-info 1:0:0 -no-undefined localcharset.
lo relocatable.lo
libtool: link: gcc -shared .libs/localcharset.o .libs/relocatable.o -Wl,-s
oname -Wl,libcharset.so.1 -o .libs/libcharset.so.1.0.0
libtool: link: (cd ".libs" && rm -f "libcharset.so.1" && ln -s "libcharset.so.1.
0.0" "libcharset.so.1")
libtool: link: (cd ".libs" && rm -f "libcharset.so" && ln -s "libcharset.so.1.0.
0" "libcharset.so")
libtool: link: ar cru .libs/libcharset.a localcharset.o relocatable.o
libtool: link: ranlib .libs/libcharset.a
libtool: link: ( cd ".libs" && rm -f "libcharset.la" && ln -s "../libcharset.la"
"libcharset.la" )
/bin/sh ./config.charset 'x86_64-unknown-linux-gnu' > t-charset.alias
mv t-charset.alias charset.alias
sed -e '/^#/d' -e 's/@'"PACKAGE"'@//g' ./ref-add.sin > t-ref-add.sed
mv t-ref-add.sed ref-add.sed
sed -e '/^#/d' -e 's/@'"PACKAGE"'@//g' ./ref-del.sin > t-ref-del.sed
mv t-ref-del.sed ref-del.sed
make[2]: Leaving directory `/home/milchstore/source/libiconv-1.13/libcharset/lib
'
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/libcharset'
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/libcharset'
cd lib && make all
make[2]: Entering directory `/home/milchstore/source/libiconv-1.13/libcharset/li
b'
make[2]: Nothing to be done for `all'.
make[2]: Leaving directory `/home/milchstore/source/libiconv-1.13/libcharset/lib
'
cd lib && make install-lib libdir='/home/milchstore/source/libiconv-1.13/lib' in
cludedir='/home/milchstore/source/libiconv-1.13/lib'
make[2]: Entering directory `/home/milchstore/source/libiconv-1.13/libcharset/li
b'

```

```

/bin/sh ../libtool --mode=install /usr/bin/install -c -m 644 libcharset.la /home
/milchstore/source/libiconv-1.13/lib/libcharset.la
libtool: install: /usr/bin/install -c -m 644 .libs/libcharset.so.1.0.0 /home/mil
chstore/source/libiconv-1.13/lib/libcharset.so.1.0.0
libtool: install: (cd /home/milchstore/source/libiconv-1.13/lib && { ln -s -f li
bcharset.so.1.0.0 libcharset.so.1 || { rm -f libcharset.so.1 && ln -s libcharset
.so.1.0.0 libcharset.so.1; }; })
libtool: install: (cd /home/milchstore/source/libiconv-1.13/lib && { ln -s -f li
bcharset.so.1.0.0 libcharset.so || { rm -f libcharset.so && ln -s libcharset.so.
1.0.0 libcharset.so; }; })
libtool: install: /usr/bin/install -c -m 644 .libs/libcharset.lai /home/milchsto
re/source/libiconv-1.13/lib/libcharset.la
libtool: install: /usr/bin/install -c -m 644 .libs/libcharset.a /home/milchstore
/source/libiconv-1.13/lib/libcharset.a
libtool: install: chmod 644 /home/milchstore/source/libiconv-1.13/lib/libcharset
.a
libtool: install: ranlib /home/milchstore/source/libiconv-1.13/lib/libcharset.a
libtool: install: warning: remember to run `libtool --finish /home/milchstore/php
p5/lib'
test -f /home/milchstore/source/libiconv-1.13/lib/charset.alias && orig=/home/mi
lchstore/source/libiconv-1.13/lib/charset.alias \
    || orig=charset.alias; \
    sed -f ref-add.sed $orig > /home/milchstore/source/libiconv-1.13/lib/t-c
harset.alias; \
    /usr/bin/install -c -m 644 /home/milchstore/source/libiconv-1.13/lib/t-c
harset.alias /home/milchstore/source/libiconv-1.13/lib/charset.alias; \
    rm -f /home/milchstore/source/libiconv-1.13/lib/t-charset.alias
make[2]: Leaving directory `/home/milchstore/source/libiconv-1.13/libcharset/lib
'
/bin/sh ../build-aux/mkinstalldirs /home/milchstore/source/libiconv-1.13/lib
/usr/bin/install -c -m 644 include/libcharset.h /home/milchstore/source/libiconv
-1.13/lib/libcharset.h
/usr/bin/install -c -m 644 include/localcharset.h.inst /home/milchstore/source/l
ibiconv-1.13/lib/localcharset.h
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/libcharset'
cd lib && make all
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/lib'
/bin/sh ../libtool --mode=compile gcc -I. -I. -I../include -I../include -I.. -
I../.. -g -O2 -fvisibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILD
ING_LIBICONV -DBUILDING_DLL -DENABLE_RELOCATABLE=1 -DIN_LIBRARY -DINSTALLDIR=\"/
home/milchstore/php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libiconv_set_rel
ocation_prefix -Drelocate=libiconv_relocate -DHAVE_CONFIG_H -c ./iconv.c
libtool: compile: gcc -I. -I. -I../include -I../include -I.. -I../.. -g -O2 -f
visibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_LIBICONV -DB
UILDING_DLL -DENABLE_RELOCATABLE=1 -DIN_LIBRARY -DINSTALLDIR=\"/home/milchstore/
php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libiconv_set_relocation_prefix -
Drelocate=libiconv_relocate -DHAVE_CONFIG_H -c ./iconv.c -fPIC -DPIC -o .libs/i
conv.o
/bin/sh ../libtool --mode=compile gcc -I. -I. -I../include -I../include -I.. -
I../.. -g -O2 -fvisibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILD

```

```

home/milchstore/php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libiconv_set_relocation_prefix -Drelocate=libiconv_relocate -DHAVE_CONFIG_H -c ../../libcharset/lib/localcharset.c
libtool: compile: gcc -I. -I. -I../include -I../include -I.. -I../.. -g -O2 -fvisibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_LIBICONV -DBUILDING_DLL -DENABLE_RELOCATABLE=1 -DIN_LIBRARY -DINSTALLDIR=\"/home/milchstore/php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libiconv_set_relocation_prefix -Drelocate=libiconv_relocate -DHAVE_CONFIG_H -c ../../libcharset/lib/localcharset.c -fPIC -DPIC -o .libs/localcharset.o
/bin/sh ../libtool --mode=compile gcc -I. -I. -I../include -I../include -I.. -I../.. -g -O2 -fvisibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_LIBICONV -DBUILDING_DLL -DENABLE_RELOCATABLE=1 -DIN_LIBRARY -DINSTALLDIR=\"/home/milchstore/php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libiconv_set_relocation_prefix -Drelocate=libiconv_relocate -DHAVE_CONFIG_H -c ./relocatable.c
libtool: compile: gcc -I. -I. -I../include -I../include -I.. -I../.. -g -O2 -fvisibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_LIBICONV -DBUILDING_DLL -DENABLE_RELOCATABLE=1 -DIN_LIBRARY -DINSTALLDIR=\"/home/milchstore/php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libiconv_set_relocation_prefix -Drelocate=libiconv_relocate -DHAVE_CONFIG_H -c ./relocatable.c -fPIC -DPIC -o .libs/relocatable.o
/bin/sh ../libtool --mode=link gcc -g -O2 -fvisibility=hidden -o libiconv.la -rpath /home/milchstore/php5/lib -version-info 7:0:5 -no-undefined iconv.lo localcharset.lo relocatable.lo
libtool: link: gcc -shared .libs/iconv.o .libs/localcharset.o .libs/relocatable.o -Wl,-soname -Wl,libiconv.so.2 -o .libs/libiconv.so.2.5.0
libtool: link: (cd ".libs" && rm -f "libiconv.so.2" && ln -s "libiconv.so.2.5.0" "libiconv.so.2")
libtool: link: (cd ".libs" && rm -f "libiconv.so" && ln -s "libiconv.so.2.5.0" "libiconv.so")
libtool: link: ( cd ".libs" && rm -f "libiconv.la" && ln -s "../libiconv.la" "libiconv.la" )
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/lib'
cd preload && make all
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/preload'
rm -f -r objects
mkdir objects && \
    for f in ../../lib/iconv.c ../../libcharset/lib/localcharset.c ../../lib/relocatable.c; do \
        /bin/sh ../libtool --mode=compile gcc -I../lib -I../lib -I../include -I../include -I.. -I../.. -g -O2 -fvisibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_LIBICONV -DBUILDING_DLL -DENABLE_RELOCATABLE=1 -DIN_LIBRARY -DINSTALLDIR=\"/home/milchstore/php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libiconv_set_relocation_prefix -Drelocate=libiconv_relocate -DPACKAGE_NAME=\"\" -DPACKAGE_TARNAME=\"\" -DPACKAGE_VERSION=\"\" -DPACKAGE_STRING=\"\" -DPACKAGE_BUGREPORT=\"\" -DINSTALLPREFIX=\"/home/milchstore/php5\" -DSTDC_HEADERS=1 -DHAVE_SYS_TYPES_H=1 -DHAVE_SYS_STAT_H=1 -DHAVE_STDLIB_H=1 -DHAVE_STRING_H=1 -DHAVE_MEMORY_H=1 -DHAVE_STRINGS_H=1 -DHAVE_INTTYPES_H=1 -DHAVE_STDINT_H=1 -DHAVE_UNISTD_H=1 -D__EXTENSIONS__=1 -D_ALL_SOURCE=1 -D_GNU_SOURCE=1 -D_POSIX_PTHREAD_SEMANTICS=1 -D_TANDEM_SOURCE=1 -DHAVE_DLFCN_H=1 -DLT_OBJDIR=\".libs/\" -DHAVE_VISIBILITY=1 -DLIBICONV_PLUG -c $f -o objects/`basename $f` | sed -e 's,\.c$,\.o,' || ex

```



```

done && \
/bin/sh ./libtool --mode=link gcc -g -O2 -fvisibility=hidden -o libicon
v.la -rpath /home/milchstore/php5/lib -no-undefined objects/*.lo && \
rm -f -r objects
libtool: compile: gcc -I../lib -I../lib -I../include -I../include -I.. -I/
.. -g -O2 -fvisibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_
LIBICONV -DBUILDING_DLL -DENABLE_RELOCATABLE=1 -DIN_LIBRARY -DINSTALLDIR=\"/home
/milchstore/php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libiconv_set_relocat
ion_prefix -Drelocate=libiconv_relocate -DPACKAGE_NAME=\"\" -DPACKAGE_TARNAME=\"
\" -DPACKAGE_VERSION=\"\" -DPACKAGE_STRING=\"\" -DPACKAGE_BUGREPORT=\"\" -DINSTA
LLPREFIX=\"/home/milchstore/php5\" -DSTDC_HEADERS=1 -DHAVE_SYS_TYPES_H=1 -DHAVE_
SYS_STAT_H=1 -DHAVE_STDLIB_H=1 -DHAVE_STRING_H=1 -DHAVE_MEMORY_H=1 -DHAVE_STRING
S_H=1 -DHAVE_INTTYPES_H=1 -DHAVE_STDINT_H=1 -DHAVE_UNISTD_H=1 -D__EXTENSIONS__=1
-D_ALL_SOURCE=1 -D_GNU_SOURCE=1 -D_POSIX_PTHREAD_SEMANTICS=1 -D_TANDEM_SOURCE=1
-DHAVE_DLFCN_H=1 -DLT_OBJDIR=\".libs/\" -DHAVE_VISIBILITY=1 -DLIBICONV_PLUG -c
./../lib/iconv.c -fPIC -DPIC -o objects/.libs/iconv.o
libtool: compile: gcc -I../lib -I../lib -I../include -I../include -I.. -I/
.. -g -O2 -fvisibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_
LIBICONV -DBUILDING_DLL -DENABLE_RELOCATABLE=1 -DIN_LIBRARY -DINSTALLDIR=\"/home
/milchstore/php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libiconv_set_relocat
ion_prefix -Drelocate=libiconv_relocate -DPACKAGE_NAME=\"\" -DPACKAGE_TARNAME=\"
\" -DPACKAGE_VERSION=\"\" -DPACKAGE_STRING=\"\" -DPACKAGE_BUGREPORT=\"\" -DINSTA
LLPREFIX=\"/home/milchstore/php5\" -DSTDC_HEADERS=1 -DHAVE_SYS_TYPES_H=1 -DHAVE_
SYS_STAT_H=1 -DHAVE_STDLIB_H=1 -DHAVE_STRING_H=1 -DHAVE_MEMORY_H=1 -DHAVE_STRING
S_H=1 -DHAVE_INTTYPES_H=1 -DHAVE_STDINT_H=1 -DHAVE_UNISTD_H=1 -D__EXTENSIONS__=1
-D_ALL_SOURCE=1 -D_GNU_SOURCE=1 -D_POSIX_PTHREAD_SEMANTICS=1 -D_TANDEM_SOURCE=1
-DHAVE_DLFCN_H=1 -DLT_OBJDIR=\".libs/\" -DHAVE_VISIBILITY=1 -DLIBICONV_PLUG -c
./../libcharset/lib/localcharset.c -fPIC -DPIC -o objects/.libs/localcharset.o
libtool: compile: gcc -I../lib -I../lib -I../include -I../include -I.. -I/
.. -g -O2 -fvisibility=hidden -DLIBDIR=\"/home/milchstore/php5/lib\" -DBUILDING_
LIBICONV -DBUILDING_DLL -DENABLE_RELOCATABLE=1 -DIN_LIBRARY -DINSTALLDIR=\"/home
/milchstore/php5/lib\" -DNO_XMALLOC -Dset_relocation_prefix=libiconv_set_relocat
ion_prefix -Drelocate=libiconv_relocate -DPACKAGE_NAME=\"\" -DPACKAGE_TARNAME=\"
\" -DPACKAGE_VERSION=\"\" -DPACKAGE_STRING=\"\" -DPACKAGE_BUGREPORT=\"\" -DINSTA
LLPREFIX=\"/home/milchstore/php5\" -DSTDC_HEADERS=1 -DHAVE_SYS_TYPES_H=1 -DHAVE_
SYS_STAT_H=1 -DHAVE_STDLIB_H=1 -DHAVE_STRING_H=1 -DHAVE_MEMORY_H=1 -DHAVE_STRING
S_H=1 -DHAVE_INTTYPES_H=1 -DHAVE_STDINT_H=1 -DHAVE_UNISTD_H=1 -D__EXTENSIONS__=1
-D_ALL_SOURCE=1 -D_GNU_SOURCE=1 -D_POSIX_PTHREAD_SEMANTICS=1 -D_TANDEM_SOURCE=1
-DHAVE_DLFCN_H=1 -DLT_OBJDIR=\".libs/\" -DHAVE_VISIBILITY=1 -DLIBICONV_PLUG -c
./../lib/relocatable.c -fPIC -DPIC -o objects/.libs/relocatable.o
libtool: link: gcc -shared objects/.libs/iconv.o objects/.libs/localcharset.o o
bjects/.libs/relocatable.o -Wl,-soname -Wl,libiconv.so.0 -o .libs/libiconv.
so.0.0.0
libtool: link: (cd ".libs" && rm -f "libiconv.so.0" && ln -s "libiconv.so.0.0.0"
"libiconv.so.0")
libtool: link: (cd ".libs" && rm -f "libiconv.so" && ln -s "libiconv.so.0.0.0" "
libiconv.so")
libtool: link: ( cd ".libs" && rm -f "libiconv.la" && ln -s "../libiconv.la" "li
biconv.la" )
cp .libs/libiconv.so preloadable_libiconv.so

```

```

cd srclib && make all
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/srclib'
{ echo '/* DO NOT EDIT! GENERATED AUTOMATICALLY! */'; \
    cat ./alloca.in.h; \
    } > alloca.h-t
mv -f alloca.h-t alloca.h
rm -f signal.h-t signal.h
{ echo '/* DO NOT EDIT! GENERATED AUTOMATICALLY! */' && \
    sed -e 's|@'INCLUDE_NEXT'|@linclude_nextlg' \
        -e 's|@'PRAGMA_SYSTEM_HEADER'|@|#pragma GCC system_headerlg' \
        -e 's|@'NEXT_SIGNAL_H'|@|<signal.h>lg' \
        -e 's|@'GNULIB_SIGNAL_H_SIGPIPE'|@|1lg' \
        -e 's|@'GNULIB_SIGPROCMAK'|@|1lg' \
        -e 's|@'GNULIB_SIGACTION'|@|0lg' \
        -e 's|@'HAVE_POSIX_SIGNALBLOCKING'|@|1lg' \
        -e 's|@'HAVE_SIGSET_T'|@|1lg' \
        -e 's|@'HAVE_SIGINFO_T'|@|1lg' \
        -e 's|@'HAVE_SIGACTION'|@|1lg' \
        -e 's|@'HAVE_STRUCT_SIGACTION_SA_SIGACTION'|@|1lg' \
        -e 's|@'HAVE_TYPE_VOLATILE_SIG_ATOMIC_T'|@|1lg' \
        -e '/definition of GL_LINK_WARNING/r ../build-aux/link-warning.h'
\
    < ./signal.in.h; \
    } > signal.h-t
mv signal.h-t signal.h
rm -f stdint.h-t stdint.h
{ echo '/* DO NOT EDIT! GENERATED AUTOMATICALLY! */'; \
    sed -e 's/@'HAVE_STDINT_H'|@/1/g' \
        -e 's|@'INCLUDE_NEXT'|@linclude_nextlg' \
        -e 's|@'PRAGMA_SYSTEM_HEADER'|@|#pragma GCC system_headerlg' \
        -e 's|@'NEXT_STDINT_H'|@|<stdint.h>lg' \
        -e 's/@'HAVE_SYS_TYPES_H'|@/1/g' \
        -e 's/@'HAVE_INTTYPES_H'|@/1/g' \
        -e 's/@'HAVE_SYS_INTTYPES_H'|@/0/g' \
        -e 's/@'HAVE_SYS_BITYPES_H'|@/1/g' \
        -e 's/@'HAVE_LONG_LONG_INT'|@/1/g' \
        -e 's/@'HAVE_UNSIGNED_LONG_LONG_INT'|@/1/g' \
        -e 's/@'APPLE_UNIVERSAL_BUILD'|@/0/g' \
        -e 's/@'BITSIZEOF_PTRDIFF_T'|@/64/g' \
        -e 's/@'PTRDIFF_T_SUFFIX'|@/l/g' \
        -e 's/@'BITSIZEOF_SIG_ATOMIC_T'|@/32/g' \
        -e 's/@'HAVE_SIGNED_SIG_ATOMIC_T'|@/1/g' \
        -e 's/@'SIG_ATOMIC_T_SUFFIX'|@/g' \
        -e 's/@'BITSIZEOF_SIZE_T'|@/64/g' \
        -e 's/@'SIZE_T_SUFFIX'|@/ul/g' \
        -e 's/@'BITSIZEOF_WCHAR_T'|@/32/g' \
        -e 's/@'HAVE_SIGNED_WCHAR_T'|@/1/g' \
        -e 's/@'WCHAR_T_SUFFIX'|@//g' \
        -e 's/@'BITSIZEOF_WINT_T'|@/32/g' \
        -e 's/@'HAVE_SIGNED_WINT_T'|@/0/g' \

```

```

    < ./stdint.in.h; \
} > stdint.h-t
mv stdint.h-t stdint.h
rm -f stdio.h-t stdio.h
{ echo '/* DO NOT EDIT! GENERATED AUTOMATICALLY! */' && \
  sed -e 's|@'|INCLUDE_NEXT'|@|include_next|g' \
      -e 's|@'|PRAGMA_SYSTEM_HEADER'|@|#pragma GCC system_header|g' \
      -e 's|@'|NEXT_STDIO_H'|@|<stdio.h>|g' \
      -e 's|@'|GNULIB_FPRINTF'|@|1|g' \
      -e 's|@'|GNULIB_FPRINTF_POSIX'|@|0|g' \
      -e 's|@'|GNULIB_PRINTF'|@|1|g' \
      -e 's|@'|GNULIB_PRINTF_POSIX'|@|0|g' \
      -e 's|@'|GNULIB_SNPRINTF'|@|0|g' \
      -e 's|@'|GNULIB_SPRINTF_POSIX'|@|0|g' \
      -e 's|@'|GNULIB_VFPRINTF'|@|1|g' \
      -e 's|@'|GNULIB_VFPRINTF_POSIX'|@|0|g' \
      -e 's|@'|GNULIB_VPRINTF'|@|1|g' \
      -e 's|@'|GNULIB_VPRINTF_POSIX'|@|0|g' \
      -e 's|@'|GNULIB_VSNPRINTF'|@|0|g' \
      -e 's|@'|GNULIB_VSPRINTF_POSIX'|@|0|g' \
      -e 's|@'|GNULIB_DPRINTF'|@|0|g' \
      -e 's|@'|GNULIB_VDPRINTF'|@|0|g' \
      -e 's|@'|GNULIB_VASPRINTF'|@|0|g' \
      -e 's|@'|GNULIB_OBSTACK_PRINTF'|@|0|g' \
      -e 's|@'|GNULIB_OBSTACK_PRINTF_POSIX'|@|0|g' \
      -e 's|@'|GNULIB_FOPEN'|@|0|g' \
      -e 's|@'|GNULIB_FREOPEN'|@|0|g' \
      -e 's|@'|GNULIB_FSEEK'|@|0|g' \
      -e 's|@'|GNULIB_FSEEKO'|@|0|g' \
      -e 's|@'|GNULIB_FTELL'|@|0|g' \
      -e 's|@'|GNULIB_FTELLO'|@|0|g' \
      -e 's|@'|GNULIB_FFLUSH'|@|0|g' \
      -e 's|@'|GNULIB_FCLOSE'|@|0|g' \
      -e 's|@'|GNULIB_FPUTC'|@|1|g' \
      -e 's|@'|GNULIB_PUTC'|@|1|g' \
      -e 's|@'|GNULIB_PUTCHAR'|@|1|g' \
      -e 's|@'|GNULIB_FPUTS'|@|1|g' \
      -e 's|@'|GNULIB_PUTS'|@|1|g' \
      -e 's|@'|GNULIB_FWRITE'|@|1|g' \
      -e 's|@'|GNULIB_GETDELIM'|@|0|g' \
      -e 's|@'|GNULIB_GETLINE'|@|0|g' \
      -e 's|@'|GNULIB_PERROR'|@|0|g' \
      -e 's|@'|GNULIB_STDIO_H_SIGPIPE'|@|1|g' \
      -e 's|@'|REPLACE_STDIO_WRITE_FUNCS'|@|0|g' \
      -e 's|@'|REPLACE_FPRINTF'|@|0|g' \
      -e 's|@'|REPLACE_VFPRINTF'|@|0|g' \
      -e 's|@'|REPLACE_PRINTF'|@|0|g' \
      -e 's|@'|REPLACE_VPRINTF'|@|0|g' \
      -e 's|@'|REPLACE_SNPRINTF'|@|0|g' \
      -e 's|@'|HAVE_DECL_SNPRINTF'|@|1|g' \

```

```

-e 's|@'|'HAVE_DECL_VSNPRINTF'|'@|1|g'| \
-e 's|@'|'REPLACE_SPRINTF'|'@|0|g'| \
-e 's|@'|'REPLACE_VPRINTF'|'@|0|g'| \
-e 's|@'|'HAVE_DPRINTF'|'@|1|g'| \
-e 's|@'|'REPLACE_DPRINTF'|'@|0|g'| \
-e 's|@'|'HAVE_VDPRINTF'|'@|1|g'| \
-e 's|@'|'REPLACE_VDPRINTF'|'@|0|g'| \
-e 's|@'|'HAVE_VASPRINTF'|'@|1|g'| \
-e 's|@'|'REPLACE_VASPRINTF'|'@|0|g'| \
-e 's|@'|'HAVE_DECL_OBSTACK_PRINTF'|'@|1|g'| \
-e 's|@'|'REPLACE_OBSTACK_PRINTF'|'@|0|g'| \
-e 's|@'|'REPLACE_FOPEN'|'@|0|g'| \
-e 's|@'|'REPLACE_FREOPEN'|'@|0|g'| \
-e 's|@'|'REPLACE_FSEEK0'|'@|0|g'| \
-e 's|@'|'REPLACE_FSEEK'|'@|0|g'| \
-e 's|@'|'REPLACE_FTELLO'|'@|0|g'| \
-e 's|@'|'REPLACE_FTELL'|'@|0|g'| \
-e 's|@'|'REPLACE_FFLUSH'|'@|0|g'| \
-e 's|@'|'REPLACE_FCLOSE'|'@|0|g'| \
-e 's|@'|'HAVE_DECL_GETDELIM'|'@|1|g'| \
-e 's|@'|'HAVE_DECL_GETLINE'|'@|1|g'| \
-e 's|@'|'REPLACE_GETLINE'|'@|0|g'| \
-e 's|@'|'REPLACE_PERROR'|'@|0|g'| \
-e '/definition of GL_LINK_WARNING/r ../build-aux/link-warning.h'

```

\

```
< ./stdio.in.h; \
```

```
} > stdio.h-t
```

```
mv stdio.h-t stdio.h
```

```
rm -f stdlib.h-t stdlib.h
```

```
{ echo '/* DO NOT EDIT! GENERATED AUTOMATICALLY! */' && \
```

```
sed -e 's|@'|'INCLUDE_NEXT'|'@|include_next|g'| \
```

```
-e 's|@'|'PRAGMA_SYSTEM_HEADER'|'@|#pragma GCC system_header|g'| \
```

```
-e 's|@'|'NEXT_STDLIB_H'|'@|<stdlib.h>|g'| \
```

```
-e 's|@'|'HAVE_RANDOM_H'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_MALLOC_POSIX'|'@|1|g'| \
```

```
-e 's|@'|'GNULIB_REALLOC_POSIX'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_CALLOC_POSIX'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_ATOLL'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_GETLOADAVG'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_GETSUBOPT'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_MKDTEMP'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_MKSTEMP'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_PUTENV'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_RANDOM_R'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_RPMATCH'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_SETENV'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_STRTOD'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_STRTOLL'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_STRTOULL'|'@|0|g'| \
```

```
-e 's|@'|'GNULIB_UNSETENV'|'@|0|g'| \
```

```

-e 's|@' 'HAVE_CALLOC_POSIX' '@|1|g' \
-e 's|@' 'HAVE_GETSUBOPT' '@|1|g' \
-e 's|@' 'HAVE_MALLOCA_POSIX' '@|1|g' \
-e 's|@' 'HAVE_MKDTEMP' '@|1|g' \
-e 's|@' 'HAVE_REALLOC_POSIX' '@|1|g' \
-e 's|@' 'HAVE_RANDOM_R' '@|1|g' \
-e 's|@' 'HAVE_RPMATCH' '@|1|g' \
-e 's|@' 'HAVE_SETENV' '@|1|g' \
-e 's|@' 'HAVE_STRTOD' '@|1|g' \
-e 's|@' 'HAVE_STRTOLL' '@|1|g' \
-e 's|@' 'HAVE_STRTOULL' '@|1|g' \
-e 's|@' 'HAVE_STRUCT_RANDOM_DATA' '@|1|g' \
-e 's|@' 'HAVE_SYS_LOADAVG_H' '@|0|g' \
-e 's|@' 'HAVE_UNSETENV' '@|1|g' \
-e 's|@' 'HAVE_DECL_GETLOADAVG' '@|1|g' \
-e 's|@' 'REPLACE_MKSTEMP' '@|0|g' \
-e 's|@' 'REPLACE_PUTENV' '@|0|g' \
-e 's|@' 'REPLACE_STRTOD' '@|0|g' \
-e 's|@' 'VOID_UNSETENV' '@|0|g' \
-e '/definition of GL_LINK_WARNING/r ../build-aux/link-warning.h'

```

\

```
< ./stdlib.in.h; \
```

```
} > stdlib.h-t
```

```
mv stdlib.h-t stdlib.h
```

```
rm -f string.h-t string.h
```

```
{ echo '/* DO NOT EDIT! GENERATED AUTOMATICALLY! */' && \
```

```
sed -e 's|@' 'INCLUDE_NEXT' '@|include_next|g' \
```

```
-e 's|@' 'PRAGMA_SYSTEM_HEADER' '@|#pragma GCC system_header|g' \
```

```
-e 's|@' 'NEXT_STRING_H' '@|<string.h>|g' \
```

```
-e 's|@' 'GNULIB_MBSLEN' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MBSNLEN' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MBSCCHR' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MBSRCHR' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MBSSTR' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MBSCASECMP' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MBSNCASECMP' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MBSPCASECMP' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MBSCASESTR' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MBSCSPN' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MBSPBRK' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MBSSPN' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MBSSEP' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MBSTOK_R' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MEMMEM' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MEMPCPY' '@|0|g' \
```

```
-e 's|@' 'GNULIB_MEMRCHR' '@|0|g' \
```

```
-e 's|@' 'GNULIB_RAWMEMCHR' '@|0|g' \
```

```
-e 's|@' 'GNULIB_STPCPY' '@|0|g' \
```

```
-e 's|@' 'GNULIB_STPNCPY' '@|0|g' \
```

```
-e 's|@' 'GNULIB_STRCHRNU' '@|0|g' \
```

```

-e 's|@'|GNULIB_STRNDUP'|@|0|g' \
-e 's|@'|GNULIB_STRNLEN'|@|0|g' \
-e 's|@'|GNULIB_STRPBRK'|@|0|g' \
-e 's|@'|GNULIB_STRSEP'|@|0|g' \
-e 's|@'|GNULIB_STRSTR'|@|0|g' \
-e 's|@'|GNULIB_STRCASESTR'|@|0|g' \
-e 's|@'|GNULIB_STRTOK_R'|@|0|g' \
-e 's|@'|GNULIB_STRERROR'|@|1|g' \
-e 's|@'|GNULIB_STRSIGNAL'|@|0|g' \
-e 's|@'|GNULIB_STRVERSCMP'|@|0|g' \
-e 's|@'|HAVE_DECL_MEMMEM'|@|1|g' \
-e 's|@'|HAVE_MEMPCPY'|@|1|g' \
-e 's|@'|HAVE_DECL_MEMRCHR'|@|1|g' \
-e 's|@'|HAVE_RAWMEMCHR'|@|1|g' \
-e 's|@'|HAVE_STPCPY'|@|1|g' \
-e 's|@'|HAVE_STPCPY'|@|1|g' \
-e 's|@'|HAVE_STRCHRNU'|@|1|g' \
-e 's|@'|HAVE_DECL_STRDUP'|@|1|g' \
-e 's|@'|HAVE_STRNDUP'|@|1|g' \
-e 's|@'|HAVE_DECL_STRNDUP'|@|1|g' \
-e 's|@'|HAVE_DECL_STRNLEN'|@|1|g' \
-e 's|@'|HAVE_STRPBRK'|@|1|g' \
-e 's|@'|HAVE_STRSEP'|@|1|g' \
-e 's|@'|HAVE_STRCASESTR'|@|1|g' \
-e 's|@'|HAVE_DECL_STRTOK_R'|@|1|g' \
-e 's|@'|HAVE_DECL_STRERROR'|@|1|g' \
-e 's|@'|HAVE_DECL_STRSIGNAL'|@|1|g' \
-e 's|@'|HAVE_STRVERSCMP'|@|1|g' \
-e 's|@'|REPLACE_MEMMEM'|@|0|g' \
-e 's|@'|REPLACE_STRCASESTR'|@|0|g' \
-e 's|@'|REPLACE_STRDUP'|@|0|g' \
-e 's|@'|REPLACE_STRSTR'|@|0|g' \
-e 's|@'|REPLACE_STRERROR'|@|0|g' \
-e 's|@'|REPLACE_STRSIGNAL'|@|0|g' \
-e '/definition of GL_LINK_WARNING/r ../build-aux/link-warning.h'

```

\

```
< ./string.in.h; \
```

```
} > string.h-t
```

```
mv string.h-t string.h
```

```
rm -f unistd.h-t unistd.h
```

```
{ echo '/* DO NOT EDIT! GENERATED AUTOMATICALLY! */'; \
```

```
sed -e 's|@'|HAVE_UNISTD_H'|@|1|g' \
```

```
-e 's|@'|INCLUDE_NEXT'|@|include_next|g' \
```

```
-e 's|@'|PRAGMA_SYSTEM_HEADER'|@|#pragma GCC system_header|g' \
```

```
-e 's|@'|NEXT_UNISTD_H'|@|<unistd.h>|g' \
```

```
-e 's|@'|GNULIB_CHOWN'|@|0|g' \
```

```
-e 's|@'|GNULIB_CLOSE'|@|0|g' \
```

```
-e 's|@'|GNULIB_DUP2'|@|0|g' \
```

```
-e 's|@'|GNULIB_ENVIRON'|@|1|g' \
```

```
-e 's|@'|GNULIB_EUIDACCESS'|@|0|g' \
```

```

-e 's|@'|GNULIB_FSYNC'|@|0|g'| \
-e 's|@'|GNULIB_FTRUNCATE'|@|0|g'| \
-e 's|@'|GNULIB_GETCWD'|@|0|g'| \
-e 's|@'|GNULIB_GETDOMAINNAME'|@|0|g'| \
-e 's|@'|GNULIB_GETDTABLESIZE'|@|0|g'| \
-e 's|@'|GNULIB_GETHOSTNAME'|@|0|g'| \
-e 's|@'|GNULIB_GETLOGIN_R'|@|0|g'| \
-e 's|@'|GNULIB_GETPAGESIZE'|@|0|g'| \
-e 's|@'|GNULIB_GETUSERSHELL'|@|0|g'| \
-e 's|@'|GNULIB_LCHOWN'|@|0|g'| \
-e 's|@'|GNULIB_LINK'|@|0|g'| \
-e 's|@'|GNULIB_LSEEK'|@|0|g'| \
-e 's|@'|GNULIB_READLINK'|@|1|g'| \
-e 's|@'|GNULIB_SLEEP'|@|0|g'| \
-e 's|@'|GNULIB_UNISTD_H_SIGPIPE'|@|1|g'| \
-e 's|@'|GNULIB_WRITE'|@|0|g'| \
-e 's|@'|HAVE_DUP2'|@|1|g'| \
-e 's|@'|HAVE_EUIDACCESS'|@|1|g'| \
-e 's|@'|HAVE_FSYNC'|@|1|g'| \
-e 's|@'|HAVE_FTRUNCATE'|@|1|g'| \
-e 's|@'|HAVE_GETDOMAINNAME'|@|1|g'| \
-e 's|@'|HAVE_GETDTABLESIZE'|@|1|g'| \
-e 's|@'|HAVE_GETHOSTNAME'|@|1|g'| \
-e 's|@'|HAVE_GETPAGESIZE'|@|1|g'| \
-e 's|@'|HAVE_GETUSERSHELL'|@|1|g'| \
-e 's|@'|HAVE_LINK'|@|1|g'| \
-e 's|@'|HAVE_READLINK'|@|1|g'| \
-e 's|@'|HAVE_SLEEP'|@|1|g'| \
-e 's|@'|HAVE_DECL_ENVIRON'|@|1|g'| \
-e 's|@'|HAVE_DECL_GETLOGIN_R'|@|1|g'| \
-e 's|@'|HAVE_OS_H'|@|0|g'| \
-e 's|@'|HAVE_SYS_PARAM_H'|@|0|g'| \
-e 's|@'|REPLACE_CHOWN'|@|0|g'| \
-e 's|@'|REPLACE_CLOSE'|@|0|g'| \
-e 's|@'|REPLACE_FCHDIR'|@|0|g'| \
-e 's|@'|REPLACE_GETCWD'|@|0|g'| \
-e 's|@'|REPLACE_GETPAGESIZE'|@|0|g'| \
-e 's|@'|REPLACE_LCHOWN'|@|0|g'| \
-e 's|@'|REPLACE_LSEEK'|@|0|g'| \
-e 's|@'|REPLACE_WRITE'|@|0|g'| \
-e 's|@'|UNISTD_H_HAVE_WINSOCK2_H'|@|0|g'| \
-e '/definition of GL_LINK_WARNING/r ../build-aux/link-warning.h'

```

\

```
< ./unistd.in.h; \
```

```
} > unistd.h-t
```

```
mv unistd.h-t unistd.h
```

```
make all-am
```

```
make[2]: Entering directory `/home/milchstore/source/libiconv-1.13/src/lib'
```

```
gcc -DHAVE_CONFIG_H -DEXEEXT=\"\" -I. -I.. -I../lib -I../intl -DDEPENDS_ON_LIBICONV=1 -DDEPENDS_ON_LIBINTL=1 -g -O2 -c areadlink.c
```

```

CONV=1 -DDEPENDS_ON_LIBINTL=1 -g -O2 -c malloca.c
gcc -DHAVE_CONFIG_H -DEXEEXT="\\" -I. -I.. -I../lib -I../intl -DDEPENDS_ON_LIBI
CONV=1 -DDEPENDS_ON_LIBINTL=1 -g -O2 -c progname.c
gcc -DHAVE_CONFIG_H -DEXEEXT="\\" -I. -I.. -I../lib -I../intl -DDEPENDS_ON_LIBI
CONV=1 -DDEPENDS_ON_LIBINTL=1 -g -O2 -c -o width.o `test -f 'uniwidth/width.c'
  || echo './`uniwidth/width.c
gcc -DHAVE_CONFIG_H -DEXEEXT="\\" -I. -I.. -I../lib -I../intl -DDEPENDS_ON_LIBI
CONV=1 -DDEPENDS_ON_LIBINTL=1 -g -O2 -c xmalloc.c
gcc -DHAVE_CONFIG_H -DEXEEXT="\\" -I. -I.. -I../lib -I../intl -DDEPENDS_ON_LIBI
CONV=1 -DDEPENDS_ON_LIBINTL=1 -g -O2 -c xstrdup.c
gcc -DHAVE_CONFIG_H -DEXEEXT="\\" -I. -I.. -I../lib -I../intl -DDEPENDS_ON_LIBI
CONV=1 -DDEPENDS_ON_LIBINTL=1 -g -O2 -c xreadlink.c
rm -f libcrt.a
ar cru libcrt.a areadlink.o malloca.o progname.o width.o xmalloc.o xstrdup.o xr
eadlink.o
ranlib libcrt.a
make[2]: Leaving directory `/home/milchstore/source/libiconv-1.13/src/lib'
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/src/lib'
cd src && make all
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/src'
gcc -c -I. -I. -I.. -I../include -I../include -I../srclib -I../srclib -I../l
ib -g -O2 -DINSTALLDIR="/home/milchstore/php5/bin\" -DLOCALEDIR="/home/milchs
tore/php5/share/locale\" ./iconv_no_i18n.c
/bin/sh ../libtool --mode=link gcc -g -O2 iconv_no_i18n.o ../srclib/libicrt.a .
./lib/libiconv.la -o iconv_no_i18n
libtool: link: gcc -g -O2 iconv_no_i18n.o -o .libs/iconv_no_i18n ../srclib/libi
crt.a ../lib/.libs/libiconv.so -Wl,-rpath -Wl,/home/milchstore/php5/lib
gcc -c -I. -I. -I.. -I../include -I../include -I../srclib -I../srclib -I../l
ib -g -O2 -DINSTALLDIR="/home/milchstore/php5/bin\" -DLOCALEDIR="/home/milchs
tore/php5/share/locale\" ./iconv.c
test `ls -ld . | sed -e 's/^d\(\.....\).*\/1/'` = rwxrwxrwx || chmod 777 .
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/src'
cd po && make all
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/po'
test ! -f ./libiconv.pot || \
    test -z "af.gmo bg.gmo ca.gmo da.gmo de.gmo el.gmo eo.gmo es.gmo et.gm
o fi.gmo fr.gmo ga.gmo gl.gmo hr.gmo hu.gmo id.gmo it.gmo nl.gmo pl.gmo pt_BR.gm
o rm.gmo ro.gmo ru.gmo sk.gmo sl.gmo sq.gmo sr.gmo sv.gmo tr.gmo uk.gmo vi.gmo w
a.gmo zh_CN.gmo zh_TW.gmo" || make af.gmo bg.gmo ca.gmo da.gmo de.gmo el.gmo eo.
gmo es.gmo et.gmo fi.gmo fr.gmo ga.gmo gl.gmo hr.gmo hu.gmo id.gmo it.gmo nl.gmo
pl.gmo pt_BR.gmo rm.gmo ro.gmo ru.gmo sk.gmo sl.gmo sq.gmo sr.gmo sv.gmo tr.gmo
uk.gmo vi.gmo wa.gmo zh_CN.gmo zh_TW.gmo
make[2]: Entering directory `/home/milchstore/source/libiconv-1.13/po'
make[2]: `af.gmo' is up to date.
make[2]: `bg.gmo' is up to date.
make[2]: `ca.gmo' is up to date.
make[2]: `da.gmo' is up to date.
make[2]: `de.gmo' is up to date.
make[2]: `el.gmo' is up to date.
make[2]: `eo.gmo' is up to date.

```



```
make[2]: `et.gmo' is up to date.
make[2]: `fi.gmo' is up to date.
make[2]: `fr.gmo' is up to date.
make[2]: `ga.gmo' is up to date.
make[2]: `gl.gmo' is up to date.
make[2]: `hr.gmo' is up to date.
make[2]: `hu.gmo' is up to date.
make[2]: `id.gmo' is up to date.
make[2]: `it.gmo' is up to date.
make[2]: `nl.gmo' is up to date.
make[2]: `pl.gmo' is up to date.
make[2]: `pt_BR.gmo' is up to date.
make[2]: `rm.gmo' is up to date.
make[2]: `ro.gmo' is up to date.
make[2]: `ru.gmo' is up to date.
make[2]: `sk.gmo' is up to date.
make[2]: `sl.gmo' is up to date.
make[2]: `sq.gmo' is up to date.
make[2]: `sr.gmo' is up to date.
make[2]: `sv.gmo' is up to date.
make[2]: `tr.gmo' is up to date.
make[2]: `uk.gmo' is up to date.
make[2]: `vi.gmo' is up to date.
make[2]: `wa.gmo' is up to date.
make[2]: `zh_CN.gmo' is up to date.
make[2]: `zh_TW.gmo' is up to date.
make[2]: Leaving directory `/home/milchstore/source/libiconv-1.13/po'
touch stamp-po
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/po'
cd man && make all
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/man'
make[1]: Nothing to be done for `all'.
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/man'
if test -d tests; then cd tests && make all; fi
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/tests'
make[1]: Nothing to be done for `all'.
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/tests'
cd libcharset && make install prefix='/home/milchstore/php5' exec_prefix='/home/
milchstore/php5' libdir='/home/milchstore/php5/lib'
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/libcharset'
cd lib && make install prefix='/home/milchstore/php5' exec_prefix='/home/milchst
ore/php5' libdir='/home/milchstore/php5/lib'
make[2]: Entering directory `/home/milchstore/source/libiconv-1.13/libcharset/li
b'
if test yes = no; then \
    case 'linux-gnu' in \
        darwin[56]*) \
            need_charset_alias=true ;; \
        darwin* | cygwin* | mingw* | pw32* | cegcc*) \
            need_charset_alias=false ;; \
```

```

        need_charset_alias=true ;; \
    esac ; \
else \
    need_charset_alias=false ; \
fi ; \
/bin/sh ../build-aux/mkinstalldirs /home/milchstore/php5/lib ; \
/bin/sh ../libtool --mode=install /usr/bin/install -c -m 644 libcharset.
la /home/milchstore/php5/lib/libcharset.la
mkdir -p -- /home/milchstore/php5/lib
libtool: install: /usr/bin/install -c -m 644 .libs/libcharset.so.1.0.0 /home/mil
chstore/php5/lib/libcharset.so.1.0.0
libtool: install: (cd /home/milchstore/php5/lib && { ln -s -f libcharset.so.1.0.
0 libcharset.so.1 || { rm -f libcharset.so.1 && ln -s libcharset.so.1.0.0 libcha
rset.so.1; }; })
libtool: install: (cd /home/milchstore/php5/lib && { ln -s -f libcharset.so.1.0.
0 libcharset.so || { rm -f libcharset.so && ln -s libcharset.so.1.0.0 libcharset
.so; }; })
libtool: install: /usr/bin/install -c -m 644 .libs/libcharset.lai /home/milchsto
re/php5/lib/libcharset.la
libtool: install: /usr/bin/install -c -m 644 .libs/libcharset.a /home/milchstore
/php5/lib/libcharset.a
libtool: install: chmod 644 /home/milchstore/php5/lib/libcharset.a
libtool: install: ranlib /home/milchstore/php5/lib/libcharset.a
libtool: finish: PATH="/home/milchstore/php5/bin:/usr/local/bin:/usr/bin:/bin:/u
sr/bin/X11:/usr/games:/sbin" ldconfig -n /home/milchstore/php5/lib
-----

```

Libraries have been installed in:
 /home/milchstore/php5/lib

If you ever happen to want to link against installed libraries in a given directory, LIBDIR, you must either use libtool, and specify the full pathname of the library, or use the '-LLIBDIR' flag during linking and do at least one of the following:

- add LIBDIR to the 'LD_LIBRARY_PATH' environment variable during execution
- add LIBDIR to the 'LD_RUN_PATH' environment variable during linking
- use the '-Wl,-rpath -Wl,LIBDIR' linker flag
- have your system administrator add LIBDIR to '/etc/ld.so.conf'

See any operating system documentation about shared libraries for more information, such as the ld(1) and ld.so(8) manual pages.

```

-----
if test -f /home/milchstore/php5/lib/charset.alias; then \
    sed -f ref-add.sed /home/milchstore/php5/lib/charset.alias > /home/mil
chstore/php5/lib/t-charset.alias; \
    /usr/bin/install -c -m 644 /home/milchstore/php5/lib/t-charset.alias /
home/milchstore/php5/lib/charset.alias; \
    rm -f /home/milchstore/php5/lib/t-charset.alias; \
else \

```

```

        sed -f ref-add.sed charset.alias > /home/milchstore/php5/lib/t-chars
et.alias; \
        /usr/bin/install -c -m 644 /home/milchstore/php5/lib/t-charset.alias
/home/milchstore/php5/lib/charset.alias; \
        rm -f /home/milchstore/php5/lib/t-charset.alias; \
    fi ; \
fi

```

```

make[2]: Leaving directory `/home/milchstore/source/libiconv-1.13/libcharset/lib
,

```

```

/bin/sh ./build-aux/mkinstalldirs /home/milchstore/php5/include
mkdir -p -- /home/milchstore/php5/include
/usr/bin/install -c -m 644 include/libcharset.h /home/milchstore/php5/include/li
bcharset.h

```

```

/usr/bin/install -c -m 644 include/localcharset.h.inst /home/milchstore/php5/inc
lude/localcharset.h

```

```

make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/libcharset'
cd lib && make install prefix='/home/milchstore/php5' exec_prefix='/home/milchst
ore/php5' libdir='/home/milchstore/php5/lib'

```

```

make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/lib'
if [ ! -d /home/milchstore/php5/lib ] ; then /bin/sh ../build-aux/mkinstalldirs
/home/milchstore/php5/lib ; fi

```

```

/bin/sh ../libtool --mode=install /usr/bin/install -c -m 644 libiconv.la /home/m
ilchstore/php5/lib/libiconv.la

```

```

libtool: install: /usr/bin/install -c -m 644 .libs/libiconv.so.2.5.0 /home/milch
store/php5/lib/libiconv.so.2.5.0

```

```

libtool: install: (cd /home/milchstore/php5/lib && { ln -s -f libiconv.so.2.5.0
libiconv.so.2 || { rm -f libiconv.so.2 && ln -s libiconv.so.2.5.0 libiconv.so.2;
}; })

```

```

libtool: install: (cd /home/milchstore/php5/lib && { ln -s -f libiconv.so.2.5.0
libiconv.so || { rm -f libiconv.so && ln -s libiconv.so.2.5.0 libiconv.so; }; })

```

```

libtool: install: /usr/bin/install -c -m 644 .libs/libiconv.lai /home/milchstore
/php5/lib/libiconv.la

```

```

libtool: finish: PATH="/home/milchstore/php5/bin:/usr/local/bin:/usr/bin:/bin:/u
sr/bin/X11:/usr/games:/sbin" ldconfig -n /home/milchstore/php5/lib

```

```

-----
Libraries have been installed in:
    /home/milchstore/php5/lib

```

If you ever happen to want to link against installed libraries in a given directory, LIBDIR, you must either use libtool, and specify the full pathname of the library, or use the `-LLIBDIR` flag during linking and do at least one of the following:

- add LIBDIR to the ``LD_LIBRARY_PATH'` environment variable during execution
- add LIBDIR to the ``LD_RUN_PATH'` environment variable during linking
- use the ``-Wl,-rpath -Wl,LIBDIR'` linker flag
- have your system administrator add LIBDIR to ``/etc/ld.so.conf'`

See any operating system documentation about shared libraries for

```

-----
case "linux-gnu" in \
    aix*) (cd /home/milchstore/php5/lib && \
        objects=`ar t libiconv.a` " "`ar t /lib/libiconv.a` && \
        ar x libiconv.a && ar x /lib/libiconv.a && \
        ar q libiconv.new.a $objects && \
        rm -f $objects && \
        mv -f libiconv.new.a libiconv.a) ;; \
    esac
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/lib'
cd preload && make install prefix='/home/milchstore/php5' exec_prefix='/home/milchstore/php5' libdir='/home/milchstore/php5/lib'
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/preload'
if [ ! -d /home/milchstore/php5/lib ] ; then /bin/sh ./build-aux/mkinstalldirs /home/milchstore/php5/lib ; fi
if test -n "preloadable_libiconv.so"; then /usr/bin/install -c -m 644 preloadable_libiconv.so /home/milchstore/php5/lib/preloadable_libiconv.so.new && mv /home/milchstore/php5/lib/preloadable_libiconv.so.new /home/milchstore/php5/lib/preloadable_libiconv.so ; fi
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/preload'
cd srclib && make install prefix='/home/milchstore/php5' exec_prefix='/home/milchstore/php5' libdir='/home/milchstore/php5/lib'
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/srclib'
make install-am
make[2]: Entering directory `/home/milchstore/source/libiconv-1.13/srclib'
make[3]: Entering directory `/home/milchstore/source/libiconv-1.13/srclib'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libiconv-1.13/srclib'
make[2]: Leaving directory `/home/milchstore/source/libiconv-1.13/srclib'
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/srclib'
cd src && make install prefix='/home/milchstore/php5' exec_prefix='/home/milchstore/php5' libdir='/home/milchstore/php5/lib'
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/src'
test `ls -ld . | sed -e 's/^d\(\.....\).*\/1/'` = rwxrwxrwx || chmod 777 .
if [ ! -d /home/milchstore/php5/bin ] ; then /bin/sh ../build-aux/mkinstalldirs /home/milchstore/php5/bin ; fi
mkdir -p -- /home/milchstore/php5/bin
case "linux-gnu" in \
    hpux*) gcc -g -O2 `if test -n ''; then /home/milchstore/php5/bin; fi` iconv.o ../srclib/libicrt.a -L/home/milchstore/php5/lib -liconv `if test -n ''; then echo " -Wl,+b -Wl,/home/milchstore/php5/lib"; fi` -o iconv;; \
    *) /bin/sh ../libtool --mode=link gcc -g -O2 `if test -n ''; then /home/milchstore/php5/bin; fi` iconv.o ../srclib/libicrt.a /home/milchstore/php5/lib/libiconv.la -o iconv;; \
    esac
libtool: link: gcc -g -O2 iconv.o -o iconv ../srclib/libicrt.a /home/milchstore/php5/lib/libiconv.so -Wl,-rpath -Wl,/home/milchstore/php5/lib -Wl,-rpath -Wl,/home/milchstore/php5/lib
/bin/sh ../libtool --mode=install /usr/bin/install -c iconv /home/milchstore/php

```

```
libtool: install: /usr/bin/install -c iconv /home/milchstore/php5/bin/iconv
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/src'
if [ ! -d /home/milchstore/php5/include ] ; then /bin/sh ./build-aux/mkinstalldi
rs /home/milchstore/php5/include ; fi
/usr/bin/install -c -m 644 include/iconv.h.inst /home/milchstore/php5/include/ic
onv.h
cd po && make install prefix='/home/milchstore/php5' exec_prefix='/home/milchsto
re/php5' datarootdir='/home/milchstore/php5/share' datadir='/home/milchstore/php
5/share'
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/po'
/bin/mkdir -p /home/milchstore/php5/share
installing af.gmo as /home/milchstore/php5/share/locale/af/LC_MESSAGES/libiconv.
mo
installing bg.gmo as /home/milchstore/php5/share/locale/bg/LC_MESSAGES/libiconv.
mo
installing ca.gmo as /home/milchstore/php5/share/locale/ca/LC_MESSAGES/libiconv.
mo
installing da.gmo as /home/milchstore/php5/share/locale/da/LC_MESSAGES/libiconv.
mo
installing de.gmo as /home/milchstore/php5/share/locale/de/LC_MESSAGES/libiconv.
mo
installing el.gmo as /home/milchstore/php5/share/locale/el/LC_MESSAGES/libiconv.
mo
installing eo.gmo as /home/milchstore/php5/share/locale/eo/LC_MESSAGES/libiconv.
mo
installing es.gmo as /home/milchstore/php5/share/locale/es/LC_MESSAGES/libiconv.
mo
installing et.gmo as /home/milchstore/php5/share/locale/et/LC_MESSAGES/libiconv.
mo
installing fi.gmo as /home/milchstore/php5/share/locale/fi/LC_MESSAGES/libiconv.
mo
installing fr.gmo as /home/milchstore/php5/share/locale/fr/LC_MESSAGES/libiconv.
mo
installing ga.gmo as /home/milchstore/php5/share/locale/ga/LC_MESSAGES/libiconv.
mo
installing gl.gmo as /home/milchstore/php5/share/locale/gl/LC_MESSAGES/libiconv.
mo
installing hr.gmo as /home/milchstore/php5/share/locale/hr/LC_MESSAGES/libiconv.
mo
installing hu.gmo as /home/milchstore/php5/share/locale/hu/LC_MESSAGES/libiconv.
mo
installing id.gmo as /home/milchstore/php5/share/locale/id/LC_MESSAGES/libiconv.
mo
installing it.gmo as /home/milchstore/php5/share/locale/it/LC_MESSAGES/libiconv.
mo
installing nl.gmo as /home/milchstore/php5/share/locale/nl/LC_MESSAGES/libiconv.
mo
installing pl.gmo as /home/milchstore/php5/share/locale/pl/LC_MESSAGES/libiconv.
mo
installing pt_BR.gmo as /home/milchstore/php5/share/locale/pt_BR/LC_MESSAGES/lib
```

```

installing rm.gmo as /home/milchstore/php5/share/locale/rm/LC_MESSAGES/libiconv.
mo
installing ro.gmo as /home/milchstore/php5/share/locale/ro/LC_MESSAGES/libiconv.
mo
installing ru.gmo as /home/milchstore/php5/share/locale/ru/LC_MESSAGES/libiconv.
mo
installing sk.gmo as /home/milchstore/php5/share/locale/sk/LC_MESSAGES/libiconv.
mo
installing sl.gmo as /home/milchstore/php5/share/locale/sl/LC_MESSAGES/libiconv.
mo
installing sq.gmo as /home/milchstore/php5/share/locale/sq/LC_MESSAGES/libiconv.
mo
installing sr.gmo as /home/milchstore/php5/share/locale/sr/LC_MESSAGES/libiconv.
mo
installing sv.gmo as /home/milchstore/php5/share/locale/sv/LC_MESSAGES/libiconv.
mo
installing tr.gmo as /home/milchstore/php5/share/locale/tr/LC_MESSAGES/libiconv.
mo
installing uk.gmo as /home/milchstore/php5/share/locale/uk/LC_MESSAGES/libiconv.
mo
installing vi.gmo as /home/milchstore/php5/share/locale/vi/LC_MESSAGES/libiconv.
mo
installing wa.gmo as /home/milchstore/php5/share/locale/wa/LC_MESSAGES/libiconv.
mo
installing zh_CN.gmo as /home/milchstore/php5/share/locale/zh_CN/LC_MESSAGES/lib
iconv.mo
installing zh_TW.gmo as /home/milchstore/php5/share/locale/zh_TW/LC_MESSAGES/lib
iconv.mo
if test "libiconv" = "gettext-tools"; then \
    /bin/mkdir -p /home/milchstore/php5/share/gettext/po; \
    for file in Makefile.in.in remove-potcdate.sin quot.sed boldquot.sed e
n@quot.header en@boldquot.header insert-header.sin Rules-quot    Makevars.templat
e; do \
        /usr/bin/install -c -m 644 ./\$file \
            /home/milchstore/php5/share/gettext/po/\$file; \
    done; \
    for file in Makevars; do \
        rm -f /home/milchstore/php5/share/gettext/po/\$file; \
    done; \
else \
    : ; \
fi
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/po'
cd man && make install prefix='/home/milchstore/php5' exec_prefix='/home/milchst
ore/php5' datarootdir='/home/milchstore/php5/share' datadir='/home/milchstore/ph
p5/share' mandir='/home/milchstore/php5/share/man'
make[1]: Entering directory `/home/milchstore/source/libiconv-1.13/man'
if [ ! -d /home/milchstore/php5/share/man/man1 ] ; then /bin/sh ../build-aux/mki
nstalldirs /home/milchstore/php5/share/man/man1 ; fi
mkdir -p -- /home/milchstore/php5/share/man/man1

```

```
ll -c -m 644 ./ $f /home/milchstore/php5/share/man/man1/$f ; /usr/bin/install -c
-m 644 ./ $f /home/milchstore/php5/share/man/man1/$f) ; done
/usr/bin/install -c -m 644 ./iconv.1 /home/milchstore/php5/share/man/man1/iconv.
1
if [ ! -d /home/milchstore/php5/share/man/man3 ] ; then /bin/sh ../build-aux/mki
nstalldirs /home/milchstore/php5/share/man/man3 ; fi
mkdir -p -- /home/milchstore/php5/share/man/man3
builddir="`pwd`"; cd . && for f in *.3 ; do (cd "$builddir"; echo /usr/bin/insta
ll -c -m 644 ./ $f /home/milchstore/php5/share/man/man3/$f ; /usr/bin/install -c
-m 644 ./ $f /home/milchstore/php5/share/man/man3/$f) ; done
/usr/bin/install -c -m 644 ./iconv.3 /home/milchstore/php5/share/man/man3/iconv.
3
/usr/bin/install -c -m 644 ./iconv_close.3 /home/milchstore/php5/share/man/man3/i
conv_close.3
/usr/bin/install -c -m 644 ./iconv_open.3 /home/milchstore/php5/share/man/man3/i
conv_open.3
/usr/bin/install -c -m 644 ./iconv_open_into.3 /home/milchstore/php5/share/man/m
an3/iconv_open_into.3
/usr/bin/install -c -m 644 ./iconvctl.3 /home/milchstore/php5/share/man/man3/ico
nvctl.3
if [ ! -d /home/milchstore/php5/share/doc/libiconv ] ; then /bin/sh ../build-aux
/mkinstalldirs /home/milchstore/php5/share/doc/libiconv ; fi
mkdir -p -- /home/milchstore/php5/share/doc/libiconv
builddir="`pwd`"; cd . && for f in *.html ; do (cd "$builddir"; echo /usr/bin/in
stall -c -m 644 ./ $f /home/milchstore/php5/share/doc/libiconv/$f ; /usr/bin/inst
all -c -m 644 ./ $f /home/milchstore/php5/share/doc/libiconv/$f) ; done
/usr/bin/install -c -m 644 ./iconv.1.html /home/milchstore/php5/share/doc/libico
nv/iconv.1.html
/usr/bin/install -c -m 644 ./iconv.3.html /home/milchstore/php5/share/doc/libico
nv/iconv.3.html
/usr/bin/install -c -m 644 ./iconv_close.3.html /home/milchstore/php5/share/doc/l
ibiconv/iconv_close.3.html
/usr/bin/install -c -m 644 ./iconv_open.3.html /home/milchstore/php5/share/doc/l
ibiconv/iconv_open.3.html
/usr/bin/install -c -m 644 ./iconv_open_into.3.html /home/milchstore/php5/share/
doc/libiconv/iconv_open_into.3.html
/usr/bin/install -c -m 644 ./iconvctl.3.html /home/milchstore/php5/share/doc/lib
iconv/iconvctl.3.html
make[1]: Leaving directory `/home/milchstore/source/libiconv-1.13/man'
checking build system type... x86_64-unknown-linux-gnu
checking host system type... x86_64-unknown-linux-gnu
checking for a BSD-compatible install... /usr/bin/install -c
checking whether build environment is sane... yes
checking for a thread-safe mkdir -p... /bin/mkdir -p
checking for gawk... gawk
checking whether make sets $(MAKE)... yes
checking for gcc... gcc
checking for C compiler default output file name... a.out
checking whether the C compiler works... yes
checking whether we are cross compiling... no
```

checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ISO C89... none needed
checking for style of include used by make... GNU
checking dependency style of gcc... gcc3
checking for a BSD-compatible install... /usr/bin/install -c
checking how to run the C preprocessor... gcc -E
checking for rm... /bin/rm
checking for mv... /bin/mv
checking for tar... /bin/tar
checking for perl... /usr/local/bin/perl
checking for wget... /usr/bin/wget
checking for xmllint... /usr/bin/xmllint
checking for xsltproc... /usr/bin/xsltproc
checking for function prototypes... yes
checking for grep that handles long lines and -e... /bin/grep
checking for egrep... /bin/grep -E
checking for ANSI C header files... yes
checking for sys/types.h... yes
checking for sys/stat.h... yes
checking for stdlib.h... yes
checking for string.h... yes
checking for memory.h... yes
checking for strings.h... yes
checking for inttypes.h... yes
checking for stdint.h... yes
checking for unistd.h... yes
checking for string.h... (cached) yes
checking for a sed that does not truncate output... /bin/sed
checking for ld used by gcc... /usr/bin/ld
checking if the linker (/usr/bin/ld) is GNU ld... yes
checking for /usr/bin/ld option to reload object files... -r
checking for BSD-compatible nm... /usr/bin/nm -B
checking whether ln -s works... yes
checking how to recognize dependent libraries... pass_all
checking dlfcn.h usability... yes
checking dlfcn.h presence... yes
checking for dlfcn.h... yes
checking for g++... g++
checking whether we are using the GNU C++ compiler... yes
checking whether g++ accepts -g... yes
checking dependency style of g++... gcc3
checking how to run the C++ preprocessor... g++ -E
checking for g77... g77
checking whether we are using the GNU Fortran 77 compiler... yes
checking whether g77 accepts -g... yes
checking the maximum length of command line arguments... 98304
checking command to parse /usr/bin/nm -B output from gcc object... ok
checking for objdir... .libs

checking for ranlib... ranlib
checking for strip... strip
checking if gcc supports -fno-rtti -fno-exceptions... no
checking for gcc option to produce PIC... -fPIC
checking if gcc PIC flag -fPIC works... yes
checking if gcc static flag -static works... yes
checking if gcc supports -c -o file.o... yes
checking whether the gcc linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking whether -lc should be explicitly linked in... no
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
checking whether stripping libraries is possible... yes
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries... yes
configure: creating libtool
appending configuration tag "CXX" to libtool
checking for ld used by g++... /usr/bin/ld -m elf_x86_64
checking if the linker (/usr/bin/ld -m elf_x86_64) is GNU ld... yes
checking whether the g++ linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking for g++ option to produce PIC... -fPIC
checking if g++ PIC flag -fPIC works... yes
checking if g++ static flag -static works... yes
checking if g++ supports -c -o file.o... yes
checking whether the g++ linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
appending configuration tag "F77" to libtool
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries... yes
checking for g77 option to produce PIC... -fPIC
checking if g77 PIC flag -fPIC works... yes
checking if g77 static flag -static works... yes
checking if g77 supports -c -o file.o... yes
checking whether the g77 linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
Checking zlib
checking zlib.h usability... yes
checking zlib.h presence... yes
checking for zlib.h... yes
checking for gzread in -lz... yes
Checking headers
checking for dirent.h that defines DIR... yes
checking for library containing opendir... none required

checking fcntl.h usability... yes
checking fcntl.h presence... yes
checking for fcntl.h... yes
checking for unistd.h... (cached) yes
checking ctype.h usability... yes
checking ctype.h presence... yes
checking for ctype.h... yes
checking dirent.h usability... yes
checking dirent.h presence... yes
checking for dirent.h... yes
checking errno.h usability... yes
checking errno.h presence... yes
checking for errno.h... yes
checking malloc.h usability... yes
checking malloc.h presence... yes
checking for malloc.h... yes
checking stdarg.h usability... yes
checking stdarg.h presence... yes
checking for stdarg.h... yes
checking for sys/stat.h... (cached) yes
checking for sys/types.h... (cached) yes
checking for stdint.h... (cached) yes
checking inttypes.h usability... no
checking inttypes.h presence... no
checking for inttypes.h... no
checking time.h usability... yes
checking time.h presence... yes
checking for time.h... yes
checking ansidecl.h usability... no
checking ansidecl.h presence... no
checking for ansidecl.h... no
checking ieee754.h usability... no
checking ieee754.h presence... no
checking for ieee754.h... no
checking nan.h usability... no
checking nan.h presence... no
checking for nan.h... no
checking math.h usability... yes
checking math.h presence... yes
checking for math.h... yes
checking limits.h usability... yes
checking limits.h presence... yes
checking for limits.h... yes
checking fp_class.h usability... no
checking fp_class.h presence... no
checking for fp_class.h... no
checking float.h usability... yes
checking float.h presence... yes
checking for float.h... yes
checking for stdlib.h... (cached) yes

checking for netinet/in.h... yes
checking for arpa/inet.h... yes
checking netdb.h usability... yes
checking netdb.h presence... yes
checking for netdb.h... yes
checking sys/time.h usability... yes
checking sys/time.h presence... yes
checking for sys/time.h... yes
checking sys/select.h usability... yes
checking sys/select.h presence... yes
checking for sys/select.h... yes
checking sys/mman.h usability... yes
checking sys/mman.h presence... yes
checking for sys/mman.h... yes
checking sys/timeb.h usability... yes
checking sys/timeb.h presence... yes
checking for sys/timeb.h... yes
checking signal.h usability... yes
checking signal.h presence... yes
checking for signal.h... yes
checking for arpa/nameser.h... yes
checking for resolv.h... yes
checking dl.h usability... no
checking dl.h presence... no
checking for dl.h... no
checking for dlfcn.h... (cached) yes
Checking libraries
checking for strftime... yes
checking for strdup... yes
checking for strndup... yes
checking for strerror... yes
checking for finite... yes
checking for isnand... no
checking for fp_class... no
checking for class... no
checking for fpclass... no
checking for strftime... (cached) yes
checking for localtime... yes
checking for gettimeofday... yes
checking for ftime... yes
checking for stat... yes
checking for _stat... no
checking for signal... yes
checking for printf... yes
checking for sprintf... yes
checking for fprintf... yes
checking for snprintf... yes
checking for vfprintf... yes
checking for vsprintf... yes
checking for vsnprintf... yes

```
checking for va_copy... yes
checking for library containing gethostent... none required
checking for library containing setsockopt... none required
checking for library containing connect... none required
checking for type of socket length (socklen_t)... socklen_t *
checking whether to enable IPv6... yes
checking struct sockaddr::ss_family... yes
checking for getaddrinfo... yes
checking for isnan... yes
checking for isinf... yes
checking for python... /usr/bin/python
Found Python version 2.4
checking for shl_load... no
checking for shl_load in -ldld... no
checking for dlopen... no
checking for dlopen in -ldl... yes
Checking configuration requirements
Enabling multithreaded support
checking pthread.h usability... yes
checking pthread.h presence... yes
checking for pthread.h... yes
checking for pthread_join in -lpthread... yes
checking iconv.h usability... yes
checking iconv.h presence... yes
checking for iconv.h... yes
checking for iconv... no
checking for iconv in -liconv... yes
checking for iconv declaration...
    extern size_t iconv (iconv_t cd, char * *inbuf, size_t *inbytesleft, ch
ar * *outbuf, size_t *outbytesleft);
Enabled Schematron support
Enabled Schemas/Relax-NG support
Disabling code coverage for GCC
configure: creating ./config.status
config.status: creating libxml2.spec
config.status: creating Makefile
config.status: creating include/Makefile
config.status: creating include/libxml/Makefile
config.status: creating doc/Makefile
config.status: creating doc/examples/Makefile
config.status: creating doc/devhelp/Makefile
config.status: creating example/Makefile
config.status: creating python/Makefile
config.status: creating python/tests/Makefile
config.status: creating xstc/Makefile
config.status: creating include/libxml/xmlversion.h
config.status: creating xml2-config
config.status: creating libxml-2.0.pc
config.status: creating libxml-2.0-uninstalled.pc
config.status: creating python/setup.py
```

```
config.status: executing depfiles commands
Done configuring
make all-recursive
make[1]: Entering directory `/home/milchstore/source/libxml2-2.7.3'
Making all in include
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3/include'
Making all in libxml
make[3]: Entering directory `/home/milchstore/source/libxml2-2.7.3/include/libxml
l'
make[3]: Nothing to be done for `all'.
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/include/libxml
'
make[3]: Entering directory `/home/milchstore/source/libxml2-2.7.3/include'
make[3]: Nothing to be done for `all-am'.
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/include'
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/include'
Making all in .
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3'
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT SAX.lo -MD -MP -MF .deps/
SAX.Tpo -c -o SAX.lo SAX.c
mkdir .libs
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT SAX.lo -MD -MP -MF .deps/SAX.Tpo -c SAX.c -fPIC -DPIC -o .libs/SAX.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT SAX.lo -MD -MP -MF .deps/SAX.Tpo -c SAX.c -o SAX.o >/dev/null 2>&1
mv -f .deps/SAX.Tpo .deps/SAX.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT entities.lo -MD -MP -MF .
deps/entities.Tpo -c -o entities.lo entities.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
```

```
ls -MT entities.lo -MD -MP -MF .deps/entities.Tpo -c entities.c -fPIC -DPIC -o
.libs/entities.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT entities.lo -MD -MP -MF .deps/entities.Tpo -c entities.c -o entities.o >/
dev/null 2>&1
mv -f .deps/entities.Tpo .deps/entities.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W
-Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT encoding.lo -MD -MP -MF .
deps/encoding.Tpo -c -o encoding.lo encoding.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT encoding.lo -MD -MP -MF .deps/encoding.Tpo -c encoding.c -fPIC -DPIC -o
.libs/encoding.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT encoding.lo -MD -MP -MF .deps/encoding.Tpo -c encoding.c -o encoding.o >/
dev/null 2>&1
mv -f .deps/encoding.Tpo .deps/encoding.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W
-Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT error.lo -MD -MP -MF .dep
s/error.Tpo -c -o error.lo error.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT error.lo -MD -MP -MF .deps/error.Tpo -c error.c -fPIC -DPIC -o .libs/err
or.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
```

```
ls -MT error.lo -MD -MP -MF .deps/error.Tpo -c error.c -o error.o >/dev/null 2>&
1
mv -f .deps/error.Tpo .deps/error.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT parserInternals.lo -MD -M
P -MF .deps/parserInternals.Tpo -c -o parserInternals.lo parserInternals.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Ws
witch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT parserInternals.lo -MD -MP -MF .deps/parserInternals.Tpo -c parserIntern
als.c -fPIC -DPIC -o .libs/parserInternals.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Ws
witch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT parserInternals.lo -MD -MP -MF .deps/parserInternals.Tpo -c parserIntern
als.c -o parserInternals.o >/dev/null 2>&1
mv -f .deps/parserInternals.Tpo .deps/parserInternals.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT parser.lo -MD -MP -MF .de
ps/parser.Tpo -c -o parser.lo parser.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Ws
witch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT parser.lo -MD -MP -MF .deps/parser.Tpo -c parser.c -fPIC -DPIC -o .libs/
parser.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Ws
witch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT parser.lo -MD -MP -MF .deps/parser.Tpo -c parser.c -o parser.o >/dev/null
2>&1
mv -f .deps/parser.Tpo .deps/parser.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
```

```
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT tree.lo -MD -MP -MF .deps/tree.Tpo -c -o tree.lo tree.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT tree.lo -MD -MP -MF .deps/tree.Tpo -c tree.c -fPIC -DPIC -o .libs/tree.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT tree.lo -MD -MP -MF .deps/tree.Tpo -c tree.c -o tree.o >/dev/null 2>&1
```

```
mv -f .deps/tree.Tpo .deps/tree.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT hash.lo -MD -MP -MF .deps/hash.Tpo -c -o hash.lo hash.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT hash.lo -MD -MP -MF .deps/hash.Tpo -c hash.c -fPIC -DPIC -o .libs/hash.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT hash.lo -MD -MP -MF .deps/hash.Tpo -c hash.c -o hash.o >/dev/null 2>&1
```

```
mv -f .deps/hash.Tpo .deps/hash.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT list.lo -MD -MP -MF .deps/list.Tpo -c -o list.lo list.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT list.lo -MD -MP -MF .deps/list.Tpo -c list.c -fPIC -DPIC -o .libs/list.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
```



```
witch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT list.lo -MD -MP -MF .deps/list.Tpo -c list.c -o list.o >/dev/null 2>&1
mv -f .deps/list.Tpo .deps/list.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlIO.lo -MD -MP -MF .deps/xmlIO.Tpo -c -o xmlIO.lo xmlIO.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlIO.lo -MD -MP -MF .deps/xmlIO.Tpo -c xmlIO.c -fPIC -DPIC -o .libs/xmlIO.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlIO.lo -MD -MP -MF .deps/xmlIO.Tpo -c xmlIO.c -o xmlIO.o >/dev/null 2>&1
mv -f .deps/xmlIO.Tpo .deps/xmlIO.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlmemory.lo -MD -MP -MF .deps/xmlmemory.Tpo -c -o xmlmemory.lo xmlmemory.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlmemory.lo -MD -MP -MF .deps/xmlmemory.Tpo -c xmlmemory.c -fPIC -DPIC -o .libs/xmlmemory.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlmemory.lo -MD -MP -MF .deps/xmlmemory.Tpo -c xmlmemory.c -o xmlmemory.o >/dev/null 2>&1
mv -f .deps/xmlmemory.Tpo .deps/xmlmemory.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
```

```
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT uri.lo -MD -MP -MF .deps/uri.Tpo -c -o uri.lo uri.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT uri.lo -MD -MP -MF .deps/uri.Tpo -c uri.c -fPIC -DPIC -o .libs/uri.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT uri.lo -MD -MP -MF .deps/uri.Tpo -c uri.c -o uri.o >/dev/null 2>&1
```

```
mv -f .deps/uri.Tpo .deps/uri.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT valid.lo -MD -MP -MF .deps/valid.Tpo -c -o valid.lo valid.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT valid.lo -MD -MP -MF .deps/valid.Tpo -c valid.c -fPIC -DPIC -o .libs/valid.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT valid.lo -MD -MP -MF .deps/valid.Tpo -c valid.c -o valid.o >/dev/null 2>&1
```

```
mv -f .deps/valid.Tpo .deps/valid.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xlink.lo -MD -MP -MF .deps/xlink.Tpo -c -o xlink.lo xlink.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
```

```
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decl  
ls -MT xlink.lo -MD -MP -MF .deps/xlink.Tpo -c xlink.c -fPIC -DPIC -o .libs/xli  
nk.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore  
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw  
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth  
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W  
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decl  
ls -MT xlink.lo -MD -MP -MF .deps/xlink.Tpo -c xlink.c -o xlink.o >/dev/null 2>&  
1
```

```
mv -f .deps/xlink.Tpo .deps/xlink.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include  
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -  
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo  
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W  
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot  
otypes -Wnested-externs -Winline -Wredundant-decls -MT HTMLparser.lo -MD -MP -MF  
.deps/HTMLparser.Tpo -c -o HTMLparser.lo HTMLparser.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore  
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw  
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth  
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W  
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decl  
ls -MT HTMLparser.lo -MD -MP -MF .deps/HTMLparser.Tpo -c HTMLparser.c -fPIC -DP  
IC -o .libs/HTMLparser.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore  
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw  
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth  
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W  
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decl  
ls -MT HTMLparser.lo -MD -MP -MF .deps/HTMLparser.Tpo -c HTMLparser.c -o HTMLpar  
ser.o >/dev/null 2>&1
```

```
mv -f .deps/HTMLparser.Tpo .deps/HTMLparser.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include  
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -  
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo  
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W  
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot  
otypes -Wnested-externs -Winline -Wredundant-decls -MT HTMLtree.lo -MD -MP -MF .  
deps/HTMLtree.Tpo -c -o HTMLtree.lo HTMLtree.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore  
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw  
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth  
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W  
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decl  
ls -MT HTMLtree.lo -MD -MP -MF .deps/HTMLtree.Tpo -c HTMLtree.c -fPIC -DPIC -o  
.libs/HTMLtree.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore  
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw  
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
```

```
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decl  
ls -MT HTMLtree.lo -MD -MP -MF .deps/HTMLtree.Tpo -c HTMLtree.c -o HTMLtree.o >/  
dev/null 2>&1
```

```
mv -f .deps/HTMLtree.Tpo .deps/HTMLtree.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include  
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -  
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo  
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W  
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot  
otypes -Wnested-externs -Winline -Wredundant-decls -MT debugXML.lo -MD -MP -MF .  
deps/debugXML.Tpo -c -o debugXML.lo debugXML.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore  
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -W  
switch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth  
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W  
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec  
ls -MT debugXML.lo -MD -MP -MF .deps/debugXML.Tpo -c debugXML.c -fPIC -DPIC -o  
.libs/debugXML.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore  
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -W  
switch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth  
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W  
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec  
ls -MT debugXML.lo -MD -MP -MF .deps/debugXML.Tpo -c debugXML.c -o debugXML.o >/  
dev/null 2>&1
```

```
mv -f .deps/debugXML.Tpo .deps/debugXML.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include  
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -  
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo  
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W  
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot  
otypes -Wnested-externs -Winline -Wredundant-decls -MT xpath.lo -MD -MP -MF .dep  
s/xpath.Tpo -c -o xpath.lo xpath.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore  
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -W  
switch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth  
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W  
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec  
ls -MT xpath.lo -MD -MP -MF .deps/xpath.Tpo -c xpath.c -fPIC -DPIC -o .libs/xpa  
th.o
```

```
xpath.c: In function 'xmlXPathRegisterFuncNS__internal_alias':
```

```
xpath.c:4756: warning: ISO C forbids passing argument 4 of 'xmlHashAddEntry2__in  
ternal_alias' between function pointer and 'void *'
```

```
xpath.c: In function 'xmlXPathFunctionLookupNS__internal_alias':
```

```
xpath.c:4837: warning: ISO C forbids assignment between function pointer and 'vo  
id *'
```

```
xpath.c: In function 'xmlXPathCompOpEval':
```

```
xpath.c:13368: warning: ISO C forbids assignment between function pointer and 'v  
oid *'
```

```
xpath.c:13393: warning: ISO C forbids assignment between function pointer and 'v
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xpath.lo -MD -MP -MF .deps/xpath.Tpo -c xpath.c -o xpath.o >/dev/null 2>&1
```

```
mv -f .deps/xpath.Tpo .deps/xpath.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xpointer.lo -MD -MP -MF .deps/xpointer.Tpo -c -o xpointer.lo xpointer.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xpointer.lo -MD -MP -MF .deps/xpointer.Tpo -c xpointer.c -fPIC -DPIC -o .libs/xpointer.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xpointer.lo -MD -MP -MF .deps/xpointer.Tpo -c xpointer.c -o xpointer.o >/dev/null 2>&1
```

```
mv -f .deps/xpointer.Tpo .deps/xpointer.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xinclude.lo -MD -MP -MF .deps/xinclude.Tpo -c -o xinclude.lo xinclude.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xinclude.lo -MD -MP -MF .deps/xinclude.Tpo -c xinclude.c -fPIC -DPIC -o .libs/xinclude.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xinclude.lo -MD -MP -MF .deps/xinclude.Tpo -c xinclude.c -o xinclude.o >/
```

```
mv -f .deps/xinclude.Tpo .deps/xinclude.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT nanohttp.lo -MD -MP -MF .
deps/nanohttp.Tpo -c -o nanohttp.lo nanohttp.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT nanohttp.lo -MD -MP -MF .deps/nanohttp.Tpo -c nanohttp.c -fPIC -DPIC -o
.libs/nanohttp.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT nanohttp.lo -MD -MP -MF .deps/nanohttp.Tpo -c nanohttp.c -o nanohttp.o >/
dev/null 2>&1
mv -f .deps/nanohttp.Tpo .deps/nanohttp.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT nanoftp.lo -MD -MP -MF .d
eps/nanoftp.Tpo -c -o nanoftp.lo nanoftp.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT nanoftp.lo -MD -MP -MF .deps/nanoftp.Tpo -c nanoftp.c -fPIC -DPIC -o .li
bs/nanoftp.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT nanoftp.lo -MD -MP -MF .deps/nanoftp.Tpo -c nanoftp.c -o nanoftp.o >/dev/
null 2>&1
mv -f .deps/nanoftp.Tpo .deps/nanoftp.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
```

```
.deps/DOCBparser.Tpo -c -o DOCBparser.lo DOCBparser.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT DOCBparser.lo -MD -MP -MF .deps/DOCBparser.Tpo -c DOCBparser.c -fPIC -DP
IC -o .libs/DOCBparser.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT DOCBparser.lo -MD -MP -MF .deps/DOCBparser.Tpo -c DOCBparser.c -o DOCBpar
ser.o >/dev/null 2>&1
mv -f .deps/DOCBparser.Tpo .deps/DOCBparser.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W
-Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT catalog.lo -MD -MP -MF .d
eps/catalog.Tpo -c -o catalog.lo catalog.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT catalog.lo -MD -MP -MF .deps/catalog.Tpo -c catalog.c -fPIC -DPIC -o .li
bs/catalog.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT catalog.lo -MD -MP -MF .deps/catalog.Tpo -c catalog.c -o catalog.o >/dev/
null 2>&1
mv -f .deps/catalog.Tpo .deps/catalog.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W
-Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT globals.lo -MD -MP -MF .d
eps/globals.Tpo -c -o globals.lo globals.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
```

bs/globals.o

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT globals.lo -MD -MP -MF .deps/globals.Tpo -c globals.c -o globals.o >/dev/null 2>&1
```

```
mv -f .deps/globals.Tpo .deps/globals.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT threads.lo -MD -MP -MF .deps/threads.Tpo -c -o threads.lo threads.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT threads.lo -MD -MP -MF .deps/threads.Tpo -c threads.c -fPIC -DPIC -o .libs/threads.o
```

```
threads.c:57: warning: redundant redeclaration of 'pthread_once'
```

```
/usr/include/pthread.h:423: warning: previous declaration of 'pthread_once' was here
```

```
threads.c:59: warning: redundant redeclaration of 'pthread_getspecific'
```

```
/usr/include/pthread.h:936: warning: previous declaration of 'pthread_getspecific' was here
```

```
threads.c:62: warning: redundant redeclaration of 'pthread_setspecific'
```

```
/usr/include/pthread.h:940: warning: previous declaration of 'pthread_setspecific' was here
```

```
threads.c:65: warning: redundant redeclaration of 'pthread_key_create'
```

```
/usr/include/pthread.h:930: warning: previous declaration of 'pthread_key_create' was here
```

```
threads.c:67: warning: redundant redeclaration of 'pthread_key_delete'
```

```
/usr/include/pthread.h:933: warning: previous declaration of 'pthread_key_delete' was here
```

```
threads.c:69: warning: function declaration isn't a prototype
```

```
threads.c:69: warning: redundant redeclaration of 'pthread_mutex_init'
```

```
/usr/include/pthread.h:677: warning: previous declaration of 'pthread_mutex_init' was here
```

```
threads.c:71: warning: function declaration isn't a prototype
```

```
threads.c:71: warning: redundant redeclaration of 'pthread_mutex_destroy'
```

```
/usr/include/pthread.h:680: warning: previous declaration of 'pthread_mutex_destroy' was here
```

```
threads.c:73: warning: function declaration isn't a prototype
```

```
threads.c:73: warning: redundant redeclaration of 'pthread_mutex_lock'
```

```
/usr/include/pthread.h:686: warning: previous declaration of 'pthread_mutex_lock' was here
```



```
threads.c:75: warning: redundant redeclaration of 'pthread_mutex_unlock'
/usr/include/pthread.h:696: warning: previous declaration of 'pthread_mutex_unlo
ck' was here
threads.c:77: warning: function declaration isn't a prototype
threads.c:77: warning: redundant redeclaration of 'pthread_cond_init'
/usr/include/pthread.h:806: warning: previous declaration of 'pthread_cond_init'
was here
threads.c:79: warning: function declaration isn't a prototype
threads.c:79: warning: redundant redeclaration of 'pthread_cond_destroy'
/usr/include/pthread.h:809: warning: previous declaration of 'pthread_cond_destr
oy' was here
threads.c:81: warning: function declaration isn't a prototype
threads.c:81: warning: redundant redeclaration of 'pthread_cond_wait'
/usr/include/pthread.h:823: warning: previous declaration of 'pthread_cond_wait'
was here
threads.c:83: warning: function declaration isn't a prototype
threads.c:83: warning: redundant redeclaration of 'pthread_equal'
/usr/include/pthread.h:240: warning: previous declaration of 'pthread_equal' was
here
threads.c:85: warning: function declaration isn't a prototype
threads.c:85: warning: redundant redeclaration of 'pthread_self'
/usr/include/pthread.h:237: warning: previous declaration of 'pthread_self' was
here
threads.c:87: warning: function declaration isn't a prototype
threads.c:87: warning: redundant redeclaration of 'pthread_key_create'
threads.c:65: warning: previous declaration of 'pthread_key_create' was here
threads.c:89: warning: function declaration isn't a prototype
threads.c:89: warning: redundant redeclaration of 'pthread_key_delete'
threads.c:67: warning: previous declaration of 'pthread_key_delete' was here
threads.c:91: warning: function declaration isn't a prototype
threads.c:91: warning: redundant redeclaration of 'pthread_cond_signal'
/usr/include/pthread.h:812: warning: previous declaration of 'pthread_cond_signa
l' was here
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT threads.lo -MD -MP -MF .deps/threads.Tpo -c threads.c -o threads.o >/dev/
null 2>&1
mv -f .deps/threads.Tpo .deps/threads.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W
-Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT c14n.lo -MD -MP -MF .deps
/c14n.Tpo -c -o c14n.lo c14n.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
```

```
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT c14n.lo -MD -MP -MF .deps/c14n.Tpo -c c14n.c -fPIC -DPIC -o .libs/c14n.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenteses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT c14n.lo -MD -MP -MF .deps/c14n.Tpo -c c14n.c -o c14n.o >/dev/null 2>&1
mv -f .deps/c14n.Tpo .deps/c14n.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenteses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlstring.lo -MD -MP -MF .deps/xmlstring.Tpo -c -o xmlstring.lo xmlstring.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenteses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlstring.lo -MD -MP -MF .deps/xmlstring.Tpo -c xmlstring.c -fPIC -DPIC -o .libs/xmlstring.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenteses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlstring.lo -MD -MP -MF .deps/xmlstring.Tpo -c xmlstring.c -o xmlstring.o >/dev/null 2>&1
mv -f .deps/xmlstring.Tpo .deps/xmlstring.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenteses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlregexp.lo -MD -MP -MF .deps/xmlregexp.Tpo -c -o xmlregexp.lo xmlregexp.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenteses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlregexp.lo -MD -MP -MF .deps/xmlregexp.Tpo -c xmlregexp.c -fPIC -DPIC -o .libs/xmlregexp.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenteses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
```

```
ls -MT xmlregexp.lo -MD -MP -MF .deps/xmlregexp.Tpo -c xmlregexp.c -o xmlregexp.o >/dev/null 2>&1
mv -f .deps/xmlregexp.Tpo .deps/xmlregexp.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlschemas.lo -MD -MP -MF .deps/xmlschemas.Tpo -c -o xmlschemas.lo xmlschemas.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlschemas.lo -MD -MP -MF .deps/xmlschemas.Tpo -c xmlschemas.c -fPIC -DPIC -o .libs/xmlschemas.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlschemas.lo -MD -MP -MF .deps/xmlschemas.Tpo -c xmlschemas.c -o xmlschemas.o >/dev/null 2>&1
mv -f .deps/xmlschemas.Tpo .deps/xmlschemas.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlschematypes.lo -MD -MP -MF .deps/xmlschematypes.Tpo -c -o xmlschematypes.lo xmlschematypes.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlschematypes.lo -MD -MP -MF .deps/xmlschematypes.Tpo -c xmlschematypes.c -fPIC -DPIC -o .libs/xmlschematypes.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlschematypes.lo -MD -MP -MF .deps/xmlschematypes.Tpo -c xmlschematypes.c -o xmlschematypes.o >/dev/null 2>&1
mv -f .deps/xmlschematypes.Tpo .deps/xmlschematypes.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
```

```
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlunicode.lo -MD -MP -MF .deps/xmlunicode.Tpo -c -o xmlunicode.lo xmlunicode.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlunicode.lo -MD -MP -MF .deps/xmlunicode.Tpo -c xmlunicode.c -fPIC -DPIC -o .libs/xmlunicode.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlunicode.lo -MD -MP -MF .deps/xmlunicode.Tpo -c xmlunicode.c -o xmlunicode.o >/dev/null 2>&1
mv -f .deps/xmlunicode.Tpo .deps/xmlunicode.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlreader.lo -MD -MP -MF .deps/xmlreader.Tpo -c -o xmlreader.lo xmlreader.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlreader.lo -MD -MP -MF .deps/xmlreader.Tpo -c xmlreader.c -fPIC -DPIC -o .libs/xmlreader.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlreader.lo -MD -MP -MF .deps/xmlreader.Tpo -c xmlreader.c -o xmlreader.o >/dev/null 2>&1
mv -f .deps/xmlreader.Tpo .deps/xmlreader.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT relaxng.lo -MD -MP -MF .deps/relaxng.Tpo -c -o relaxng.lo relaxng.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses
```

```
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decl  
ls -MT relaxng.lo -MD -MP -MF .deps/relaxng.Tpo -c relaxng.c -fPIC -DPIC -o .li  
bs/relaxng.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore  
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw  
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth  
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W  
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decl  
ls -MT relaxng.lo -MD -MP -MF .deps/relaxng.Tpo -c relaxng.c -o relaxng.o >/dev/  
null 2>&1
```

```
mv -f .deps/relaxng.Tpo .deps/relaxng.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include  
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -  
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo  
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W  
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot  
otypes -Wnested-externs -Winline -Wredundant-decls -MT dict.lo -MD -MP -MF .deps  
/dict.Tpo -c -o dict.lo dict.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore  
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw  
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth  
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W  
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decl  
ls -MT dict.lo -MD -MP -MF .deps/dict.Tpo -c dict.c -fPIC -DPIC -o .libs/dict.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore  
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw  
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth  
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W  
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decl  
ls -MT dict.lo -MD -MP -MF .deps/dict.Tpo -c dict.c -o dict.o >/dev/null 2>&1
```

```
mv -f .deps/dict.Tpo .deps/dict.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include  
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -  
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo  
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W  
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot  
otypes -Wnested-externs -Winline -Wredundant-decls -MT SAX2.lo -MD -MP -MF .deps  
/SAX2.Tpo -c -o SAX2.lo SAX2.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore  
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw  
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth  
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W  
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decl  
ls -MT SAX2.lo -MD -MP -MF .deps/SAX2.Tpo -c SAX2.c -fPIC -DPIC -o .libs/SAX2.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore  
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw  
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth  
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W  
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decl  
ls -MT SAX2.lo -MD -MP -MF .deps/SAX2.Tpo -c SAX2.c -o SAX2.o >/dev/null 2>&1
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT xmlwriter.lo -MD -MP -MF
.deps/xmlwriter.Tpo -c -o xmlwriter.lo xmlwriter.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Ws
witch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT xmlwriter.lo -MD -MP -MF .deps/xmlwriter.Tpo -c xmlwriter.c -fPIC -DPIC
-o .libs/xmlwriter.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Ws
witch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT xmlwriter.lo -MD -MP -MF .deps/xmlwriter.Tpo -c xmlwriter.c -o xmlwriter.
o >/dev/null 2>&1
mv -f .deps/xmlwriter.Tpo .deps/xmlwriter.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT legacy.lo -MD -MP -MF .de
ps/legacy.Tpo -c -o legacy.lo legacy.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Ws
witch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT legacy.lo -MD -MP -MF .deps/legacy.Tpo -c legacy.c -fPIC -DPIC -o .libs/
legacy.o
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Ws
witch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT legacy.lo -MD -MP -MF .deps/legacy.Tpo -c legacy.c -o legacy.o >/dev/null
2>&1
mv -f .deps/legacy.Tpo .deps/legacy.Plo
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -
W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT chvalid.lo -MD -MP -MF .d
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT chvalid.lo -MD -MP -MF .deps/chvalid.Tpo -c chvalid.c -fPIC -DPIC -o libs/chvalid.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT chvalid.lo -MD -MP -MF .deps/chvalid.Tpo -c chvalid.c -o chvalid.o >/dev/null 2>&1
```

```
mv -f .deps/chvalid.Tpo .deps/chvalid.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT pattern.lo -MD -MP -MF .deps/pattern.Tpo -c -o pattern.lo pattern.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT pattern.lo -MD -MP -MF .deps/pattern.Tpo -c pattern.c -fPIC -DPIC -o libs/pattern.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT pattern.lo -MD -MP -MF .deps/pattern.Tpo -c pattern.c -o pattern.o >/dev/null 2>&1
```

```
mv -f .deps/pattern.Tpo .deps/pattern.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlsave.lo -MD -MP -MF .deps/xmlsave.Tpo -c -o xmlsave.lo xmlsave.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlsave.lo -MD -MP -MF .deps/xmlsave.Tpo -c xmlsave.c -fPIC -DPIC -o li
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT xmlsave.lo -MD -MP -MF .deps/xmlsave.Tpo -c xmlsave.c -o xmlsave.o >/dev/
null 2>&1
```

```
mv -f .deps/xmlsave.Tpo .deps/xmlsave.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W
-Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT xmlmodule.lo -MD -MP -MF
.deps/xmlmodule.Tpo -c -o xmlmodule.lo xmlmodule.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT xmlmodule.lo -MD -MP -MF .deps/xmlmodule.Tpo -c xmlmodule.c -fPIC -DPIC
-o .libs/xmlmodule.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT xmlmodule.lo -MD -MP -MF .deps/xmlmodule.Tpo -c xmlmodule.c -o xmlmodule.
o >/dev/null 2>&1
```

```
mv -f .deps/xmlmodule.Tpo .deps/xmlmodule.Plo
```

```
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W
-Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot
otypes -Wnested-externs -Winline -Wredundant-decls -MT schematron.lo -MD -MP -MF
.deps/schematron.Tpo -c -o schematron.lo schematron.c
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT schematron.lo -MD -MP -MF .deps/schematron.Tpo -c schematron.c -fPIC -DP
IC -o .libs/schematron.o
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wsw
itch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec
ls -MT schematron.lo -MD -MP -MF .deps/schematron.Tpo -c schematron.c -o schemat
```



```

mv -f .deps/schematron.Tpo .deps/schematron.Plo
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wun-
sed -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-sub-
cripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwri-
te-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-
externs -Winline -Wredundant-decls -version-info 9:3:7 -ldl -o libxml2.la -rpat-
h /home/milchstore/php5/lib SAX.lo entities.lo encoding.lo error.lo parserIntern-
als.lo parser.lo tree.lo hash.lo list.lo xmlIO.lo xmlmemory.lo uri.lo valid.lo x-
link.lo HTMLparser.lo HTMLtree.lo debugXML.lo xpath.lo xpointer.lo xinclude.lo n-
anohttp.lo nanoftp.lo DOCBparser.lo catalog.lo globals.lo threads.lo c14n.lo xml-
string.lo xmlregexp.lo xmlschemas.lo xmlschematypes.lo xmlunicode.lo xmlreader-
.lo relaxng.lo dict.lo SAX2.lo xmlwriter.lo legacy.lo chvalid.lo pattern.lo xmlsa-
ve.lo xmlmodule.lo schematron.lo -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -shared .libs/SAX.o .libs/entities.o .libs/encoding.o .libs/error.o .libs/p-
arserInternals.o .libs/parser.o .libs/tree.o .libs/hash.o .libs/list.o .libs/xml-
IO.o .libs/xmlmemory.o .libs/uri.o .libs/valid.o .libs/xlink.o .libs/HTMLparser-
.o .libs/HTMLtree.o .libs/debugXML.o .libs/xpath.o .libs/xpointer.o .libs/xinclud-
e.o .libs/nanohttp.o .libs/nanoftp.o .libs/DOCBparser.o .libs/catalog.o .libs/gl-
obals.o .libs/threads.o .libs/c14n.o .libs/xmlstring.o .libs/xmlregexp.o .libs/x-
mlschemas.o .libs/xmlschematypes.o .libs/xmlunicode.o .libs/xmlreader.o .libs/r-
elaxng.o .libs/dict.o .libs/SAX2.o .libs/xmlwriter.o .libs/legacy.o .libs/chvali-
d.o .libs/pattern.o .libs/xmlsave.o .libs/xmlmodule.o .libs/schematron.o -Wl,--
rpath -Wl,/home/milchstore/php5/lib -Wl,--rpath -Wl,/home/milchstore/php5/lib -l-
dl -lz -L/home/milchstore/php5/lib /home/milchstore/php5/lib/libiconv.so -lm -W-
l,-soname -Wl,libxml2.so.2 -o .libs/libxml2.so.2.7.3
(cd .libs && rm -f libxml2.so.2 && ln -s libxml2.so.2.7.3 libxml2.so.2)
(cd .libs && rm -f libxml2.so && ln -s libxml2.so.2.7.3 libxml2.so)
ar cru .libs/libxml2.a SAX.o entities.o encoding.o error.o parserInternals.o pa-
rser.o tree.o hash.o list.o xmlIO.o xmlmemory.o uri.o valid.o xlink.o HTMLparser-
.o HTMLtree.o debugXML.o xpath.o xpointer.o xinclude.o nanohttp.o nanoftp.o DOCB-
parser.o catalog.o globals.o threads.o c14n.o xmlstring.o xmlregexp.o xmlschemas-
.o xmlschematypes.o xmlunicode.o xmlreader.o relaxng.o dict.o SAX2.o xmlwriter-
.o legacy.o chvalid.o pattern.o xmlsave.o xmlmodule.o schematron.o
ranlib .libs/libxml2.a
creating libxml2.la
(cd .libs && rm -f libxml2.la && ln -s ../libxml2.la libxml2.la)
/bin/sh ./libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I./include
-I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W
-Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wfo-
rmat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -W-
cast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prot-
otypes -Wnested-externs -Winline -Wredundant-decls -MT testdso.lo -MD -MP -MF .d-
eps/testdso.Tpo -c -o testdso.lo testdso.c
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore-
/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Ws-
witch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenth-
eses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -W-
strict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-dec-
ls -MT testdso.lo -MD -MP -MF .deps/testdso.Tpo -c testdso.c -fPIC -DPIC -o .li-
bs/testdso.o

```

```

/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testdso.lo -MD -MP -MF .deps/testdso.Tpo -c testdso.c -o testdso.o >/dev/null 2>&1
mv -f .deps/testdso.Tpo .deps/testdso.Plo
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -module -rpath /home/milchstore/php5/lib -o testdso.la testdso.lo
gcc -shared .libs/testdso.o -Wl,-soname -Wl,testdso.so.0 -o .libs/testdso.so.0.0.0
(cd .libs && rm -f testdso.so.0 && ln -s testdso.so.0.0.0 testdso.so.0)
(cd .libs && rm -f testdso.so && ln -s testdso.so.0.0.0 testdso.so)
ar cru .libs/testdso.a testdso.o
ranlib .libs/testdso.a
creating testdso.la
(cd .libs && rm -f testdso.la && ln -s ../testdso.la testdso.la)
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlLint.o -MD -MP -MF .deps/xmlLint.Tpo -c -o xmlLint.o xmlLint.c
mv -f .deps/xmlLint.Tpo .deps/xmlLint.Po
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o xmlLint xmlLint.o ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/xmlLint xmlLint.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating xmlLint
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xmlCatalog.o -MD -MP -MF .deps/xmlCatalog.Tpo -c -o xmlCatalog.o xmlCatalog.c
mv -f .deps/xmlCatalog.Tpo .deps/xmlCatalog.Po

```

```
sed -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o xmlcatalog xmlcatalog.o ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/xmlcatalog xmlcatalog.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
```

creating xmlcatalog

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testSchemas.o -MD -MP -MF .deps/testSchemas.Tpo -c -o testSchemas.o testSchemas.c
```

```
mv -f .deps/testSchemas.Tpo .deps/testSchemas.Po
```

```
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testSchemas testSchemas.o ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testSchemas testSchemas.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
```

creating testSchemas

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testRelax.o -MD -MP -MF .deps/testRelax.Tpo -c -o testRelax.o testRelax.c
```

```
mv -f .deps/testRelax.Tpo .deps/testRelax.Po
```

```
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testRelax testRelax.o ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wco
```

```
dow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testRelax testRelax.o ../libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
```

creating testRelax

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testSAX.o -MD -MP -MF .deps/testSAX.Tpo -c -o testSAX.o testSAX.c mv -f .deps/testSAX.Tpo .deps/testSAX.Po
```

```
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testSAX testSAX.o ../libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testSAX testSAX.o ../libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
```

creating testSAX

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testHTML.o -MD -MP -MF .deps/testHTML.Tpo -c -o testHTML.o testHTML.c mv -f .deps/testHTML.Tpo .deps/testHTML.Po
```

```
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testHTML testHTML.o ../libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testHTML testHTML.o ../libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
```

creating testHTML

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type
```

```
entheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return  
-Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant  
-decls -MT testXPath.o -MD -MP -MF .deps/testXPath.Tpo -c -o testXPath.o testXP  
ath.c
```

```
mv -f .deps/testXPath.Tpo .deps/testXPath.Po
```

```
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wun  
used -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subs  
cripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwri  
te-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-  
externs -Winline -Wredundant-decls -o testXPath testXPath.o ./libxml2.la -lz  
-L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wco  
mment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wsha  
dow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-pro  
totypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .lib  
s/testXPath testXPath.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz  
/home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php  
5/lib
```

```
creating testXPath
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchst  
ore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type  
-Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wpar  
entheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-retur  
n -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant  
-decls -MT testURI.o -MD -MP -MF .deps/testURI.Tpo -c -o testURI.o testURI.c
```

```
mv -f .deps/testURI.Tpo .deps/testURI.Po
```

```
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wun  
used -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subs  
cripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwri  
te-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-  
externs -Winline -Wredundant-decls -o testURI testURI.o ./libxml2.la -lz -L/h  
ome/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wco  
mment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wsha  
dow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-pro  
totypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .lib  
s/testURI testURI.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /ho  
me/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/li  
b
```

```
creating testURI
```

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchst  
ore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type  
-Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wpar  
entheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-retur  
n -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant  
-decls -MT testThreads.o -MD -MP -MF .deps/testThreads.Tpo -c -o testThreads.o t  
estThreads.c
```

```
mv -f .deps/testThreads.Tpo .deps/testThreads.Po
```

```
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wun  
used -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subs
```

```
te-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testThreads testThreads.o -lpthread ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testThreads testThreads.o -lpthread ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating testThreads
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testC14N.o -MD -MP -MF .deps/testC14N.Tpo -c -o testC14N.o testC14N.c
mv -f .deps/testC14N.Tpo .deps/testC14N.Po
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testC14N testC14N.o ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testC14N testC14N.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating testC14N
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testAutomata.o -MD -MP -MF .deps/testAutomata.Tpo -c -o testAutomata.o testAutomata.c
mv -f .deps/testAutomata.Tpo .deps/testAutomata.Po
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testAutomata testAutomata.o ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .lib
```

```
ib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating testAutomata
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testRegexp.o -MD -MP -MF .deps/testRegexp.Tpo -c -o testRegexp.o testRegexp.c
mv -f .deps/testRegexp.Tpo .deps/testRegexp.Po
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testRegexp testRegexp.o ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testRegexp testRegexp.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating testRegexp
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testReader.o -MD -MP -MF .deps/testReader.Tpo -c -o testReader.o testReader.c
mv -f .deps/testReader.Tpo .deps/testReader.Po
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testReader testReader.o ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testReader testReader.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating testReader
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wpar
```

```
n -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testapi.o -MD -MP -MF .deps/testapi.Tpo -c -o testapi.o testapi.c
testapi.c: In function 'test_xmlBufferSetAllocationScheme':
testapi.c:18831: warning: comparison of distinct pointer types lacks a cast
testapi.c: At top level:
testapi.c:18047: warning: 'gen_xmlSchematronPtr' defined but not used
testapi.c:18050: warning: 'des_xmlSchematronPtr' defined but not used
testapi.c:18067: warning: 'gen_xmlSchematronParserCtxtPtr' defined but not used
testapi.c:18070: warning: 'des_xmlSchematronParserCtxtPtr' defined but not used
testapi.c:34166: warning: 'gen_xmlSAXHandlerPtr_ptr' defined but not used
testapi.c:34169: warning: 'des_xmlSAXHandlerPtr_ptr' defined but not used
mv -f .deps/testapi.Tpo .deps/testapi.Po
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testapi testapi.o ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testapi testapi.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating testapi
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testModule.o -MD -MP -MF .deps/testModule.Tpo -c -o testModule.o testModule.c
mv -f .deps/testModule.Tpo .deps/testModule.Po
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testModule testModule.o ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testModule testModule.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating testModule
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type
```



```
entheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-retur
n -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant
-decls -MT runtest.o -MD -MP -MF .deps/runtest.Tpo -c -o runtest.o runtest.c
mv -f .deps/runtest.Tpo .deps/runtest.Po
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunu
sed -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subs
cripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwri
te-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-
externs -Winline -Wredundant-decls -o runtest runtest.o -lpthread ./libxml2.l
a -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wco
mment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wsha
dow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-pro
totypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .lib
s/runtest runtest.o -lpthread ./libs/libxml2.so -ldl -L/home/milchstore/php5/l
ib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchsto
re/php5/lib
creating runtest
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchst
ore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type
-Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wpar
entheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-retur
n -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant
-decls -MT runsuite.o -MD -MP -MF .deps/runsuite.Tpo -c -o runsuite.o runsuite.c
mv -f .deps/runsuite.Tpo .deps/runsuite.Po
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunu
sed -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subs
cripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwri
te-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-
externs -Winline -Wredundant-decls -o runsuite runsuite.o ./libxml2.la -lz -L
/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wco
mment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wsha
dow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-pro
totypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .lib
s/runsuite runsuite.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /
home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/
lib
creating runsuite
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchst
ore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type
-Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wpar
entheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-retur
n -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant
-decls -MT testchar.o -MD -MP -MF .deps/testchar.Tpo -c -o testchar.o testchar.c
mv -f .deps/testchar.Tpo .deps/testchar.Po
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunu
sed -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subs
cripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwri
te-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-
```

```
/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testchar testchar.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating testchar
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testdict.o -MD -MP -MF .deps/testdict.Tpo -c -o testdict.o testdict.c
mv -f .deps/testdict.Tpo .deps/testdict.Po
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testdict testdict.o ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testdict testdict.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating testdict
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT runxmlconf.o -MD -MP -MF .deps/runxmlconf.Tpo -c -o runxmlconf.o runxmlconf.c
mv -f .deps/runxmlconf.Tpo .deps/runxmlconf.Po
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o runxmlconf runxmlconf.o ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/runxmlconf runxmlconf.o ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/p
```

creating runxmlconf

```
gcc -DHAVE_CONFIG_H -I. -I./include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testrecurse.o -MD -MP -MF .deps/testrecurse.Tpo -c -o testrecurse.o testrecurse.c
```

```
mv -f .deps/testrecurse.Tpo .deps/testrecurse.Po
```

```
/bin/sh ./libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testrecurse testrecurse.o -lpthread ./libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testrecurse testrecurse.o -lpthread ./libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
```

creating testrecurse

```
sed -e 's?\@XML_LIBDIR\@?-L/home/milchstore/php5/lib?g' \  
-e 's?\@XML_INCLUDEDIR\@?-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include?g' \  
-e 's?\@VERSION\@?2.7.3?g' \  
-e 's?\@XML_LIBS\@?-lxml2 -lz -L/home/milchstore/php5/lib -liconv -lm ?g' \  
    < ./xml2Conf.sh.in > xml2Conf.tmp \  
    && mv xml2Conf.tmp xml2Conf.sh
```

```
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3'
```

Making all in doc

```
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3/doc'
```

Making all in devhelp

```
make[3]: Entering directory `/home/milchstore/source/libxml2-2.7.3/doc/devhelp'
```

```
make[3]: Nothing to be done for `all'.
```

```
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/doc/devhelp'
```

Making all in examples

```
make[3]: Entering directory `/home/milchstore/source/libxml2-2.7.3/doc/examples'
```

```
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..../include -I../..../include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xpath2.o -MD -MP -MF .deps/xpath2.Tpo -c -o xpath2.o xpath2.c
```

```
mv -f .deps/xpath2.Tpo .deps/xpath2.Po
```

```
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-
```

```
Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o xpath2 xpath2.o ../../libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
mkdir .libs
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/xpath2 xpath2.o ../../.libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating xpath2
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..include -I../..include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT reader1.o -MD -MP -MF .deps/reader1.Tpo -c -o reader1.o reader1.c
mv -f .deps/reader1.Tpo .deps/reader1.Po
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o reader1 reader1.o ../../libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/reader1 reader1.o ../../.libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating reader1
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..include -I../..include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT reader4.o -MD -MP -MF .deps/reader4.Tpo -c -o reader4.o reader4.c
mv -f .deps/reader4.Tpo .deps/reader4.Po
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o reader4 reader4.o ../../libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow
```

```
totypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/reader4 reader4.o ../../libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
```

creating reader4

```
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..include -I../..include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT parse2.o -MD -MP -MF .deps/parse2.Tpo -c -o parse2.o parse2.c
```

```
mv -f .deps/parse2.Tpo .deps/parse2.Po
```

```
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o parse2 parse2.o ../../libs/libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/parse2 parse2.o ../../libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
```

creating parse2

```
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..include -I../..include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT reader2.o -MD -MP -MF .deps/reader2.Tpo -c -o reader2.o reader2.c
```

```
mv -f .deps/reader2.Tpo .deps/reader2.Po
```

```
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o reader2 reader2.o ../../libs/libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/reader2 reader2.o ../../libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
```

creating reader2

```
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..include -I../..include -I./include -D_
```

```
ed -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subsc
ripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrit
e-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-e
xterns -Winline -Wredundant-decls -MT parse3.o -MD -MP -MF .deps/parse3.Tpo -c -
o parse3.o parse3.c
```

```
mv -f .deps/parse3.Tpo .deps/parse3.Po
```

```
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -
Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-
subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -
Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnes
ted-externs -Winline -Wredundant-decls -o parse3 parse3.o ../../libxml2.la -l
z -L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wco
mment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wsha
dow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-pro
totypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .lib
s/parse3 parse3.o ../../libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /
home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/
lib
```

```
creating parse3
```

```
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..include -I../..include -I./include -D_
REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunus
ed -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subsc
ripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrit
e-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-e
xterns -Winline -Wredundant-decls -MT reader3.o -MD -MP -MF .deps/reader3.Tpo -c
-o reader3.o reader3.c
```

```
mv -f .deps/reader3.Tpo .deps/reader3.Po
```

```
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -
Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-
subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -
Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnes
ted-externs -Winline -Wredundant-decls -o reader3 reader3.o ../../libxml2.la
-lz -L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wco
mment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wsha
dow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-pro
totypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .lib
s/reader3 reader3.o ../../libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz
/home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php
5/lib
```

```
creating reader3
```

```
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..include -I../..include -I./include -D_
REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunus
ed -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subsc
ripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrit
e-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-e
xterns -Winline -Wredundant-decls -MT tree2.o -MD -MP -MF .deps/tree2.Tpo -c -o
tree2.o tree2.c
```

```
mv -f .deps/tree2.Tpo .deps/tree2.Po
```

```
Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-
subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -
Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnes
ted-externs -Winline -Wredundant-decls -o tree2 tree2.o ../../libxml2.la -lz
-L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wco
mment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wsha
dow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-pro
totypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .lib
s/tree2 tree2.o ../../libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /ho
me/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/li
b
```

creating tree2

```
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..include -I../..include -I./include -D_
REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunus
ed -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subsc
ripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrit
e-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-e
xterns -Winline -Wredundant-decls -MT parse4.o -MD -MP -MF .deps/parse4.Tpo -c -
o parse4.o parse4.c
```

```
mv -f .deps/parse4.Tpo .deps/parse4.Po
```

```
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -
Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-
subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -
Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnes
ted-externs -Winline -Wredundant-decls -o parse4 parse4.o ../../libxml2.la -lz
-L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wco
mment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wsha
dow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-pro
totypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .lib
s/parse4 parse4.o ../../libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /
home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/
lib
```

creating parse4

```
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..include -I../..include -I./include -D_
REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunus
ed -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subsc
ripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrit
e-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-e
xterns -Winline -Wredundant-decls -MT io2.o -MD -MP -MF .deps/io2.Tpo -c -o io2.
o io2.c
```

```
mv -f .deps/io2.Tpo .deps/io2.Po
```

```
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -
Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-
subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -
Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnes
ted-externs -Winline -Wredundant-decls -o io2 io2.o ../../libxml2.la -lz -L/h
ome/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wco
```

```
dow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/io2 io2.o ../../libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib creating io2
```

```
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..include -I../..include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT testWriter.o -MD -MP -MF .deps/testWriter.Tpo -c -o testWriter.o testWriter.c
```

```
testWriter.c: In function 'testXmlwriterFilename':
```

```
testWriter.c:163: warning: format '%010d' expects type 'int', but argument 4 has type 'long int'
```

```
testWriter.c: In function 'testXmlwriterMemory':
```

```
testWriter.c:442: warning: format '%010d' expects type 'int', but argument 4 has type 'long int'
```

```
testWriter.c: In function 'testXmlwriterDoc':
```

```
testWriter.c:712: warning: format '%010d' expects type 'int', but argument 4 has type 'long int'
```

```
testWriter.c: In function 'testXmlwriterTree':
```

```
testWriter.c:978: warning: format '%010d' expects type 'int', but argument 4 has type 'long int'
```

```
mv -f .deps/testWriter.Tpo .deps/testWriter.Po
```

```
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o testWriter testWriter.o ../../libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
```

```
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/testWriter testWriter.o ../../libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib creating testWriter
```

```
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..include -I../..include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT io1.o -MD -MP -MF .deps/io1.Tpo -c -o io1.o io1.c
```

```
mv -f .deps/io1.Tpo .deps/io1.Po
```

```
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -
```



```
ted-externs -Winline -Wredundant-decls -o io1 io1.o ../../libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/io1 io1.o ../../.libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating io1
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..include -I../..include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT xpath1.o -MD -MP -MF .deps/xpath1.Tpo -c -o xpath1.o xpath1.c
mv -f .deps/xpath1.Tpo .deps/xpath1.Po
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o xpath1 xpath1.o ../../libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/xpath1 xpath1.o ../../.libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating xpath1
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..include -I../..include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT parse1.o -MD -MP -MF .deps/parse1.Tpo -c -o parse1.o parse1.c
mv -f .deps/parse1.Tpo .deps/parse1.Po
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o parse1 parse1.o ../../libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/parse1 parse1.o ../../.libs/libxml2.so -ldl -L/home/milchstore/php5/lib -lz /
```

```
lib
creating parse1
gcc -DHAVE_CONFIG_H -I. -I../.. -I../..../include -I../..../include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT tree1.o -MD -MP -MF .deps/tree1.Tpo -c -o tree1.o tree1.c
mv -f .deps/tree1.Tpo .deps/tree1.Po
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o tree1 tree1.o ../libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .libs/tree1 tree1.o ../libxml2.so -ldl -L/home/milchstore/php5/lib -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating tree1
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/doc/examples'
make[3]: Entering directory `/home/milchstore/source/libxml2-2.7.3/doc'
make[3]: Nothing to be done for `all-am'.
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/doc'
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/doc'
Making all in example
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3/example'
gcc -DHAVE_CONFIG_H -I. -I.. -I../include -I../include -I./include -D_REENTRANT -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT gjobread.o -MD -MP -MF .deps/gjobread.Tpo -c -o gjobread.o gjobread.c
mv -f .deps/gjobread.Tpo .deps/gjobread.Po
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o gjobread gjobread.o ../libxml2.la -lz -L/home/milchstore/php5/lib -liconv -lm
mkdir .libs
gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -o .lib
```

```
/home/milchstore/php5/lib/libconv.so -lm -Wl,--rpath -Wl,/home/milchstore/php5
/lib
creating gjobread
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/example'
Making all in xstc
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3/xstc'
make[2]: Nothing to be done for `all'.
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/xstc'
Making all in python
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3/python'
Making all in .
make[3]: Entering directory `/home/milchstore/source/libxml2-2.7.3/python'
/usr/bin/python ./generator.py .
/usr/lib/python2.4/xmllib.py:9: DeprecationWarning: The xmllib module is obsolet
e. Use xml.sax instead.
  warnings.warn("The xmllib module is obsolete. Use xml.sax instead.", Deprecat
ionWarning)
Found 1604 functions in libxml2-api.xml
Found 55 functions in libxml2-python-api.xml
Generated 886 wrapper functions, 557 failed, 216 skipped
```

Missing type converters:

```
xmlRelaxNGValidityErrorFunc *:2 xmlXPathObjectPtr:22 const htmlEntityDesc *:2
xmlOutputMatchCallback:1 xmlElementContentPtr *:1 xmlStructuredErrorFunc:5 x
mlSchematronValidCtxtPtr:3 xmlParserInputBufferCreateFilenameFunc:2 xmlSchemaV
alType:2 size_t:1 xmlEnumerationPtr:5 xmlSchemaWildcardPtr:1 xmlXIncludeCtxt
Ptr:4 xmlRelaxNGValidityErrorFunc:2 xmlSAXHandler *:4 ...:1 xmlShellReadline
Func:1 xmlDict *:1 xmlAutomataPtr:19 unsigned long:1 xmlParserInputPtr:17 x
mlCatalogAllow:2 xmlExpNodePtr:3 xmlElementContent *:1 xmlCharEncodingOutputF
unc:1 xmlDictPtr:10 xmlTextWriterPtr:77 const htmlElemDesc *:1 xmlChRangeGro
up *:1 xmlIDPtr:1 xmlSchemaValPtr:13 xmlInputMatchCallback:1 xmlElementTable
Ptr:2 xmlChar **:16 xmlXPathCompExprPtr:6 xmlTextReaderErrorFunc:1 xmlExtern
alEntityLoader:2 xmlNotationTablePtr:2 xmlXPathVariableLookupFunc:1 xmlParser
NodeInfoPtr:1 xmlExpCtxtPtr:14 xmlPatternPtr:8 xmlC14NIsVisibleCallback:1 xm
lDeregisterNodeFunc:2 va_list:1 xmlSchemaTypePtr:9 htmlStatus:1 xmlRegisterN
odeFunc:2 xmlAttributeType:2 xmlRefPtr:1 xmlCharEncodingHandler *:4 xmlNotat
ionPtr:3 xmlSaveCtxtPtr:8 xmlRegExecCallbacks:1 xmlNsPtr *:1 xmlLocationSetP
tr:6 xmlSchemaSAXPlugPtr:1 xmlModulePtr:4 xmlEnumerationPtr *:2 xmlShellCtxt
Ptr:10 xlinkNodeDetectFunc:2 xmlRefTablePtr:1 xmlStreamCtxtPtr:6 xmlSchemaVa
lidityErrorFunc *:2 xmlAttributeTablePtr:2 xmlSchematronParserCtxtPtr:5 xmlCa
talogPrefer:1 xmlParserNodeInfoSeqPtr:3 xmlSchematronPtr:2 xmlNodePtr *:2 xm
lInputReadCallback:7 char **:5 xmlCharEncoding:13 xmlRegExecCtxtPtr:5 xmlEle
mentContentType:2 void *:86 xmlTextReaderErrorFunc *:1 xmlSAXHandlerPtr *:1
xmlEntityReferenceFunc:1 xmlDocPtr *:1 xmlBufferAllocationScheme:3 xmlSchemaV
alidityErrorFunc:2 xmlDOMWrapCtxtPtr:6 xmlOutputWriteCallback:2 xmlSchemaFace
tPtr:7 xlinkHandlerPtr:2 xmlXPathFuncLookupFunc:1 htmlElemDesc *:3 xmlCharEn
codingHandlerPtr:7 xmlCharEncodingInputFunc:1 xmlFeature:1 const xmlParserNod
eInfo *:1 xmlNodeSetPtr:32 xmlEntitiesTablePtr:3 xmlIDTablePtr:1 xmlXPathFun
ction:4 xmlOutputBufferCreateFilenameFunc:2 xmlElementContentPtr:8 xmlElement
TypeVal:1 xlinkType:1 xmlGenericErrorFunc *:1
```

```
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I/usr
/include/python2.4 -I../include -I../include -I../python -I/home/milchstore/php
5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswit
ch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparenthese
s -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstr
ict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls
-MT libxml.lo -MD -MP -MF .deps/libxml.Tpo -c -o libxml.lo libxml.c
mkdir .libs
gcc -DHAVE_CONFIG_H -I. -I.. -I/usr/include/python2.4 -I../include -I../include
-I../python -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunus
ed -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subsc
ripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrit
e-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-e
xterns -Winline -Wredundant-decls -MT libxml.lo -MD -MP -MF .deps/libxml.Tpo -c
libxml.c -fPIC -DPIC -o .libs/libxml.o
In file included from /usr/include/python2.4/Python.h:82,
    from libxml.c:14:
/usr/include/python2.4/intobject.h:41: warning: ISO C90 does not support 'long l
ong'
In file included from /usr/include/python2.4/Python.h:84,
    from libxml.c:14:
/usr/include/python2.4/longobject.h:37: warning: ISO C90 does not support 'long
long'
/usr/include/python2.4/longobject.h:38: warning: ISO C90 does not support 'long
long'
/usr/include/python2.4/longobject.h:39: warning: ISO C90 does not support 'long
long'
/usr/include/python2.4/longobject.h:40: warning: ISO C90 does not support 'long
long'
/usr/include/python2.4/longobject.h:41: warning: ISO C90 does not support 'long
long'
libxml.c: In function 'libxml_xmlValidCtxtGenericErrorHandler':
libxml.c:1748: warning: unused parameter 'severity'
libxml.c: In function 'libxml_xmlValidCtxtGenericWarningFuncHandler':
libxml.c:1775: warning: unused parameter 'severity'
libxml.c: At top level:
libxml.c:2677: warning: no previous prototype for 'libxml_xmlNodeRemoveNsDef'
libxml.c: In function 'libxml_serializeNode':
libxml.c:2764: warning: unused variable 'len'
gcc -DHAVE_CONFIG_H -I. -I.. -I/usr/include/python2.4 -I../include -I../include
-I../python -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunus
ed -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subsc
ripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrit
e-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-e
xterns -Winline -Wredundant-decls -MT libxml.lo -MD -MP -MF .deps/libxml.Tpo -c
libxml.c -o libxml.o >/dev/null 2>&1
mv -f .deps/libxml.Tpo .deps/libxml.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I/usr
/include/python2.4 -I../include -I../include -I../python -I/home/milchstore/php
5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswit
```

```
s -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT types.lo -MD -MP -MF .deps/types.Tpo -c -o types.lo types.c
gcc -DHAVE_CONFIG_H -I. -I.. -I/usr/include/python2.4 -I../include -I../include -I../python -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT types.lo -MD -MP -MF .deps/types.Tpo -c types.c -fPIC -DPIC -o .libs/types.o
In file included from /usr/include/python2.4/Python.h:82,
    from libxml_wrap.h:1,
    from types.c:9:
/usr/include/python2.4/intobject.h:41: warning: ISO C90 does not support 'long long'
In file included from /usr/include/python2.4/Python.h:84,
    from libxml_wrap.h:1,
    from types.c:9:
/usr/include/python2.4/longobject.h:37: warning: ISO C90 does not support 'long long'
/usr/include/python2.4/longobject.h:38: warning: ISO C90 does not support 'long long'
/usr/include/python2.4/longobject.h:39: warning: ISO C90 does not support 'long long'
/usr/include/python2.4/longobject.h:40: warning: ISO C90 does not support 'long long'
/usr/include/python2.4/longobject.h:41: warning: ISO C90 does not support 'long long'
gcc -DHAVE_CONFIG_H -I. -I.. -I/usr/include/python2.4 -I../include -I../include -I../python -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT types.lo -MD -MP -MF .deps/types.Tpo -c types.c -o types.o >/dev/null 2>&1
mv -f .deps/types.Tpo .deps/types.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I/usr/include/python2.4 -I../include -I../include -I../python -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT libxml2-py.lo -MD -MP -MF .deps/libxml2-py.Tpo -c -o libxml2-py.lo libxml2-py.c
gcc -DHAVE_CONFIG_H -I. -I.. -I/usr/include/python2.4 -I../include -I../include -I../python -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-decls -MT libxml2-py.lo -MD -MP -MF .deps/libxml2-py
```

```
In file included from /usr/include/python2.4/Python.h:82,
    from libxml2-py.c:3:
/usr/include/python2.4/intobject.h:41: warning: ISO C90 does not support 'long l
ong'
In file included from /usr/include/python2.4/Python.h:84,
    from libxml2-py.c:3:
/usr/include/python2.4/longobject.h:37: warning: ISO C90 does not support 'long
long'
/usr/include/python2.4/longobject.h:38: warning: ISO C90 does not support 'long
long'
/usr/include/python2.4/longobject.h:39: warning: ISO C90 does not support 'long
long'
/usr/include/python2.4/longobject.h:40: warning: ISO C90 does not support 'long
long'
/usr/include/python2.4/longobject.h:41: warning: ISO C90 does not support 'long
long'
gcc -DHAVE_CONFIG_H -I. -I.. -I/usr/include/python2.4 -I../include -I../include
-I../python -I/home/milchstore/php5/include -g -O2 -pedantic -W -Wformat -Wunus
ed -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subsc
ripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwrit
e-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested-e
xterns -Winline -Wredundant-decls -MT libxml2-py.lo -MD -MP -MF .deps/libxml2-py
.Tpo -c libxml2-py.c -o libxml2-py.o >/dev/null 2>&1
mv -f .deps/libxml2-py.Tpo .deps/libxml2-py.Plo
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -pedantic -W -Wformat -Wun
used -Wimplicit -Wreturn-type -Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-sub
scripts -Wuninitialized -Wparentheses -Wshadow -Wpointer-arith -Wcast-align -Wwr
ite-strings -Waggregate-return -Wstrict-prototypes -Wmissing-prototypes -Wnested
-externs -Winline -Wredundant-decls -module -avoid-version -o libxml2mod.la -r
path /home/milchstore/php5/lib/python2.4/site-packages libxml.lo types.lo libxml
2-py.lo ../libxml2.la
gcc -shared .libs/libxml.lo .libs/types.o .libs/libxml2-py.o -Wl,--rpath -Wl,/h
ome/milchstore/source/libxml2-2.7.3/.libs -Wl,--rpath -Wl,/home/milchstore/php5/
lib ../.libs/libxml2.so -L/home/milchstore/php5/lib -Wl,-soname -Wl,libxml2mod.
so -o .libs/libxml2mod.so
ar cru .libs/libxml2mod.a libxml.lo types.o libxml2-py.o
ranlib .libs/libxml2mod.a
creating libxml2mod.la
(cd .libs && rm -f libxml2mod.la && ln -s ../libxml2mod.la libxml2mod.la)
cat ./libxml.py libxml2class.py > libxml2.py
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/python'
Making all in tests
make[3]: Entering directory `/home/milchstore/source/libxml2-2.7.3/python/tests'
make[3]: Nothing to be done for `all'.
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/python/tests'
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/python'
make[1]: Leaving directory `/home/milchstore/source/libxml2-2.7.3'
Making install in include
make[1]: Entering directory `/home/milchstore/source/libxml2-2.7.3/include'
Making install in libxml
```

```
l'
make[3]: Entering directory `/home/milchstore/source/libxml2-2.7.3/include/libxm
l'
make install-exec-hook
make[4]: Entering directory `/home/milchstore/source/libxml2-2.7.3/include/libxm
l'
/bin/sh ../../mkinstalldirs /home/milchstore/php5/include/libxml2/libxml
mkdir -p -- /home/milchstore/php5/include/libxml2/libxml
make[4]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/include/libxml
'
test -z "/home/milchstore/php5/include/libxml2/libxml" || /bin/mkdir -p "/home/m
ilchstore/php5/include/libxml2/libxml"
/usr/bin/install -c -m 644 'SAX.h' '/home/milchstore/php5/include/libxml2/libxm
l/SAX.h'
/usr/bin/install -c -m 644 'entities.h' '/home/milchstore/php5/include/libxml2/
libxml/entities.h'
/usr/bin/install -c -m 644 'encoding.h' '/home/milchstore/php5/include/libxml2/
libxml/encoding.h'
/usr/bin/install -c -m 644 'parser.h' '/home/milchstore/php5/include/libxml2/li
bxml/parser.h'
/usr/bin/install -c -m 644 'parserInternals.h' '/home/milchstore/php5/include/l
ibxml2/libxml/parserInternals.h'
/usr/bin/install -c -m 644 'xmlerror.h' '/home/milchstore/php5/include/libxml2/
libxml/xmlerror.h'
/usr/bin/install -c -m 644 'HTMLparser.h' '/home/milchstore/php5/include/libxml
2/libxml/HTMLparser.h'
/usr/bin/install -c -m 644 'HTMLtree.h' '/home/milchstore/php5/include/libxml2/
libxml/HTMLtree.h'
/usr/bin/install -c -m 644 'debugXML.h' '/home/milchstore/php5/include/libxml2/
libxml/debugXML.h'
/usr/bin/install -c -m 644 'tree.h' '/home/milchstore/php5/include/libxml2/libx
ml/tree.h'
/usr/bin/install -c -m 644 'list.h' '/home/milchstore/php5/include/libxml2/libx
ml/list.h'
/usr/bin/install -c -m 644 'hash.h' '/home/milchstore/php5/include/libxml2/libx
ml/hash.h'
/usr/bin/install -c -m 644 'xpath.h' '/home/milchstore/php5/include/libxml2/lib
xml/xpath.h'
/usr/bin/install -c -m 644 'xpathInternals.h' '/home/milchstore/php5/include/li
bxml2/libxml/xpathInternals.h'
/usr/bin/install -c -m 644 'xpointer.h' '/home/milchstore/php5/include/libxml2/
libxml/xpointer.h'
/usr/bin/install -c -m 644 'xinclude.h' '/home/milchstore/php5/include/libxml2/
libxml/xinclude.h'
/usr/bin/install -c -m 644 'xmlIO.h' '/home/milchstore/php5/include/libxml2/lib
xml/xmlIO.h'
/usr/bin/install -c -m 644 'xmlmemory.h' '/home/milchstore/php5/include/libxml2
/libxml/xmlmemory.h'
/usr/bin/install -c -m 644 'nanohttp.h' '/home/milchstore/php5/include/libxml2/
libxml/nanohttp.h'
```

```
ibxml/nanoftp.h'
/usr/bin/install -c -m 644 'uri.h' '/home/milchstore/php5/include/libxml2/libxml
l/uri.h'
/usr/bin/install -c -m 644 'valid.h' '/home/milchstore/php5/include/libxml2/lib
xml/valid.h'
/usr/bin/install -c -m 644 'xlink.h' '/home/milchstore/php5/include/libxml2/lib
xml/xlink.h'
/usr/bin/install -c -m 644 'xmlversion.h' '/home/milchstore/php5/include/libxml
2/libxml/xmlversion.h'
/usr/bin/install -c -m 644 'DOCBparser.h' '/home/milchstore/php5/include/libxml
2/libxml/DOCBparser.h'
/usr/bin/install -c -m 644 'catalog.h' '/home/milchstore/php5/include/libxml2/l
ibxml/catalog.h'
/usr/bin/install -c -m 644 'threads.h' '/home/milchstore/php5/include/libxml2/l
ibxml/threads.h'
/usr/bin/install -c -m 644 'globals.h' '/home/milchstore/php5/include/libxml2/l
ibxml/globals.h'
/usr/bin/install -c -m 644 'c14n.h' '/home/milchstore/php5/include/libxml2/libx
ml/c14n.h'
/usr/bin/install -c -m 644 'xmlautomata.h' '/home/milchstore/php5/include/libxm
l2/libxml/xmlautomata.h'
/usr/bin/install -c -m 644 'xmlregexp.h' '/home/milchstore/php5/include/libxml2
/libxml/xmlregexp.h'
/usr/bin/install -c -m 644 'xmlmodule.h' '/home/milchstore/php5/include/libxml2
/libxml/xmlmodule.h'
/usr/bin/install -c -m 644 'xmlschemas.h' '/home/milchstore/php5/include/libxml
2/libxml/xmlschemas.h'
/usr/bin/install -c -m 644 'schemasInternals.h' '/home/milchstore/php5/include/
libxml2/libxml/schemasInternals.h'
/usr/bin/install -c -m 644 'xmlschematypes.h' '/home/milchstore/php5/include/l
ibxml2/libxml/xmlschematypes.h'
/usr/bin/install -c -m 644 'xmlstring.h' '/home/milchstore/php5/include/libxml2
/libxml/xmlstring.h'
/usr/bin/install -c -m 644 'xmlunicode.h' '/home/milchstore/php5/include/libxml
2/libxml/xmlunicode.h'
/usr/bin/install -c -m 644 'xmlreader.h' '/home/milchstore/php5/include/libxml2
/libxml/xmlreader.h'
/usr/bin/install -c -m 644 'relaxng.h' '/home/milchstore/php5/include/libxml2/l
ibxml/relaxng.h'
/usr/bin/install -c -m 644 'dict.h' '/home/milchstore/php5/include/libxml2/libx
ml/dict.h'
/usr/bin/install -c -m 644 'SAX2.h' '/home/milchstore/php5/include/libxml2/libx
ml/SAX2.h'
/usr/bin/install -c -m 644 'xmlexports.h' '/home/milchstore/php5/include/libxml
2/libxml/xmlexports.h'
/usr/bin/install -c -m 644 'xmlwriter.h' '/home/milchstore/php5/include/libxml2
/libxml/xmlwriter.h'
/usr/bin/install -c -m 644 'chvalid.h' '/home/milchstore/php5/include/libxml2/l
ibxml/chvalid.h'
/usr/bin/install -c -m 644 'pattern.h' '/home/milchstore/php5/include/libxml2/l
```



```
/usr/bin/install -c -m 644 'xmlsave.h' '/home/milchstore/php5/include/libxml2/libxml/xmlsave.h'
/usr/bin/install -c -m 644 'schematron.h' '/home/milchstore/php5/include/libxml2/libxml/schematron.h'
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/include/libxml'
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/include/libxml'
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3/include'
make[3]: Entering directory `/home/milchstore/source/libxml2-2.7.3/include'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/include'
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/include'
make[1]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/include'
Making install in .
make[1]: Entering directory `/home/milchstore/source/libxml2-2.7.3'
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3'
test -z "/home/milchstore/php5/lib" || /bin/mkdir -p "/home/milchstore/php5/lib"
/bin/sh ./libtool --mode=install /usr/bin/install -c 'libxml2.la' '/home/milchstore/php5/lib/libxml2.la'
/usr/bin/install -c .libs/libxml2.so.2.7.3 /home/milchstore/php5/lib/libxml2.so.2.7.3
(cd /home/milchstore/php5/lib && { ln -s -f libxml2.so.2.7.3 libxml2.so.2 || { rm -f libxml2.so.2 && ln -s libxml2.so.2.7.3 libxml2.so.2; }; })
(cd /home/milchstore/php5/lib && { ln -s -f libxml2.so.2.7.3 libxml2.so || { rm -f libxml2.so && ln -s libxml2.so.2.7.3 libxml2.so; }; })
/usr/bin/install -c .libs/libxml2.lai /home/milchstore/php5/lib/libxml2.la
/usr/bin/install -c .libs/libxml2.a /home/milchstore/php5/lib/libxml2.a
chmod 644 /home/milchstore/php5/lib/libxml2.a
ranlib /home/milchstore/php5/lib/libxml2.a
PATH="$PATH:/sbin" ldconfig -n /home/milchstore/php5/lib
```

Libraries have been installed in:
 /home/milchstore/php5/lib

If you ever happen to want to link against installed libraries in a given directory, LIBDIR, you must either use libtool, and specify the full pathname of the library, or use the `-LLIBDIR` flag during linking and do at least one of the following:

- add LIBDIR to the ``LD_LIBRARY_PATH'` environment variable during execution
- add LIBDIR to the ``LD_RUN_PATH'` environment variable during linking
- use the ``-Wl,--rpath -Wl,LIBDIR'` linker flag
- have your system administrator add LIBDIR to ``/etc/ld.so.conf'`

See any operating system documentation about shared libraries for more information, such as the `ld(1)` and `ld.so(8)` manual pages.

```
/bin/sh ./libtool --mode=install /usr/bin/install -c 'xllint' '/home/milchstore/php5/bin/xllint'
/usr/bin/install -c .libs/xllint /home/milchstore/php5/bin/xllint
/bin/sh ./libtool --mode=install /usr/bin/install -c 'xmlcatalog' '/home/milchstore/php5/bin/xmlcatalog'
/usr/bin/install -c .libs/xmlcatalog /home/milchstore/php5/bin/xmlcatalog
test -z "/home/milchstore/php5/bin" || /bin/mkdir -p "/home/milchstore/php5/bin"
/usr/bin/install -c 'xml2-config' '/home/milchstore/php5/bin/xml2-config'
test -z "/home/milchstore/php5/lib" || /bin/mkdir -p "/home/milchstore/php5/lib"
/usr/bin/install -c -m 644 'xml2Conf.sh' '/home/milchstore/php5/lib/xml2Conf.sh'
,
/bin/sh ./mkinstalldirs /home/milchstore/php5/share/doc/libxml2-2.7.3
mkdir -p -- /home/milchstore/php5/share/doc/libxml2-2.7.3
/usr/bin/install -c -m 0644 ./Copyright /home/milchstore/php5/share/doc/libxml2-2.7.3
/bin/sh ./mkinstalldirs /home/milchstore/php5/share/doc/libxml2-2.7.3/examples
mkdir -p -- /home/milchstore/php5/share/doc/libxml2-2.7.3/examples
/usr/bin/install -c -m 0644 ./xllint.c /home/milchstore/php5/share/doc/libxml2-2.7.3/examples
/usr/bin/install -c -m 0644 ./testSAX.c /home/milchstore/php5/share/doc/libxml2-2.7.3/examples
/usr/bin/install -c -m 0644 ./testHTML.c /home/milchstore/php5/share/doc/libxml2-2.7.3/examples
/usr/bin/install -c -m 0644 ./testXPath.c /home/milchstore/php5/share/doc/libxml2-2.7.3/examples
test -z "/home/milchstore/php5/share/aclocal" || /bin/mkdir -p "/home/milchstore/php5/share/aclocal"
/usr/bin/install -c -m 644 'libxml.m4' '/home/milchstore/php5/share/aclocal/libxml.m4'
test -z "/home/milchstore/php5/share/man/man1" || /bin/mkdir -p "/home/milchstore/php5/share/man/man1"
/usr/bin/install -c -m 644 './xml2-config.1' '/home/milchstore/php5/share/man/man1/xml2-config.1'
test -z "/home/milchstore/php5/share/man/man3" || /bin/mkdir -p "/home/milchstore/php5/share/man/man3"
/usr/bin/install -c -m 644 './libxml.3' '/home/milchstore/php5/share/man/man3/libxml.3'
test -z "/home/milchstore/php5/lib/pkgconfig" || /bin/mkdir -p "/home/milchstore/php5/lib/pkgconfig"
/usr/bin/install -c -m 644 'libxml-2.0.pc' '/home/milchstore/php5/lib/pkgconfig/libxml-2.0.pc'
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3'
make[1]: Leaving directory `/home/milchstore/source/libxml2-2.7.3'
Making install in doc
make[1]: Entering directory `/home/milchstore/source/libxml2-2.7.3/doc'
Making install in devhelp
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3/doc/devhelp'
make[3]: Entering directory `/home/milchstore/source/libxml2-2.7.3/doc/devhelp'
make[3]: Nothing to be done for `install-exec-am'.
/bin/sh ../../mkinstalldirs /home/milchstore/php5/share/gtk-doc/html/libxml2
```

```
/usr/bin/install -c -m 0644 libxml2.devhelp /home/milchstore/php5/share/gtk-doc/html/libxml2
/usr/bin/install -c -m 0644 home.png left.png right.png up.png style.css /home/milchstore/php5/share/gtk-doc/html/libxml2
/usr/bin/install -c -m 0644 index.html general.html libxml2-c14n.html libxml2-catalog.html libxml2-chvalid.html libxml2-debugXML.html libxml2-dict.html libxml2-DOCBparser.html libxml2-encoding.html libxml2-entities.html libxml2-globals.html libxml2-hash.html libxml2-HTMLparser.html libxml2-HTMLtree.html libxml2-list.html libxml2-nanoftp.html libxml2-nanohttp.html libxml2-parser.html libxml2-parserInternals.html libxml2-pattern.html libxml2-relaxng.html libxml2-SAX2.html libxml2-SAX.html libxml2-schemasInternals.html libxml2-schematron.html libxml2-thread.s.html libxml2-tree.html libxml2-uri.html libxml2-valid.html libxml2-xinclude.html libxml2-xlink.html libxml2-xmlautomata.html libxml2-xmlerror.html libxml2-xmlexports.html libxml2-xmlIO.html libxml2-xmlmemory.html libxml2-xmlmodule.html libxml2-xmlreader.html libxml2-xmlregexp.html libxml2-xmlsave.html libxml2-xmlschemas.html libxml2-xmlschematypes.html libxml2-xmlstring.html libxml2-xmlunicode.html libxml2-xmlversion.html libxml2-xmlwriter.html libxml2-xpath.html libxml2-xpathInternals.html libxml2-xpointer.html /home/milchstore/php5/share/gtk-doc/html/libxml2
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/doc/devhelp'
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/doc/devhelp'
Making install in examples
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3/doc/examples'
make[3]: Entering directory `/home/milchstore/source/libxml2-2.7.3/doc/examples'
make[3]: Nothing to be done for `install-exec-am'.
/bin/sh ../../mkinstalldirs /home/milchstore/php5/share/doc/libxml2-2.7.3/html
mkdir -p -- /home/milchstore/php5/share/doc/libxml2-2.7.3/html
/usr/bin/install -c -m 0644 /*.html /*.c /*.xml /*.xsl /*.res /home/milchstore/php5/share/doc/libxml2-2.7.3/html
/usr/bin/install: cannot stat `/*.html': No such file or directory
make[3]: [install-data-local] Error 1 (ignored)
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/doc/examples'
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/doc/examples'
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3/doc'
make[3]: Entering directory `/home/milchstore/source/libxml2-2.7.3/doc'
make[3]: Nothing to be done for `install-exec-am'.
/bin/sh ../../mkinstalldirs /home/milchstore/php5/share/doc/libxml2-2.7.3/html
/usr/bin/install -c -m 0644 ./xml.html ./encoding.html ./FAQ.html ./structure.gif ./DOM.gif ./smallfootonly.gif ./redhat.gif ./libxml.gif ./w3c.png ./Libxml2-Logo-180x168.gif ./Libxml2-Logo-90x34.gif /home/milchstore/php5/share/doc/libxml2-2.7.3/html
/bin/sh ../../mkinstalldirs /home/milchstore/php5/share/doc/libxml2-2.7.3/html/html
mkdir -p -- /home/milchstore/php5/share/doc/libxml2-2.7.3/html/html
/usr/bin/install -c -m 0644 ./html/*.html /home/milchstore/php5/share/doc/libxml2-2.7.3/html/html
/usr/bin/install -c -m 0644 ./html/*.png /home/milchstore/php5/share/doc/libxml2-2.7.3/html/html
/bin/sh ../../mkinstalldirs /home/milchstore/php5/share/doc/libxml2-2.7.3/html/tutorial
mkdir -p -- /home/milchstore/php5/share/doc/libxml2-2.7.3/html/tutorial
```

```
        /home/milchstore/php5/share/doc/libxml2-2.7.3/html/tutorial
/bin/sh ../mkinstalldirs /home/milchstore/php5/share/doc/libxml2-2.7.3/html/tuto
rial/images
mkdir -p -- /home/milchstore/php5/share/doc/libxml2-2.7.3/html/tutorial/images
/usr/bin/install -c -m 0644 ./tutorial/images/*. * \
        /home/milchstore/php5/share/doc/libxml2-2.7.3/html/tutorial/imag
es
/bin/sh ../mkinstalldirs /home/milchstore/php5/share/doc/libxml2-2.7.3/html/tuto
rial/images/callouts
mkdir -p -- /home/milchstore/php5/share/doc/libxml2-2.7.3/html/tutorial/images/c
allouts
/usr/bin/install -c -m 0644 ./tutorial/images/callouts/*. * \
        /home/milchstore/php5/share/doc/libxml2-2.7.3/html/tutorial/imag
es/callouts
test -z "/home/milchstore/php5/share/man/man1" || /bin/mkdir -p "/home/milchstor
e/php5/share/man/man1"
  /usr/bin/install -c -m 644 './xllint.1' '/home/milchstore/php5/share/man/man1/
xllint.1'
  /usr/bin/install -c -m 644 './xmlcatalog.1' '/home/milchstore/php5/share/man/ma
n1/xmlcatalog.1'
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/doc'
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/doc'
make[1]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/doc'
Making install in example
make[1]: Entering directory `/home/milchstore/source/libxml2-2.7.3/example'
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3/example'
make[2]: Nothing to be done for `install-exec-am'.
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/example'
make[1]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/example'
Making install in xstc
make[1]: Entering directory `/home/milchstore/source/libxml2-2.7.3/xstc'
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3/xstc'
make[2]: Nothing to be done for `install-exec-am'.
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/xstc'
make[1]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/xstc'
Making install in python
make[1]: Entering directory `/home/milchstore/source/libxml2-2.7.3/python'
Making install in .
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3/python'
make[3]: Entering directory `/home/milchstore/source/libxml2-2.7.3/python'
make[3]: Nothing to be done for `install-exec-am'.
test -z "/home/milchstore/php5/share/doc/libxml2-python-2.7.3" || /bin/mkdir -p
"/home/milchstore/php5/share/doc/libxml2-python-2.7.3"
  /usr/bin/install -c -m 644 'TODO' '/home/milchstore/php5/share/doc/libxml2-pyth
on-2.7.3/TODO'
test -z "/home/milchstore/php5/lib/python2.4/site-packages" || /bin/mkdir -p "/h
ome/milchstore/php5/lib/python2.4/site-packages"
  /usr/bin/install -c -m 644 'drv_libxml2.py' '/home/milchstore/php5/lib/python2.
```

```

test -z "/home/milchstore/php5/lib/python2.4/site-packages" || /bin/mkdir -p "/h
ome/milchstore/php5/lib/python2.4/site-packages"
/usr/bin/install -c -m 644 'libxml2.py' '/home/milchstore/php5/lib/python2.4/si
te-packages/libxml2.py'
test -z "/home/milchstore/php5/lib/python2.4/site-packages" || /bin/mkdir -p "/h
ome/milchstore/php5/lib/python2.4/site-packages"
/bin/sh ../libtool --mode=install /usr/bin/install -c 'libxml2mod.la' '/home
/milchstore/php5/lib/python2.4/site-packages/libxml2mod.la'
libtool: install: warning: relinking `libxml2mod.la'
(cd /home/milchstore/source/libxml2-2.7.3/python; /bin/sh ../libtool --tag=CC -
-mode=relink gcc -g -O2 -pedantic -W -Wformat -Wunused -Wimplicit -Wreturn-type
-Wswitch -Wcomment -Wtrigraphs -Wformat -Wchar-subscripts -Wuninitialized -Wpare
ntheses -Wshadow -Wpointer-arith -Wcast-align -Wwrite-strings -Waggregate-return
-Wstrict-prototypes -Wmissing-prototypes -Wnested-externs -Winline -Wredundant-
decls -module -avoid-version -o libxml2mod.la -rpath /home/milchstore/php5/lib/p
ython2.4/site-packages libxml.lo types.lo libxml2-py.lo ../libxml2.la )
gcc -shared .libs/libxml.o .libs/types.o .libs/libxml2-py.o -Wl,--rpath -Wl,/h
ome/milchstore/php5/lib -L/home/milchstore/php5/lib -lxml2 -Wl,-soname -Wl,libx
ml2mod.so -o .libs/libxml2mod.so
/usr/bin/install -c .libs/libxml2mod.soT /home/milchstore/php5/lib/python2.4/sit
e-packages/libxml2mod.so
/usr/bin/install -c .libs/libxml2mod.lai /home/milchstore/php5/lib/python2.4/sit
e-packages/libxml2mod.la
/usr/bin/install -c .libs/libxml2mod.a /home/milchstore/php5/lib/python2.4/site-
packages/libxml2mod.a
chmod 644 /home/milchstore/php5/lib/python2.4/site-packages/libxml2mod.a
ranlib /home/milchstore/php5/lib/python2.4/site-packages/libxml2mod.a
PATH="$PATH:/sbin" ldconfig -n /home/milchstore/php5/lib/python2.4/site-packages
-----

```

Libraries have been installed in:

```

/home/milchstore/php5/lib/python2.4/site-packages

```

If you ever happen to want to link against installed libraries in a given directory, LIBDIR, you must either use libtool, and specify the full pathname of the library, or use the `-LLIBDIR` flag during linking and do at least one of the following:

- add LIBDIR to the `'LD_LIBRARY_PATH'` environment variable during execution
- add LIBDIR to the `'LD_RUN_PATH'` environment variable during linking
- use the `'-Wl,--rpath -Wl,LIBDIR'` linker flag
- have your system administrator add LIBDIR to `'/etc/ld.so.conf'`

See any operating system documentation about shared libraries for more information, such as the `ld(1)` and `ld.so(8)` manual pages.

```

-----
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/python'
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/python'
Making install in tests
make[2]: Entering directory `/home/milchstore/source/libxml2-2.7.3/python/tests'

```

```
make[3]: Nothing to be done for `install-exec-am'.
test -z "/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples" || /bin/
mkdir -p "/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples"
/usr/bin/install -c -m 644 'build.py' '/home/milchstore/php5/share/doc/libxml2-
python-2.7.3/examples/build.py'
/usr/bin/install -c -m 644 'attribs.py' '/home/milchstore/php5/share/doc/libxml
2-python-2.7.3/examples/attribs.py'
/usr/bin/install -c -m 644 'tst.py' '/home/milchstore/php5/share/doc/libxml2-py
thon-2.7.3/examples/tst.py'
/usr/bin/install -c -m 644 'tstxpath.py' '/home/milchstore/php5/share/doc/libxm
l2-python-2.7.3/examples/tstxpath.py'
/usr/bin/install -c -m 644 'xpathext.py' '/home/milchstore/php5/share/doc/libxm
l2-python-2.7.3/examples/xpathext.py'
/usr/bin/install -c -m 644 'push.py' '/home/milchstore/php5/share/doc/libxml2-p
ython-2.7.3/examples/push.py'
/usr/bin/install -c -m 644 'pushSAX.py' '/home/milchstore/php5/share/doc/libxml
2-python-2.7.3/examples/pushSAX.py'
/usr/bin/install -c -m 644 'pushSAXhtml.py' '/home/milchstore/php5/share/doc/li
bxml2-python-2.7.3/examples/pushSAXhtml.py'
/usr/bin/install -c -m 644 'error.py' '/home/milchstore/php5/share/doc/libxml2-
python-2.7.3/examples/error.py'
/usr/bin/install -c -m 644 'serialize.py' '/home/milchstore/php5/share/doc/libx
ml2-python-2.7.3/examples/serialize.py'
/usr/bin/install -c -m 644 'validate.py' '/home/milchstore/php5/share/doc/libxm
l2-python-2.7.3/examples/validate.py'
/usr/bin/install -c -m 644 'tstURI.py' '/home/milchstore/php5/share/doc/libxml2
-python-2.7.3/examples/tstURI.py'
/usr/bin/install -c -m 644 'cutnpaste.py' '/home/milchstore/php5/share/doc/libx
ml2-python-2.7.3/examples/cutnpaste.py'
/usr/bin/install -c -m 644 'xpathret.py' '/home/milchstore/php5/share/doc/libxm
l2-python-2.7.3/examples/xpathret.py'
/usr/bin/install -c -m 644 'xpath.py' '/home/milchstore/php5/share/doc/libxml2-
python-2.7.3/examples/xpath.py'
/usr/bin/install -c -m 644 'outbuf.py' '/home/milchstore/php5/share/doc/libxml2
-python-2.7.3/examples/outbuf.py'
/usr/bin/install -c -m 644 'inbuf.py' '/home/milchstore/php5/share/doc/libxml2-
python-2.7.3/examples/inbuf.py'
/usr/bin/install -c -m 644 'resolver.py' '/home/milchstore/php5/share/doc/libxm
l2-python-2.7.3/examples/resolver.py'
/usr/bin/install -c -m 644 'regexp.py' '/home/milchstore/php5/share/doc/libxml2
-python-2.7.3/examples/regexp.py'
/usr/bin/install -c -m 644 'reader.py' '/home/milchstore/php5/share/doc/libxml2
-python-2.7.3/examples/reader.py'
/usr/bin/install -c -m 644 'reader2.py' '/home/milchstore/php5/share/doc/libxml
2-python-2.7.3/examples/reader2.py'
/usr/bin/install -c -m 644 'reader3.py' '/home/milchstore/php5/share/doc/libxml
2-python-2.7.3/examples/reader3.py'
/usr/bin/install -c -m 644 'reader4.py' '/home/milchstore/php5/share/doc/libxml
2-python-2.7.3/examples/reader4.py'
/usr/bin/install -c -m 644 'reader5.py' '/home/milchstore/php5/share/doc/libxml
```

```
/usr/bin/install -c -m 644 'reader6.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/reader6.py'
/usr/bin/install -c -m 644 'reader7.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/reader7.py'
/usr/bin/install -c -m 644 'reader8.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/reader8.py'
/usr/bin/install -c -m 644 'readernext.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/readernext.py'
/usr/bin/install -c -m 644 'walker.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/walker.py'
/usr/bin/install -c -m 644 'nsdel.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/nsdel.py'
/usr/bin/install -c -m 644 'ctxterror.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/ctxterror.py'
/usr/bin/install -c -m 644 'readererr.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/readererr.py'
/usr/bin/install -c -m 644 'relaxng.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/relaxng.py'
/usr/bin/install -c -m 644 'schema.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/schema.py'
/usr/bin/install -c -m 644 'thread2.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/thread2.py'
/usr/bin/install -c -m 644 'sync.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/sync.py'
/usr/bin/install -c -m 644 'tstLastError.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/tstLastError.py'
/usr/bin/install -c -m 644 'indexes.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/indexes.py'
/usr/bin/install -c -m 644 'dtdvalid.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/dtdvalid.py'
/usr/bin/install -c -m 644 'tstmem.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/tstmem.py'
/usr/bin/install -c -m 644 'validDTD.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/validDTD.py'
/usr/bin/install -c -m 644 'validSchemas.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/validSchemas.py'
/usr/bin/install -c -m 644 'validRNG.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/validRNG.py'
/usr/bin/install -c -m 644 'compareNodes.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/compareNodes.py'
/usr/bin/install -c -m 644 'xpathns.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/xpathns.py'
/usr/bin/install -c -m 644 'xpathleak.py' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/xpathleak.py'
/usr/bin/install -c -m 644 'tst.xml' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/tst.xml'
/usr/bin/install -c -m 644 'valid.xml' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/valid.xml'
/usr/bin/install -c -m 644 'invalid.xml' '/home/milchstore/php5/share/doc/libxml2-python-2.7.3/examples/invalid.xml'
```

```
python-2.7.3/examples/test.dtd'  
make[3]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/python/tests'  
make[2]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/python/tests'  
make[1]: Leaving directory `/home/milchstore/source/libxml2-2.7.3/python'  
checking build system type... x86_64-unknown-linux-gnu  
checking host system type... x86_64-unknown-linux-gnu  
checking for a BSD-compatible install... /usr/bin/install -c  
checking whether build environment is sane... yes  
checking for a thread-safe mkdir -p... /bin/mkdir -p  
checking for gawk... gawk  
checking whether make sets $(MAKE)... yes  
checking for style of include used by make... GNU  
checking for gcc... gcc  
checking for C compiler default output file name... a.out  
checking whether the C compiler works... yes  
checking whether we are cross compiling... no  
checking for suffix of executables...  
checking for suffix of object files... o  
checking whether we are using the GNU C compiler... yes  
checking whether gcc accepts -g... yes  
checking for gcc option to accept ISO C89... none needed  
checking dependency style of gcc... gcc3  
checking for library containing strerror... none required  
checking for gcc... (cached) gcc  
checking whether we are using the GNU C compiler... (cached) yes  
checking whether gcc accepts -g... (cached) yes  
checking for gcc option to accept ISO C89... (cached) none needed  
checking dependency style of gcc... (cached) gcc3  
checking for a BSD-compatible install... /usr/bin/install -c  
checking how to run the C preprocessor... gcc -E  
checking for rm... /bin/rm  
checking for mv... /bin/mv  
checking for tar... /bin/tar  
checking for grep that handles long lines and -e... /bin/grep  
checking for egrep... /bin/grep -E  
checking for ANSI C header files... yes  
checking for a sed that does not truncate output... /bin/sed  
checking for ld used by gcc... /usr/bin/ld  
checking if the linker (/usr/bin/ld) is GNU ld... yes  
checking for /usr/bin/ld option to reload object files... -r  
checking for BSD-compatible nm... /usr/bin/nm -B  
checking whether ln -s works... yes  
checking how to recognize dependent libraries... pass_all  
checking for sys/types.h... yes  
checking for sys/stat.h... yes  
checking for stdlib.h... yes  
checking for string.h... yes  
checking for memory.h... yes  
checking for strings.h... yes  
checking for inttypes.h... yes
```


checking for unistd.h... yes
checking dlfcn.h usability... yes
checking dlfcn.h presence... yes
checking for dlfcn.h... yes
checking for g++... g++
checking whether we are using the GNU C++ compiler... yes
checking whether g++ accepts -g... yes
checking dependency style of g++... gcc3
checking how to run the C++ preprocessor... g++ -E
checking for g77... g77
checking whether we are using the GNU Fortran 77 compiler... yes
checking whether g77 accepts -g... yes
checking the maximum length of command line arguments... 98304
checking command to parse /usr/bin/nm -B output from gcc object... ok
checking for objdir... .libs
checking for ar... ar
checking for ranlib... ranlib
checking for strip... strip
checking if gcc supports -fno-rtti -fno-exceptions... no
checking for gcc option to produce PIC... -fPIC
checking if gcc PIC flag -fPIC works... yes
checking if gcc static flag -static works... yes
checking if gcc supports -c -o file.o... yes
checking whether the gcc linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking whether -lc should be explicitly linked in... no
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
checking whether stripping libraries is possible... yes
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries... yes
configure: creating libtool
appending configuration tag "CXX" to libtool
checking for ld used by g++... /usr/bin/ld -m elf_x86_64
checking if the linker (/usr/bin/ld -m elf_x86_64) is GNU ld... yes
checking whether the g++ linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking for g++ option to produce PIC... -fPIC
checking if g++ PIC flag -fPIC works... yes
checking if g++ static flag -static works... yes
checking if g++ supports -c -o file.o... yes
checking whether the g++ linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
appending configuration tag "F77" to libtool
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries... yes

checking if g77 PIC flag -fPIC works... yes
checking if g77 static flag -static works... yes
checking if g77 supports -c -o file.o... yes
checking whether the g77 linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
checking for sys/types.h... (cached) yes
checking sys/time.h usability... yes
checking sys/time.h presence... yes
checking for sys/time.h... yes
checking for stdlib.h... (cached) yes
checking for unistd.h... (cached) yes
checking for string.h... (cached) yes
checking ieee754.h usability... no
checking ieee754.h presence... no
checking for ieee754.h... no
checking nan.h usability... no
checking nan.h presence... no
checking for nan.h... no
checking math.h usability... yes
checking math.h presence... yes
checking for math.h... yes
checking fp_class.h usability... no
checking fp_class.h presence... no
checking for fp_class.h... no
checking float.h usability... yes
checking float.h presence... yes
checking for float.h... yes
checking ansidecl.h usability... no
checking ansidecl.h presence... no
checking for ansidecl.h... no
checking sys/timeb.h usability... yes
checking sys/timeb.h presence... yes
checking for sys/timeb.h... yes
checking time.h usability... yes
checking time.h presence... yes
checking for time.h... yes
checking for sys/stat.h... (cached) yes
checking sys/select.h usability... yes
checking sys/select.h presence... yes
checking for sys/select.h... yes
checking stdarg.h usability... yes
checking stdarg.h presence... yes
checking for stdarg.h... yes
checking for stat... yes
checking for _stat... no
checking for isnan... yes
checking for isinf... yes
checking for pow... no

```
checking for floor... no
checking for floor in -lm... yes
checking for fabs... no
checking for fabs in -lm... yes
checking for gettimeofday... yes
checking for mktime... yes
checking for localtime... yes
checking for localtime_r... yes
checking for asctime... yes
checking for time... yes
checking for gmtime_r... yes
checking for ftime... yes
checking for printf... yes
checking for sprintf... yes
checking for fprintf... yes
checking for snprintf... yes
checking for vfprintf... yes
checking for vsprintf... yes
checking for vsnprintf... yes
checking for sscanf... yes
checking for perl... perl
checking for python... /usr/bin/python
PYTHON is pointing at /usr/bin/python
Found Python version 2.4
Warning: Missing libxml2-python
checking for libgcrypt-config... no
Crypto extensions will not be available. Install libgcrypt and reconfigure to ma
ke available.
Enabling debugger
checking for libxml libraries >= 2.6.27... 2.7.3 found
checking whether shared libraries will be built (required for plugins)... yes
checking libxml2 module support... yes
configure: creating ./config.status
config.status: creating Makefile
config.status: creating libxslt.pc
config.status: creating libexslt.pc
config.status: creating libxslt/Makefile
config.status: creating libxslt/xsltconfig.h
config.status: creating libxslt/xsltwindows32config.h
config.status: creating libexslt/Makefile
config.status: creating libexslt/exsltconfig.h
config.status: creating xsltproc/Makefile
config.status: creating python/Makefile
config.status: creating python/tests/Makefile
config.status: creating tests/Makefile
config.status: creating tests/docs/Makefile
config.status: creating tests/REC1/Makefile
config.status: creating tests/REC2/Makefile
config.status: creating tests/REC/Makefile
config.status: creating tests/general/Makefile
```

```
config.status: creating tests/extensions/Makefile
config.status: creating tests/namespaces/Makefile
config.status: creating tests/keys/Makefile
config.status: creating tests/numbers/Makefile
config.status: creating tests/documents/Makefile
config.status: creating tests/xmlspec/Makefile
config.status: creating tests/multiple/Makefile
config.status: creating tests/xinclude/Makefile
config.status: creating tests/XSLTMark/Makefile
config.status: creating tests/docbook/Makefile
config.status: creating tests/exslt/Makefile
config.status: creating tests/exslt/common/Makefile
config.status: creating tests/exslt/functions/Makefile
config.status: creating tests/exslt/math/Makefile
config.status: creating tests/exslt/sets/Makefile
config.status: creating tests/exslt/strings/Makefile
config.status: creating tests/exslt/date/Makefile
config.status: creating tests/exslt/dynamic/Makefile
config.status: creating tests/plugins/Makefile
config.status: creating doc/Makefile
config.status: creating xslt-config
config.status: creating libxslt.spec
config.status: creating config.h
config.status: executing depfiles commands
make all-recursive
make[1]: Entering directory `/home/milchstore/source/libxslt-1.1.24'
Making all in libxslt
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/libxslt'
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT attrvt.lo -MD -MP -MF .deps/attrvt.Tpo -c -o attrvt.lo attrvt.c
mkdir .libs
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT attrvt.lo -MD -MP -MF .deps/attrvt.Tpo -c attrvt.c -fPIC -DPIC -o .libs/attrvt.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT attrvt.lo -MD -MP -MF .deps/attrvt.Tpo -c attrvt.c -o attrvt.o >/dev/null 2>&1
mv -f .deps/attrvt.Tpo .deps/attrvt.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT xslt.lo -MD -MP -MF .deps/xslt.Tpo -c -o xslt.lo xslt.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT xslt.lo -MD -MP -MF .deps/xslt.Tpo -c xslt.c -fPIC -DPIC -o .libs/xslt.o
```

```
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT xslt.lo -MD -MP -MF .deps/xslt.Tpo -c xslt.c -o xslt.o >/dev/null 2>&1
mv -f .deps/xslt.Tpo .deps/xslt.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/lib
xml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT xsltutils.lo -MD -MP -M
F .deps/xsltutils.Tpo -c -o xsltutils.lo xsltutils.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT xsltutils.lo -MD -MP -MF .deps/xsltutils.Tpo -c xsltutils.c -fPIC -DP
IC -o .libs/xsltutils.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT xsltutils.lo -MD -MP -MF .deps/xsltutils.Tpo -c xsltutils.c -o xsltu
ils.o >/dev/null 2>&1
mv -f .deps/xsltutils.Tpo .deps/xsltutils.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/lib
xml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT pattern.lo -MD -MP -MF
.deps/pattern.Tpo -c -o pattern.lo pattern.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT pattern.lo -MD -MP -MF .deps/pattern.Tpo -c pattern.c -fPIC -DPIC -o
.libs/pattern.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT pattern.lo -MD -MP -MF .deps/pattern.Tpo -c pattern.c -o pattern.o >/d
ev/null 2>&1
mv -f .deps/pattern.Tpo .deps/pattern.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/lib
xml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT templates.lo -MD -MP -M
F .deps/templates.Tpo -c -o templates.lo templates.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT templates.lo -MD -MP -MF .deps/templates.Tpo -c templates.c -fPIC -DP
IC -o .libs/templates.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT templates.lo -MD -MP -MF .deps/templates.Tpo -c templates.c -o templat
es.o >/dev/null 2>&1
mv -f .deps/templates.Tpo .deps/templates.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/lib
xml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT variables.lo -MD -MP -M
F .deps/variables.Tpo -c -o variables.lo variables.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT variables.lo -MD -MP -MF .deps/variables.Tpo -c variables.c -fPIC -DP
IC -o .libs/variables.o
```

```
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT variables.lo -MD -MP -MF .deps/variables.Tpo -c variables.c -o variables.o >/dev/null 2>&1
mv -f .deps/variables.Tpo .deps/variables.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT keys.lo -MD -MP -MF .deps/keys.Tpo -c -o keys.lo keys.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT keys.lo -MD -MP -MF .deps/keys.Tpo -c keys.c -fPIC -DPIC -o .libs/keys.o
keys.c: In function 'xsltInitDocKeyTable':
keys.c:477: warning: 'keyd' may be used uninitialized in this function
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT keys.lo -MD -MP -MF .deps/keys.Tpo -c keys.c -o keys.o >/dev/null 2>&1
mv -f .deps/keys.Tpo .deps/keys.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT numbers.lo -MD -MP -MF .deps/numbers.Tpo -c -o numbers.lo numbers.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT numbers.lo -MD -MP -MF .deps/numbers.Tpo -c numbers.c -fPIC -DPIC -o .libs/numbers.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT numbers.lo -MD -MP -MF .deps/numbers.Tpo -c numbers.c -o numbers.o >/dev/null 2>&1
mv -f .deps/numbers.Tpo .deps/numbers.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT extensions.lo -MD -MP -MF .deps/extensions.Tpo -c -o extensions.lo extensions.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT extensions.lo -MD -MP -MF .deps/extensions.Tpo -c extensions.c -fPIC -DPIC -o .libs/extensions.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT extensions.lo -MD -MP -MF .deps/extensions.Tpo -c extensions.c -o extensions.o >/dev/null 2>&1
mv -f .deps/extensions.Tpo .deps/extensions.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT extra.lo -MD -MP -MF .deps/extra.Tpo -c -o extra.lo extra.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
```

extra.o

```
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/  
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2  
-Wall -MT extra.lo -MD -MP -MF .deps/extra.Tpo -c extra.c -o extra.o >/dev/null  
2>&1
```

```
mv -f .deps/extra.Tpo .deps/extra.Plo
```

```
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -  
I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/lib  
xml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT functions.lo -MD -MP -M  
F .deps/functions.Tpo -c -o functions.lo functions.c
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/  
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2  
-Wall -MT functions.lo -MD -MP -MF .deps/functions.Tpo -c functions.c -fPIC -DP  
IC -o .libs/functions.o
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/  
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2  
-Wall -MT functions.lo -MD -MP -MF .deps/functions.Tpo -c functions.c -o functio  
ns.o >/dev/null 2>&1
```

```
mv -f .deps/functions.Tpo .deps/functions.Plo
```

```
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -  
I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/lib  
xml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT namespaces.lo -MD -MP -  
MF .deps/namespaces.Tpo -c -o namespaces.lo namespaces.c
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/  
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2  
-Wall -MT namespaces.lo -MD -MP -MF .deps/namespaces.Tpo -c namespaces.c -fPIC  
-DPIC -o .libs/namespaces.o
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/  
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2  
-Wall -MT namespaces.lo -MD -MP -MF .deps/namespaces.Tpo -c namespaces.c -o name  
spaces.o >/dev/null 2>&1
```

```
mv -f .deps/namespaces.Tpo .deps/namespaces.Plo
```

```
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -  
I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/lib  
xml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT imports.lo -MD -MP -MF  
.deps/imports.Tpo -c -o imports.lo imports.c
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/  
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2  
-Wall -MT imports.lo -MD -MP -MF .deps/imports.Tpo -c imports.c -fPIC -DPIC -o  
.libs/imports.o
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/  
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2  
-Wall -MT imports.lo -MD -MP -MF .deps/imports.Tpo -c imports.c -o imports.o >/d  
ev/null 2>&1
```

```
mv -f .deps/imports.Tpo .deps/imports.Plo
```

```
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -  
I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/lib  
xml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT attributes.lo -MD -MP -  
MF .deps/attributes.Tpo -c -o attributes.lo attributes.c
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
```

```

-Wall -MT attributes.lo -MD -MP -MF .deps/attributes.Tpo -c attributes.c -fPIC
-DPIC -o .libs/attributes.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT attributes.lo -MD -MP -MF .deps/attributes.Tpo -c attributes.c -o attr
ibutes.o >/dev/null 2>&1
mv -f .deps/attributes.Tpo .deps/attributes.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/lib
xml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT documents.lo -MD -MP -M
F .deps/documents.Tpo -c -o documents.lo documents.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT documents.lo -MD -MP -MF .deps/documents.Tpo -c documents.c -fPIC -DP
IC -o .libs/documents.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT documents.lo -MD -MP -MF .deps/documents.Tpo -c documents.c -o documen
ts.o >/dev/null 2>&1
mv -f .deps/documents.Tpo .deps/documents.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/lib
xml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT preproc.lo -MD -MP -MF
.deps/preproc.Tpo -c -o preproc.lo preproc.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT preproc.lo -MD -MP -MF .deps/preproc.Tpo -c preproc.c -fPIC -DPIC -o
.libs/preproc.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT preproc.lo -MD -MP -MF .deps/preproc.Tpo -c preproc.c -o preproc.o >/d
ev/null 2>&1
mv -f .deps/preproc.Tpo .deps/preproc.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/lib
xml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT transform.lo -MD -MP -M
F .deps/transform.Tpo -c -o transform.lo transform.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT transform.lo -MD -MP -MF .deps/transform.Tpo -c transform.c -fPIC -DP
IC -o .libs/transform.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT transform.lo -MD -MP -MF .deps/transform.Tpo -c transform.c -o transfo
rm.o >/dev/null 2>&1
mv -f .deps/transform.Tpo .deps/transform.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/lib
xml2 -I/home/milchstore/php5/include -g -O2 -Wall -MT security.lo -MD -MP -MF
.deps/security.Tpo -c -o security.lo security.c

```



```

-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT security.lo -MD -MP -MF .deps/security.Tpo -c security.c -fPIC -DPIC
-o .libs/security.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I/home/milchstore/php5/include/
-I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include -g -O2
-Wall -MT security.lo -MD -MP -MF .deps/security.Tpo -c security.c -o security.o
>/dev/null 2>&1
mv -f .deps/security.Tpo .deps/security.Plo
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -Wall -version-info 2:24:1
-o libxslt.la -rpath /home/milchstore/php5/lib attrvt.lo xslt.lo xsltutils.lo
pattern.lo templates.lo variables.lo keys.lo numbers.lo extensions.lo extra.lo f
unctions.lo namespaces.lo imports.lo attributes.lo documents.lo preproc.lo trans
form.lo security.lo -L/home/milchstore/php5/lib/ -L/home/milchstore/php5/lib -lx
ml2 -lz -L/home/milchstore/php5/lib -liconv -lm -lm
gcc -shared .libs/attrvt.o .libs/xslt.o .libs/xsltutils.o .libs/pattern.o .libs
/templates.o .libs/variables.o .libs/keys.o .libs/numbers.o .libs/extensions.o .
libs/extra.o .libs/functions.o .libs/namespaces.o .libs/imports.o .libs/attribut
es.o .libs/documents.o .libs/preproc.o .libs/transform.o .libs/security.o -Wl,-
-rpath -Wl,/home/milchstore/php5/lib -Wl,--rpath -Wl,/home/milchstore/php5/lib -
L/home/milchstore/php5/lib/ -L/home/milchstore/php5/lib /home/milchstore/php5/li
b/libxml2.so -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,-soname -Wl,libx
slt.so.1 -o .libs/libxslt.so.1.1.24
(cd .libs && rm -f libxslt.so.1 && ln -s libxslt.so.1.1.24 libxslt.so.1)
(cd .libs && rm -f libxslt.so && ln -s libxslt.so.1.1.24 libxslt.so)
ar cru .libs/libxslt.a attrvt.o xslt.o xsltutils.o pattern.o templates.o variab
les.o keys.o numbers.o extensions.o extra.o functions.o namespaces.o imports.o a
ttributes.o documents.o preproc.o transform.o security.o
ranlib .libs/libxslt.a
creating libxslt.la
(cd .libs && rm -f libxslt.la && ln -s ../libxslt.la libxslt.la)
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/libxslt'
Making all in libexslt
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/libexslt'
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I../libexslt -I.. -I../libxslt -I../libexslt -I/home/milchstore/php
5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/inclu
de -g -O2 -Wall -g -O2 -Wall -MT exslt.lo -MD -MP -MF .deps/exslt.Tpo -c -o e
xslt.lo exslt.c
mkdir .libs
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT exslt.lo -M
D -MP -MF .deps/exslt.Tpo -c exslt.c -fPIC -DPIC -o .libs/exslt.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT exslt.lo -M
D -MP -MF .deps/exslt.Tpo -c exslt.c -o exslt.o >/dev/null 2>&1
mv -f .deps/exslt.Tpo .deps/exslt.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I../libexslt -I.. -I../libxslt -I../libexslt -I/home/milchstore/php

```

```
de -g -O2 -Wall -g -O2 -Wall -MT common.lo -MD -MP -MF .deps/common.Tpo -c -o
common.lo common.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT common.lo -
MD -MP -MF .deps/common.Tpo -c common.c -fPIC -DPIC -o .libs/common.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT common.lo -
MD -MP -MF .deps/common.Tpo -c common.c -o common.o >/dev/null 2>&1
mv -f .deps/common.Tpo .deps/common.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I../libexslt -I.. -I../libxslt -I../libexslt -I/home/milchstore/php
5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/inclu
de -g -O2 -Wall -g -O2 -Wall -MT crypto.lo -MD -MP -MF .deps/crypto.Tpo -c -o
crypto.lo crypto.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT crypto.lo -
MD -MP -MF .deps/crypto.Tpo -c crypto.c -fPIC -DPIC -o .libs/crypto.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT crypto.lo -
MD -MP -MF .deps/crypto.Tpo -c crypto.c -o crypto.o >/dev/null 2>&1
mv -f .deps/crypto.Tpo .deps/crypto.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I../libexslt -I.. -I../libxslt -I../libexslt -I/home/milchstore/php
5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/inclu
de -g -O2 -Wall -g -O2 -Wall -MT math.lo -MD -MP -MF .deps/math.Tpo -c -o mat
h.lo math.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT math.lo -MD
-MP -MF .deps/math.Tpo -c math.c -fPIC -DPIC -o .libs/math.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT math.lo -MD
-MP -MF .deps/math.Tpo -c math.c -o math.o >/dev/null 2>&1
mv -f .deps/math.Tpo .deps/math.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I../libexslt -I.. -I../libxslt -I../libexslt -I/home/milchstore/php
5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/inclu
de -g -O2 -Wall -g -O2 -Wall -MT sets.lo -MD -MP -MF .deps/sets.Tpo -c -o set
s.lo sets.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT sets.lo -MD
-MP -MF .deps/sets.Tpo -c sets.c -fPIC -DPIC -o .libs/sets.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
```

```

-MP -MF .deps/sets.Tpo -c sets.c -o sets.o >/dev/null 2>&1
mv -f .deps/sets.Tpo .deps/sets.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I../libexslt -I.. -I../libxslt -I../libexslt -I/home/milchstore/php
5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/inclu
de -g -O2 -Wall -g -O2 -Wall -MT functions.lo -MD -MP -MF .deps/functions.Tpo
-c -o functions.lo functions.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT functions.l
o -MD -MP -MF .deps/functions.Tpo -c functions.c -fPIC -DPIC -o .libs/functions
.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT functions.l
o -MD -MP -MF .deps/functions.Tpo -c functions.c -o functions.o >/dev/null 2>&1
mv -f .deps/functions.Tpo .deps/functions.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I../libexslt -I.. -I../libxslt -I../libexslt -I/home/milchstore/php
5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/inclu
de -g -O2 -Wall -g -O2 -Wall -MT strings.lo -MD -MP -MF .deps/strings.Tpo -c
-o strings.lo strings.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT strings.lo
-MD -MP -MF .deps/strings.Tpo -c strings.c -fPIC -DPIC -o .libs/strings.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT strings.lo
-MD -MP -MF .deps/strings.Tpo -c strings.c -o strings.o >/dev/null 2>&1
mv -f .deps/strings.Tpo .deps/strings.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I../libexslt -I.. -I../libxslt -I../libexslt -I/home/milchstore/php
5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/inclu
de -g -O2 -Wall -g -O2 -Wall -MT date.lo -MD -MP -MF .deps/date.Tpo -c -o dat
e.lo date.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT date.lo -MD
-MP -MF .deps/date.Tpo -c date.c -fPIC -DPIC -o .libs/date.o
date.c: In function 'exsltDateCurrent':
date.c:750: warning: unused variable 'gsecs'
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libexslt -I.. -I../libxslt
-I../libexslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT date.lo -MD
-MP -MF .deps/date.Tpo -c date.c -o date.o >/dev/null 2>&1
mv -f .deps/date.Tpo .deps/date.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I../libexslt -I.. -I../libxslt -I../libexslt -I/home/milchstore/php
5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/inclu

```

```

axon.lo saxon.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libxslt -I.. -I../libxslt
-I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT saxon.lo -M
D -MP -MF .deps/saxon.Tpo -c saxon.c -fPIC -DPIC -o .libs/saxon.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libxslt -I.. -I../libxslt
-I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT saxon.lo -M
D -MP -MF .deps/saxon.Tpo -c saxon.c -o saxon.o >/dev/null 2>&1
mv -f .deps/saxon.Tpo .deps/saxon.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I.. -
I../libxslt -I../libxslt -I.. -I../libxslt -I../libxslt -I/home/milchstore/php
5/include/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/inclu
de -g -O2 -Wall -g -O2 -Wall -MT dynamic.lo -MD -MP -MF .deps/dynamic.Tpo -c
-o dynamic.lo dynamic.c
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libxslt -I.. -I../libxslt
-I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT dynamic.lo
-MD -MP -MF .deps/dynamic.Tpo -c dynamic.c -fPIC -DPIC -o .libs/dynamic.o
gcc -DHAVE_CONFIG_H -I. -I.. -I.. -I../libxslt -I../libxslt -I.. -I../libxslt
-I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/l
ibxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT dynamic.lo
-MD -MP -MF .deps/dynamic.Tpo -c dynamic.c -o dynamic.o >/dev/null 2>&1
mv -f .deps/dynamic.Tpo .deps/dynamic.Plo
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -Wall -version-info 8:13:8
-o libxslt.la -rpath /home/milchstore/php5/lib exslt.lo common.lo crypto.lo
math.lo sets.lo functions.lo strings.lo date.lo saxon.lo dynamic.lo ../libxslt/l
ibxslt.la -L/home/milchstore/php5/lib/ -L/home/milchstore/php5/lib -lxml2 -lz -L
/home/milchstore/php5/lib -liconv -lm -lm
libtool: link: warning: `/home/milchstore/php5/lib//libxml2.la' seems to be move
d
libtool: link: warning: `/home/milchstore/php5/lib//libiconv.la' seems to be mov
ed
gcc -shared .libs/exslt.o .libs/common.o .libs/crypto.o .libs/math.o .libs/sets
.o .libs/functions.o .libs/strings.o .libs/date.o .libs/saxon.o .libs/dynamic.o
-Wl,--rpath -Wl,/home/milchstore/source/libxslt-1.1.24/libxslt/.libs -Wl,--rpat
h -Wl,/home/milchstore/php5/lib -Wl,--rpath -Wl,/home/milchstore/php5/lib ../lib
xslt/.libs/libxslt.so -L/home/milchstore/php5/lib/ -L/home/milchstore/php5/lib /
home/milchstore/php5/lib/libxml2.so -lz /home/milchstore/php5/lib/libiconv.so -l
m -Wl,-soname -Wl,libxslt.so.0 -o .libs/libxslt.so.0.8.13
(cd .libs && rm -f libxslt.so.0 && ln -s libxslt.so.0.8.13 libxslt.so.0)
(cd .libs && rm -f libxslt.so && ln -s libxslt.so.0.8.13 libxslt.so)
ar cru .libs/libxslt.a exslt.o common.o crypto.o math.o sets.o functions.o str
ings.o date.o saxon.o dynamic.o
ranlib .libs/libxslt.a
creating libxslt.la
(cd .libs && rm -f libxslt.la && ln -s ../libxslt.la libxslt.la)
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/libxslt'
Making all in xsltproc
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/xsltproc'

```

```
I../libxslt -I/home/milchstore/php5/include/ -I/home/milchstore/php5/include/li
bxml2 -I/home/milchstore/php5/include -g -O2 -Wall -g -O2 -Wall -MT xsltproc.
o -MD -MP -MF .deps/xsltproc.Tpo -c -o xsltproc.o xsltproc.c
mv -f .deps/xsltproc.Tpo .deps/xsltproc.Po
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -Wall -o xsltproc xsltp
roc.o ../libxslt/libxslt.la ../libxslt/libxslt.la -L/home/milchstore/php5/lib/
-L/home/milchstore/php5/lib -lxml2 -lz -L/home/milchstore/php5/lib -liconv -lm
-L/home/milchstore/php5/lib/ -L/home/milchstore/php5/lib -lxml2 -lz -L/home/milc
hstore/php5/lib -liconv -lm -lm
mkdir .libs
gcc -g -O2 -Wall -o .libs/xsltproc xsltproc.o ../libxslt/.libs/libxslt.so -L/ho
me/milchstore/php5/lib/ -L/home/milchstore/php5/lib ../libxslt/.libs/libxslt.s
o /home/milchstore/source/libxslt-1.1.24/libxslt/.libs/libxslt.so /home/milchsto
re/php5/lib/libxml2.so -ldl -lz /home/milchstore/php5/lib/libiconv.so -lm -Wl,-
-rpath -Wl,/home/milchstore/php5/lib
creating xsltproc
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/xsltproc'
Making all in doc
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/doc'
Validating the HTML Web pages
I/O error : Attempt to load network entity http://www.w3.org/TR/xhtml1/DTD/xhtmll
1-transitional.dtd
API.html:2: warning: failed to load external entity "http://www.w3.org/TR/xhtml1
/DTD/xhtml1-transitional.dtd"
 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"
      ^
API.html:3: validity error : Validation failed: no DTD found !
<html xmlns="http://www.w3.org/1999/xhtml"><head><meta http-equiv="Content-Type"
      ^
I/O error : Attempt to load network entity http://www.w3.org/TR/xhtml1/DTD/xhtmll
1-transitional.dtd
bugs.html:2: warning: failed to load external entity "http://www.w3.org/TR/xhtmll
1/DTD/xhtml1-transitional.dtd"
 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"
      ^
bugs.html:3: validity error : Validation failed: no DTD found !
<html xmlns="http://www.w3.org/1999/xhtml"><head><meta http-equiv="Content-Type"
      ^
I/O error : Attempt to load network entity http://www.w3.org/TR/xhtml1/DTD/xhtmll
1-transitional.dtd
contribs.html:2: warning: failed to load external entity "http://www.w3.org/TR/x
html1/DTD/xhtml1-transitional.dtd"
 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"
      ^
contribs.html:3: validity error : Validation failed: no DTD found !
<html xmlns="http://www.w3.org/1999/xhtml"><head><meta http-equiv="Content-Type"
      ^
I/O error : Attempt to load network entity http://www.w3.org/TR/xhtml1/DTD/xhtmll
1-transitional.dtd
FAQ.html:2: warning: failed to load external entity "http://www.w3.org/TR/xhtml1
```

1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"
^
FAQ.html:3: validity error : Validation failed: no DTD found !
<html xmlns="http://www.w3.org/1999/xhtml"><head><meta http-equiv="Content-Type"
^
I/O error : Attempt to load network entity http://www.w3.org/TR/xhtml1/DTD/xhtml1-
1-transitional.dtd
docs.html:2: warning: failed to load external entity "http://www.w3.org/TR/xhtml1
1/DTD/xhtml1-transitional.dtd"
1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"
^
docs.html:3: validity error : Validation failed: no DTD found !
<html xmlns="http://www.w3.org/1999/xhtml"><head><meta http-equiv="Content-Type"
^
I/O error : Attempt to load network entity http://www.w3.org/TR/xhtml1/DTD/xhtml1
1-transitional.dtd
downloads.html:2: warning: failed to load external entity "http://www.w3.org/TR/
xhtml1/DTD/xhtml1-transitional.dtd"
1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"
^
downloads.html:3: validity error : Validation failed: no DTD found !
<html xmlns="http://www.w3.org/1999/xhtml"><head><meta http-equiv="Content-Type"
^
I/O error : Attempt to load network entity http://www.w3.org/TR/xhtml1/DTD/xhtml1
1-transitional.dtd
help.html:2: warning: failed to load external entity "http://www.w3.org/TR/xhtml1
1/DTD/xhtml1-transitional.dtd"
1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"
^
help.html:3: validity error : Validation failed: no DTD found !
<html xmlns="http://www.w3.org/1999/xhtml"><head><meta http-equiv="Content-Type"
^
I/O error : Attempt to load network entity http://www.w3.org/TR/xhtml1/DTD/xhtml1
1-transitional.dtd
index.html:2: warning: failed to load external entity "http://www.w3.org/TR/xhtm
l1/DTD/xhtml1-transitional.dtd"
1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"
^
index.html:3: validity error : Validation failed: no DTD found !
<html xmlns="http://www.w3.org/1999/xhtml"><head><meta http-equiv="Content-Type"
^
I/O error : Attempt to load network entity http://www.w3.org/TR/xhtml1/DTD/xhtml1
1-transitional.dtd
intro.html:2: warning: failed to load external entity "http://www.w3.org/TR/xhtm
l1/DTD/xhtml1-transitional.dtd"
1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"
^
intro.html:3: validity error : Validation failed: no DTD found !
<html xmlns="http://www.w3.org/1999/xhtml"><head><meta http-equiv="Content-Type"
^

1-transitional.dtd

news.html:2: warning: failed to load external entity "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"

1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd" ^

news.html:3: validity error : Validation failed: no DTD found !

<html xmlns="http://www.w3.org/1999/xhtml"><head><meta http-equiv="Content-Type" ^

xsltproc.html:1: validity error : Validation failed: no DTD found !

<html><head><meta http-equiv="Content-Type" content="text/html; charset=ISO-8859 ^

xsltproc.html:1: parser error : Opening and ending tag mismatch: meta line 1 and head

</title><meta name="generator" content="DocBook XSL Stylesheets V1.61.2"></head> ^

xsltproc.html:101: parser error : Opening and ending tag mismatch: meta line 1 and html

R/xslt" target="_top">http://www.w3.org/TR/xslt</p></div></div></body></html ^

xsltproc.html:102: parser error : Premature end of data in tag head line 1

^

xsltproc.html:102: parser error : Premature end of data in tag html line 1

^

I/O error : Attempt to load network entity http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd

xsltproc2.html:2: warning: failed to load external entity "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd"

1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd" ^

xsltproc2.html:3: validity error : Validation failed: no DTD found !

<html xmlns="http://www.w3.org/1999/xhtml"><head><meta http-equiv="Content-Type" ^

make[2]: [xsltproc.html] Error 4 (ignored)

make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/doc'

Making all in python

make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/python'

Making all in .

make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/python'

cd . && /usr/bin/python generator.py

/usr/lib/python2.4/xmllib.py:9: DeprecationWarning: The xmllib module is obsolete. Use xml.sax instead.

warnings.warn("The xmllib module is obsolete. Use xml.sax instead.", DeprecationWarning)

Found 237 functions in libxslt-api.xml

Found 32 functions in libxslt-python-api.xml

Generated 141 wrapper functions, 96 failed, 32 skipped

Missing type converters:

```
2 xmlXPathCompExprPtr:4 xsltPreComputeFunction:1 xsltElemPreCompPtr:2 xsltDe
bugTraceCodes:2 xsltDocumentPtr:8 xsltSecurityPrefsPtr:11 xsltTemplatePtr:4
pythonObject *:5 ...:1 xsltNumberDataPtr:1 xmlHashTablePtr:1 xmlNodePtr *:3
xsltExtInitFunction:2 xsltCompilerCtxtPtr:2 char **:2 xmlXPathObjectPtr *:1
xmlNodeSetPtr:2 xmlXPathFunction:4 xsltTransformFunction:5 xsltCompMatchPtr:
3 void *:13 xmlOutputBufferPtr:1 xsltPointerListPtr:4 xmlDictPtr:1 xsltSort
Func:2 xsltNsMapPtr:1 xsltStackElemPtr:3
```

```
touch gen_prog
```

```
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I/usr
/include/python2.4 -I/home/milchstore/php5/include/ -I/home/milchstore/php5/incl
ude/libxml2 -I/home/milchstore/php5/include -I../libxslt -I.. -I../libexslt -
g -O2 -Wall -MT libxslt.lo -MD -MP -MF .deps/libxslt.Tpo -c -o libxslt.lo libxsl
t.c
```

```
mkdir .libs
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I/usr/include/python2.4 -I/home/milchstore/php5/i
nclude/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include
-I../libxslt -I.. -I../libexslt -g -O2 -Wall -MT libxslt.lo -MD -MP -MF .deps/li
bxslt.Tpo -c libxslt.c -fPIC -DPIC -o .libs/libxslt.o
```

```
libxslt.c: In function 'libxslt_xsltApplyStylesheetUser':
```

```
libxslt.c:690: warning: passing argument 2 of 'PyDict_Next' from incompatible po
inter type
```

```
libxslt.c: In function 'libxslt_xsltApplyStylesheet':
```

```
libxslt.c:766: warning: passing argument 2 of 'PyDict_Next' from incompatible po
inter type
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I/usr/include/python2.4 -I/home/milchstore/php5/i
nclude/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include
-I../libxslt -I.. -I../libexslt -g -O2 -Wall -MT libxslt.lo -MD -MP -MF .deps/li
bxslt.Tpo -c libxslt.c -o libxslt.o >/dev/null 2>&1
```

```
mv -f .deps/libxslt.Tpo .deps/libxslt.Plo
```

```
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I/usr
/include/python2.4 -I/home/milchstore/php5/include/ -I/home/milchstore/php5/incl
ude/libxml2 -I/home/milchstore/php5/include -I../libxslt -I.. -I../libexslt -
g -O2 -Wall -MT types.lo -MD -MP -MF .deps/types.Tpo -c -o types.lo types.c
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I/usr/include/python2.4 -I/home/milchstore/php5/i
nclude/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include
-I../libxslt -I.. -I../libexslt -g -O2 -Wall -MT types.lo -MD -MP -MF .deps/type
s.Tpo -c types.c -fPIC -DPIC -o .libs/types.o
```

```
types.c: In function 'libxml_xmlXPathObjectPtrConvert':
```

```
types.c:462: warning: dereferencing type-punned pointer will break strict-aliasi
ng rules
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I/usr/include/python2.4 -I/home/milchstore/php5/i
nclude/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include
-I../libxslt -I.. -I../libexslt -g -O2 -Wall -MT types.lo -MD -MP -MF .deps/type
s.Tpo -c types.c -o types.o >/dev/null 2>&1
```

```
mv -f .deps/types.Tpo .deps/types.Plo
```

```
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I/usr
/include/python2.4 -I/home/milchstore/php5/include/ -I/home/milchstore/php5/incl
ude/libxml2 -I/home/milchstore/php5/include -I../libxslt -I.. -I../libexslt -
g -O2 -Wall -MT libxslt-py.lo -MD -MP -MF .deps/libxslt-py.Tpo -c -o libxslt-py.
lo libxslt-py.c
```



```
nclude/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include
-I../libxslt -I.. -I../libxslt -g -O2 -Wall -MT libxslt-py.lo -MD -MP -MF .deps
/libxslt-py.Tpo -c libxslt-py.c -fPIC -DPIC -o .libs/libxslt-py.o
gcc -DHAVE_CONFIG_H -I. -I.. -I/usr/include/python2.4 -I/home/milchstore/php5/i
nclude/ -I/home/milchstore/php5/include/libxml2 -I/home/milchstore/php5/include
-I../libxslt -I.. -I../libxslt -g -O2 -Wall -MT libxslt-py.lo -MD -MP -MF .deps
/libxslt-py.Tpo -c libxslt-py.c -o libxslt-py.o >/dev/null 2>&1
mv -f .deps/libxslt-py.Tpo .deps/libxslt-py.Plo
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -Wall -module -avoid-versi
on -o libxsltmod.la -rpath /home/milchstore/php5/lib/python2.4/site-packages li
bxslt.lo types.lo libxslt-py.lo ../libxslt/libxslt.la ../libxslt/libxslt.la
libtool: link: warning: `/home/milchstore/php5/lib//libxml2.la' seems to be move
d
libtool: link: warning: `/home/milchstore/php5/lib//libiconv.la' seems to be mov
ed
libtool: link: warning: `/home/milchstore/php5/lib//libxml2.la' seems to be move
d
libtool: link: warning: `/home/milchstore/php5/lib//libiconv.la' seems to be mov
ed
gcc -shared .libs/libxslt.o .libs/types.o .libs/libxslt-py.o -Wl,--rpath -Wl,/
home/milchstore/source/libxslt-1.1.24/libxslt/.libs -Wl,--rpath -Wl,/home/milchs
tore/source/libxslt-1.1.24/libxslt/.libs -Wl,--rpath -Wl,/home/milchstore/php5/
lib -L/home/milchstore/source/libxslt-1.1.24/libxslt/.libs ../libxslt/.libs/libx
slt.so -L/home/milchstore/php5/lib/ -L/home/milchstore/php5/lib ../libxslt/.lib
s/libxslt.so -Wl,-soname -Wl,libxsltmod.so -o .libs/libxsltmod.so
ar cru .libs/libxsltmod.a libxslt.o types.o libxslt-py.o
ranlib .libs/libxsltmod.a
creating libxsltmod.la
(cd .libs && rm -f libxsltmod.la && ln -s ../libxsltmod.la libxsltmod.la)
cat ./libxsl.py ./libxsltclass.py > libxslt.py
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/python'
Making all in tests
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/python/tests
'
make[3]: Nothing to be done for `all'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/python/tests'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/python'
Making all in tests
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests'
Making all in docs
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/docs'
make[3]: Nothing to be done for `all'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/docs'
Making all in REC1
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/REC1'
make[3]: Nothing to be done for `all'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/REC1'
Making all in REC2
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/REC2'
make[3]: Nothing to be done for `all'.
```

Making all in REC

make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/REC'

make[3]: Nothing to be done for `all'.

make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/REC'

Making all in general

make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/general'

make[3]: Nothing to be done for `all'.

make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/general'

Making all in namespaces

make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/namespaces'

make[3]: Nothing to be done for `all'.

make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/namespaces'

Making all in keys

make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/keys'

make[3]: Nothing to be done for `all'.

make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/keys'

Making all in numbers

make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/numbers'

make[3]: Nothing to be done for `all'.

make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/numbers'

Making all in documents

make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/documents'

make[3]: Nothing to be done for `all'.

make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/documents'

Making all in extensions

make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/extensions'

make[3]: Nothing to be done for `all'.

make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/extensions'

Making all in reports

make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/reports'

make[3]: Nothing to be done for `all'.

make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/reports'

Making all in xmlspec

make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/xmlspec'

make[3]: Nothing to be done for `all'.

make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/xmlspec'

```
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/multiple'
make[3]: Nothing to be done for `all'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/multiple'
Making all in xinclude
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/xinclude'
make[3]: Nothing to be done for `all'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/xinclude'
Making all in XSLTMark
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/XSLTMark'
make[3]: Nothing to be done for `all'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/XSLTMark'
Making all in docbook
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/docbook'
make[3]: Nothing to be done for `all'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/docbook'
Making all in exslt
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt'
Making all in common
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/common'
make[4]: Nothing to be done for `all'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/common'
Making all in functions
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/functions'
make[4]: Nothing to be done for `all'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/functions'
Making all in math
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/math'
make[4]: Nothing to be done for `all'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/math'
Making all in sets
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/sets'
make[4]: Nothing to be done for `all'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/sets'
Making all in strings
```

```
strings'
make[4]: Nothing to be done for `all'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/s
trings'
Making all in dynamic
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/
dynamic'
make[4]: Nothing to be done for `all'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/d
ynamic'
Making all in date
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/
date'
make[4]: Nothing to be done for `all'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/d
ate'
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt'
make[4]: Nothing to be done for `all-am'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt'
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt'
Making all in plugins
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/plugin
s'
make[3]: Nothing to be done for `all'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/plugins
'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests'
make[3]: Nothing to be done for `all-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests'
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24'
sed -e 's?\@XSLT_LIBDIR\@?-L/home/milchstore/php5/lib?g' \
    -e 's?\@XSLT_INCLUDEDIR\@?-I/home/milchstore/php5/include?g' \
    -e 's?\@VERSION\@?1.1.24?g' \
    -e 's?\@XSLT_LIBS\@?-lxml2 -lz -L/home/milchstore/php5/lib/ -L/home/milc
hstore/php5/lib -lxml2 -lz -L/home/milchstore/php5/lib -liconv -lm -lm?g' \
    < ./xsltConf.sh.in > xsltConf.tmp \
    && mv xsltConf.tmp xsltConf.sh
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24'
make[1]: Leaving directory `/home/milchstore/source/libxslt-1.1.24'
Making install in libxslt
make[1]: Entering directory `/home/milchstore/source/libxslt-1.1.24/libxslt'
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/libxslt'
test -z "/home/milchstore/php5/lib" || /bin/mkdir -p "/home/milchstore/php5/lib"
/bin/sh ../libtool --mode=install /usr/bin/install -c 'libxslt.la' '/home/milc
hstore/php5/lib/libxslt.la'
/usr/bin/install -c .libs/libxslt.so.1.1.24 /home/milchstore/php5/lib/libxslt.so
.1.1.24
(cd /home/milchstore/php5/lib && { ln -s -f libxslt.so.1.1.24 libxslt.so.1 || {
rm -f libxslt.so.1 && ln -s libxslt.so.1.1.24 libxslt.so.1; }; })
```

```
-f libxslt.so && ln -s libxslt.so.1.1.24 libxslt.so; }; })
/usr/bin/install -c .libs/libxslt.lai /home/milchstore/php5/lib/libxslt.la
/usr/bin/install -c .libs/libxslt.a /home/milchstore/php5/lib/libxslt.a
chmod 644 /home/milchstore/php5/lib/libxslt.a
ranlib /home/milchstore/php5/lib/libxslt.a
PATH="$PATH:/sbin" ldconfig -n /home/milchstore/php5/lib
```

Libraries have been installed in:

 /home/milchstore/php5/lib

If you ever happen to want to link against installed libraries in a given directory, LIBDIR, you must either use libtool, and specify the full pathname of the library, or use the `-LLIBDIR` flag during linking and do at least one of the following:

- add LIBDIR to the `'LD_LIBRARY_PATH'` environment variable during execution
- add LIBDIR to the `'LD_RUN_PATH'` environment variable during linking
- use the `'-Wl,--rpath -Wl,LIBDIR'` linker flag
- have your system administrator add LIBDIR to `'/etc/ld.so.conf'`

See any operating system documentation about shared libraries for more information, such as the `ld(1)` and `ld.so(8)` manual pages.

make install-exec-hook
make[3]: Entering directory `'/home/milchstore/source/libxslt-1.1.24/libxslt'`
/bin/sh /home/milchstore/source/libxslt-1.1.24/install-sh -d "/home/milchstore/php5/lib/libxslt-plugins"
make[3]: Leaving directory `'/home/milchstore/source/libxslt-1.1.24/libxslt'`
test -z "/home/milchstore/php5/share/man/man3" || /bin/mkdir -p "/home/milchstore/php5/share/man/man3"
 /usr/bin/install -c -m 644 './libxslt.3' '/home/milchstore/php5/share/man/man3/libxslt.3'
test -z "/home/milchstore/php5/include/libxslt" || /bin/mkdir -p "/home/milchstore/php5/include/libxslt"
 /usr/bin/install -c -m 644 'xslt.h' '/home/milchstore/php5/include/libxslt/xslt.h'
 /usr/bin/install -c -m 644 'xsltutils.h' '/home/milchstore/php5/include/libxslt/xsltutils.h'
 /usr/bin/install -c -m 644 'pattern.h' '/home/milchstore/php5/include/libxslt/pattern.h'
 /usr/bin/install -c -m 644 'templates.h' '/home/milchstore/php5/include/libxslt/templates.h'
 /usr/bin/install -c -m 644 'variables.h' '/home/milchstore/php5/include/libxslt/variables.h'
 /usr/bin/install -c -m 644 'keys.h' '/home/milchstore/php5/include/libxslt/keys.h'
 /usr/bin/install -c -m 644 'numbersInternals.h' '/home/milchstore/php5/include/libxslt/numbersInternals.h'
 /usr/bin/install -c -m 644 'extensions.h' '/home/milchstore/php5/include/libxsl

```
/usr/bin/install -c -m 644 'extra.h' '/home/milchstore/php5/include/libxslt/ext
ra.h'
/usr/bin/install -c -m 644 'functions.h' '/home/milchstore/php5/include/libxslt
/functions.h'
/usr/bin/install -c -m 644 'namespaces.h' '/home/milchstore/php5/include/libxsl
t/namespaces.h'
/usr/bin/install -c -m 644 'imports.h' '/home/milchstore/php5/include/libxslt/i
mports.h'
/usr/bin/install -c -m 644 'attributes.h' '/home/milchstore/php5/include/libxsl
t/attributes.h'
/usr/bin/install -c -m 644 'documents.h' '/home/milchstore/php5/include/libxslt
/documents.h'
/usr/bin/install -c -m 644 'preproc.h' '/home/milchstore/php5/include/libxslt/p
reproc.h'
/usr/bin/install -c -m 644 'transform.h' '/home/milchstore/php5/include/libxslt
/transform.h'
/usr/bin/install -c -m 644 'security.h' '/home/milchstore/php5/include/libxslt/
security.h'
/usr/bin/install -c -m 644 'xsltInternals.h' '/home/milchstore/php5/include/lib
xslt/xsltInternals.h'
/usr/bin/install -c -m 644 'xsltconfig.h' '/home/milchstore/php5/include/libxsl
t/xsltconfig.h'
/usr/bin/install -c -m 644 'xsltexports.h' '/home/milchstore/php5/include/libxs
lt/xsltexports.h'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/libxslt'
make[1]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/libxslt'
Making install in libexslt
make[1]: Entering directory `/home/milchstore/source/libxslt-1.1.24/libexslt'
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/libexslt'
test -z "/home/milchstore/php5/lib" || /bin/mkdir -p "/home/milchstore/php5/lib"
/bin/sh ../libtool --mode=install /usr/bin/install -c 'libexslt.la' '/home/mil
chstore/php5/lib/libexslt.la'
libtool: install: warning: relinking `libexslt.la'
(cd /home/milchstore/source/libxslt-1.1.24/libexslt; /bin/sh ../libtool --tag=C
C --mode=relink gcc -g -O2 -Wall -version-info 8:13:8 -o libexslt.la -rpath /hom
e/milchstore/php5/lib exslt.lo common.lo crypto.lo math.lo sets.lo functions.lo
strings.lo date.lo saxon.lo dynamic.lo ../libxslt/libxslt.la -L/home/milchstore/
php5/lib/ -L/home/milchstore/php5/lib -lxml2 -lz -L/home/milchstore/php5/lib -li
conv -lm -lm )
libtool: link: warning: `/home/milchstore/php5/lib//libxml2.la' seems to be move
d
libtool: link: warning: `/home/milchstore/php5/lib//libiconv.la' seems to be mov
ed
gcc -shared .libs/exslt.o .libs/common.o .libs/crypto.o .libs/math.o .libs/sets
.o .libs/functions.o .libs/strings.o .libs/date.o .libs/saxon.o .libs/dynamic.o
-Wl,--rpath -Wl,/home/milchstore/php5/lib -L/home/milchstore/php5/lib -lxslt -L
/home/milchstore/php5/lib/ -lxml2 -lz -liconv -lm -Wl,-soname -Wl,libexslt.so.0
-o .libs/libexslt.so.0.8.13
/usr/bin/install -c .libs/libexslt.so.0.8.13T /home/milchstore/php5/lib/libexslt
.so.0.8.13
```

```
{ rm -f libexslt.so.0 && ln -s libexslt.so.0.8.13 libexslt.so.0; }; })
(cd /home/milchstore/php5/lib && { ln -s -f libexslt.so.0.8.13 libexslt.so || {
rm -f libexslt.so && ln -s libexslt.so.0.8.13 libexslt.so; }; })
/usr/bin/install -c .libs/libexslt.lai /home/milchstore/php5/lib/libexslt.la
/usr/bin/install -c .libs/libexslt.a /home/milchstore/php5/lib/libexslt.a
chmod 644 /home/milchstore/php5/lib/libexslt.a
ranlib /home/milchstore/php5/lib/libexslt.a
PATH="$PATH:/sbin" ldconfig -n /home/milchstore/php5/lib
```

Libraries have been installed in:
 /home/milchstore/php5/lib

If you ever happen to want to link against installed libraries in a given directory, LIBDIR, you must either use libtool, and specify the full pathname of the library, or use the '-LLIBDIR' flag during linking and do at least one of the following:

- add LIBDIR to the 'LD_LIBRARY_PATH' environment variable during execution
- add LIBDIR to the 'LD_RUN_PATH' environment variable during linking
- use the '-Wl,--rpath -Wl,LIBDIR' linker flag
- have your system administrator add LIBDIR to '/etc/ld.so.conf'

See any operating system documentation about shared libraries for more information, such as the ld(1) and ld.so(8) manual pages.

test -z "/home/milchstore/php5/include/libexslt" || /bin/mkdir -p "/home/milchstore/php5/include/libexslt"
 /usr/bin/install -c -m 644 'exslt.h' '/home/milchstore/php5/include/libexslt/exslt.h'
 /usr/bin/install -c -m 644 'exsltconfig.h' '/home/milchstore/php5/include/libexslt/exsltconfig.h'
 /usr/bin/install -c -m 644 'exslt.h' '/home/milchstore/php5/include/libexslt/exslt.h'
 /usr/bin/install -c -m 644 'exsltconfig.h' '/home/milchstore/php5/include/libexslt/exsltconfig.h'
 /usr/bin/install -c -m 644 'exslexport.h' '/home/milchstore/php5/include/libexslt/exslexport.h'
test -z "/home/milchstore/php5/share/man/man3" || /bin/mkdir -p "/home/milchstore/php5/share/man/man3"
 /usr/bin/install -c -m 644 './libexslt.3' '/home/milchstore/php5/share/man/man3/libexslt.3'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/libexslt'
make[1]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/libexslt'
Making install in xsltproc
make[1]: Entering directory `/home/milchstore/source/libxslt-1.1.24/xsltproc'
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/xsltproc'
test -z "/home/milchstore/php5/bin" || /bin/mkdir -p "/home/milchstore/php5/bin"
 /bin/sh ../libtool --mode=install /usr/bin/install -c 'xsltproc' '/home/milchstore/php5/bin/xsltproc'

```
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/xsltproc'
make[1]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/xsltproc'
Making install in doc
make[1]: Entering directory `/home/milchstore/source/libxslt-1.1.24/doc'
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/doc'
make[2]: Nothing to be done for `install-exec-am'.
/bin/sh /home/milchstore/source/libxslt-1.1.24/install-sh -d /home/milchstore/php5/share/doc/libxslt-1.1.24/html
/usr/bin/install -c -m 0644 /*.html /home/milchstore/php5/share/doc/libxslt-1.1.24/html
/usr/bin/install -c -m 0644 /*.gif /home/milchstore/php5/share/doc/libxslt-1.1.24/html
/bin/sh /home/milchstore/source/libxslt-1.1.24/install-sh -d /home/milchstore/php5/share/doc/libxslt-1.1.24/html/html
/usr/bin/install -c -m 0644 ./html/*.html /home/milchstore/php5/share/doc/libxslt-1.1.24/html/html
/usr/bin/install -c -m 0644 ./html/*.png /home/milchstore/php5/share/doc/libxslt-1.1.24/html/html
/usr/bin/install -c -m 0644 ./html/index.sgml /home/milchstore/php5/share/doc/libxslt-1.1.24/html/html
/usr/bin/install: cannot stat `./html/index.sgml': No such file or directory
make[2]: [install-data-local] Error 1 (ignored)
/bin/sh /home/milchstore/source/libxslt-1.1.24/install-sh -d /home/milchstore/php5/share/doc/libxslt-1.1.24/html/EXSLT
/usr/bin/install -c -m 0644 ./EXSLT/*.html /home/milchstore/php5/share/doc/libxslt-1.1.24/html/EXSLT
/bin/sh /home/milchstore/source/libxslt-1.1.24/install-sh -d /home/milchstore/php5/share/doc/libxslt-1.1.24/html/tutorial
/usr/bin/install -c -m 0644 ./tutorial/* /home/milchstore/php5/share/doc/libxslt-1.1.24/html/tutorial
/bin/sh /home/milchstore/source/libxslt-1.1.24/install-sh -d /home/milchstore/php5/share/doc/libxslt-1.1.24/html/tutorial2
/usr/bin/install -c -m 0644 ./tutorial2/* /home/milchstore/php5/share/doc/libxslt-1.1.24/html/tutorial2
test -z "/home/milchstore/php5/share/man/man1" || /bin/mkdir -p "/home/milchstore/php5/share/man/man1"
/usr/bin/install -c -m 644 './xsltproc.1' '/home/milchstore/php5/share/man/man1/xsltproc.1'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/doc'
make[1]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/doc'
Making install in python
make[1]: Entering directory `/home/milchstore/source/libxslt-1.1.24/python'
Making install in .
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/python'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/python'
make[3]: Nothing to be done for `install-exec-am'.
/bin/sh /home/milchstore/source/libxslt-1.1.24/install-sh -d /home/milchstore/php5/lib/python2.4/site-packages
/usr/bin/install -c -m 0644 libxslt.py /home/milchstore/php5/lib/python2.4/site-
```



```
/bin/sh /home/milchstore/source/libxslt-1.1.24/install-sh -d /home/milchstore/php5/share/doc/libxslt-python-1.1.24
test -z "/home/milchstore/php5/lib/python2.4/site-packages" || /bin/mkdir -p "/home/milchstore/php5/lib/python2.4/site-packages"
/bin/sh ../libtool --mode=install /usr/bin/install -c 'libxsltmod.la' '/home/milchstore/php5/lib/python2.4/site-packages/libxsltmod.la'
libtool: install: warning: relinking `libxsltmod.la'
(cd /home/milchstore/source/libxslt-1.1.24/python; /bin/sh ../libtool --tag=CC --mode=relink gcc -g -O2 -Wall -module -avoid-version -o libxsltmod.la -rpath /home/milchstore/php5/lib/python2.4/site-packages libxslt.lo types.lo libxslt-py.lo ../libxslt/libxslt.la ../libexslt/libexslt.la )
libtool: link: warning: `/home/milchstore/php5/lib//libxml2.la' seems to be moved
libtool: link: warning: `/home/milchstore/php5/lib//libiconv.la' seems to be moved
libtool: link: warning: `/home/milchstore/php5/lib//libxml2.la' seems to be moved
libtool: link: warning: `/home/milchstore/php5/lib//libiconv.la' seems to be moved
gcc -shared .libs/libxslt.o .libs/types.o .libs/libxslt-py.o -Wl,--rpath -Wl,/home/milchstore/php5/lib -L/home/milchstore/source/libxslt-1.1.24/libxslt/.libs -L/home/milchstore/php5/lib -lxslt -L/home/milchstore/php5/lib/ -lexslt -Wl,-so name -Wl,libxsltmod.so -o .libs/libxsltmod.so
/usr/bin/install -c .libs/libxsltmod.soT /home/milchstore/php5/lib/python2.4/site-packages/libxsltmod.so
/usr/bin/install -c .libs/libxsltmod.lai /home/milchstore/php5/lib/python2.4/site-packages/libxsltmod.la
/usr/bin/install -c .libs/libxsltmod.a /home/milchstore/php5/lib/python2.4/site-packages/libxsltmod.a
chmod 644 /home/milchstore/php5/lib/python2.4/site-packages/libxsltmod.a
ranlib /home/milchstore/php5/lib/python2.4/site-packages/libxsltmod.a
PATH="$PATH:/sbin" ldconfig -n /home/milchstore/php5/lib/python2.4/site-packages
```

Libraries have been installed in:

 /home/milchstore/php5/lib/python2.4/site-packages

If you ever happen to want to link against installed libraries in a given directory, LIBDIR, you must either use libtool, and specify the full pathname of the library, or use the `-LLIBDIR` flag during linking and do at least one of the following:

- add LIBDIR to the ``LD_LIBRARY_PATH'` environment variable during execution
- add LIBDIR to the ``LD_RUN_PATH'` environment variable during linking
- use the ``-Wl,--rpath -Wl,LIBDIR'` linker flag
- have your system administrator add LIBDIR to ``/etc/ld.so.conf'`

See any operating system documentation about shared libraries for more information, such as the `ld(1)` and `ld.so(8)` manual pages.

```
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/python'
Making install in tests
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/python/tests'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/python/tests'
make[3]: Nothing to be done for `install-exec-am'.
/bin/sh /home/milchstore/source/libxslt-1.1.24/install-sh -d /home/milchstore/php5/share/doc/libxslt-python-1.1.24/examples
(for test in basic.py exslt.py extelem.py extfunc.py test.xml test.xsl pyxsltproc.py; \
    do /usr/bin/install -c -m 0644 ./test /home/milchstore/php5/share/doc/libxslt-python-1.1.24/examples ; done)
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/python/tests'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/python/tests'
make[1]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/python'
Making install in tests
make[1]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests'
Making install in docs
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/docs'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/docs'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/docs'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/docs'
Making install in REC1
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/REC1'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/REC1'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/REC1'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/REC1'
Making install in REC2
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/REC2'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/REC2'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/REC2'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/REC2'
Making install in REC
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/REC'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/REC'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/REC'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/REC'
Making install in general
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/general'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/general'
```

```
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/general
'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/general
'
Making install in namespaces
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/namesp
aces'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/namesp
aces'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/namespa
ces'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/namespa
ces'
Making install in keys
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/keys'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/keys'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/keys'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/keys'
Making install in numbers
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/number
s'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/number
s'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/numbers
'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/numbers
'
Making install in documents
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/docume
nts'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/docume
nts'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/documen
ts'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/documen
ts'
Making install in extensions
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/extens
ions'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/extens
```

```
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/extension
s'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/extension
s'
Making install in reports
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/report
s'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/report
s'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/report
s'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/report
s'
Making install in xmlspec
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/xmlspe
c'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/xmlspe
c'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/xmlspec
'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/xmlspec
'
Making install in multiple
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/multip
le'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/multip
le'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/multip
le'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/multip
le'
Making install in xinclude
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/xinclu
de'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/xinclu
de'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/xinclud
e'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/xinclud
e'
```

```
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/XSLTMark'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/XSLTMark'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/XSLTMark'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/XSLTMark'
Making install in docbook
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/docbook'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/docbook'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/docbook'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/docbook'
Making install in exslt
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt'
Making install in common
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/common'
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/common'
make[4]: Nothing to be done for `install-exec-am'.
make[4]: Nothing to be done for `install-data-am'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/common'
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/common'
Making install in functions
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/functions'
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/functions'
make[4]: Nothing to be done for `install-exec-am'.
make[4]: Nothing to be done for `install-data-am'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/functions'
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/functions'
Making install in math
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/math'
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/math'
```

```
make[4]: Nothing to be done for `install-data-am'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/math'
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/math'
Making install in sets
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/sets'
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/sets'
make[4]: Nothing to be done for `install-exec-am'.
make[4]: Nothing to be done for `install-data-am'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/sets'
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/sets'
Making install in strings
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/strings'
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/strings'
make[4]: Nothing to be done for `install-exec-am'.
make[4]: Nothing to be done for `install-data-am'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/strings'
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/strings'
Making install in dynamic
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/dynamic'
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/dynamic'
make[4]: Nothing to be done for `install-exec-am'.
make[4]: Nothing to be done for `install-data-am'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/dynamic'
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/dynamic'
Making install in date
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/date'
make[4]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/date'
make[4]: Nothing to be done for `install-exec-am'.
make[4]: Nothing to be done for `install-data-am'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/date'
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt/date'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt'
```

```
make[4]: Nothing to be done for `install-exec-am'.
make[4]: Nothing to be done for `install-data-am'.
make[4]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt'
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/exslt'
Making install in plugins
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/plugin
s'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests/plugin
s'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/plugin
s'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests/plugin
s'
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests'
make[3]: Entering directory `/home/milchstore/source/libxslt-1.1.24/tests'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests'
make[1]: Leaving directory `/home/milchstore/source/libxslt-1.1.24/tests'
make[1]: Entering directory `/home/milchstore/source/libxslt-1.1.24'
make[2]: Entering directory `/home/milchstore/source/libxslt-1.1.24'
test -z "/home/milchstore/php5/bin" || /bin/mkdir -p "/home/milchstore/php5/bin"
/usr/bin/install -c 'xslt-config' '/home/milchstore/php5/bin/xslt-config'
test -z "/home/milchstore/php5/lib" || /bin/mkdir -p "/home/milchstore/php5/lib"
/usr/bin/install -c -m 644 'xsltConf.sh' '/home/milchstore/php5/lib/xsltConf.sh'
test -z "/home/milchstore/php5/share/aclocal" || /bin/mkdir -p "/home/milchstore
/php5/share/aclocal"
/usr/bin/install -c -m 644 'libxslt.m4' '/home/milchstore/php5/share/aclocal/li
bxslt.m4'
test -z "/home/milchstore/php5/lib/pkgconfig" || /bin/mkdir -p "/home/milchstore
/php5/lib/pkgconfig"
/usr/bin/install -c -m 644 'libxslt.pc' '/home/milchstore/php5/lib/pkgconfig/li
bxslt.pc'
/usr/bin/install -c -m 644 'libexslt.pc' '/home/milchstore/php5/lib/pkgconfig/l
ibexslt.pc'
make[2]: Leaving directory `/home/milchstore/source/libxslt-1.1.24'
make[1]: Leaving directory `/home/milchstore/source/libxslt-1.1.24'
Checking for gcc...
Checking for shared library support...
Building shared library libz.so.1.2.3 with gcc.
Checking for unistd.h... Yes.
Checking whether to use vs[n]printf() or s[n]printf()... using vs[n]printf()
Checking for vsnprintf() in stdio.h... Yes.
Checking for return value of vsnprintf()... Yes.
Checking for errno.h... Yes.
```

```

gcc -fPIC -O3 -DUSE_MMAP -c -o example.o example.c
gcc -fPIC -O3 -DUSE_MMAP -c -o adler32.o adler32.c
gcc -fPIC -O3 -DUSE_MMAP -c -o compress.o compress.c
gcc -fPIC -O3 -DUSE_MMAP -c -o crc32.o crc32.c
gcc -fPIC -O3 -DUSE_MMAP -c -o gzio.o gzio.c
gcc -fPIC -O3 -DUSE_MMAP -c -o uncompr.o uncompr.c
gcc -fPIC -O3 -DUSE_MMAP -c -o deflate.o deflate.c
gcc -fPIC -O3 -DUSE_MMAP -c -o trees.o trees.c
gcc -fPIC -O3 -DUSE_MMAP -c -o zutil.o zutil.c
gcc -fPIC -O3 -DUSE_MMAP -c -o inflate.o inflate.c
gcc -fPIC -O3 -DUSE_MMAP -c -o inffast.o inffast.c
gcc -fPIC -O3 -DUSE_MMAP -c -o inftrees.o inftrees.c
gcc -fPIC -O3 -DUSE_MMAP -c -o inffast.o inffast.c
gcc -shared -Wl,-soname,libz.so.1 -o libz.so.1.2.3 adler32.o compress.o crc32.o
gzio.o uncompr.o deflate.o trees.o zutil.o inflate.o inffast.o inftrees.o inffas
t.o
rm -f libz.so libz.so.1
ln -s libz.so.1.2.3 libz.so
ln -s libz.so.1.2.3 libz.so.1
gcc -fPIC -O3 -DUSE_MMAP -o example example.o -L. libz.so.1.2.3
gcc -fPIC -O3 -DUSE_MMAP -c -o minigzip.o minigzip.c
gcc -fPIC -O3 -DUSE_MMAP -o minigzip minigzip.o -L. libz.so.1.2.3
cp zlib.h zconf.h /home/milchstore/php5/include
chmod 644 /home/milchstore/php5/include/zlib.h /home/milchstore/php5/include/zco
nf.h
cp libz.so.1.2.3 /home/milchstore/php5/lib
cd /home/milchstore/php5/lib; chmod 755 libz.so.1.2.3
cd /home/milchstore/php5/lib; if test -f libz.so.1.2.3; then \
    rm -f libz.so libz.so.1; \
    ln -s libz.so.1.2.3 libz.so; \
    ln -s libz.so.1.2.3 libz.so.1; \
    (ldconfig || true) >/dev/null 2>&1; \
fi
cp zlib.3 /home/milchstore/php5/share/man/man3
chmod 644 /home/milchstore/php5/share/man/man3/zlib.3
checking build system type... x86_64-unknown-linux-gnu
checking host system type... x86_64-unknown-linux-gnu
checking target system type... x86_64-unknown-linux-gnu
checking for a BSD-compatible install... /usr/bin/install -c
checking whether build environment is sane... yes
checking for gawk... gawk
checking whether make sets $(MAKE)... yes
checking whether to enable maintainer-specific portions of Makefiles... no
checking whether make sets $(MAKE)... (cached) yes
checking for g++... g++
checking for C++ compiler default output file name... a.out
checking whether the C++ compiler works... yes
checking whether we are cross compiling... no
checking for suffix of executables...
checking for suffix of object files... o

```


checking whether g++ accepts -g... yes
checking for style of include used by make... GNU
checking dependency style of g++... gcc3
checking for gcc... gcc
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ANSI C... none needed
checking dependency style of gcc... gcc3
checking how to run the C preprocessor... gcc -E
checking for a BSD-compatible install... /usr/bin/install -c
checking whether ln -s works... yes
checking whether make sets \$(MAKE)... (cached) yes
checking for a BSD-compatible install... /usr/bin/install -c
checking whether ln -s works... yes
checking whether in maintanance mode... no
checking whether in dmalloc mode... no
checking whether to enable dynamic module loading... no

*** Dynamic loading has been disabled
checking which algorithms to include into library... cbc cfb ctr ecb ncfb nofb o
fb stream threeway cast-128 gost rijndael-128 safer-sk64 twofish arcfour cast-2
56 loki97 rijndael-192 saferplus wake blowfish-compat des rijndael-256 serpent
xtea blowfish enigma rc2 safer-sk128 tripledes
checking for dirent.h that defines DIR... yes
checking for library containing opendir... none required
checking for egrep... grep -E
checking for ANSI C header files... yes
checking for inline... inline
checking for an ANSI C-conforming const... yes
checking for sys/types.h... yes
checking for sys/stat.h... yes
checking for stdlib.h... yes
checking for string.h... yes
checking for memory.h... yes
checking for strings.h... yes
checking for inttypes.h... yes
checking for stdint.h... yes
checking for unistd.h... yes
checking argz.h usability... yes
checking argz.h presence... yes
checking for argz.h... yes
checking byteswap.h usability... yes
checking byteswap.h presence... yes
checking for byteswap.h... yes
checking dirent.h usability... yes
checking dirent.h presence... yes
checking for dirent.h... yes
checking dlfcn.h usability... yes
checking dlfcn.h presence... yes
checking for dlfcn.h... yes

checking endian.h presence... yes
checking for endian.h... yes
checking malloc.h usability... yes
checking malloc.h presence... yes
checking for malloc.h... yes
checking for memory.h... (cached) yes
checking for stdlib.h... (cached) yes
checking for string.h... (cached) yes
checking for strings.h... (cached) yes
checking sys/endian.h usability... no
checking sys/endian.h presence... no
checking for sys/endian.h... no
checking for sys/types.h... (cached) yes
checking sys/mman.h usability... yes
checking sys/mman.h presence... yes
checking for sys/mman.h... yes
checking limits.h usability... yes
checking limits.h presence... yes
checking for limits.h... yes
checking for unistd.h... (cached) yes
checking whether closedir returns void... no
checking for stdlib.h... (cached) yes
checking for GNU libc compatible malloc... yes
checking for working memcmp... yes
checking for stdlib.h... (cached) yes
checking for GNU libc compatible realloc... yes
checking for bzero... yes
checking for memmove... yes
checking for memset... yes
checking for mlock... yes
checking for readdir_r... yes
checking for strchr... yes
checking for strdup... yes
checking for strrchr... yes
checking for readdir,,... no
checking for bcopy,,... no
checking whether byte ordering is bigendian... no
checking for unsigned long int... yes
checking size of unsigned long int... 8
checking for unsigned int... yes
checking size of unsigned int... 4
checking for unsigned short int... yes
checking size of unsigned short int... 2
checking for unsigned char... yes
checking size of unsigned char... 1
checking for a sed that does not truncate output... /bin/sed
checking for ld used by gcc... /usr/bin/ld
checking if the linker (/usr/bin/ld) is GNU ld... yes
checking for /usr/bin/ld option to reload object files... -r
checking for BSD-compatible nm... /usr/bin/nm -B

checking for dlfcn.h... (cached) yes
checking how to run the C++ preprocessor... g++ -E
checking for g77... g77
checking whether we are using the GNU Fortran 77 compiler... yes
checking whether g77 accepts -g... yes
checking the maximum length of command line arguments... 32768
checking command to parse /usr/bin/nm -B output from gcc object... ok
checking for objdir... .libs
checking for ar... ar
checking for ranlib... ranlib
checking for strip... strip
checking if gcc supports -fno-rtti -fno-exceptions... no
checking for gcc option to produce PIC... -fPIC
checking if gcc PIC flag -fPIC works... yes
checking if gcc static flag -static works... yes
checking if gcc supports -c -o file.o... yes
checking whether the gcc linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking whether -lc should be explicitly linked in... no
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
checking whether stripping libraries is possible... yes
checking for shl_load... no
checking for shl_load in -ldld... no
checking for dlopen... no
checking for dlopen in -ldl... yes
checking whether a program can dlopen itself... yes
checking whether a statically linked program can dlopen itself... no
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries...
configure: creating libtool
appending configuration tag "CXX" to libtool
checking for ld used by g++... /usr/bin/ld -m elf_x86_64
checking if the linker (/usr/bin/ld -m elf_x86_64) is GNU ld... yes
checking whether the g++ linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking for g++ option to produce PIC... -fPIC
checking if g++ PIC flag -fPIC works... yes
checking if g++ static flag -static works... yes
checking if g++ supports -c -o file.o... yes
checking whether the g++ linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
appending configuration tag "F77" to libtool
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries...
checking for g77 option to produce PIC... -fPIC

```
checking if g77 static flag -static works... yes
checking if g77 supports -c -o file.o... yes
checking whether the g77 linker (/usr/bin/ld -m elf_x86_64) supports shared libr
aries... yes
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
configure: creating ./config.status
config.status: creating Makefile
config.status: creating libmccrypt.spec
config.status: creating lib/Makefile
config.status: creating doc/Makefile
config.status: creating src/Makefile
config.status: creating include/mutils/mccrypt.h
config.status: creating include/Makefile
config.status: creating modules/Makefile
config.status: creating modules/modes/Makefile
config.status: creating modules/algorithms/Makefile
config.status: creating lib/libmccrypt-config
config.status: creating config.h
config.status: executing depfiles commands
config.status: executing default-1 commands
make all-recursive
make[1]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8'
Making all in modules
make[2]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/modules'
Making all in algorithms
make[3]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/modules/alg
orithms'
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT 3-way.lo -MD -MP -MF ".deps/3-way.T
po" -c -o 3-way.lo 3-way.c; \
    then mv -f ".deps/3-way.Tpo" ".deps/3-way.Plo"; else rm -f ".deps/3-way.
Tpo"; exit 1; fi
mkdir .libs
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT 3-way.lo
-MD -MP -MF .deps/3-way.Tpo -c 3-way.c -fPIC -DPIC -o .libs/3-way.o
3-way.c:73: warning: conflicting types for built-in function 'gamma'
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -o threeway.la -module
-avoid-version -rpath /home/milchstore/php5/lib/libmccrypt 3-way.lo
gcc -shared .libs/3-way.o -Wl,-soname -Wl,threeway.so -o .libs/threeway.so
creating threeway.la
(cd .libs && rm -f threeway.la && ln -s ../threeway.la threeway.la)
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT cast-128.lo -MD -MP -MF ".deps/cast
-128.Tpo" -c -o cast-128.lo cast-128.c; \
    then mv -f ".deps/cast-128.Tpo" ".deps/cast-128.Plo"; else rm -f ".deps/
cast-128.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT cast-128
.lo -MD -MP -MF .deps/cast-128.Tpo -c cast-128.c -fPIC -DPIC -o .libs/cast-128.
o
```

```

-avoid-version -rpath /home/milchstore/php5/lib/libmccrypt cast-128.lo
gcc -shared .libs/cast-128.o -Wl,-soname -Wl,cast-128.so -o .libs/cast-128.so
creating cast-128.la
(cd .libs && rm -f cast-128.la && ln -s ../cast-128.la cast-128.la)
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT gost.lo -MD -MP -MF ".deps/gost.Tpo
" -c -o gost.lo gost.c; \
    then mv -f ".deps/gost.Tpo" ".deps/gost.Plo"; else rm -f ".deps/gost.Tpo
"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT gost.lo
-MD -MP -MF .deps/gost.Tpo -c gost.c -fPIC -DPIC -o .libs/gost.o
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -o gost.la -module -av
oid-version -rpath /home/milchstore/php5/lib/libmccrypt gost.lo
gcc -shared .libs/gost.o -Wl,-soname -Wl,gost.so -o .libs/gost.so
creating gost.la
(cd .libs && rm -f gost.la && ln -s ../gost.la gost.la)
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT rijndael-128.lo -MD -MP -MF ".deps/
rijndael-128.Tpo" -c -o rijndael-128.lo rijndael-128.c; \
    then mv -f ".deps/rijndael-128.Tpo" ".deps/rijndael-128.Plo"; else rm -f
".deps/rijndael-128.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT rijndael
-128.lo -MD -MP -MF .deps/rijndael-128.Tpo -c rijndael-128.c -fPIC -DPIC -o .li
bs/rijndael-128.o
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -o rijndael-128.la -mo
dule -avoid-version -rpath /home/milchstore/php5/lib/libmccrypt rijndael-128.lo
gcc -shared .libs/rijndael-128.o -Wl,-soname -Wl,rijndael-128.so -o .libs/rij
ndael-128.so
creating rijndael-128.la
(cd .libs && rm -f rijndael-128.la && ln -s ../rijndael-128.la rijndael-128.la)
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT safer64.lo -MD -MP -MF ".deps/safer
64.Tpo" -c -o safer64.lo safer64.c; \
    then mv -f ".deps/safer64.Tpo" ".deps/safer64.Plo"; else rm -f ".deps/sa
fer64.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT safer64.
lo -MD -MP -MF .deps/safer64.Tpo -c safer64.c -fPIC -DPIC -o .libs/safer64.o
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -o safer-sk64.la -modu
le -avoid-version -rpath /home/milchstore/php5/lib/libmccrypt safer64.lo
gcc -shared .libs/safer64.o -Wl,-soname -Wl,safer-sk64.so -o .libs/safer-sk64
.so
creating safer-sk64.la
(cd .libs && rm -f safer-sk64.la && ln -s ../safer-sk64.la safer-sk64.la)
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT twofish.lo -MD -MP -MF ".deps/twofi
sh.Tpo" -c -o twofish.lo twofish.c; \
    then mv -f ".deps/twofish.Tpo" ".deps/twofish.Plo"; else rm -f ".deps/tw
ofish.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT twofish.
lo -MD -MP -MF .deps/twofish.Tpo -c twofish.c -fPIC -DPIC -o .libs/twofish.o

```

```

-avoid-version -rpath /home/milchstore/php5/lib/libmccrypt twofish.lo
gcc -shared .libs/twofish.o -WL,-soname -WL,twofish.so -o .libs/twofish.so
creating twofish.la
(cd .libs && rm -f twofish.la && ln -s ../twofish.la twofish.la)
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT arcfour.lo -MD -MP -MF ".deps/arcfo
ur.Tpo" -c -o arcfour.lo arcfour.c; \
    then mv -f ".deps/arcfour.Tpo" ".deps/arcfour.Plo"; else rm -f ".deps/ar
cfour.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT arcfour.
lo -MD -MP -MF .deps/arcfour.Tpo -c arcfour.c -fPIC -DPIC -o .libs/arcfour.o
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -o arcfour.la -module
-avoid-version -rpath /home/milchstore/php5/lib/libmccrypt arcfour.lo
gcc -shared .libs/arcfour.o -WL,-soname -WL,arcfour.so -o .libs/arcfour.so
creating arcfour.la
(cd .libs && rm -f arcfour.la && ln -s ../arcfour.la arcfour.la)
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT cast-256.lo -MD -MP -MF ".deps/cast
-256.Tpo" -c -o cast-256.lo cast-256.c; \
    then mv -f ".deps/cast-256.Tpo" ".deps/cast-256.Plo"; else rm -f ".deps/
cast-256.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT cast-256
.lo -MD -MP -MF .deps/cast-256.Tpo -c cast-256.c -fPIC -DPIC -o .libs/cast-256.
o
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -o cast-256.la -module
-avoid-version -rpath /home/milchstore/php5/lib/libmccrypt cast-256.lo
gcc -shared .libs/cast-256.o -WL,-soname -WL,cast-256.so -o .libs/cast-256.so
creating cast-256.la
(cd .libs && rm -f cast-256.la && ln -s ../cast-256.la cast-256.la)
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT loki97.lo -MD -MP -MF ".deps/loki97
.Tpo" -c -o loki97.lo loki97.c; \
    then mv -f ".deps/loki97.Tpo" ".deps/loki97.Plo"; else rm -f ".deps/loki
97.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT loki97.l
o -MD -MP -MF .deps/loki97.Tpo -c loki97.c -fPIC -DPIC -o .libs/loki97.o
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -o loki97.la -module -
avoid-version -rpath /home/milchstore/php5/lib/libmccrypt loki97.lo
gcc -shared .libs/loki97.o -WL,-soname -WL,loki97.so -o .libs/loki97.so
creating loki97.la
(cd .libs && rm -f loki97.la && ln -s ../loki97.la loki97.la)
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT rijndael-192.lo -MD -MP -MF ".deps/
rijndael-192.Tpo" -c -o rijndael-192.lo rijndael-192.c; \
    then mv -f ".deps/rijndael-192.Tpo" ".deps/rijndael-192.Plo"; else rm -f
".deps/rijndael-192.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT rijndael
-192.lo -MD -MP -MF .deps/rijndael-192.Tpo -c rijndael-192.c -fPIC -DPIC -o .li
bs/rijndael-192.o
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -o rijndael-192.la -mo

```



```

gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..../lib -g -O2 -MT des.lo -
MD -MP -MF .deps/des.Tpo -c des.c -fPIC -DPIC -o .libs/des.o
/bin/sh ../..../libtool --tag=CC --mode=link gcc -g -O2 -o des.la -module -avo
id-version -rpath /home/milchstore/php5/lib/libmcrypt des.lo
gcc -shared .libs/des.o -Wl,-soname -Wl,des.so -o .libs/des.so
creating des.la
(cd .libs && rm -f des.la && ln -s ../des.la des.la)
if /bin/sh ../..../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../.. -I. -I../.. -I../..../lib -g -O2 -MT rijndael-256.lo -MD -MP -MF ".deps/
rijndael-256.Tpo" -c -o rijndael-256.lo rijndael-256.c; \
    then mv -f ".deps/rijndael-256.Tpo" ".deps/rijndael-256.Plo"; else rm -f
".deps/rijndael-256.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..../lib -g -O2 -MT rijndael
-256.lo -MD -MP -MF .deps/rijndael-256.Tpo -c rijndael-256.c -fPIC -DPIC -o .li
bs/rijndael-256.o
/bin/sh ../..../libtool --tag=CC --mode=link gcc -g -O2 -o rijndael-256.la -mo
dule -avoid-version -rpath /home/milchstore/php5/lib/libmcrypt rijndael-256.lo

gcc -shared .libs/rijndael-256.o -Wl,-soname -Wl,rijndael-256.so -o .libs/rij
ndael-256.so
creating rijndael-256.la
(cd .libs && rm -f rijndael-256.la && ln -s ../rijndael-256.la rijndael-256.la)
if /bin/sh ../..../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../.. -I. -I../.. -I../..../lib -g -O2 -MT serpent.lo -MD -MP -MF ".deps/serpe
nt.Tpo" -c -o serpent.lo serpent.c; \
    then mv -f ".deps/serpent.Tpo" ".deps/serpent.Plo"; else rm -f ".deps/se
rpent.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..../lib -g -O2 -MT serpent.
lo -MD -MP -MF .deps/serpent.Tpo -c serpent.c -fPIC -DPIC -o .libs/serpent.o
/bin/sh ../..../libtool --tag=CC --mode=link gcc -g -O2 -o serpent.la -module
-avoid-version -rpath /home/milchstore/php5/lib/libmcrypt serpent.lo
gcc -shared .libs/serpent.o -Wl,-soname -Wl,serpent.so -o .libs/serpent.so
creating serpent.la
(cd .libs && rm -f serpent.la && ln -s ../serpent.la serpent.la)
if /bin/sh ../..../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../.. -I. -I../.. -I../..../lib -g -O2 -MT xtea.lo -MD -MP -MF ".deps/xtea.Tpo
" -c -o xtea.lo xtea.c; \
    then mv -f ".deps/xtea.Tpo" ".deps/xtea.Plo"; else rm -f ".deps/xtea.Tpo
"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..../lib -g -O2 -MT xtea.lo
-MD -MP -MF .deps/xtea.Tpo -c xtea.c -fPIC -DPIC -o .libs/xtea.o
/bin/sh ../..../libtool --tag=CC --mode=link gcc -g -O2 -o xtea.la -module -av
oid-version -rpath /home/milchstore/php5/lib/libmcrypt xtea.lo
gcc -shared .libs/xtea.o -Wl,-soname -Wl,xtea.so -o .libs/xtea.so
creating xtea.la
(cd .libs && rm -f xtea.la && ln -s ../xtea.la xtea.la)
if /bin/sh ../..../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../.. -I. -I../.. -I../..../lib -g -O2 -MT blowfish.lo -MD -MP -MF ".deps/blow
fish.Tpo" -c -o blowfish.lo blowfish.c; \
    then mv -f ".deps/blowfish.Tpo" ".deps/blowfish.Plo"; else rm -f ".deps/

```



```

gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..../lib -g -O2 -MT blowfish
.lo -MD -MP -MF .deps/blowfish.Tpo -c blowfish.c -fPIC -DPIC -o .libs/blowfish.
o
/bin/sh ../..../libtool --tag=CC --mode=link gcc -g -O2 -o blowfish.la -module
-avoid-version -rpath /home/milchstore/php5/lib/libmccrypt blowfish.lo
gcc -shared .libs/blowfish.o -Wl,-soname -Wl,blowfish.so -o .libs/blowfish.so
creating blowfish.la
(cd .libs && rm -f blowfish.la && ln -s ../blowfish.la blowfish.la)
if /bin/sh ../..../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../.. -I. -I../.. -I../..../lib -g -O2 -MT enigma.lo -MD -MP -MF ".deps/enigma
.Tpo" -c -o enigma.lo enigma.c; \
    then mv -f ".deps/enigma.Tpo" ".deps/enigma.Plo"; else rm -f ".deps/enig
ma.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..../lib -g -O2 -MT enigma.l
o -MD -MP -MF .deps/enigma.Tpo -c enigma.c -fPIC -DPIC -o .libs/enigma.o
/bin/sh ../..../libtool --tag=CC --mode=link gcc -g -O2 -o enigma.la -module -
avoid-version -rpath /home/milchstore/php5/lib/libmccrypt enigma.lo
gcc -shared .libs/enigma.o -Wl,-soname -Wl,enigma.so -o .libs/enigma.so
creating enigma.la
(cd .libs && rm -f enigma.la && ln -s ../enigma.la enigma.la)
if /bin/sh ../..../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../.. -I. -I../.. -I../..../lib -g -O2 -MT rc2.lo -MD -MP -MF ".deps/rc2.Tpo"
-c -o rc2.lo rc2.c; \
    then mv -f ".deps/rc2.Tpo" ".deps/rc2.Plo"; else rm -f ".deps/rc2.Tpo";
exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..../lib -g -O2 -MT rc2.lo -
MD -MP -MF .deps/rc2.Tpo -c rc2.c -fPIC -DPIC -o .libs/rc2.o
/bin/sh ../..../libtool --tag=CC --mode=link gcc -g -O2 -o rc2.la -module -avo
id-version -rpath /home/milchstore/php5/lib/libmccrypt rc2.lo
gcc -shared .libs/rc2.o -Wl,-soname -Wl,rc2.so -o .libs/rc2.so
creating rc2.la
(cd .libs && rm -f rc2.la && ln -s ../rc2.la rc2.la)
if /bin/sh ../..../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../.. -I. -I../.. -I../..../lib -g -O2 -MT safer128.lo -MD -MP -MF ".deps/safe
r128.Tpo" -c -o safer128.lo safer128.c; \
    then mv -f ".deps/safer128.Tpo" ".deps/safer128.Plo"; else rm -f ".deps/
safer128.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..../lib -g -O2 -MT safer128
.lo -MD -MP -MF .deps/safer128.Tpo -c safer128.c -fPIC -DPIC -o .libs/safer128.
o
/bin/sh ../..../libtool --tag=CC --mode=link gcc -g -O2 -o safer-sk128.la -mod
ule -avoid-version -rpath /home/milchstore/php5/lib/libmccrypt safer128.lo
gcc -shared .libs/safer128.o -Wl,-soname -Wl,safer-sk128.so -o .libs/safer-sk
128.so
creating safer-sk128.la
(cd .libs && rm -f safer-sk128.la && ln -s ../safer-sk128.la safer-sk128.la)
if /bin/sh ../..../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../.. -I. -I../.. -I../..../lib -g -O2 -MT tripledес.lo -MD -MP -MF ".deps/tri
pledес.Tpo" -c -o tripledес.lo tripledес.c; \
    then mv -f ".deps/triplедес.Tpo" ".deps/triplедес.Plo"; else rm -f ".dep

```

```

gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..lib -g -O2 -MT tripledes.lo -MD -MP -MF .deps/tripledes.Tpo -c tripledes.c -fPIC -DPIC -o .libs/tripledes.o
/bin/sh ../..libtool --tag=CC --mode=link gcc -g -O2 -o tripledes.la -module -avoid-version -rpath /home/milchstore/php5/lib/libmcrypt tripledes.lo
gcc -shared .libs/tripledes.o -Wl,-soname -Wl,tripledes.so -o .libs/tripledes.so
creating tripledes.la
(cd .libs && rm -f tripledes.la && ln -s ../tripledes.la tripledes.la)
make[3]: Leaving directory `/home/milchstore/source/libmcrypt-2.5.8/modules/algorithms'
Making all in modes
make[3]: Entering directory `/home/milchstore/source/libmcrypt-2.5.8/modules/modes'
if /bin/sh ../..libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..lib -g -O2 -MT cbc.lo -MD -MP -MF ".deps/cbc.Tpo" -c -o cbc.lo cbc.c; \
    then mv -f ".deps/cbc.Tpo" ".deps/cbc.Plo"; else rm -f ".deps/cbc.Tpo";
exit 1; fi
mkdir .libs
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..lib -g -O2 -MT cbc.lo -MD -MP -MF .deps/cbc.Tpo -c cbc.c -fPIC -DPIC -o .libs/cbc.o
/bin/sh ../..libtool --tag=CC --mode=link gcc -g -O2 -o cbc.la -module -avoid-version -rpath /home/milchstore/php5/lib/libmcrypt cbc.lo
gcc -shared .libs/cbc.o -Wl,-soname -Wl,cbc.so -o .libs/cbc.so
creating cbc.la
(cd .libs && rm -f cbc.la && ln -s ../cbc.la cbc.la)
if /bin/sh ../..libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..lib -g -O2 -MT cfb.lo -MD -MP -MF ".deps/cfb.Tpo" -c -o cfb.lo cfb.c; \
    then mv -f ".deps/cfb.Tpo" ".deps/cfb.Plo"; else rm -f ".deps/cfb.Tpo";
exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..lib -g -O2 -MT cfb.lo -MD -MP -MF .deps/cfb.Tpo -c cfb.c -fPIC -DPIC -o .libs/cfb.o
/bin/sh ../..libtool --tag=CC --mode=link gcc -g -O2 -o cfb.la -module -avoid-version -rpath /home/milchstore/php5/lib/libmcrypt cfb.lo
gcc -shared .libs/cfb.o -Wl,-soname -Wl,cfb.so -o .libs/cfb.so
creating cfb.la
(cd .libs && rm -f cfb.la && ln -s ../cfb.la cfb.la)
if /bin/sh ../..libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..lib -g -O2 -MT ctr.lo -MD -MP -MF ".deps/ctr.Tpo" -c -o ctr.lo ctr.c; \
    then mv -f ".deps/ctr.Tpo" ".deps/ctr.Plo"; else rm -f ".deps/ctr.Tpo";
exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..lib -g -O2 -MT ctr.lo -MD -MP -MF .deps/ctr.Tpo -c ctr.c -fPIC -DPIC -o .libs/ctr.o
/bin/sh ../..libtool --tag=CC --mode=link gcc -g -O2 -o ctr.la -module -avoid-version -rpath /home/milchstore/php5/lib/libmcrypt ctr.lo
gcc -shared .libs/ctr.o -Wl,-soname -Wl,ctr.so -o .libs/ctr.so
creating ctr.la

```

```

if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT ecb.lo -MD -MP -MF ".deps/ecb.Tpo"
-c -o ecb.lo ecb.c; \
    then mv -f ".deps/ecb.Tpo" ".deps/ecb.Plo"; else rm -f ".deps/ecb.Tpo";
exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT ecb.lo -
MD -MP -MF .deps/ecb.Tpo -c ecb.c -fPIC -DPIC -o .libs/ecb.o
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -o ecb.la -module -avo
id-version -rpath /home/milchstore/php5/lib/libmccrypt ecb.lo
gcc -shared .libs/ecb.o -Wl,-soname -Wl,ecb.so -o .libs/ecb.so
creating ecb.la
(cd .libs && rm -f ecb.la && ln -s ../ecb.la ecb.la)
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT ncfb.lo -MD -MP -MF ".deps/ncfb.Tpo
" -c -o ncfb.lo ncfb.c; \
    then mv -f ".deps/ncfb.Tpo" ".deps/ncfb.Plo"; else rm -f ".deps/ncfb.Tpo
"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT ncfb.lo
-MD -MP -MF .deps/ncfb.Tpo -c ncfb.c -fPIC -DPIC -o .libs/ncfb.o
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -o ncfb.la -module -av
oid-version -rpath /home/milchstore/php5/lib/libmccrypt ncfb.lo
gcc -shared .libs/ncfb.o -Wl,-soname -Wl,ncfb.so -o .libs/ncfb.so
creating ncfb.la
(cd .libs && rm -f ncfb.la && ln -s ../ncfb.la ncfb.la)
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT nofb.lo -MD -MP -MF ".deps/nofb.Tpo
" -c -o nofb.lo nofb.c; \
    then mv -f ".deps/nofb.Tpo" ".deps/nofb.Plo"; else rm -f ".deps/nofb.Tpo
"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT nofb.lo
-MD -MP -MF .deps/nofb.Tpo -c nofb.c -fPIC -DPIC -o .libs/nofb.o
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -o nofb.la -module -av
oid-version -rpath /home/milchstore/php5/lib/libmccrypt nofb.lo
gcc -shared .libs/nofb.o -Wl,-soname -Wl,nofb.so -o .libs/nofb.so
creating nofb.la
(cd .libs && rm -f nofb.la && ln -s ../nofb.la nofb.la)
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT ofb.lo -MD -MP -MF ".deps/ofb.Tpo"
-c -o ofb.lo ofb.c; \
    then mv -f ".deps/ofb.Tpo" ".deps/ofb.Plo"; else rm -f ".deps/ofb.Tpo";
exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../.. /lib -g -O2 -MT ofb.lo -
MD -MP -MF .deps/ofb.Tpo -c ofb.c -fPIC -DPIC -o .libs/ofb.o
/bin/sh ../../libtool --tag=CC --mode=link gcc -g -O2 -o ofb.la -module -avo
id-version -rpath /home/milchstore/php5/lib/libmccrypt ofb.lo
gcc -shared .libs/ofb.o -Wl,-soname -Wl,ofb.so -o .libs/ofb.so
creating ofb.la
(cd .libs && rm -f ofb.la && ln -s ../ofb.la ofb.la)
if /bin/sh ../../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I
../../ -I. -I../.. -I../.. /lib -g -O2 -MT stream.lo -MD -MP -MF ".deps/stream

```

```

    then mv -f ".deps/stream.Tpo" ".deps/stream.Plo"; else rm -f ".deps/stre
am.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../.. -I. -I../.. -I../..lib -g -O2 -MT stream.l
o -MD -MP -MF .deps/stream.Tpo -c stream.c -fPIC -DPIC -o .libs/stream.o
/bin/sh ../..libtool --tag=CC --mode=link gcc -g -O2 -o stream.la -module -
avoid-version -rpath /home/milchstore/php5/lib/libmcrypt stream.lo
gcc -shared .libs/stream.o -Wl,-soname -Wl,stream.so -o .libs/stream.so
creating stream.la
(cd .libs && rm -f stream.la && ln -s ../stream.la stream.la)
make[3]: Leaving directory `/home/milchstore/source/libmcrypt-2.5.8/modules/mode
s'
make[3]: Entering directory `/home/milchstore/source/libmcrypt-2.5.8/modules'
make[3]: Nothing to be done for `all-am'.
make[3]: Leaving directory `/home/milchstore/source/libmcrypt-2.5.8/modules'
make[2]: Leaving directory `/home/milchstore/source/libmcrypt-2.5.8/modules'
Making all in include
make[2]: Entering directory `/home/milchstore/source/libmcrypt-2.5.8/include'
make[2]: Nothing to be done for `all'.
make[2]: Leaving directory `/home/milchstore/source/libmcrypt-2.5.8/include'
Making all in lib
make[2]: Entering directory `/home/milchstore/source/libmcrypt-2.5.8/lib'
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -DLIBDIR="/ho
me/milchstore/php5/lib/libmcrypt/" -I. -I. -I.. -I. -I.. -I../modules/algorit
hms -I../modules/modes -g -O2 -MT mcrypt_extra.lo -MD -MP -MF ".deps/mcrypt_e
xtra.Tpo" -c -o mcrypt_extra.lo mcrypt_extra.c; \
    then mv -f ".deps/mcrypt_extra.Tpo" ".deps/mcrypt_extra.Plo"; else rm -f
".deps/mcrypt_extra.Tpo"; exit 1; fi
mkdir .libs
gcc -DHAVE_CONFIG_H -DLIBDIR="/home/milchstore/php5/lib/libmcrypt/" -I. -I. -
I.. -I. -I.. -I../modules/algorithms -I../modules/modes -g -O2 -MT mcrypt_extra.
lo -MD -MP -MF .deps/mcrypt_extra.Tpo -c mcrypt_extra.c -fPIC -DPIC -o .libs/mc
rypt_extra.o
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -DLIBDIR="/ho
me/milchstore/php5/lib/libmcrypt/" -I. -I. -I.. -I. -I.. -I../modules/algorit
hms -I../modules/modes -g -O2 -MT mcrypt.lo -MD -MP -MF ".deps/mcrypt.Tpo" -c
-o mcrypt.lo mcrypt.c; \
    then mv -f ".deps/mcrypt.Tpo" ".deps/mcrypt.Plo"; else rm -f ".deps/mcry
pt.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -DLIBDIR="/home/milchstore/php5/lib/libmcrypt/" -I. -I. -
I.. -I. -I.. -I../modules/algorithms -I../modules/modes -g -O2 -MT mcrypt.lo -MD
-MP -MF .deps/mcrypt.Tpo -c mcrypt.c -fPIC -DPIC -o .libs/mcrypt.o
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -DLIBDIR="/ho
me/milchstore/php5/lib/libmcrypt/" -I. -I. -I.. -I. -I.. -I../modules/algorit
hms -I../modules/modes -g -O2 -MT bzero.lo -MD -MP -MF ".deps/bzero.Tpo" -c -
o bzero.lo bzero.c; \
    then mv -f ".deps/bzero.Tpo" ".deps/bzero.Plo"; else rm -f ".deps/bzero.
Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -DLIBDIR="/home/milchstore/php5/lib/libmcrypt/" -I. -I. -
I.. -I. -I.. -I../modules/algorithms -I../modules/modes -g -O2 -MT bzero.lo -MD
-MP -MF .deps/bzero.Tpo -c bzero.c -fPIC -DPIC -o .libs/bzero.o

```

```

me/milchstore/php5/lib/libmccrypt/" -I. -I. -I.. -I. -I.. -I../modules/algorit
hms -I../modules/modes -g -O2 -MT xmemory.lo -MD -MP -MF ".deps/xmemory.Tpo"
-c -o xmemory.lo xmemory.c; \
    then mv -f ".deps/xmemory.Tpo" ".deps/xmemory.Plo"; else rm -f ".deps/xm
emory.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -DLIBDIR="/home/milchstore/php5/lib/libmccrypt/" -I. -I. -
I.. -I. -I.. -I../modules/algorithms -I../modules/modes -g -O2 -MT xmemory.lo -M
D -MP -MF .deps/xmemory.Tpo -c xmemory.c -fPIC -DPIC -o .libs/xmemory.o
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -DLIBDIR="/ho
me/milchstore/php5/lib/libmccrypt/" -I. -I. -I.. -I. -I.. -I../modules/algorit
hms -I../modules/modes -g -O2 -MT mcrpt_modules.lo -MD -MP -MF ".deps/mcrpt
_modules.Tpo" -c -o mcrpt_modules.lo mcrpt_modules.c; \
    then mv -f ".deps/mcrpt_modules.Tpo" ".deps/mcrpt_modules.Plo"; else r
m -f ".deps/mcrpt_modules.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -DLIBDIR="/home/milchstore/php5/lib/libmccrypt/" -I. -I. -
I.. -I. -I.. -I../modules/algorithms -I../modules/modes -g -O2 -MT mcrpt_module
s.lo -MD -MP -MF .deps/mcrpt_modules.Tpo -c mcrpt_modules.c -fPIC -DPIC -o .l
ibs/mcrpt_modules.o
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -DLIBDIR="/ho
me/milchstore/php5/lib/libmccrypt/" -I. -I. -I.. -I. -I.. -I../modules/algorit
hms -I../modules/modes -g -O2 -MT win32_comp.lo -MD -MP -MF ".deps/win32_comp
.Tpo" -c -o win32_comp.lo win32_comp.c; \
    then mv -f ".deps/win32_comp.Tpo" ".deps/win32_comp.Plo"; else rm -f ".d
eps/win32_comp.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -DLIBDIR="/home/milchstore/php5/lib/libmccrypt/" -I. -I. -
I.. -I. -I.. -I../modules/algorithms -I../modules/modes -g -O2 -MT win32_comp.lo
-MD -MP -MF .deps/win32_comp.Tpo -c win32_comp.c -fPIC -DPIC -o .libs/win32_co
mp.o
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -DLIBDIR="/ho
me/milchstore/php5/lib/libmccrypt/" -I. -I. -I.. -I. -I.. -I../modules/algorit
hms -I../modules/modes -g -O2 -MT mcrpt_threads.lo -MD -MP -MF ".deps/mcrpt
_threads.Tpo" -c -o mcrpt_threads.lo mcrpt_threads.c; \
    then mv -f ".deps/mcrpt_threads.Tpo" ".deps/mcrpt_threads.Plo"; else r
m -f ".deps/mcrpt_threads.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -DLIBDIR="/home/milchstore/php5/lib/libmccrypt/" -I. -I. -
I.. -I. -I.. -I../modules/algorithms -I../modules/modes -g -O2 -MT mcrpt_thread
s.lo -MD -MP -MF .deps/mcrpt_threads.Tpo -c mcrpt_threads.c -fPIC -DPIC -o .l
ibs/mcrpt_threads.o
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -DLIBDIR="/ho
me/milchstore/php5/lib/libmccrypt/" -I. -I. -I.. -I. -I.. -I../modules/algorit
hms -I../modules/modes -g -O2 -MT mcrpt_symb.lo -MD -MP -MF ".deps/mcrpt_sy
mb.Tpo" -c -o mcrpt_symb.lo mcrpt_symb.c; \
    then mv -f ".deps/mcrpt_symb.Tpo" ".deps/mcrpt_symb.Plo"; else rm -f "
.deps/mcrpt_symb.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -DLIBDIR="/home/milchstore/php5/lib/libmccrypt/" -I. -I. -
I.. -I. -I.. -I../modules/algorithms -I../modules/modes -g -O2 -MT mcrpt_symb.l
o -MD -MP -MF .deps/mcrpt_symb.Tpo -c mcrpt_symb.c -fPIC -DPIC -o .libs/mcryp
t_symb.o
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o libmccrypt.la -rpath /ho
me/milchstore/php5/lib -version-info 8:8:4 -version-info 8:8:4 -export-symbols l

```

```
in32_comp.lo mcrypt_threads.lo mcrypt_symb.lo ../modules/modes/cbc.lo ../modules
/modes/cfb.lo ../modules/modes/ctr.lo ../modules/modes/ecb.lo ../modules/modes/n
cfb.lo ../modules/modes/nofb.lo ../modules/modes/ofb.lo ../modules/modes/stream.
lo ../modules/algorithms/cast-128.lo ../modules/algorithms/gost.lo ../modules/al
gorithms/rijndael-128.lo ../modules/algorithms/twofish.lo ../modules/algorithms/
arcfour.lo ../modules/algorithms/cast-256.lo ../modules/algorithms/loki97.lo ../
modules/algorithms/rijndael-192.lo ../modules/algorithms/saferplus.lo ../modules
/algorithms/wake.lo ../modules/algorithms/blowfish-compatible.lo ../modules/algorith
ms/des.lo ../modules/algorithms/rijndael-256.lo ../modules/algorithms/serpent.lo
../modules/algorithms/xtea.lo ../modules/algorithms/blowfish.lo ../modules/algo
rithms/enigma.lo ../modules/algorithms/rc2.lo ../modules/algorithms/tripledes.lo
```

```
echo "{ global:" > .libs/libmcrypt.ver
cat libmcrypt.sym | sed -e "s/\(.*\)\/\1;/" >> .libs/libmcrypt.ver
echo "local: *; };" >> .libs/libmcrypt.ver
gcc -shared .libs/mcrypt_extra.o .libs/mcrypt.o .libs/bzero.o .libs/xmemory.o
.libs/mcrypt_modules.o .libs/win32_comp.o .libs/mcrypt_threads.o .libs/mcrypt_sy
mb.o ../modules/modes/.libs/cbc.o ../modules/modes/.libs/cfb.o ../modules/modes/
.libs/ctr.o ../modules/modes/.libs/ecb.o ../modules/modes/.libs/ncfb.o ../module
s/modes/.libs/nofb.o ../modules/modes/.libs/ofb.o ../modules/modes/.libs/stream.
o ../modules/algorithms/.libs/cast-128.o ../modules/algorithms/.libs/gost.o ../m
odules/algorithms/.libs/rijndael-128.o ../modules/algorithms/.libs/twofish.o ../
modules/algorithms/.libs/arcfour.o ../modules/algorithms/.libs/cast-256.o ../mod
ules/algorithms/.libs/loki97.o ../modules/algorithms/.libs/rijndael-192.o ../mod
ules/algorithms/.libs/saferplus.o ../modules/algorithms/.libs/wake.o ../modules/
algorithms/.libs/blowfish-compatible.o ../modules/algorithms/.libs/des.o ../modules/
algorithms/.libs/rijndael-256.o ../modules/algorithms/.libs/serpent.o ../modules
/algorithms/.libs/xtea.o ../modules/algorithms/.libs/blowfish.o ../modules/algor
ithms/.libs/enigma.o ../modules/algorithms/.libs/rc2.o ../modules/algorithms/.li
bs/tripledes.o -Wl,-soname -Wl,libmcrypt.so.4 -Wl,-version-script -Wl,.libs/li
bmcrypt.ver -o .libs/libmcrypt.so.4.4.8
(cd .libs && rm -f libmcrypt.so.4 && ln -s libmcrypt.so.4.4.8 libmcrypt.so.4)
(cd .libs && rm -f libmcrypt.so && ln -s libmcrypt.so.4.4.8 libmcrypt.so)
creating libmcrypt.la
(cd .libs && rm -f libmcrypt.la && ln -s ../libmcrypt.la libmcrypt.la)
make[2]: Leaving directory `/home/milchstore/source/libmcrypt-2.5.8/lib'
Making all in src
make[2]: Entering directory `/home/milchstore/source/libmcrypt-2.5.8/src'
if gcc -DHAVE_CONFIG_H -I. -I. -I.. -g -O2 -MT cipher_test.o -MD -MP -MF ".d
eps/cipher_test.Tpo" -c -o cipher_test.o cipher_test.c; \
    then mv -f ".deps/cipher_test.Tpo" ".deps/cipher_test.Po"; else rm -f ".
deps/cipher_test.Tpo"; exit 1; fi
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o ciphertest cipher_test
.o ../lib/libmcrypt.la
mkdir .libs
gcc -g -O2 -o .libs/ciphertest cipher_test.o ../lib/.libs/libmcrypt.so -Wl,--r
path -Wl,/home/milchstore/php5/lib
creating ciphertest
if gcc -DHAVE_CONFIG_H -I. -I. -I.. -g -O2 -MT aes_test.o -MD -MP -MF ".deps
/aes_test.Tpo" -c -o aes_test.o aes_test.c; \
```

```
es_test.Tpo"; exit 1; fi
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o aestest aes_test.o ../
lib/libmccrypt.la
gcc -g -O2 -o .libs/aestest aes_test.o ../lib/.libs/libmccrypt.so -Wl,--rpath -
Wl,/home/milchstore/php5/lib
creating aestest
make[2]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/src'
Making all in doc
make[2]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/doc'
make[2]: Nothing to be done for `all'.
make[2]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/doc'
make[2]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8'
make[2]: Nothing to be done for `all-am'.
make[2]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8'
make[1]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8'
Making install in modules
make[1]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/modules'
Making install in algorithms
make[2]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/modules/alg
orithms'
make[3]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/modules/alg
orithms'
test -z "/home/milchstore/php5/lib/libmccrypt" || mkdir -p -- "/home/milchstore/p
hp5/lib/libmccrypt"
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/modules/alg
orithms'
make[2]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/modules/alg
orithms'
Making install in modes
make[2]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/modules/mod
es'
make[3]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/modules/mod
es'
test -z "/home/milchstore/php5/lib/libmccrypt" || mkdir -p -- "/home/milchstore/p
hp5/lib/libmccrypt"
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/modules/mode
s'
make[2]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/modules/mode
s'
make[2]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/modules'
make[3]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/modules'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/modules'
make[2]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/modules'
make[1]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/modules'
Making install in include
make[1]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/include'
```

```

make[2]: Nothing to be done for `install-exec-am'.
test -z "/home/milchstore/php5/include" || mkdir -p -- "/home/milchstore/php5/in
clude"
/home/milchstore/source/libmccrypt-2.5.8/install-sh -c -m 644 'mccrypt.h' '/home/
milchstore/php5/include/mccrypt.h'
/home/milchstore/source/libmccrypt-2.5.8/install-sh -c -m 644 'utils/mccrypt.h'
'/home/milchstore/php5/include/utils/mccrypt.h'
make[2]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/include'
make[1]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/include'
Making install in lib
make[1]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/lib'
make[2]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/lib'
test -z "/home/milchstore/php5/bin" || mkdir -p -- "/home/milchstore/php5/bin"
/usr/bin/install -c 'libmccrypt-config' '/home/milchstore/php5/bin/libmccrypt-con
fig'
test -z "/home/milchstore/php5/lib" || mkdir -p -- "/home/milchstore/php5/lib"
/bin/sh ../libtool --mode=install /usr/bin/install -c 'libmccrypt.la' '/home/mi
lchstore/php5/lib/libmccrypt.la'
/usr/bin/install -c .libs/libmccrypt.so.4.4.8 /home/milchstore/php5/lib/libmccrypt
.so.4.4.8
(cd /home/milchstore/php5/lib && { ln -s -f libmccrypt.so.4.4.8 libmccrypt.so.4 ||
{ rm -f libmccrypt.so.4 && ln -s libmccrypt.so.4.4.8 libmccrypt.so.4; }; })
(cd /home/milchstore/php5/lib && { ln -s -f libmccrypt.so.4.4.8 libmccrypt.so || {
rm -f libmccrypt.so && ln -s libmccrypt.so.4.4.8 libmccrypt.so; }; })
/usr/bin/install -c .libs/libmccrypt.lai /home/milchstore/php5/lib/libmccrypt.la
PATH="$PATH:/sbin" ldconfig -n /home/milchstore/php5/lib

```

```

-----
Libraries have been installed in:
    /home/milchstore/php5/lib

```

If you ever happen to want to link against installed libraries in a given directory, LIBDIR, you must either use libtool, and specify the full pathname of the library, or use the `-LLIBDIR` flag during linking and do at least one of the following:

- add LIBDIR to the ``LD_LIBRARY_PATH'` environment variable during execution
- add LIBDIR to the ``LD_RUN_PATH'` environment variable during linking
- use the ``-Wl,--rpath -Wl,LIBDIR'` linker flag
- have your system administrator add LIBDIR to ``/etc/ld.so.conf'`

See any operating system documentation about shared libraries for more information, such as the `ld(1)` and `ld.so(8)` manual pages.

```

-----
test -z "/home/milchstore/php5/share/aclocal" || mkdir -p -- "/home/milchstore/p
hp5/share/aclocal"
/usr/bin/install -c -m 644 'libmccrypt.m4' '/home/milchstore/php5/share/aclocal/
libmccrypt.m4'
make[2]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/lib'
make[1]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/lib'

```



```
make[1]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/src'
make[2]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/src'
make[2]: Nothing to be done for `install-exec-am'.
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/src'
make[1]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/src'
Making install in doc
make[1]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/doc'
make[2]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/doc'
make[2]: Nothing to be done for `install-exec-am'.
test -z "/home/milchstore/php5/man/man3" || mkdir -p -- "/home/milchstore/php5/m
an/man3"
  /usr/bin/install -c -m 644 './mccrypt.3' '/home/milchstore/php5/man/man3/mccrypt.
3'
make[2]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/doc'
make[1]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/doc'
make[1]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8'
make[2]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8'
make[2]: Nothing to be done for `install-exec-am'.
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8'
make[1]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8'
creating cache ./config.cache
checking for a BSD compatible install... /usr/bin/install -c
checking whether build environment is sane... yes
checking whether make sets ${MAKE}... yes
checking for working aclocal... missing
checking for working autoconf... missing
checking for working automake... missing
checking for working autoheader... missing
checking for working makeinfo... found
checking whether to enable maintainer-specific portions of Makefiles... no
checking for gcc... gcc
checking whether the C compiler (gcc ) works... yes
checking whether the C compiler (gcc ) is a cross-compiler... no
checking whether we are using GNU C... yes
checking whether gcc accepts -g... yes
checking for working const... yes
checking for inline... inline
checking for Cygwin environment... no
checking for mingw32 environment... no
checking how to run the C preprocessor... gcc -E
checking host system type... x86_64-unknown-linux-gnu
checking build system type... x86_64-unknown-linux-gnu
checking for ld used by GCC... /usr/bin/ld
checking if the linker (/usr/bin/ld) is GNU ld... yes
checking for /usr/bin/ld option to reload object files... -r
checking for BSD-compatible nm... /usr/bin/nm -B
checking for a sed that does not truncate output... /bin/sed
checking whether ln -s works... yes
```

```
[LM]SB (shared object|dynamic lib )
checking for object suffix... o
checking for executable suffix... no
checking command to parse /usr/bin/nm -B output... ok
checking for dlfcn.h... yes
checking for file... /usr/bin/file
checking for ranlib... ranlib
checking for strip... strip
checking for objdir... .libs
checking for gcc option to produce PIC... -fPIC
checking if gcc PIC flag -fPIC works... yes
checking if gcc static flag -static works... yes
checking if gcc supports -c -o file.o... yes
checking if gcc supports -c -o file.lo... yes
checking if gcc supports -fno-rtti -fno-exceptions... yes
checking whether the linker (/usr/bin/ld) supports shared libraries... yes
checking how to hardcode library paths into programs... immediate
checking whether stripping libraries is possible... yes
checking dynamic linker characteristics... GNU/Linux ld.so
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries... yes
checking whether -lc should be explicitly linked in... no
creating libtool
checking for ANSI C header files... yes
checking for dirent.h that defines DIR... yes
checking for opendir in -ldir... no
checking whether gcc supports assert without backlinking...
checking which extension is used for shared libraries... .so
checking which variable specifies run-time library path... LD_LIBRARY_PATH
checking for the default library search path... /lib /usr/lib
checking for objdir... .libs
checking whether libtool supports -dlopen/-dlpreopen... yes
checking for shl_load... no
checking for shl_load in -ldld... no
checking for dlopen in -ldl... yes
checking for dlerror... yes
checking for _ prefix in compiled symbols... no
checking whether deplibs are loaded by dlopen... yes
checking for argz.h... yes
checking for error_t... yes
checking for argz_append... yes
checking for argz_create_sep... yes
checking for argz_insert... yes
checking for argz_next... yes
checking for argz_stringify... yes
checking for errno.h... yes
checking for malloc.h... yes
checking for memory.h... yes
checking for stdlib.h... yes
```

```
checking for ctype.h... yes
checking for unistd.h... yes
checking for dl.h... no
checking for sys/dl.h... no
checking for dld.h... no
checking for string.h... yes
checking for strchr... yes
checking for strrchr... yes
checking for memcpy... yes
checking for memmove... yes
checking for strcmp... yes
updating cache ./config.cache
creating ./config.status
creating Makefile
creating config.h
/bin/sh ./libtool --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I. -g -O2 -c l
tdl.c
mkdir .libs
gcc -DHAVE_CONFIG_H -I. -I. -I. -g -O2 -c ltdl.c -fPIC -o .libs/ltdl.o
gcc -DHAVE_CONFIG_H -I. -I. -I. -g -O2 -c ltdl.c -o ltdl.o >/dev/null 2>&1
/bin/sh ./libtool --mode=link gcc -g -O2 -o libltdl.la -rpath /home/milchstore
/php5/lib -no-undefined -version-info 4:0:1 ltdl.lo -ldl
./libtool: line 3965: ELF [0-9][0-9]*-bit [LM]SB (shared objectldynamic lib ): c
ommand not found
./libtool: line 3965: ELF [0-9][0-9]*-bit [LM]SB (shared objectldynamic lib ): c
ommand not found
./libtool: line 3965: ELF [0-9][0-9]*-bit [LM]SB (shared objectldynamic lib ): c
ommand not found
./libtool: line 3965: ELF [0-9][0-9]*-bit [LM]SB (shared objectldynamic lib ): c
ommand not found

*** Warning: linker path does not have real file for library -ldl.
*** I have the capability to make that library automatically link in when
*** you link to this library. But I can only do this if you have a
*** shared version of the library, which you do not appear to have
*** because I did check the linker path looking for a file starting
*** with libdl and none of the candidates passed a file format test
*** using a file magic. Last file checked: /lib/libdl-2.3.6.so
*** The inter-library dependencies that have been dropped here will be
*** automatically added whenever a program is linked with this library
*** or is declared to -dlopen it.

*** Since this library must not contain undefined symbols,
*** because either the platform does not support them or
*** it was explicitly requested with -no-undefined,
*** libtool will only create a static version of it.
./libtool: line 5837: test: : integer expression expected
./libtool: line 5837: test: : integer expression expected
using piecewise archive linking...
./libtool: line 5859: test: : integer expression expected
```

```
ranlib .libs/libltdl.a
creating libltdl.la
(cd .libs && rm -f libltdl.la && ln -s ../libltdl.la libltdl.la)
make[1]: Entering directory `/home/milchstore/source/libmccrypt-2.5.8/libltdl'
/bin/sh ./../mkinstalldirs /home/milchstore/php5/lib
/bin/sh ./libtool --mode=install /usr/bin/install -c libltdl.la /home/milchstor
e/php5/lib/libltdl.la
/usr/bin/install -c .libs/libltdl.lai /home/milchstore/php5/lib/libltdl.la
/usr/bin/install -c .libs/libltdl.a /home/milchstore/php5/lib/libltdl.a
ranlib /home/milchstore/php5/lib/libltdl.a
chmod 644 /home/milchstore/php5/lib/libltdl.a
PATH="$PATH:/sbin" ldconfig -n /home/milchstore/php5/lib
```

Libraries have been installed in:
 /home/milchstore/php5/lib

If you ever happen to want to link against installed libraries in a given directory, LIBDIR, you must either use libtool, and specify the full pathname of the library, or use the `-LLIBDIR` flag during linking and do at least one of the following:

- add LIBDIR to the `'LD_LIBRARY_PATH'` environment variable during execution
- add LIBDIR to the `'LD_RUN_PATH'` environment variable during linking
- use the `'-Wl,--rpath -Wl,LIBDIR'` linker flag
- have your system administrator add LIBDIR to `'/etc/ld.so.conf'`

See any operating system documentation about shared libraries for more information, such as the `ld(1)` and `ld.so(8)` manual pages.

/bin/sh ./../mkinstalldirs /home/milchstore/php5/include
 /usr/bin/install -c -m 644 ltdl.h /home/milchstore/php5/include/ltdl.h
make[1]: Leaving directory `/home/milchstore/source/libmccrypt-2.5.8/libltdl'
checking build system type... x86_64-unknown-linux-gnu
checking host system type... x86_64-unknown-linux-gnu
checking target system type... x86_64-unknown-linux-gnu
checking for a BSD-compatible install... /usr/bin/install -c
checking whether build environment is sane... yes
checking for gawk... gawk
checking whether make sets \$(MAKE)... yes
checking for style of include used by make... GNU
checking for gcc... gcc
checking for C compiler default output file name... a.out
checking whether the C compiler works... yes
checking whether we are cross compiling... no
checking for suffix of executables...
checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ISO C89... none needed

checking how to run the C preprocessor... gcc -E
checking for grep that handles long lines and -e... /bin/grep
checking for egrep... /bin/grep -E
checking for AIX... no
checking for library containing strerror... none required
checking for ANSI C header files... yes
checking for sys/types.h... yes
checking for sys/stat.h... yes
checking for stdlib.h... yes
checking for string.h... yes
checking for memory.h... yes
checking for strings.h... yes
checking for inttypes.h... yes
checking for stdint.h... yes
checking for unistd.h... yes
checking minix/config.h usability... no
checking minix/config.h presence... no
checking for minix/config.h... no
checking for gcc... (cached) gcc
checking whether we are using the GNU C compiler... (cached) yes
checking whether gcc accepts -g... (cached) yes
checking for gcc option to accept ISO C89... (cached) none needed
checking dependency style of gcc... (cached) gcc3
checking whether gcc and cc understand -c and -o together... yes
checking for g++... g++
checking whether we are using the GNU C++ compiler... yes
checking whether g++ accepts -g... yes
checking dependency style of g++... gcc3
checking whether gcc needs -traditional... no
checking for a BSD-compatible install... /usr/bin/install -c
checking whether ln -s works... yes
checking whether make sets \$(MAKE)... (cached) yes
checking for an ANSI C-conforming const... yes
checking for inline... inline
checking for function prototypes... yes
checking whether byte ordering is bigendian... no
checking for an ANSI C-conforming const... (cached) yes
checking for a sed that does not truncate output... /bin/sed
checking for ld used by gcc... /usr/bin/ld
checking if the linker (/usr/bin/ld) is GNU ld... yes
checking for /usr/bin/ld option to reload object files... -r
checking for BSD-compatible nm... /usr/bin/nm -B
checking how to recognise dependent libraries... pass_all
checking dlfcn.h usability... yes
checking dlfcn.h presence... yes
checking for dlfcn.h... yes
checking how to run the C++ preprocessor... g++ -E
checking for g77... g77
checking whether we are using the GNU Fortran 77 compiler... yes
checking whether g77 accepts -g... yes

checking command to parse /usr/bin/nm -B output from gcc object... ok
checking for objdir... .libs
checking for ar... ar
checking for ranlib... ranlib
checking for strip... strip
checking if gcc supports -fno-rtti -fno-exceptions... no
checking for gcc option to produce PIC... -fPIC
checking if gcc PIC flag -fPIC works... yes
checking if gcc static flag -static works... yes
checking if gcc supports -c -o file.o... yes
checking whether the gcc linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking whether -lc should be explicitly linked in... no
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
checking whether stripping libraries is possible... yes
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries... yes
configure: creating libtool
appending configuration tag "CXX" to libtool
checking for ld used by g++... /usr/bin/ld -m elf_x86_64
checking if the linker (/usr/bin/ld -m elf_x86_64) is GNU ld... yes
checking whether the g++ linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking for g++ option to produce PIC... -fPIC
checking if g++ PIC flag -fPIC works... yes
checking if g++ static flag -static works... yes
checking if g++ supports -c -o file.o... yes
checking whether the g++ linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
appending configuration tag "F77" to libtool
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries... yes
checking for g77 option to produce PIC... -fPIC
checking if g77 PIC flag -fPIC works... yes
checking if g77 static flag -static works... yes
checking if g77 supports -c -o file.o... yes
checking whether the g77 linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
checking for size_t... yes
checking for stdbool.h that conforms to C99... yes
checking for _Bool... yes
checking for ANSI C header files... (cached) yes
checking sys/endian.h usability... no

checking for sys/endian.h... no
checking for sys/stat.h... (cached) yes
checking for sys/types.h... (cached) yes
checking sys/mman.h usability... yes
checking sys/mman.h presence... yes
checking for sys/mman.h... yes
checking assert.h usability... yes
checking assert.h presence... yes
checking for assert.h... yes
checking byteswap.h usability... yes
checking byteswap.h presence... yes
checking for byteswap.h... yes
checking for dlfcn.h... (cached) yes
checking ctype.h usability... yes
checking ctype.h presence... yes
checking for ctype.h... yes
checking errno.h usability... yes
checking errno.h presence... yes
checking for errno.h... yes
checking endian.h usability... yes
checking endian.h presence... yes
checking for endian.h... yes
checking fcntl.h usability... yes
checking fcntl.h presence... yes
checking for fcntl.h... yes
checking for inttypes.h... (cached) yes
checking limits.h usability... yes
checking limits.h presence... yes
checking for limits.h... yes
checking malloc.h usability... yes
checking malloc.h presence... yes
checking for malloc.h... yes
checking for unistd.h... (cached) yes
checking utime.h usability... yes
checking utime.h presence... yes
checking for utime.h... yes
checking values.h usability... yes
checking values.h presence... yes
checking for values.h... yes
checking signal.h usability... yes
checking signal.h presence... yes
checking for signal.h... yes
checking for stdint.h... (cached) yes
checking stdio.h usability... yes
checking stdio.h presence... yes
checking for stdio.h... yes
checking for stdlib.h... (cached) yes
checking for string.h... (cached) yes
checking for strings.h... (cached) yes
checking for stdlib.h... (cached) yes

```
checking for working memcmp... yes
checking for bcopy... yes
checking for bzero... yes
checking for fcntl... yes
checking for fsync... yes
checking for memset... yes
checking for memmove... yes
checking for mlock... yes
checking for sigaction... yes
checking for signal... yes
checking for readdir_r... yes
checking for readdir... yes
checking for strtol... yes
checking for lstat... yes
checking for stat... yes
checking for umask... yes
checking for utime... yes
checking for unsigned long long int... yes
checking size of unsigned long long int... 8
checking for unsigned long int... yes
checking size of unsigned long int... 8
checking for unsigned int... yes
checking size of unsigned int... 4
checking for unsigned short int... yes
checking size of unsigned short int... 2
checking for unsigned char... yes
checking size of unsigned char... 1
checking if malloc debugging is wanted... no
checking whether to enable maintainer-specific portions of Makefiles... no
configure: creating ./config.status
config.status: creating Makefile
config.status: creating mhash.spec
config.status: creating include/Makefile
config.status: creating doc/Makefile
config.status: creating src/Makefile
config.status: creating lib/Makefile
config.status: creating include/mutils/mhash_config.h
config.status: executing depfiles commands
Making all in include
make[1]: Entering directory `/home/milchstore/source/mhash-0.9.9.9/include'
make[1]: Nothing to be done for `all'.
make[1]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9/include'
Making all in lib
make[1]: Entering directory `/home/milchstore/source/mhash-0.9.9.9/lib'
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT mhash.lo -MD -MP -MF ".deps/mhash.Tpo"
-c -o mhash.lo mhash.c; \
    then mv -f ".deps/mhash.Tpo" ".deps/mhash.Plo"; else rm -f ".deps/mhash.
Tpo"; exit 1; fi
mkdir .libs
```



```

o -MD -MP -MF .deps/mhash.Tpo -c mhash.c -fPIC -DPIC -o .libs/mhash.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT mhash.l
o -MD -MP -MF .deps/mhash.Tpo -c mhash.c -o mhash.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT stdfns.lo -MD -MP -MF ".deps/stdfns.Tpo
" -c -o stdfns.lo stdfns.c; \
    then mv -f ".deps/stdfns.Tpo" ".deps/stdfns.Plo"; else rm -f ".deps/stdf
ns.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT stdfns.
lo -MD -MP -MF .deps/stdfns.Tpo -c stdfns.c -fPIC -DPIC -o .libs/stdfns.o
stdfns.c: In function 'mutils_memcpy':
stdfns.c:227: warning: cast from pointer to integer of different size
stdfns.c:228: warning: cast from pointer to integer of different size
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT stdfns.
lo -MD -MP -MF .deps/stdfns.Tpo -c stdfns.c -o stdfns.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT keygen_hex.lo -MD -MP -MF ".deps/keygen
_hex.Tpo" -c -o keygen_hex.lo keygen_hex.c; \
    then mv -f ".deps/keygen_hex.Tpo" ".deps/keygen_hex.Plo"; else rm -f ".d
eps/keygen_hex.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT keygen_
hex.lo -MD -MP -MF .deps/keygen_hex.Tpo -c keygen_hex.c -fPIC -DPIC -o .libs/ke
ygen_hex.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT keygen_
hex.lo -MD -MP -MF .deps/keygen_hex.Tpo -c keygen_hex.c -o keygen_hex.o >/dev/nu
ll 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT keygen_mcrypt.lo -MD -MP -MF ".deps/key
gen_mcrypt.Tpo" -c -o keygen_mcrypt.lo keygen_mcrypt.c; \
    then mv -f ".deps/keygen_mcrypt.Tpo" ".deps/keygen_mcrypt.Plo"; else rm
-f ".deps/keygen_mcrypt.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT keygen_
mcrypt.lo -MD -MP -MF .deps/keygen_mcrypt.Tpo -c keygen_mcrypt.c -fPIC -DPIC -o
.libs/keygen_mcrypt.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT keygen_
mcrypt.lo -MD -MP -MF .deps/keygen_mcrypt.Tpo -c keygen_mcrypt.c -o keygen_mcryp
t.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT keygen_asis.lo -MD -MP -MF ".deps/keyge
n_asis.Tpo" -c -o keygen_asis.lo keygen_asis.c; \
    then mv -f ".deps/keygen_asis.Tpo" ".deps/keygen_asis.Plo"; else rm -f "
.deps/keygen_asis.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT keygen_
asis.lo -MD -MP -MF .deps/keygen_asis.Tpo -c keygen_asis.c -fPIC -DPIC -o .libs
/keygen_asis.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT keygen_
asis.lo -MD -MP -MF .deps/keygen_asis.Tpo -c keygen_asis.c -o keygen_asis.o >/de
v/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT keygen.lo -MD -MP -MF ".deps/keygen.Tpo

```

```

    then mv -f ".deps/keygen.Tpo" ".deps/keygen.Plo"; else rm -f ".deps/keygen.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT keygen.lo -MD -MP -MF .deps/keygen.Tpo -c keygen.c -fPIC -DPIC -o .libs/keygen.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT keygen.lo -MD -MP -MF .deps/keygen.Tpo -c keygen.c -o keygen.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT keygen_s2k.lo -MD -MP -MF ".deps/keygen_s2k.Tpo" -c -o keygen_s2k.lo keygen_s2k.c; \
    then mv -f ".deps/keygen_s2k.Tpo" ".deps/keygen_s2k.Plo"; else rm -f ".deps/keygen_s2k.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT keygen_s2k.lo -MD -MP -MF .deps/keygen_s2k.Tpo -c keygen_s2k.c -fPIC -DPIC -o .libs/keygen_s2k.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT keygen_s2k.lo -MD -MP -MF .deps/keygen_s2k.Tpo -c keygen_s2k.c -o keygen_s2k.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT crc32.lo -MD -MP -MF ".deps/crc32.Tpo" -c -o crc32.lo crc32.c; \
    then mv -f ".deps/crc32.Tpo" ".deps/crc32.Plo"; else rm -f ".deps/crc32.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT crc32.lo -MD -MP -MF .deps/crc32.Tpo -c crc32.c -fPIC -DPIC -o .libs/crc32.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT crc32.lo -MD -MP -MF .deps/crc32.Tpo -c crc32.c -o crc32.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT Adler32.lo -MD -MP -MF ".deps/Adler32.Tpo" -c -o Adler32.lo Adler32.c; \
    then mv -f ".deps/Adler32.Tpo" ".deps/Adler32.Plo"; else rm -f ".deps/Adler32.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT Adler32.lo -MD -MP -MF .deps/Adler32.Tpo -c Adler32.c -fPIC -DPIC -o .libs/Adler32.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT Adler32.lo -MD -MP -MF .deps/Adler32.Tpo -c Adler32.c -o Adler32.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT md2.lo -MD -MP -MF ".deps/md2.Tpo" -c -o md2.lo md2.c; \
    then mv -f ".deps/md2.Tpo" ".deps/md2.Plo"; else rm -f ".deps/md2.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT md2.lo -MD -MP -MF .deps/md2.Tpo -c md2.c -fPIC -DPIC -o .libs/md2.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT md2.lo -MD -MP -MF .deps/md2.Tpo -c md2.c -o md2.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT md4.lo -MD -MP -MF ".deps/md4.Tpo" -c -o md4.lo md4.c; \
    then mv -f ".deps/md4.Tpo" ".deps/md4.Plo"; else rm -f ".deps/md4.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT md4.lo

```

```

gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT md4.lo
-MD -MP -MF .deps/md4.Tpo -c md4.c -o md4.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT md5.lo -MD -MP -MF ".deps/md5.Tpo" -c -
o md5.lo md5.c; \
    then mv -f ".deps/md5.Tpo" ".deps/md5.Plo"; else rm -f ".deps/md5.Tpo";
exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT md5.lo
-MD -MP -MF .deps/md5.Tpo -c md5.c -fPIC -DPIC -o .libs/md5.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT md5.lo
-MD -MP -MF .deps/md5.Tpo -c md5.c -o md5.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT ripemd.lo -MD -MP -MF ".deps/ripemd.Tpo
" -c -o ripemd.lo ripemd.c; \
    then mv -f ".deps/ripemd.Tpo" ".deps/ripemd.Plo"; else rm -f ".deps/ripe
md.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT ripemd.
lo -MD -MP -MF .deps/ripemd.Tpo -c ripemd.c -fPIC -DPIC -o .libs/ripemd.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT ripemd.
lo -MD -MP -MF .deps/ripemd.Tpo -c ripemd.c -o ripemd.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT sha1.lo -MD -MP -MF ".deps/sha1.Tpo" -c
-o sha1.lo sha1.c; \
    then mv -f ".deps/sha1.Tpo" ".deps/sha1.Plo"; else rm -f ".deps/sha1.Tpo
"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT sha1.lo
-MD -MP -MF .deps/sha1.Tpo -c sha1.c -fPIC -DPIC -o .libs/sha1.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT sha1.lo
-MD -MP -MF .deps/sha1.Tpo -c sha1.c -o sha1.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT sha256_sha224.lo -MD -MP -MF ".deps/sha
256_sha224.Tpo" -c -o sha256_sha224.lo sha256_sha224.c; \
    then mv -f ".deps/sha256_sha224.Tpo" ".deps/sha256_sha224.Plo"; else rm
-f ".deps/sha256_sha224.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT sha256_
sha224.lo -MD -MP -MF .deps/sha256_sha224.Tpo -c sha256_sha224.c -fPIC -DPIC -o
.libs/sha256_sha224.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT sha256_
sha224.lo -MD -MP -MF .deps/sha256_sha224.Tpo -c sha256_sha224.c -o sha256_sha22
4.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT sha512_sha384.lo -MD -MP -MF ".deps/sha
512_sha384.Tpo" -c -o sha512_sha384.lo sha512_sha384.c; \
    then mv -f ".deps/sha512_sha384.Tpo" ".deps/sha512_sha384.Plo"; else rm
-f ".deps/sha512_sha384.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT sha512_
sha384.lo -MD -MP -MF .deps/sha512_sha384.Tpo -c sha512_sha384.c -fPIC -DPIC -o
.libs/sha512_sha384.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT sha512_
sha384.lo -MD -MP -MF .deps/sha512_sha384.Tpo -c sha512_sha384.c -o sha512_sha38

```

```

if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT tiger.lo -MD -MP -MF ".deps/tiger.Tpo"
-c -o tiger.lo tiger.c; \
    then mv -f ".deps/tiger.Tpo" ".deps/tiger.Plo"; else rm -f ".deps/tiger.
Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT tiger.l
o -MD -MP -MF .deps/tiger.Tpo -c tiger.c -fPIC -DPIC -o .libs/tiger.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT tiger.l
o -MD -MP -MF .deps/tiger.Tpo -c tiger.c -o tiger.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT tiger_sboxes.lo -MD -MP -MF ".deps/tige
r_sboxes.Tpo" -c -o tiger_sboxes.lo tiger_sboxes.c; \
    then mv -f ".deps/tiger_sboxes.Tpo" ".deps/tiger_sboxes.Plo"; else rm -f
".deps/tiger_sboxes.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT tiger_s
boxes.lo -MD -MP -MF .deps/tiger_sboxes.Tpo -c tiger_sboxes.c -fPIC -DPIC -o .l
ibs/tiger_sboxes.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT tiger_s
boxes.lo -MD -MP -MF .deps/tiger_sboxes.Tpo -c tiger_sboxes.c -o tiger_sboxes.o
>/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT haval.lo -MD -MP -MF ".deps/haval.Tpo"
-c -o haval.lo haval.c; \
    then mv -f ".deps/haval.Tpo" ".deps/haval.Plo"; else rm -f ".deps/haval.
Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT haval.l
o -MD -MP -MF .deps/haval.Tpo -c haval.c -fPIC -DPIC -o .libs/haval.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT haval.l
o -MD -MP -MF .deps/haval.Tpo -c haval.c -o haval.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT gosthash.lo -MD -MP -MF ".deps/gosthash
.Tpo" -c -o gosthash.lo gosthash.c; \
    then mv -f ".deps/gosthash.Tpo" ".deps/gosthash.Plo"; else rm -f ".deps/
gosthash.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT gosthas
h.lo -MD -MP -MF .deps/gosthash.Tpo -c gosthash.c -fPIC -DPIC -o .libs/gosthas
h.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT gosthas
h.lo -MD -MP -MF .deps/gosthash.Tpo -c gosthash.c -o gosthash.o >/dev/null 2>&1
if /bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I. -I../i
nclude/mutils -I../include -g -O2 -MT whirlpool.lo -MD -MP -MF ".deps/whirlpo
ol.Tpo" -c -o whirlpool.lo whirlpool.c; \
    then mv -f ".deps/whirlpool.Tpo" ".deps/whirlpool.Plo"; else rm -f ".dep
s/whirlpool.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT whirlpo
ol.lo -MD -MP -MF .deps/whirlpool.Tpo -c whirlpool.c -fPIC -DPIC -o .libs/whirl
pool.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT whirlpo
ol.lo -MD -MP -MF .deps/whirlpool.Tpo -c whirlpool.c -o whirlpool.o >/dev/null 2
>&1

```

```

nclude/mutils -I../include -g -O2 -MT snefru.lo -MD -MP -MF ".deps/snefru.Tpo"
" -c -o snefru.lo snefru.c; \
    then mv -f ".deps/snefru.Tpo" ".deps/snefru.Plo"; else rm -f ".deps/snefru.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT snefru.lo -MD -MP -MF .deps/snefru.Tpo -c snefru.c -fPIC -DPIC -o .libs/snefru.o
gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT snefru.lo -MD -MP -MF .deps/snefru.Tpo -c snefru.c -o snefru.o >/dev/null 2>&1
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o libmhash.la -rpath /home/milchstore/php5/lib -version-info 2:1 mhash.lo stdfns.lo keygen_hex.lo keygen_mcrypt.lo keygen_asis.lo keygen.lo keygen_s2k.lo crc32.lo adler32.lo md2.lo md4.lo md5.lo ripemd.lo sha1.lo sha256_sha224.lo sha512_sha384.lo tiger.lo tiger_sboxes.lo haval.lo gosthash.lo whirlpool.lo snefru.lo
gcc -shared .libs/mhash.o .libs/stdfns.o .libs/keygen_hex.o .libs/keygen_mcrypt.o .libs/keygen_asis.o .libs/keygen.o .libs/keygen_s2k.o .libs/crc32.o .libs/adler32.o .libs/md2.o .libs/md4.o .libs/md5.o .libs/ripemd.o .libs/sha1.o .libs/sha256_sha224.o .libs/sha512_sha384.o .libs/tiger.o .libs/tiger_sboxes.o .libs/haval.o .libs/gosthash.o .libs/whirlpool.o .libs/snefru.o -Wl,-soname -Wl,libmhash.so.2 -o .libs/libmhash.so.2.0.1
(cd .libs && rm -f libmhash.so.2 && ln -s libmhash.so.2.0.1 libmhash.so.2)
(cd .libs && rm -f libmhash.so && ln -s libmhash.so.2.0.1 libmhash.so)
ar cru .libs/libmhash.a mhash.o stdfns.o keygen_hex.o keygen_mcrypt.o keygen_asis.o keygen.o keygen_s2k.o crc32.o adler32.o md2.o md4.o md5.o ripemd.o sha1.o sha256_sha224.o sha512_sha384.o tiger.o tiger_sboxes.o haval.o gosthash.o whirlpool.o snefru.o
ranlib .libs/libmhash.a
creating libmhash.la
(cd .libs && rm -f libmhash.la && ln -s ../libmhash.la libmhash.la)
make[1]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9/lib'
Making all in doc
make[1]: Entering directory `/home/milchstore/source/mhash-0.9.9.9/doc'
make[1]: Nothing to be done for `all'.
make[1]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9/doc'
Making all in src
make[1]: Entering directory `/home/milchstore/source/mhash-0.9.9.9/src'
if gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT driver.o -MD -MP -MF ".deps/driver.Tpo" -c -o driver.o driver.c; \
    then mv -f ".deps/driver.Tpo" ".deps/driver.Po"; else rm -f ".deps/driver.Tpo"; exit 1; fi
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o driver driver.o ../lib/libmhash.la
mkdir .libs
gcc -g -O2 -o .libs/driver driver.o ../lib/.libs/libmhash.so -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating driver
if gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT hmac_test.o -MD -MP -MF ".deps/hmac_test.Tpo" -c -o hmac_test.o hmac_test.c; \
    then mv -f ".deps/hmac_test.Tpo" ".deps/hmac_test.Po"; else rm -f ".deps/hmac_test.Tpo"; exit 1; fi
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o hmac_test hmac_test.o

```

```

gcc -g -O2 -o .libs/hmac_test hmac_test.o ../lib/.libs/libmhash.so -Wl,--rpath
-Wl,/home/milchstore/php5/lib
creating hmac_test
if gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT ke
ygen_test.o -MD -MP -MF ".deps/keygen_test.Tpo" -c -o keygen_test.o keygen_test.
c; \
    then mv -f ".deps/keygen_test.Tpo" ".deps/keygen_test.Po"; else rm -f ".
deps/keygen_test.Tpo"; exit 1; fi
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o keygen_test keygen_tes
t.o ../lib/libmhash.la
gcc -g -O2 -o .libs/keygen_test keygen_test.o ../lib/.libs/libmhash.so -Wl,--rp
ath -Wl,/home/milchstore/php5/lib
creating keygen_test
if gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT mh
ash_save_restore_test.o -MD -MP -MF ".deps/mhash_save_restore_test.Tpo" -c -o mh
ash_save_restore_test.o mhash_save_restore_test.c; \
    then mv -f ".deps/mhash_save_restore_test.Tpo" ".deps/mhash_save_restore
_test.Po"; else rm -f ".deps/mhash_save_restore_test.Tpo"; exit 1; fi
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o rest_test mhash_save_r
estore_test.o ../lib/libmhash.la
gcc -g -O2 -o .libs/rest_test mhash_save_restore_test.o ../lib/.libs/libmhash.s
o -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating rest_test
if gcc -DHAVE_CONFIG_H -I. -I. -I../include/mutils -I../include -g -O2 -MT fr
ag_test.o -MD -MP -MF ".deps/frag_test.Tpo" -c -o frag_test.o frag_test.c; \
    then mv -f ".deps/frag_test.Tpo" ".deps/frag_test.Po"; else rm -f ".deps
/frag_test.Tpo"; exit 1; fi
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o frag_test frag_test.o
../lib/libmhash.la
gcc -g -O2 -o .libs/frag_test frag_test.o ../lib/.libs/libmhash.so -Wl,--rpath
-Wl,/home/milchstore/php5/lib
creating frag_test
make[1]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9/src'
make[1]: Entering directory `/home/milchstore/source/mhash-0.9.9.9'
make[1]: Nothing to be done for `all-am'.
make[1]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9'
Making install in include
make[1]: Entering directory `/home/milchstore/source/mhash-0.9.9.9/include'
make[2]: Entering directory `/home/milchstore/source/mhash-0.9.9.9/include'
make[2]: Nothing to be done for `install-exec-am'.
test -z "/home/milchstore/php5/include" || mkdir -p -- "/home/milchstore/php5/in
clude"
/home/milchstore/source/mhash-0.9.9.9/install-sh -c -m 644 'mhash.h' '/home/mil
chstore/php5/include/mhash.h'
/home/milchstore/source/mhash-0.9.9.9/install-sh -c -m 644 'mutils/mhash.h' '/h
ome/milchstore/php5/include/mutils/mhash.h'
/home/milchstore/source/mhash-0.9.9.9/install-sh -c -m 644 'mutils/mglobal.h' '
/home/milchstore/php5/include/mutils/mglobal.h'
/home/milchstore/source/mhash-0.9.9.9/install-sh -c -m 644 'mutils/mtypes.h' '/
home/milchstore/php5/include/mutils/mtypes.h'

```

```
home/milchstore/php5/include/mutils/mutils.h'
/home/milchstore/source/mhash-0.9.9.9/install-sh -c -m 644 'mutils/mhash_config
.h' '/home/milchstore/php5/include/mutils/mhash_config.h'
/home/milchstore/source/mhash-0.9.9.9/install-sh -c -m 644 'mutils/mincludes.h'
'/home/milchstore/php5/include/mutils/mincludes.h'
make[2]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9/include'
make[1]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9/include'
Making install in lib
make[1]: Entering directory `/home/milchstore/source/mhash-0.9.9.9/lib'
make[2]: Entering directory `/home/milchstore/source/mhash-0.9.9.9/lib'
test -z "/home/milchstore/php5/lib" || mkdir -p -- "/home/milchstore/php5/lib"
/bin/sh ../libtool --mode=install /usr/bin/install -c 'libmhash.la' '/home/mil
chstore/php5/lib/libmhash.la'
/usr/bin/install -c .libs/libmhash.so.2.0.1 /home/milchstore/php5/lib/libmhash.s
o.2.0.1
(cd /home/milchstore/php5/lib && { ln -s -f libmhash.so.2.0.1 libmhash.so.2 || {
rm -f libmhash.so.2 && ln -s libmhash.so.2.0.1 libmhash.so.2; }; })
(cd /home/milchstore/php5/lib && { ln -s -f libmhash.so.2.0.1 libmhash.so || { r
m -f libmhash.so && ln -s libmhash.so.2.0.1 libmhash.so; }; })
/usr/bin/install -c .libs/libmhash.lai /home/milchstore/php5/lib/libmhash.la
/usr/bin/install -c .libs/libmhash.a /home/milchstore/php5/lib/libmhash.a
chmod 644 /home/milchstore/php5/lib/libmhash.a
ranlib /home/milchstore/php5/lib/libmhash.a
PATH="$PATH:/sbin" ldconfig -n /home/milchstore/php5/lib
```

Libraries have been installed in:
 /home/milchstore/php5/lib

If you ever happen to want to link against installed libraries
in a given directory, LIBDIR, you must either use libtool, and
specify the full pathname of the library, or use the `-LLIBDIR`
flag during linking and do at least one of the following:

- add LIBDIR to the `'LD_LIBRARY_PATH'` environment variable
 during execution
- add LIBDIR to the `'LD_RUN_PATH'` environment variable
 during linking
- use the `'-Wl,--rpath -Wl,LIBDIR'` linker flag
- have your system administrator add LIBDIR to `'/etc/ld.so.conf'`

See any operating system documentation about shared libraries for
more information, such as the `ld(1)` and `ld.so(8)` manual pages.

make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9/lib'
make[1]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9/lib'
Making install in doc
make[1]: Entering directory `/home/milchstore/source/mhash-0.9.9.9/doc'
make[2]: Entering directory `/home/milchstore/source/mhash-0.9.9.9/doc'
make[2]: Nothing to be done for `install-exec-am'.
test -z "/home/milchstore/php5/share/man/man3" || mkdir -p -- "/home/milchstore/

```

/usr/bin/install -c -m 644 '././mhash.3' '/home/milchstore/php5/share/man/man3/
mhash.3'
make[2]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9/doc'
make[1]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9/doc'
Making install in src
make[1]: Entering directory `/home/milchstore/source/mhash-0.9.9.9/src'
make[2]: Entering directory `/home/milchstore/source/mhash-0.9.9.9/src'
make[2]: Nothing to be done for `install-exec-am'.
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9/src'
make[1]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9/src'
make[1]: Entering directory `/home/milchstore/source/mhash-0.9.9.9'
make[2]: Entering directory `/home/milchstore/source/mhash-0.9.9.9'
make[2]: Nothing to be done for `install-exec-am'.
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9'
make[1]: Leaving directory `/home/milchstore/source/mhash-0.9.9.9'

```

FreeType build system -- automatic system detection

The following settings are used:

```

platform                unix
compiler                 cc
configuration directory  ./builds/unix
configuration rules      ./builds/unix/unix.mk

```

If this does not correspond to your system or settings please remove the file `config.mk' from this directory then read the INSTALL file for help.

Otherwise, simply type `make' again to build the library, or `make reldoc' to build the API reference (the latter needs python).

Generating modules list in ./objs/ftmodule.h...

```

* module: truetype      (Windows/Mac font files with extension *.ttf or *.ttc)
* module: type1         (Postscript font files with extension *.pfa or *.pfb)
* module: cff           (OpenType fonts with extension *.otf)
* module: cid           (Postscript CID-keyed fonts, no known extension)
* module: pfr           (PFR/TrueDoc font files with extension *.pfr)
* module: type42        (Type 42 font files with no known extension)
* module: winfnt        (Windows bitmap fonts with extension *.fnt or *.fon)
* module: pcf           (pcf bitmap fonts)
* module: bdf           (bdf bitmap fonts)
* module: sfnt          (helper module for TrueType & OpenType formats)
* module: autofit       (automatic hinting module)
* module: pshinter      (Postscript hinter module)
* module: raster        (monochrome bitmap renderer)
* module: smooth        (anti-aliased bitmap renderer)
* module: smooth        (anti-aliased bitmap renderer for LCDs)
* module: smooth        (anti-aliased bitmap renderer for vertical LCDs)

```



```
* module: psnames (Postscript & Unicode Glyph name handling)
done.
cd builds/unix; ./configure '--prefix=/home/milchstore/php5'
checking build system type... x86_64-unknown-linux-gnu
checking host system type... x86_64-unknown-linux-gnu
checking for gcc... gcc
checking for C compiler default output file name... a.out
checking whether the C compiler works... yes
checking whether we are cross compiling... no
checking for suffix of executables...
checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ISO C89... none needed
checking how to run the C preprocessor... gcc -E
checking for rm... rm -f
checking for rmdir... rmdir
checking for a BSD-compatible install... /usr/bin/install -c
checking for grep that handles long lines and -e... /bin/grep
checking for egrep... /bin/grep -E
checking for ANSI C header files... yes
checking for sys/types.h... yes
checking for sys/stat.h... yes
checking for stdlib.h... yes
checking for string.h... yes
checking for memory.h... yes
checking for strings.h... yes
checking for inttypes.h... yes
checking for stdint.h... yes
checking for unistd.h... yes
checking fcntl.h usability... yes
checking fcntl.h presence... yes
checking for fcntl.h... yes
checking for unistd.h... (cached) yes
checking for an ANSI C-conforming const... yes
checking size of int... 4
checking size of long... 8
checking cpp computation of bit length in ftconfig.in works... yes
checking for stdlib.h... (cached) yes
checking for unistd.h... (cached) yes
checking for getpagesize... yes
checking for working mmap... yes
checking whether munmap is declared... yes
checking for munmap's first parameter type... void *
checking for memcpy... yes
checking for memmove... yes
checking for gzsetparams in -lz... yes
checking zlib.h usability... yes
checking zlib.h presence... yes
checking for zlib.h... yes
```

checking for a sed that does not truncate output... /bin/sed
checking for fgrep... /bin/grep -F
checking for ld used by gcc... /usr/bin/ld
checking if the linker (/usr/bin/ld) is GNU ld... yes
checking for BSD- or MS-compatible name lister (nm)... /usr/bin/nm -B
checking the name lister (/usr/bin/nm -B) interface... BSD nm
checking whether ln -s works... yes
checking the maximum length of command line arguments... 98304
checking whether the shell understands some XSI constructs... yes
checking whether the shell understands "+="... yes
checking for /usr/bin/ld option to reload object files... -r
checking for objdump... objdump
checking how to recognize dependent libraries... pass_all
checking for ar... ar
checking for strip... strip
checking for ranlib... ranlib
checking command to parse /usr/bin/nm -B output from gcc object... ok
checking for dlfcn.h... yes
checking for objdir... .libs
checking if gcc supports -fno-rtti -fno-exceptions... no
checking for gcc option to produce PIC... -fPIC -DPIC
checking if gcc PIC flag -fPIC -DPIC works... yes
checking if gcc static flag -static works... yes
checking if gcc supports -c -o file.o... yes
checking if gcc supports -c -o file.o... (cached) yes
checking whether the gcc linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking whether -lc should be explicitly linked in... no
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
checking whether stripping libraries is possible... yes
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries... yes
configure: creating ./config.status
config.status: creating unix-cc.mk
config.status: creating unix-def.mk
config.status: creating freetype-config
config.status: creating freetype2.pc
config.status: creating ftconfig.h
config.status: executing libtool commands
make: Nothing to be done for `unix'.
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="
ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="
ftmodule.h>" -o /home/milchstore/source/freetype-2.3.9/objs/ftsystem.lo builds/unix/ftsystem.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="
ftconfig.h>" -DFT2_B

```
-DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftsystem.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" builds/unix/ftsystem.c -o /hom
e/milchstore/source/freetype-2.3.9/objs/ftsystem.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/sou
rce/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9
/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<f
tconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -o /home/m
ilchstore/source/freetype-2.3.9/objs/ftdebug.lo /home/milchstore/source/freetype
-2.3.9/src/base/ftdebug.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" /home/milchstore/source/freety
pe-2.3.9/src/base/ftdebug.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3
.9/objs/.libs/ftdebug.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" /home/milchstore/source/freety
pe-2.3.9/src/base/ftdebug.c -o /home/milchstore/source/freetype-2.3.9/objs/ftdeb
ug.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/sou
rce/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9
/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<f
tconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -o /home/m
ilchstore/source/freetype-2.3.9/objs/ftinit.lo /home/milchstore/source/freetype-
2.3.9/src/base/ftinit.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" /home/milchstore/source/freety
pe-2.3.9/src/base/ftinit.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.
9/objs/.libs/ftinit.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" /home/milchstore/source/freety
pe-2.3.9/src/base/ftinit.c -o /home/milchstore/source/freetype-2.3.9/objs/ftinit
.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/sou
rce/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9
/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<f
tconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/mi
lchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.
9/objs/ftbase.lo /home/milchstore/source/freetype-2.3.9/src/base/ftbase.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
```

```
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftbase.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftbase.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftbase.c -o /home/milchstore/source/freetype-2.3.9/objs/ftbase.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.9/objs/ftbbox.lo /home/milchstore/source/freetype-2.3.9/src/base/ftbbox.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftbbox.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftbbox.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftbbox.c -o /home/milchstore/source/freetype-2.3.9/objs/ftbbox.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.9/objs/ftbdf.lo /home/milchstore/source/freetype-2.3.9/src/base/ftbdf.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftbdf.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftbdf.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftbdf.c -o /home/milchstore/source/freetype-2.3.9/objs/ftbdf.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.9/objs/ftbdf.o >/dev/null 2>&1
```

```
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftbitmap.c
-fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftbitmap.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftbitmap.c -
o /home/milchstore/source/freetype-2.3.9/objs/ftbitmap.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/sou
rce/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9
/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<f
tconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/mi
lchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.
9/objs/ftcid.lo /home/milchstore/source/freetype-2.3.9/src/base/ftcid.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftcid.c -fP
IC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftcid.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftcid.c -o /
home/milchstore/source/freetype-2.3.9/objs/ftcid.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/sou
rce/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9
/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<f
tconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/mi
lchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.
9/objs/ftfstype.lo /home/milchstore/source/freetype-2.3.9/src/base/ftfstype.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftfstype.c
-fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftfstype.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftfstype.c -
o /home/milchstore/source/freetype-2.3.9/objs/ftfstype.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/sou
rce/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9
```

```
tconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.9/objs/ftgasp.lo /home/milchstore/source/freetype-2.3.9/src/base/ftgasp.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftgasp.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftgasp.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftgasp.c -o /home/milchstore/source/freetype-2.3.9/objs/ftgasp.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.9/objs/ftglyph.lo /home/milchstore/source/freetype-2.3.9/src/base/ftglyph.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftglyph.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftglyph.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftglyph.c -o /home/milchstore/source/freetype-2.3.9/objs/ftglyph.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.9/objs/ftgxval.lo /home/milchstore/source/freetype-2.3.9/src/base/ftgxval.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftgxval.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftgxval.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftgxval.c -o
```

```
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H=<ftconfig.h> -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H=<ftmodule.h> -I/home/milchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.9/objs/ftlcdfil.lo /home/milchstore/source/freetype-2.3.9/src/base/ftlcdfil.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H=<ftconfig.h> -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H=<ftmodule.h> -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftlcdfil.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftlcdfil.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H=<ftconfig.h> -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H=<ftmodule.h> -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftlcdfil.c -o /home/milchstore/source/freetype-2.3.9/objs/ftlcdfil.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H=<ftconfig.h> -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H=<ftmodule.h> -I/home/milchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.9/objs/ftmm.lo /home/milchstore/source/freetype-2.3.9/src/base/ftmm.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H=<ftconfig.h> -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H=<ftmodule.h> -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftmm.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftmm.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H=<ftconfig.h> -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H=<ftmodule.h> -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftmm.c -o /home/milchstore/source/freetype-2.3.9/objs/ftmm.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H=<ftconfig.h> -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H=<ftmodule.h> -I/home/milchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.9/objs/ftotval.lo /home/milchstore/source/freetype-2.3.9/src/base/ftotval.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H=<ftconfig.h> -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H=<ftmodule.h> -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftotval.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftotval.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
```

```
UUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftotval.c -o /home/milchstore/source/freetype-2.3.9/objs/ftotval.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.9/objs/ftpatent.lo /home/milchstore/source/freetype-2.3.9/src/base/ftpatent.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftpatent.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftpatent.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftpatent.c -o /home/milchstore/source/freetype-2.3.9/objs/ftpatent.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.9/objs/ftpfr.lo /home/milchstore/source/freetype-2.3.9/src/base/ftpfr.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftpfr.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftpfr.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftpfr.c -o /home/milchstore/source/freetype-2.3.9/objs/ftpfr.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.9/objs/ftstroke.lo /home/milchstore/source/freetype-2.3.9/src/base/ftstroke.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftstroke.c
```



```
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftstroke.c -
o /home/milchstore/source/freetype-2.3.9/objs/ftstroke.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/sou
rce/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9
/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<f
tconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/mi
lchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.
9/objs/ftsynth.lo /home/milchstore/source/freetype-2.3.9/src/base/ftsynth.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftsynth.c -
fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftsynth.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftsynth.c -o
/home/milchstore/source/freetype-2.3.9/objs/ftsynth.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/sou
rce/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9
/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<f
tconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/mi
lchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.
9/objs/fttype1.lo /home/milchstore/source/freetype-2.3.9/src/base/fttype1.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/fttype1.c -
fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/fttype1.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/fttype1.c -o
/home/milchstore/source/freetype-2.3.9/objs/fttype1.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/sou
rce/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9
/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<f
tconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/mi
lchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.
9/objs/ftwinfnt.lo /home/milchstore/source/freetype-2.3.9/src/base/ftwinfnt.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
```

```
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftwinfnt.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftwinfnt.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftwinfnt.c -o /home/milchstore/source/freetype-2.3.9/objs/ftwinfnt.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base -o /home/milchstore/source/freetype-2.3.9/objs/ftxf86.lo /home/milchstore/source/freetype-2.3.9/src/base/ftxf86.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftxf86.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftxf86.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/base /home/milchstore/source/freetype-2.3.9/src/base/ftxf86.c -o /home/milchstore/source/freetype-2.3.9/objs/ftxf86.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/truetype -o /home/milchstore/source/freetype-2.3.9/objs/truetype.lo /home/milchstore/source/freetype-2.3.9/src/truetype/truetype.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/truetype /home/milchstore/source/freetype-2.3.9/src/truetype/truetype.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/truetype.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/truetype /home/milchstore/source/freetype-2.3.9/src/truetype/truetype.c -o /home/milchstore/source/freetype-2.3.9/objs/truetype.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>"
```

```
lchstore/source/freetype-2.3.9/src/type1 -o /home/milchstore/source/freetype-2.3.9/objs/type1.lo /home/milchstore/source/freetype-2.3.9/src/type1/type1.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/type1 /home/milchstore/source/freetype-2.3.9/src/type1/type1.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/type1.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/type1 /home/milchstore/source/freetype-2.3.9/src/type1/type1.c -o /home/milchstore/source/freetype-2.3.9/objs/type1.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/cff -o /home/milchstore/source/freetype-2.3.9/objs/cff.lo /home/milchstore/source/freetype-2.3.9/src/cff/cff.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/cff /home/milchstore/source/freetype-2.3.9/src/cff/cff.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/cff.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/cff /home/milchstore/source/freetype-2.3.9/src/cff/cff.c -o /home/milchstore/source/freetype-2.3.9/objs/cff.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/cid -o /home/milchstore/source/freetype-2.3.9/objs/type1cid.lo /home/milchstore/source/freetype-2.3.9/src/cid/type1cid.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/cid /home/milchstore/source/freetype-2.3.9/src/cid/type1cid.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/type1cid.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/cid /home/milchstore/source/freetype-2.3.9/src/cid/type1cid.c -o /home/milchstore/source/freetype-2.3.9/objs/type1cid.o >/dev/null 2>&1
```

```
rce/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9
/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="  
ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="  
ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/pfr -o /home/milchstore/source/freetype-2.3.9/objs/pfr.lo /home/milchstore/source/freetype-2.3.9/src/pfr/pfr.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/pfr /home/milchstore/source/freetype-2.3.9/src/pfr/pfr.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/pfr.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/pfr /home/milchstore/source/freetype-2.3.9/src/pfr/pfr.c -o /home/milchstore/source/freetype-2.3.9/objs/pfr.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="  
ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="  
ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/type42 -o /home/milchstore/source/freetype-2.3.9/objs/type42.lo /home/milchstore/source/freetype-2.3.9/src/type42/type42.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/type42 /home/milchstore/source/freetype-2.3.9/src/type42/type42.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/type42.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/type42 /home/milchstore/source/freetype-2.3.9/src/type42/type42.c -o /home/milchstore/source/freetype-2.3.9/objs/type42.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="  
ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="  
ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/winfonts -o /home/milchstore/source/freetype-2.3.9/objs/winfnt.lo /home/milchstore/source/freetype-2.3.9/src/winfonts/winfnt.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/winfonts /home/milchstore/source/freetype-2.3.9/src/winfonts/winfnt.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/winfnt.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
```

```
UUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/winfonts /home/milchstore/source/freetype-2.3.9/src/winfonts/winfnt.c -o /home/milchstore/source/freetype-2.3.9/objs/winfnt.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/pcf -o /home/milchstore/source/freetype-2.3.9/objs/pcf.lo /home/milchstore/source/freetype-2.3.9/src/pcf/pcf.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/pcf /home/milchstore/source/freetype-2.3.9/src/pcf/pcf.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/pcf.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/pcf /home/milchstore/source/freetype-2.3.9/src/pcf/pcf.c -o /home/milchstore/source/freetype-2.3.9/objs/pcf.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/bdf -o /home/milchstore/source/freetype-2.3.9/objs/bdf.lo /home/milchstore/source/freetype-2.3.9/src/bdf/bdf.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/bdf /home/milchstore/source/freetype-2.3.9/src/bdf/bdf.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/bdf.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/bdf /home/milchstore/source/freetype-2.3.9/src/bdf/bdf.c -o /home/milchstore/source/freetype-2.3.9/objs/bdf.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/sfnt -o /home/milchstore/source/freetype-2.3.9/objs/sfnt.lo /home/milchstore/source/freetype-2.3.9/src/sfnt/sfnt.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/sfnt /home/milchstore/source/freetype-2.3.9/src/sfnt/sfnt.c -fPI
```

```
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/sfnt /home/milchstore/source/freetype-2.3.9/src/sfnt/sfnt.c -o /home/milchstore/source/freetype-2.3.9/objs/sfnt.o >/dev/null 2>&1
```

```
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/autofit -o /home/milchstore/source/freetype-2.3.9/objs/autofit.lo /home/milchstore/source/freetype-2.3.9/src/autofit/autofit.c
```

```
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/autofit /home/milchstore/source/freetype-2.3.9/src/autofit/autofit.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/autofit.o
```

```
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/autofit /home/milchstore/source/freetype-2.3.9/src/autofit/autofit.c -o /home/milchstore/source/freetype-2.3.9/objs/autofit.o >/dev/null 2>&1
```

```
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/pshinter -o /home/milchstore/source/freetype-2.3.9/objs/pshinter.lo /home/milchstore/source/freetype-2.3.9/src/pshinter/pshinter.c
```

```
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/pshinter /home/milchstore/source/freetype-2.3.9/src/pshinter/pshinter.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/pshinter.o
```

```
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/pshinter /home/milchstore/source/freetype-2.3.9/src/pshinter/pshinter.c -o /home/milchstore/source/freetype-2.3.9/objs/pshinter.o >/dev/null 2>&1
```

```
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/raster -o /home/milchstore/source/freetype-2.
```

```
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/raster /home/milchstore/source/freetype-2.3.9/src/raster/raster.c
-fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/raster.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/raster /home/milchstore/source/freetype-2.3.9/src/raster/raster.c
-o /home/milchstore/source/freetype-2.3.9/objs/raster.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/sou
rce/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9
/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<f
tconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/mi
lchstore/source/freetype-2.3.9/src/smooth -o /home/milchstore/source/freetype-2.
3.9/objs/smooth.lo /home/milchstore/source/freetype-2.3.9/src/smooth/smooth.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/smooth /home/milchstore/source/freetype-2.3.9/src/smooth/smooth.c
-fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/smooth.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/smooth /home/milchstore/source/freetype-2.3.9/src/smooth/smooth.c
-o /home/milchstore/source/freetype-2.3.9/objs/smooth.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/sou
rce/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9
/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<f
tconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/mi
lchstore/source/freetype-2.3.9/src/cache -o /home/milchstore/source/freetype-2.3
.9/objs/ftcache.lo /home/milchstore/source/freetype-2.3.9/src/cache/ftcache.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/cache /home/milchstore/source/freetype-2.3.9/src/cache/ftcache.c
-fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftcache.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/
objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -
g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_B
UILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/free
type-2.3.9/src/cache /home/milchstore/source/freetype-2.3.9/src/cache/ftcache.c
-o /home/milchstore/source/freetype-2.3.9/objs/ftcache.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/sou
rce/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9
```

```
tconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -o /home/milchstore/source/freetype-2.3.9/objs/ftgzip.lo /home/milchstore/source/freetype-2.3.9/src/gzip/ftgzip.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" /home/milchstore/source/freetype-2.3.9/src/gzip/ftgzip.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftgzip.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" /home/milchstore/source/freetype-2.3.9/src/gzip/ftgzip.c -o /home/milchstore/source/freetype-2.3.9/objs/ftgzip.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/lzw -o /home/milchstore/source/freetype-2.3.9/objs/ftlzw.lo /home/milchstore/source/freetype-2.3.9/src/lzw/ftlzw.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/lzw /home/milchstore/source/freetype-2.3.9/src/lzw/ftlzw.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftlzw.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/lzw /home/milchstore/source/freetype-2.3.9/src/lzw/ftlzw.c -o /home/milchstore/source/freetype-2.3.9/objs/ftlzw.o >/dev/null 2>&1
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H="<ftconfig.h>" -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H="<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/psaux -o /home/milchstore/source/freetype-2.3.9/objs/psaux.lo /home/milchstore/source/freetype-2.3.9/src/psaux/psaux.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/psaux /home/milchstore/source/freetype-2.3.9/src/psaux/psaux.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/psaux.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB "-DFT_CONFIG_CONFIG_H=<ftconfig.h>" -DFT2_BUILD_LIBRARY "-DFT_CONFIG_MODULES_H=<ftmodule.h>" -I/home/milchstore/source/freetype-2.3.9/src/psaux /home/milchstore/source/freetype-2.3.9/src/psaux/psaux.c -o
```



```
./builds/unix/libtool --mode=compile gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H=<ftconfig.h> -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H=<ftmodule.h> -I/home/milchstore/source/freetype-2.3.9/src/psnames -o /home/milchstore/source/freetype-2.3.9/objs/psnames.lo /home/milchstore/source/freetype-2.3.9/src/psnames/psmodule.c
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H=<ftconfig.h> -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H=<ftmodule.h> -I/home/milchstore/source/freetype-2.3.9/src/psnames /home/milchstore/source/freetype-2.3.9/src/psnames/psmodule.c -fPIC -DPIC -o /home/milchstore/source/freetype-2.3.9/objs/.libs/psnames.o
libtool: compile: gcc -pedantic -ansi -I/home/milchstore/source/freetype-2.3.9/objs -I./builds/unix -I/home/milchstore/source/freetype-2.3.9/include -c -Wall -g -O2 -DFT_CONFIG_OPTION_SYSTEM_ZLIB -DFT_CONFIG_CONFIG_H=<ftconfig.h> -DFT2_BUILD_LIBRARY -DFT_CONFIG_MODULES_H=<ftmodule.h> -I/home/milchstore/source/freetype-2.3.9/src/psnames /home/milchstore/source/freetype-2.3.9/src/psnames/psmodule.c -o /home/milchstore/source/freetype-2.3.9/objs/psnames.o >/dev/null 2>&1
gcc -o /home/milchstore/source/freetype-2.3.9/objs/apinames /home/milchstore/source/freetype-2.3.9/src/tools/apinames.c
/home/milchstore/source/freetype-2.3.9/objs/apinames -o/home/milchstore/source/freetype-2.3.9/objs/ftexport.sym /home/milchstore/source/freetype-2.3.9/include/freetype/freetype.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftadvanc.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftbbox.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftbdf.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftbitmap.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftcache.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftchapters.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftcid.h /home/milchstore/source/freetype-2.3.9/include/freetype/fterrdef.h /home/milchstore/source/freetype-2.3.9/include/freetype/fterrors.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftgasp.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftglyph.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftgxval.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftgzip.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftimage.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftincrem.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftlcdfil.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftlist.h /home/milchstore/source/freetype-2.3.9/include/freetype/fttlzw.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftmac.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftmm.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftmodapi.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftmoderr.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftotval.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftoutln.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftpfr.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftrender.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftsizes.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftsnames.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftstroke.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftsynth.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftsystem.h /home/milchstore/source/freetype-2.3.9/include/freetype/fttrigon.h /home/milchstore/source/freet
```

ude/freetype/ftwinfnt.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftxf86.h /home/milchstore/source/freetype-2.3.9/include/freetype/t1tables.h /home/milchstore/source/freetype-2.3.9/include/freetype/ttnameid.h /home/milchstore/source/freetype-2.3.9/include/freetype/tttables.h /home/milchstore/source/freetype-2.3.9/include/freetype/ttags.h /home/milchstore/source/freetype-2.3.9/include/freetype/ttunpat.h

```
./builds/unix/libtool --mode=link gcc -o /home/milchstore/source/freetype-2.3.9/objs/libfreetype.la /home/milchstore/source/freetype-2.3.9/objs/ftsyste  
m.lo /home/milchstore/source/freetype-2.3.9/objs/ftdebug.lo /home/milchstore/source/freetype-2.3.9/objs/ftinit.lo /home/milchstore/source/freetype-2.3.9/obj  
s/ftbase.lo /home/milchstore/source/freetype-2.3.9/objs/ftbbox.lo /home/milchstore/source/freetype-2.3.9/objs/ftbdf.lo /home/milchstore/source/freetype-2.3.9/obj  
s/ftbitmap.lo /home/milchstore/source/freetype-2.3.9/objs/ftcid.lo /home/milchstore/source/freetype-2.3.9/objs/ftfstype.lo /home/milchstore/source/freetype-2.3.9/obj  
s/ftgasp.lo /home/milchstore/source/freetype-2.3.9/objs/ftglyph.lo /home/milchstore/source/freetype-2.3.9/objs/ftgxval.lo /home/milchstore/source/freetype-2.3.9/obj  
s/ftlcdfil.lo /home/milchstore/source/freetype-2.3.9/objs/ftmm.lo /home/milchstore/source/freetype-2.3.9/objs/ftotval.lo /home/milchstore/source/freetype-2.3.9/obj  
s/ftpatent.lo /home/milchstore/source/freetype-2.3.9/objs/ftpfr.lo /home/milchstore/source/freetype-2.3.9/objs/ftstroke.lo /home/milchstore/source/freetype-2.3.9/obj  
s/ftsynth.lo /home/milchstore/source/freetype-2.3.9/objs/fttype1.lo /home/milchstore/source/freetype-2.3.9/objs/ftwinfnt.lo /home/milchstore/source/freetype-2.3.9/obj  
s/ftxf86.lo /home/milchstore/source/freetype-2.3.9/objs/truetype.lo /home/milchstore/source/freetype-2.3.9/objs/type1.lo /home/milchstore/source/freetype-2.3.9/obj  
s/cff.lo /home/milchstore/source/freetype-2.3.9/objs/type1cid.lo /home/milchstore/source/freetype-2.3.9/objs/pfr.lo /home/milchstore/source/freetype-2.3.9/obj  
s/type42.lo /home/milchstore/source/freetype-2.3.9/objs/winfnt.lo /home/milchstore/source/freetype-2.3.9/objs/pcf.lo /home/milchstore/source/freetype-2.3.9/obj  
s/bdf.lo /home/milchstore/source/freetype-2.3.9/objs/sfnt.lo /home/milchstore/source/freetype-2.3.9/objs/autofit.lo /home/milchstore/source/freetype-2.3.9/obj  
s/pshinter.lo /home/milchstore/source/freetype-2.3.9/objs/raster.lo /home/milchstore/source/freetype-2.3.9/objs/smooth.lo /home/milchstore/source/freetype-2.3.9/obj  
s/ftcache.lo /home/milchstore/source/freetype-2.3.9/objs/ftgzip.lo /home/milchstore/source/freetype-2.3.9/objs/ftlwz.lo /home/milchstore/source/freetype-2.3.9/obj  
s/psaux.lo /home/milchstore/source/freetype-2.3.9/objs/psnames.lo -rpath /home/milchstore/php5/lib -version-info 9:20:3 -lz -no-undefined  
libtool: link: gcc -shared /home/milchstore/source/freetype-2.3.9/objs/.libs/ftsyste  
m.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftdebug.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftinit.o /home/milchstore/source/freetype-2.3.9/obj  
s/.libs/ftbase.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftbbox.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftbdf.o /home/milchstore  
/source/freetype-2.3.9/objs/.libs/ftbitmap.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftcid.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftfstyp  
e.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftgasp.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftglyph.o /home/milchstore/source/freetype-2.3.  
9/objs/.libs/ftgxval.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftlcdfi  
l.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftmm.o /home/milchstore/so  
urce/freetype-2.3.9/objs/.libs/ftotval.o /home/milchstore/source/freetype-2.3.9/  
objs/.libs/ftpatent.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftpfr.o  
/home/milchstore/source/freetype-2.3.9/objs/.libs/ftstroke.o /home/milchstore/so
```

```
objs/.libs/fttype1.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftwinfnt.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftxf86.o /home/milchstore/source/freetype-2.3.9/objs/.libs/truetype.o /home/milchstore/source/freetype-2.3.9/objs/.libs/type1.o /home/milchstore/source/freetype-2.3.9/objs/.libs/cff.o /home/milchstore/source/freetype-2.3.9/objs/.libs/type1cid.o /home/milchstore/source/freetype-2.3.9/objs/.libs/pfr.o /home/milchstore/source/freetype-2.3.9/objs/.libs/type42.o /home/milchstore/source/freetype-2.3.9/objs/.libs/winfnt.o /home/milchstore/source/freetype-2.3.9/objs/.libs/pcf.o /home/milchstore/source/freetype-2.3.9/objs/.libs/bdf.o /home/milchstore/source/freetype-2.3.9/objs/.libs/sfnt.o /home/milchstore/source/freetype-2.3.9/objs/.libs/autofit.o /home/milchstore/source/freetype-2.3.9/objs/.libs/pshinter.o /home/milchstore/source/freetype-2.3.9/objs/.libs/raster.o /home/milchstore/source/freetype-2.3.9/objs/.libs/smooth.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftcache.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftgzip.o /home/milchstore/source/freetype-2.3.9/objs/.libs/ftlw.o /home/milchstore/source/freetype-2.3.9/objs/.libs/psaux.o /home/milchstore/source/freetype-2.3.9/objs/.libs/psnames.o -lz -Wl,-soname -Wl,libfreetype.so.6 -o /home/milchstore/source/freetype-2.3.9/objs/.libs/libfreetype.so.6.3.20
```

```
libtool: link: (cd "/home/milchstore/source/freetype-2.3.9/objs/.libs" && rm -f "libfreetype.so.6" && ln -s "libfreetype.so.6.3.20" "libfreetype.so.6")
```

```
libtool: link: (cd "/home/milchstore/source/freetype-2.3.9/objs/.libs" && rm -f "libfreetype.so" && ln -s "libfreetype.so.6.3.20" "libfreetype.so")
```

```
libtool: link: ar cru /home/milchstore/source/freetype-2.3.9/objs/.libs/libfreetype.a /home/milchstore/source/freetype-2.3.9/objs/ftsystem.o /home/milchstore/source/freetype-2.3.9/objs/ftdebug.o /home/milchstore/source/freetype-2.3.9/objs/ftinit.o /home/milchstore/source/freetype-2.3.9/objs/ftbase.o /home/milchstore/source/freetype-2.3.9/objs/ftbbox.o /home/milchstore/source/freetype-2.3.9/objs/ftbdf.o /home/milchstore/source/freetype-2.3.9/objs/ftbitmap.o /home/milchstore/source/freetype-2.3.9/objs/ftcid.o /home/milchstore/source/freetype-2.3.9/objs/ftfstype.o /home/milchstore/source/freetype-2.3.9/objs/ftgasp.o /home/milchstore/source/freetype-2.3.9/objs/ftglyph.o /home/milchstore/source/freetype-2.3.9/objs/ftgxval.o /home/milchstore/source/freetype-2.3.9/objs/ftlcdfil.o /home/milchstore/source/freetype-2.3.9/objs/ftmm.o /home/milchstore/source/freetype-2.3.9/objs/ftotval.o /home/milchstore/source/freetype-2.3.9/objs/ftpatent.o /home/milchstore/source/freetype-2.3.9/objs/ftpfr.o /home/milchstore/source/freetype-2.3.9/objs/ftstroke.o /home/milchstore/source/freetype-2.3.9/objs/ftsynth.o /home/milchstore/source/freetype-2.3.9/objs/fttype1.o /home/milchstore/source/freetype-2.3.9/objs/ftwinfnt.o /home/milchstore/source/freetype-2.3.9/objs/ftxf86.o /home/milchstore/source/freetype-2.3.9/objs/truetype.o /home/milchstore/source/freetype-2.3.9/objs/type1.o /home/milchstore/source/freetype-2.3.9/objs/cff.o /home/milchstore/source/freetype-2.3.9/objs/type1cid.o /home/milchstore/source/freetype-2.3.9/objs/pfr.o /home/milchstore/source/freetype-2.3.9/objs/type42.o /home/milchstore/source/freetype-2.3.9/objs/winfnt.o /home/milchstore/source/freetype-2.3.9/objs/pcf.o /home/milchstore/source/freetype-2.3.9/objs/bdf.o /home/milchstore/source/freetype-2.3.9/objs/sfnt.o /home/milchstore/source/freetype-2.3.9/objs/autofit.o /home/milchstore/source/freetype-2.3.9/objs/pshinter.o /home/milchstore/source/freetype-2.3.9/objs/raster.o /home/milchstore/source/freetype-2.3.9/objs/smooth.o /home/milchstore/source/freetype-2.3.9/objs/ftcache.o /home/milchstore/source/freetype-2.3.9/objs/ftgzip.o /home/milchstore/source/freetype-2.3.9/objs/ftlw.o /home/milchstore/source/freetype-2.3.9/objs/psaux.o /home/milchstore/source/fre
```


- have your system administrator add LIBDIR to `/etc/ld.so.conf'

See any operating system documentation about shared libraries for more information, such as the ld(1) and ld.so(8) manual pages.

```
-----  
for P in /home/milchstore/source/freetype-2.3.9/include/freetype/freetype.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftadvanc.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftbbox.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftbdf.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftbitmap.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftcache.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftchapters.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftcid.h /home/milchstore/source/freetype-2.3.9/include/freetype/fterrdef.h /home/milchstore/source/freetype-2.3.9/include/freetype/fterrors.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftgasp.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftglyph.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftgxval.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftgzip.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftimage.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftincrem.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftlcdfil.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftlist.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftlzw.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftmac.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftmm.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftmodapi.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftmoderr.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftotval.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftoutln.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftpfr.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftrender.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftsizes.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftsnames.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftstroke.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftsynth.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftsystem.h /home/milchstore/source/freetype-2.3.9/include/freetype/fttrigon.h /home/milchstore/source/freetype-2.3.9/include/freetype/fttypes.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftwinfnt.h /home/milchstore/source/freetype-2.3.9/include/freetype/ftxf86.h /home/milchstore/source/freetype-2.3.9/include/freetype/t1tables.h /home/milchstore/source/freetype-2.3.9/include/freetype/ttnameid.h /home/milchstore/source/freetype-2.3.9/include/freetype/tttables.h /home/milchstore/source/freetype-2.3.9/include/freetype/tttags.h /home/milchstore/source/freetype-2.3.9/include/freetype/ttunpat.h ; do
```

```
o \
    /usr/bin/install -c -m 644 \
    $P /home/milchstore/php5/include/freetype2/freetype ; \
```

done

```
for P in /home/milchstore/source/freetype-2.3.9/include/freetype/config/ftconfig.h /home/milchstore/source/freetype-2.3.9/include/freetype/config/fthead.h /home/milchstore/source/freetype-2.3.9/include/freetype/config/ftmodule.h /home/milchstore/source/freetype-2.3.9/include/freetype/config/ftoption.h /home/milchstore/source/freetype-2.3.9/include/freetype/config/ftstdlib.h /home/milchstore/source/freetype-2.3.9/objs/ftmodule.h ; do \
```

```
    /usr/bin/install -c -m 644 \
```

```
done
rm -f /home/milchstore/php5/include/freetype2/freetype/cache/*
rmdir /home/milchstore/php5/include/freetype2/freetype/cache
rm -f /home/milchstore/php5/include/freetype2/freetype/internal/*
rmdir /home/milchstore/php5/include/freetype2/freetype/internal
rmdir: /home/milchstore/php5/include/freetype2/freetype/internal: No such file or
directory
make: [install] Error 1 (ignored)
/usr/bin/install -c -m 644 ./builds/unix/ft2unix.h \
    /home/milchstore/php5/include/ft2build.h
/usr/bin/install -c -m 644 ./builds/unix/ftconfig.h \
    /home/milchstore/php5/include/freetype2/freetype/config/ftconfig.h
/usr/bin/install -c -m 644 /home/milchstore/source/freetype-2.3.9/objs/ftmodule.
h \
    /home/milchstore/php5/include/freetype2/freetype/config/ftmodule.h
/usr/bin/install -c -m 755 ./builds/unix/freetype-config \
    /home/milchstore/php5/bin/freetype-config
/usr/bin/install -c -m 644 ./builds/unix/freetype2.m4 \
    /home/milchstore/php5/share/aclocal/freetype2.m4
/usr/bin/install -c -m 644 ./builds/unix/freetype2.pc \
    /home/milchstore/php5/lib/pkgconfig/freetype2.pc
checking for a BSD-compatible install... /usr/bin/install -c
checking whether build environment is sane... yes
checking for a thread-safe mkdir -p... /bin/mkdir -p
checking for gawk... gawk
checking whether make sets $(MAKE)... yes
checking build system type... x86_64-unknown-linux-gnu
checking host system type... x86_64-unknown-linux-gnu
configure: autobuild project... libidn
configure: autobuild revision... 0.6.14
configure: autobuild hostname... colts
configure: autobuild timestamp... 20100305-074941
checking whether NLS is requested... yes
checking for msgfmt... /usr/bin/msgfmt
checking for gmsgfmt... /usr/bin/msgfmt
checking for xgettext... /usr/bin/xgettext
checking for msgmerge... /usr/bin/msgmerge
checking for style of include used by make... GNU
checking for gcc... gcc
checking for C compiler default output file name... a.out
checking whether the C compiler works... yes
checking whether we are cross compiling... no
checking for suffix of executables...
checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ISO C89... none needed
checking dependency style of gcc... gcc3
checking for ld used by GCC... /usr/bin/ld
checking if the linker (/usr/bin/ld) is GNU ld... yes
```

checking for CFPreferencesCopyAppValue... no
checking for CFLocaleCopyCurrent... no
checking for GNU gettext in libc... yes
checking whether to use NLS... yes
checking where the gettext function comes from... libc
checking for gcc... (cached) gcc
checking whether we are using the GNU C compiler... (cached) yes
checking whether gcc accepts -g... (cached) yes
checking for gcc option to accept ISO C89... (cached) none needed
checking dependency style of gcc... (cached) gcc3
checking for ranlib... ranlib
checking how to run the C preprocessor... gcc -E
checking for grep that handles long lines and -e... /bin/grep
checking for egrep... /bin/grep -E
checking for AIX... no
checking for ANSI C header files... yes
checking for sys/types.h... yes
checking for sys/stat.h... yes
checking for stdlib.h... yes
checking for string.h... yes
checking for memory.h... yes
checking for strings.h... yes
checking for inttypes.h... yes
checking for stdint.h... yes
checking for unistd.h... yes
checking minix/config.h usability... no
checking minix/config.h presence... no
checking for minix/config.h... no
checking whether it is safe to define __EXTENSIONS__... yes
checking for a sed that does not truncate output... /bin/sed
checking for ld used by gcc... /usr/bin/ld
checking if the linker (/usr/bin/ld) is GNU ld... yes
checking for /usr/bin/ld option to reload object files... -r
checking for BSD-compatible nm... /usr/bin/nm -B
checking whether ln -s works... yes
checking how to recognise dependent libraries... pass_all
checking dlfcn.h usability... yes
checking dlfcn.h presence... yes
checking for dlfcn.h... yes
checking for g++... g++
checking whether we are using the GNU C++ compiler... yes
checking whether g++ accepts -g... yes
checking dependency style of g++... gcc3
checking how to run the C++ preprocessor... g++ -E
checking for g77... g77
checking whether we are using the GNU Fortran 77 compiler... yes
checking whether g77 accepts -g... yes
checking the maximum length of command line arguments... 32768
checking command to parse /usr/bin/nm -B output from gcc object... ok
checking for objdir... .libs

checking for ranlib... (cached) ranlib
checking for strip... strip
checking if gcc supports -fno-rtti -fno-exceptions... no
checking for gcc option to produce PIC... -fPIC
checking if gcc PIC flag -fPIC works... yes
checking if gcc static flag -static works... yes
checking if gcc supports -c -o file.o... yes
checking whether the gcc linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking whether -lc should be explicitly linked in... no
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
checking whether stripping libraries is possible... yes
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries... yes
configure: creating libtool
appending configuration tag "CXX" to libtool
checking for ld used by g++... /usr/bin/ld -m elf_x86_64
checking if the linker (/usr/bin/ld -m elf_x86_64) is GNU ld... yes
checking whether the g++ linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking for g++ option to produce PIC... -fPIC
checking if g++ PIC flag -fPIC works... yes
checking if g++ static flag -static works... yes
checking if g++ supports -c -o file.o... yes
checking whether the g++ linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
appending configuration tag "F77" to libtool
checking if libtool supports shared libraries... yes
checking whether to build shared libraries... yes
checking whether to build static libraries... yes
checking for g77 option to produce PIC... -fPIC
checking if g77 PIC flag -fPIC works... yes
checking if g77 static flag -static works... yes
checking if g77 supports -c -o file.o... yes
checking whether the g77 linker (/usr/bin/ld -m elf_x86_64) supports shared libraries... yes
checking dynamic linker characteristics... GNU/Linux ld.so
checking how to hardcode library paths into programs... immediate
checking for iconv... yes
checking how to link with libiconv... /home/milchstore/php5/lib/libiconv.so -Wl, -rpath -Wl,/home/milchstore/php5/lib
checking for iconv declaration...
extern size_t iconv (iconv_t cd, char * *inbuf, size_t *inbytesleft, char * *outbuf, size_t *outbytesleft);
checking for emacs... emacs
checking where .elc files should go... \${datarootdir}/emacs/site-lisp

checking for preferred C# implementation... any
checking for C# compiler... no
checking whether strerror_r is declared... yes
checking for strerror_r... yes
checking whether strerror_r returns char *... yes
checking getopt.h usability... yes
checking getopt.h presence... yes
checking for getopt.h... yes
checking for getopt_long_only... yes
checking whether optreset is declared... no
checking for working GNU getopt function... yes
checking whether getenv is declared... yes
checking for unistd.h... (cached) yes
checking iconv.h usability... yes
checking iconv.h presence... yes
checking for iconv.h... yes
checking for stdint.h... (cached) yes
checking for string.h... (cached) yes
checking wchar.h usability... yes
checking wchar.h presence... yes
checking for wchar.h... yes
checking for error_at_line... yes
checking absolute name of <unistd.h>... ///usr/include/unistd.h
checking for stdbool.h that conforms to C99... yes
checking for _Bool... yes
checking for long long int... yes
checking for unsigned long long int... yes
checking whether strdup is declared... yes
checking for C/C++ restrict keyword... __restrict
checking absolute name of <string.h>... ///usr/include/string.h
checking for iconv... (cached) yes
checking how to link with libiconv... /home/milchstore/php5/lib/libiconv.so -Wl,
-rpath -Wl,/home/milchstore/php5/lib
checking for iconv declaration... (cached)
extern size_t iconv (iconv_t cd, char * *inbuf, size_t *inbytesleft, ch
ar * *outbuf, size_t *outbytesleft);
checking absolute name of <iconv.h>... ///home/milchstore/php5/include/iconv.h
checking absolute name of <stdint.h>... ///usr/include/stdint.h
checking whether stdint.h conforms to C99... no
checking sys/inttypes.h usability... no
checking sys/inttypes.h presence... no
checking for sys/inttypes.h... no
checking sys/bitypes.h usability... yes
checking sys/bitypes.h presence... yes
checking for sys/bitypes.h... yes
checking for bit size of ptrdiff_t... 64
checking for bit size of sig_atomic_t... 32
checking for bit size of size_t... 64
checking for bit size of wchar_t... 32
checking for bit size of wint_t... 32

```
checking whether wchar_t is signed... yes
checking whether wint_t is signed... no
checking for ptrdiff_t integer literal suffix... l
checking for sig_atomic_t integer literal suffix...
checking for size_t integer literal suffix... ul
checking for wchar_t integer literal suffix...
checking for wint_t integer literal suffix... u
checking for strdup... yes
checking for strverscmp... yes
checking whether <wchar.h> is standalone... yes
checking for nl_langinfo and CODESET... yes
checking for valgrind... no
checking whether self tests are run under valgrind... no
checking if TLD API for specific TLD rules should be built... yes
checking if implementation in Java should be built... no
checking if implementation in C# should be built... no
configure: creating ./config.status
config.status: creating csharpcomp.sh
config.status: creating Makefile
config.status: creating libidn.pc
config.status: creating doc/reference/Makefile
config.status: creating doc/java/Makefile
config.status: creating gl/Makefile
config.status: creating lib/gl/Makefile
config.status: creating lib/stringprep.h
config.status: creating contrib/doxygen/Doxyfile
config.status: creating doc/Makefile
config.status: creating doc/specifications/Makefile
config.status: creating doc/tld/Makefile
config.status: creating lib/Makefile
config.status: creating src/Makefile
config.status: creating tests/Makefile
config.status: creating examples/Makefile
config.status: creating java/Makefile
config.status: creating java/gnu/Makefile
config.status: creating java/gnu/inet/Makefile
config.status: creating java/gnu/inet/encoding/Makefile
config.status: creating java/misc/Makefile
config.status: creating csharp/Makefile
config.status: creating po/Makefile.in
config.status: creating config.h
config.status: executing po-directories commands
config.status: creating po/POTFILES
config.status: creating po/Makefile
config.status: executing depfiles commands
make all-recursive
make[1]: Entering directory `/home/milchstore/source/libidn-0.6.14'
Making all in gl
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/gl'
rm -f unistd.h-t unistd.h
```

```

sed -e 's|@''HAVE_UNISTD_H''@|1|g' \
    -e 's|@''ABSOLUTE_UNISTD_H''@|'''''usr/include/unistd.h''|g' \
    -e 's/@''HAVE_INCLUDE_NEXT''@/(__GNUC__ || 60000000 <= __DECC_VER)
/g' \

    -e 's|@''GNULIB_CHOWN''@|0|g' \
    -e 's|@''GNULIB_DUP2''@|0|g' \
    -e 's|@''GNULIB_FCHDIR''@|0|g' \
    -e 's|@''GNULIB_FTRUNCATE''@|0|g' \
    -e 's|@''GNULIB_GETCWD''@|0|g' \
    -e 's|@''GNULIB_GETLOGIN_R''@|0|g' \
    -e 's|@''GNULIB_LSEEK''@|0|g' \
    -e 's|@''GNULIB_READLINK''@|0|g' \
    -e 's|@''GNULIB_SLEEP''@|0|g' \
    -e 's|@''HAVE_DUP2''@|1|g' \
    -e 's|@''HAVE_FTRUNCATE''@|1|g' \
    -e 's|@''HAVE_READLINK''@|1|g' \
    -e 's|@''HAVE_SLEEP''@|1|g' \
    -e 's|@''HAVE_DECL_GETLOGIN_R''@|1|g' \
    -e 's|@''REPLACE_CHOWN''@|0|g' \
    -e 's|@''REPLACE_FCHDIR''@|0|g' \
    -e 's|@''REPLACE_GETCWD''@|0|g' \
    -e 's|@''REPLACE_LSEEK''@|0|g' \
    < ./unistd.h; \
} > unistd.h-t
mv unistd.h-t unistd.h
make all-am
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/gl'
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I/h
ome/milchstore/php5/include -g -O2 -MT dummy.lo -MD -MP -MF .deps/dummy.Tpo -c
-o dummy.lo dummy.c
mkdir .libs
gcc -DHAVE_CONFIG_H -I. -I.. -I/home/milchstore/php5/include -g -O2 -MT dummy.l
o -MD -MP -MF .deps/dummy.Tpo -c dummy.c -fPIC -DPIC -o .libs/dummy.o
gcc -DHAVE_CONFIG_H -I. -I.. -I/home/milchstore/php5/include -g -O2 -MT dummy.l
o -MD -MP -MF .deps/dummy.Tpo -c dummy.c -o dummy.o >/dev/null 2>&1
mv -f .deps/dummy.Tpo .deps/dummy.Plo
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o libgnu.la dummy.lo
ar cru .libs/libgnu.a .libs/dummy.o
ranlib .libs/libgnu.a
creating libgnu.la
(cd .libs && rm -f libgnu.la && ln -s ../libgnu.la libgnu.la)
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/gl'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/gl'
Making all in lib/gl
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/lib/gl'
rm -f stdint.h-t stdint.h
{ echo '/* DO NOT EDIT! GENERATED AUTOMATICALLY! */'; \
    sed -e 's/@''HAVE_STDINT_H''@/1/g' \
        -e 's|@''ABSOLUTE_STDINT_H''@|'''''usr/include/stdint.h''|g' \
        -e 's/@''HAVE_INCLUDE_NEXT''@/(__GNUC__ || 60000000 <= __DECC_VER)

```

```

-e 's/@' 'HAVE_SYS_TYPES_H' '@/1/g' \
-e 's/@' 'HAVE_INTTYPES_H' '@/1/g' \
-e 's/@' 'HAVE_SYS_INTTYPES_H' '@/0/g' \
-e 's/@' 'HAVE_SYS_BITYPES_H' '@/1/g' \
-e 's/@' 'HAVE_LONG_LONG_INT' '@/1/g' \
-e 's/@' 'HAVE_UNSIGNED_LONG_LONG_INT' '@/1/g' \
-e 's/@' 'BITSIZEOF_PTRDIFF_T' '@/64/g' \
-e 's/@' 'PTRDIFF_T_SUFFIX' '@/1/g' \
-e 's/@' 'BITSIZEOF_SIG_ATOMIC_T' '@/32/g' \
-e 's/@' 'HAVE_SIGNED_SIG_ATOMIC_T' '@/1/g' \
-e 's/@' 'SIG_ATOMIC_T_SUFFIX' '@/1/g' \
-e 's/@' 'BITSIZEOF_SIZE_T' '@/64/g' \
-e 's/@' 'SIZE_T_SUFFIX' '@/u1/g' \
-e 's/@' 'BITSIZEOF_WCHAR_T' '@/32/g' \
-e 's/@' 'HAVE_SIGNED_WCHAR_T' '@/1/g' \
-e 's/@' 'WCHAR_T_SUFFIX' '@/1/g' \
-e 's/@' 'BITSIZEOF_WINT_T' '@/32/g' \
-e 's/@' 'HAVE_SIGNED_WINT_T' '@/0/g' \
-e 's/@' 'WINT_T_SUFFIX' '@/u/g' \
< ./stdint.h; \
} > stdint.h-t
mv stdint.h-t stdint.h
rm -f string.h-t string.h
{ echo '/* DO NOT EDIT! GENERATED AUTOMATICALLY! */' && \
  sed -e 's|@' 'ABSOLUTE_STRING_H' '|@|"/usr/include/string.h"|g' \
    -e 's/@' 'HAVE_INCLUDE_NEXT' '@/(__GNUC__ || 60000000 <= __DECC_VER)
/g' \

-e 's|@' 'GNULIB_MBSLEN' '@|0|g' \
-e 's|@' 'GNULIB_MBSCHR' '@|0|g' \
-e 's|@' 'GNULIB_MBSRCHR' '@|0|g' \
-e 's|@' 'GNULIB_MBSSTR' '@|0|g' \
-e 's|@' 'GNULIB_MBSCASECMP' '@|0|g' \
-e 's|@' 'GNULIB_MBSNCASECMP' '@|0|g' \
-e 's|@' 'GNULIB_MBSPCASECMP' '@|0|g' \
-e 's|@' 'GNULIB_MBSCASESTR' '@|0|g' \
-e 's|@' 'GNULIB_MBSCSPN' '@|0|g' \
-e 's|@' 'GNULIB_MBSPBRK' '@|0|g' \
-e 's|@' 'GNULIB_MBSSPN' '@|0|g' \
-e 's|@' 'GNULIB_MBSSEP' '@|0|g' \
-e 's|@' 'GNULIB_MBSTOK_R' '@|0|g' \
-e 's|@' 'GNULIB_MEMMEM' '@|0|g' \
-e 's|@' 'GNULIB_MEMPCPY' '@|0|g' \
-e 's|@' 'GNULIB_MEMRCHR' '@|0|g' \
-e 's|@' 'GNULIB_STPCPY' '@|0|g' \
-e 's|@' 'GNULIB_STPNCPY' '@|0|g' \
-e 's|@' 'GNULIB_STRCHRNU' '@|0|g' \
-e 's|@' 'GNULIB_STRDUP' '@|1|g' \
-e 's|@' 'GNULIB_STRNDUP' '@|0|g' \
-e 's|@' 'GNULIB_STRNLEN' '@|0|g' \
-e 's|@' 'GNULIB_STRPBRK' '@|0|g' \

```



```

gcc -DHAVE_CONFIG_H -I. -I../.. -I/home/milchstore/php5/include -g -O2 -MT c-strncasecmp.lo -MD -MP -MF .deps/c-strncasecmp.Tpo -c c-strncasecmp.c -o c-strncasecmp.o >/dev/null 2>&1
mv -f .deps/c-strncasecmp.Tpo .deps/c-strncasecmp.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I../.. -I/home/milchstore/php5/include -g -O2 -MT striconv.lo -MD -MP -MF .deps/striconv.Tpo -c -o striconv.lo striconv.c
gcc -DHAVE_CONFIG_H -I. -I../.. -I/home/milchstore/php5/include -g -O2 -MT striconv.lo -MD -MP -MF .deps/striconv.Tpo -c striconv.c -fPIC -DPIC -o .libs/striconv.o
gcc -DHAVE_CONFIG_H -I. -I../.. -I/home/milchstore/php5/include -g -O2 -MT striconv.lo -MD -MP -MF .deps/striconv.Tpo -c striconv.c -o striconv.o >/dev/null 2>&1
mv -f .deps/striconv.Tpo .deps/striconv.Plo
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -L/home/milchstore/php5/lib -liconv -R/home/milchstore/php5/lib -o libgnu.la c-ctype.lo c-strcasecmp.lo c-strncasecmp.lo striconv.lo
ar cru .libs/libgnu.a .libs/c-ctype.o .libs/c-strcasecmp.o .libs/c-strncasecmp.o .libs/striconv.o
ranlib .libs/libgnu.a
creating libgnu.la
(cd .libs && rm -f libgnu.la && ln -s ../libgnu.la libgnu.la)
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/lib/gl'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/lib/gl'
Making all in lib
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/lib'
if test -n "stdint.h"; then \
    cp gl/stdint.h idn-int.h; \
else \
    echo '#include <stdint.h>' > idn-int.h; \
fi
make all-am
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/lib'
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT nfkc.lo -MD -MP -MF .deps/nfkc.Tpo -c -o nfkc.lo nfkc.c
mkdir .libs
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT nfkc.lo -MD -MP -MF .deps/nfkc.Tpo -c nfkc.c -fPIC -DPIC -o .libs/nfkc.o
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT nfkc.lo -MD -MP -MF .deps/nfkc.Tpo -c nfkc.c -o nfkc.o >/dev/null 2>&1
mv -f .deps/nfkc.Tpo .deps/nfkc.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT toutf8.lo -MD -MP -MF .deps/toutf8.Tpo -c -o toutf8.lo toutf8.c
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT toutf8.lo -MD -MP -MF .d

```

```
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT toutf8.lo -MD -MP -MF .d
eps/toutf8.Tpo -c toutf8.c -o toutf8.o >/dev/null 2>&1
mv -f .deps/toutf8.Tpo .deps/toutf8.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/
php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php
5/include -g -O2 -MT version.lo -MD -MP -MF .deps/version.Tpo -c -o version.lo
version.c
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT version.lo -MD -MP -MF .
deps/version.Tpo -c version.c -fPIC -DPIC -o .libs/version.o
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT version.lo -MD -MP -MF .
deps/version.Tpo -c version.c -o version.o >/dev/null 2>&1
mv -f .deps/version.Tpo .deps/version.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/
php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php
5/include -g -O2 -MT stringprep.lo -MD -MP -MF .deps/stringprep.Tpo -c -o strin
gprep.lo stringprep.c
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT stringprep.lo -MD -MP -M
F .deps/stringprep.Tpo -c stringprep.c -fPIC -DPIC -o .libs/stringprep.o
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT stringprep.lo -MD -MP -M
F .deps/stringprep.Tpo -c stringprep.c -o stringprep.o >/dev/null 2>&1
mv -f .deps/stringprep.Tpo .deps/stringprep.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/
php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php
5/include -g -O2 -MT rfc3454.lo -MD -MP -MF .deps/rfc3454.Tpo -c -o rfc3454.lo
rfc3454.c
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT rfc3454.lo -MD -MP -MF .
deps/rfc3454.Tpo -c rfc3454.c -fPIC -DPIC -o .libs/rfc3454.o
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT rfc3454.lo -MD -MP -MF .
deps/rfc3454.Tpo -c rfc3454.c -o rfc3454.o >/dev/null 2>&1
mv -f .deps/rfc3454.Tpo .deps/rfc3454.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/
php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php
5/include -g -O2 -MT profiles.lo -MD -MP -MF .deps/profiles.Tpo -c -o profiles.
lo profiles.c
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT profiles.lo -MD -MP -MF
.deps/profiles.Tpo -c profiles.c -fPIC -DPIC -o .libs/profiles.o
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT profiles.lo -MD -MP -MF
.deps/profiles.Tpo -c profiles.c -o profiles.o >/dev/null 2>&1
mv -f .deps/profiles.Tpo .deps/profiles.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/
php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php
```

lo punycode.c

```
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT punycode.lo -MD -MP -MF .deps/punycode.Tpo -c punycode.c -fPIC -DPIC -o .libs/punycode.o
```

```
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT punycode.lo -MD -MP -MF .deps/punycode.Tpo -c punycode.c -o punycode.o >/dev/null 2>&1
```

```
mv -f .deps/punycode.Tpo .deps/punycode.Plo
```

```
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT idna.lo -MD -MP -MF .deps/idna.Tpo -c -o idna.lo idna.c
```

```
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT idna.lo -MD -MP -MF .deps/idna.Tpo -c idna.c -fPIC -DPIC -o .libs/idna.o
```

```
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT idna.lo -MD -MP -MF .deps/idna.Tpo -c idna.c -o idna.o >/dev/null 2>&1
```

```
mv -f .deps/idna.Tpo .deps/idna.Plo
```

```
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT pr29.lo -MD -MP -MF .deps/pr29.Tpo -c -o pr29.lo pr29.c
```

```
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT pr29.lo -MD -MP -MF .deps/pr29.Tpo -c pr29.c -fPIC -DPIC -o .libs/pr29.o
```

```
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT pr29.lo -MD -MP -MF .deps/pr29.Tpo -c pr29.c -o pr29.o >/dev/null 2>&1
```

```
mv -f .deps/pr29.Tpo .deps/pr29.Plo
```

```
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT idn-free.lo -MD -MP -MF .deps/idn-free.Tpo -c -o idn-free.lo idn-free.c
```

```
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT idn-free.lo -MD -MP -MF .deps/idn-free.Tpo -c idn-free.c -fPIC -DPIC -o .libs/idn-free.o
```

```
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT idn-free.lo -MD -MP -MF .deps/idn-free.Tpo -c idn-free.c -o idn-free.o >/dev/null 2>&1
```

```
mv -f .deps/idn-free.Tpo .deps/idn-free.Plo
```

```
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT strerror-idna.lo -MD -MP -MF .deps/strerror-idna.Tpo -c -o strerror-idna.lo strerror-idna.c
```

```
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT strerror-idna.lo -MD -MP -MF .deps/strerror-idna.Tpo -c strerror-idna.c -fPIC -DPIC -o .libs/strerror-idna.o
```

```
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT strerror-idna.lo -MD -MP -MF .deps/strerror-idna.Tpo -c strerror-idna.c -o strerror-idna.o >/dev/null 2>
```



```

mv -f .deps/streerror-idna.Tpo .deps/streerror-idna.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/
php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php
5/include -g -O2 -MT streerror-pr29.lo -MD -MP -MF .deps/streerror-pr29.Tpo -c -o
streerror-pr29.lo streerror-pr29.c
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT streerror-pr29.lo -MD -MP
-MF .deps/streerror-pr29.Tpo -c streerror-pr29.c -fPIC -DPIC -o .libs/streerror-p
r29.o
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT streerror-pr29.lo -MD -MP
-MF .deps/streerror-pr29.Tpo -c streerror-pr29.c -o streerror-pr29.o >/dev/null 2>
&1
mv -f .deps/streerror-pr29.Tpo .deps/streerror-pr29.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/
php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php
5/include -g -O2 -MT streerror-punycodelo -MD -MP -MF .deps/streerror-punycodelo
.Tpo -c -o streerror-punycodelo streerror-punycodelo.c
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT streerror-punycodelo -MD
-MP -MF .deps/streerror-punycodelo.Tpo -c streerror-punycodelo.c -fPIC -DPIC -o .lib
s/streerror-punycodelo.o
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT streerror-punycodelo -MD
-MP -MF .deps/streerror-punycodelo.Tpo -c streerror-punycodelo.c -o streerror-punycod
elo >/dev/null 2>&1
mv -f .deps/streerror-punycodelo.Tpo .deps/streerror-punycodelo.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/
php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php
5/include -g -O2 -MT streerror-stringprep.lo -MD -MP -MF .deps/streerror-stringpr
ep.Tpo -c -o streerror-stringprep.lo streerror-stringprep.c
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT streerror-stringprep.lo -
MD -MP -MF .deps/streerror-stringprep.Tpo -c streerror-stringprep.c -fPIC -DPIC -
o .libs/streerror-stringprep.o
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT streerror-stringprep.lo -
MD -MP -MF .deps/streerror-stringprep.Tpo -c streerror-stringprep.c -o streerror-st
ringprep.o >/dev/null 2>&1
mv -f .deps/streerror-stringprep.Tpo .deps/streerror-stringprep.Plo
/bin/sh ../libtool --tag=CC --mode=compile gcc -DLOCALEDIR=\"/home/milchstore/
php5/share/locale\" -DHAVE_CONFIG_H -I. -I.. -I./gl -Igl -I/home/milchstore/php
5/include -g -O2 -MT streerror-tld.lo -MD -MP -MF .deps/streerror-tld.Tpo -c -o s
treerror-tld.lo streerror-tld.c
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT streerror-tld.lo -MD -MP
-MF .deps/streerror-tld.Tpo -c streerror-tld.c -fPIC -DPIC -o .libs/streerror-tld.
o
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I./gl -Igl -I/home/milchstore/php5/include -g -O2 -MT streerror-tld.lo -MD -MP

```



```
(cd .libs && rm -f libidn.so && ln -s libidn.so.11.5.28 libidn.so)
rm -fr .libs/libidn.lax
mkdir .libs/libidn.lax
rm -fr .libs/libidn.lax/libgnu.a
mkdir .libs/libidn.lax/libgnu.a
(cd .libs/libidn.lax/libgnu.a && ar x /home/milchstore/source/libidn-0.6.14/lib/
gl/.libs/libgnu.a)
ar cru .libs/libidn.a nfkc.o toutf8.o version.o stringprep.o rfc3454.o profiles
.o punycode.o idna.o pr29.o idn-free.o strerror-idna.o strerror-pr29.o strerror-
punycode.o strerror-stringprep.o strerror-tld.o tld.o tlds.o .libs/libidn.lax/l
ibgnu.a/c-strncasecmp.o .libs/libidn.lax/libgnu.a/c-strcasecmp.o .libs/libidn.la
x/libgnu.a/striconv.o .libs/libidn.lax/libgnu.a/c-ctype.o
ranlib .libs/libidn.a
rm -fr .libs/libidn.lax
creating libidn.la
(cd .libs && rm -f libidn.la && ln -s ../libidn.la libidn.la)
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/lib'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/lib'
Making all in po
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/po'
make[2]: Nothing to be done for `all'.
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/po'
Making all in src
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/src'
make all-am
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/src'
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I../lib -I../lib -I../gl -I../gl -I/home/milchstore/php5/include -g -O2 -MT i
dn.o -MD -MP -MF .deps/idn.Tpo -c -o idn.o idn.c
mv -f .deps/idn.Tpo .deps/idn.Po
gcc -DLOCALEDIR=\"/home/milchstore/php5/share/locale\" -DHAVE_CONFIG_H -I. -I..
-I../lib -I../lib -I../gl -I../gl -I/home/milchstore/php5/include -g -O2 -MT i
dn_cmd.o -MD -MP -MF .deps/idn_cmd.Tpo -c -o idn_cmd.o idn_cmd.c
mv -f .deps/idn_cmd.Tpo .deps/idn_cmd.Po
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o idn idn.o idn_cmd.o .
../lib/libidn.la ../gl/libgnu.la
mkdir .libs
gcc -g -O2 -o .libs/idn idn.o idn_cmd.o ../lib/.libs/libidn.so ../gl/.libs/libg
nu.a -Wl,--rpath -Wl,/home/milchstore/php5/lib
creating idn
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/src'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/src'
Making all in doc
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc'
make all-recursive
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc'
Making all in specifications
make[4]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc/specifica
tions'
make[4]: Nothing to be done for `all'.
```

ions'

Making all in tld

```
make[4]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc/tld'
```

```
make[4]: Nothing to be done for `all'.
```

```
make[4]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc/tld'
```

Making all in java

```
make[4]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc/java'
```

```
make[4]: Nothing to be done for `all'.
```

```
make[4]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc/java'
```

```
make[4]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc'
```

```
make[4]: Nothing to be done for `all-am'.
```

```
make[4]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc'
```

```
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc'
```

```
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc'
```

Making all in tests

```
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/tests'
```

```
/bin/sh ../libtool --tag=CC --mode=compile gcc -DHAVE_CONFIG_H -I. -I.. -I../lib -I../lib -I../gl -I../gl -I/home/milchstore/php5/include -g -O2 -MT utils.lo -MD -MP -MF .deps/utils.Tpo -c -o utils.lo utils.c
```

```
mkdir .libs
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I../lib -I../lib -I../gl -I../gl -I/home/milchstore/php5/include -g -O2 -MT utils.lo -MD -MP -MF .deps/utils.Tpo -c utils.c -FPI C -DPIC -o .libs/utils.o
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I../lib -I../lib -I../gl -I../gl -I/home/milchstore/php5/include -g -O2 -MT utils.lo -MD -MP -MF .deps/utils.Tpo -c utils.c -o utils.o >/dev/null 2>&1
```

```
mv -f .deps/utils.Tpo .deps/utils.Plo
```

```
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -no-install -o libutils.la utils.lo
```

```
ar cru .libs/libutils.a .libs/utils.o
```

```
ranlib .libs/libutils.a
```

```
creating libutils.la
```

```
(cd .libs && rm -f libutils.la && ln -s ../libutils.la libutils.la)
```

```
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/tests'
```

Making all in examples

```
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/examples'
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I../lib -I../lib -I/home/milchstore/php5/include -g -O2 -MT example.o -MD -MP -MF .deps/example.Tpo -c -o example.o example.c
```

```
mv -f .deps/example.Tpo .deps/example.Po
```

```
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o example example.o ../lib/libidn.la
```

```
mkdir .libs
```

```
gcc -g -O2 -o .libs/example example.o ../lib/.libs/libidn.so -Wl,--rpath -Wl,/home/milchstore/php5/lib
```

```
creating example
```

```
gcc -DHAVE_CONFIG_H -I. -I.. -I../lib -I../lib -I/home/milchstore/php5/include -g -O2 -MT example2.o -MD -MP -MF .deps/example2.Tpo -c -o example2.o example2.c
```

```
mv -f .deps/example2.Tpo .deps/example2.Po
```

```
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o example2 example2.o .
```

```
gcc -g -O2 -o .libs/example2 example2.o ../lib/.libs/libidn.so -Wl,--rpath -Wl,
/home/milchstore/php5/lib
creating example2
gcc -DHAVE_CONFIG_H -I. -I.. -I../lib -I../lib -I/home/milchstore/php5/include
-g -O2 -MT example3.o -MD -MP -MF .deps/example3.Tpo -c -o example3.o example3.
c
mv -f .deps/example3.Tpo .deps/example3.Po
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o example3 example3.o .
../lib/libidn.la
gcc -g -O2 -o .libs/example3 example3.o ../lib/.libs/libidn.so -Wl,--rpath -Wl,
/home/milchstore/php5/lib
creating example3
gcc -DHAVE_CONFIG_H -I. -I.. -I../lib -I../lib -I/home/milchstore/php5/include
-g -O2 -MT example4.o -MD -MP -MF .deps/example4.Tpo -c -o example4.o example4.
c
mv -f .deps/example4.Tpo .deps/example4.Po
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o example4 example4.o .
../lib/libidn.la
gcc -g -O2 -o .libs/example4 example4.o ../lib/.libs/libidn.so -Wl,--rpath -Wl,
/home/milchstore/php5/lib
creating example4
gcc -DHAVE_CONFIG_H -I. -I.. -I../lib -I../lib -I/home/milchstore/php5/include
-g -O2 -MT example5.o -MD -MP -MF .deps/example5.Tpo -c -o example5.o example5.
c
mv -f .deps/example5.Tpo .deps/example5.Po
/bin/sh ../libtool --tag=CC --mode=link gcc -g -O2 -o example5 example5.o .
../lib/libidn.la
gcc -g -O2 -o .libs/example5 example5.o ../lib/.libs/libidn.so -Wl,--rpath -Wl,
/home/milchstore/php5/lib
creating example5
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/examples'
Making all in java
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/java'
Making all in gnu
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/gnu'
Making all in inet
make[4]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet
'
Making all in encoding
make[5]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet
/encoding'
echo timestamp > classdist_noinst.stamp
make[5]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet/
encoding'
make[5]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet
'
make[5]: Nothing to be done for `all-am'.
make[5]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet'
make[4]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet'
make[4]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/gnu'
```

```
make[4]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/gnu'
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/gnu'
Making all in .
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/java'
make[3]: Nothing to be done for `all-am'.
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java'
Making all in misc
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/misc'
echo timestamp > classdist_noinst.stamp
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/misc'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java'
Making all in csharp
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/csharp'
make[2]: Nothing to be done for `all'.
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/csharp'
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14'
make[2]: Nothing to be done for `all-am'.
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14'
make[1]: Leaving directory `/home/milchstore/source/libidn-0.6.14'
Making install in gl
make[1]: Entering directory `/home/milchstore/source/libidn-0.6.14/gl'
make install-am
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/gl'
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/gl'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/gl'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/gl'
make[1]: Leaving directory `/home/milchstore/source/libidn-0.6.14/gl'
Making install in lib/gl
make[1]: Entering directory `/home/milchstore/source/libidn-0.6.14/lib/gl'
make install-am
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/lib/gl'
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/lib/gl'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/lib/gl'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/lib/gl'
make[1]: Leaving directory `/home/milchstore/source/libidn-0.6.14/lib/gl'
Making install in lib
make[1]: Entering directory `/home/milchstore/source/libidn-0.6.14/lib'
make install-am
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/lib'
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/lib'
test -z "/home/milchstore/php5/lib" || /bin/mkdir -p "/home/milchstore/php5/lib"
/bin/sh ../libtool --mode=install /usr/bin/install -c 'libidn.la' '/home/milchstore/php5/lib/libidn.la'
/usr/bin/install -c .libs/libidn.so.11.5.28 /home/milchstore/php5/lib/libidn.so.11.5.28
(cd /home/milchstore/php5/lib && { ln -s -f libidn.so.11.5.28 libidn.so.11 || {
```

```
(cd /home/milchstore/php5/lib && { ln -s -f libidn.so.11.5.28 libidn.so || { rm
-f libidn.so && ln -s libidn.so.11.5.28 libidn.so; }; })
/usr/bin/install -c .libs/libidn.lai /home/milchstore/php5/lib/libidn.la
/usr/bin/install -c .libs/libidn.a /home/milchstore/php5/lib/libidn.a
chmod 644 /home/milchstore/php5/lib/libidn.a
ranlib /home/milchstore/php5/lib/libidn.a
PATH="$PATH:/sbin" ldconfig -n /home/milchstore/php5/lib
```

```
-----
Libraries have been installed in:
  /home/milchstore/php5/lib
```

If you ever happen to want to link against installed libraries in a given directory, LIBDIR, you must either use libtool, and specify the full pathname of the library, or use the `-LLIBDIR` flag during linking and do at least one of the following:

- add LIBDIR to the `'LD_LIBRARY_PATH'` environment variable during execution
- add LIBDIR to the `'LD_RUN_PATH'` environment variable during linking
- use the `'-Wl,--rpath -Wl,LIBDIR'` linker flag
- have your system administrator add LIBDIR to `'/etc/ld.so.conf'`

See any operating system documentation about shared libraries for more information, such as the `ld(1)` and `ld.so(8)` manual pages.

```
-----
test -z "/home/milchstore/php5/include" || /bin/mkdir -p "/home/milchstore/php5/include"
/usr/bin/install -c -m 644 'stringprep.h' '/home/milchstore/php5/include/stringprep.h'
/usr/bin/install -c -m 644 'idna.h' '/home/milchstore/php5/include/idna.h'
/usr/bin/install -c -m 644 'punycode.h' '/home/milchstore/php5/include/punycode.h'
/usr/bin/install -c -m 644 'idn-free.h' '/home/milchstore/php5/include/idn-free.h'
/usr/bin/install -c -m 644 'pr29.h' '/home/milchstore/php5/include/pr29.h'
/usr/bin/install -c -m 644 'tld.h' '/home/milchstore/php5/include/tld.h'
test -z "/home/milchstore/php5/include" || /bin/mkdir -p "/home/milchstore/php5/include"
/usr/bin/install -c -m 644 'idn-int.h' '/home/milchstore/php5/include/idn-int.h'
,
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/lib'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/lib'
make[1]: Leaving directory `/home/milchstore/source/libidn-0.6.14/lib'
Making install in po
make[1]: Entering directory `/home/milchstore/source/libidn-0.6.14/po'
/bin/mkdir -p /home/milchstore/php5/share
installing en@boldquot.gmo as /home/milchstore/php5/share/locale/en@boldquot/LC_MESSAGES/libidn.mo
installing en@quot.gmo as /home/milchstore/php5/share/locale/en@quot/LC_MESSAGES/libidn.mo
```

```

installing de.gmo as /home/milchstore/php5/share/locale/de/LC_MESSAGES/libidn.mo
installing eo.gmo as /home/milchstore/php5/share/locale/eo/LC_MESSAGES/libidn.mo
installing fr.gmo as /home/milchstore/php5/share/locale/fr/LC_MESSAGES/libidn.mo
installing it.gmo as /home/milchstore/php5/share/locale/it/LC_MESSAGES/libidn.mo
installing ja.gmo as /home/milchstore/php5/share/locale/ja/LC_MESSAGES/libidn.mo
installing nl.gmo as /home/milchstore/php5/share/locale/nl/LC_MESSAGES/libidn.mo
installing pl.gmo as /home/milchstore/php5/share/locale/pl/LC_MESSAGES/libidn.mo
installing ro.gmo as /home/milchstore/php5/share/locale/ro/LC_MESSAGES/libidn.mo
installing rw.gmo as /home/milchstore/php5/share/locale/rw/LC_MESSAGES/libidn.mo
installing sr.gmo as /home/milchstore/php5/share/locale/sr/LC_MESSAGES/libidn.mo
installing vi.gmo as /home/milchstore/php5/share/locale/vi/LC_MESSAGES/libidn.mo
installing zh_CN.gmo as /home/milchstore/php5/share/locale/zh_CN/LC_MESSAGES/libidn.mo
installing sv.gmo as /home/milchstore/php5/share/locale/sv/LC_MESSAGES/libidn.mo
if test "libidn" = "gettext-tools"; then \
    /bin/mkdir -p /home/milchstore/php5/share/gettext/po; \
    for file in Makefile.in.in remove-potcdate.sin quot.sed boldquot.sed en@quot.header en@boldquot.header insert-header.sin Rules-quot Makevars.template; do \
        /usr/bin/install -c -m 644 ./\$file \
            /home/milchstore/php5/share/gettext/po/\$file; \
    done; \
    for file in Makevars; do \
        rm -f /home/milchstore/php5/share/gettext/po/\$file; \
    done; \
else \
    : ; \
fi
make[1]: Leaving directory `/home/milchstore/source/libidn-0.6.14/po'
Making install in src
make[1]: Entering directory `/home/milchstore/source/libidn-0.6.14/src'
make install-am
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/src'
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/src'
test -z "/home/milchstore/php5/bin" || /bin/mkdir -p "/home/milchstore/php5/bin"
  /bin/sh ../libtool --mode=install /usr/bin/install -c 'idn' '/home/milchstore/php5/bin/idn'
/usr/bin/install -c .libs/idn /home/milchstore/php5/bin/idn
test -z "/home/milchstore/php5/share/emacs/site-lisp" || /bin/mkdir -p "/home/milchstore/php5/share/emacs/site-lisp"
  /usr/bin/install -c -m 644 'punycode.el' '/home/milchstore/php5/share/emacs/site-lisp/punycode.el'
  /usr/bin/install -c -m 644 'idna.el' '/home/milchstore/php5/share/emacs/site-lisp/idna.el'
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/src'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/src'
make[1]: Leaving directory `/home/milchstore/source/libidn-0.6.14/src'
Making install in doc
make[1]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc'
make install-recursive

```


Making install in specifications

```
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc/specifications'
```

```
make[4]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc/specifications'
```

```
make[4]: Nothing to be done for `install-exec-am'.
```

```
make[4]: Nothing to be done for `install-data-am'.
```

```
make[4]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc/specifications'
```

```
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc/specifications'
```

Making install in tld

```
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc/tld'
```

```
make[4]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc/tld'
```

```
make[4]: Nothing to be done for `install-exec-am'.
```

```
make[4]: Nothing to be done for `install-data-am'.
```

```
make[4]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc/tld'
```

```
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc/tld'
```

Making install in java

```
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc/java'
```

```
make[4]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc/java'
```

```
make[4]: Nothing to be done for `install-exec-am'.
```

```
make[4]: Nothing to be done for `install-data-am'.
```

```
make[4]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc/java'
```

```
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc/java'
```

```
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc'
```

```
make[4]: Entering directory `/home/milchstore/source/libidn-0.6.14/doc'
```

```
make[4]: Nothing to be done for `install-exec-am'.
```

```
test -z "/home/milchstore/php5/share/info" || /bin/mkdir -p "/home/milchstore/php5/share/info"
```

```
 /usr/bin/install -c -m 644 'libidn-components.png' '/home/milchstore/php5/share/info/libidn-components.png'
```

```
test -z "/home/milchstore/php5/share/info" || /bin/mkdir -p "/home/milchstore/php5/share/info"
```

```
 /usr/bin/install -c -m 644 './libidn.info' '/home/milchstore/php5/share/info/libidn.info'
```

```
test -z "/home/milchstore/php5/share/man/man1" || /bin/mkdir -p "/home/milchstore/php5/share/man/man1"
```

```
 /usr/bin/install -c -m 644 './idn.1' '/home/milchstore/php5/share/man/man1/idn.1'
```

```
test -z "/home/milchstore/php5/share/man/man3" || /bin/mkdir -p "/home/milchstore/php5/share/man/man3"
```

```
 /usr/bin/install -c -m 644 './man/idna_to_ascii_4i.3' '/home/milchstore/php5/share/man/man3/idna_to_ascii_4i.3'
```

```
 /usr/bin/install -c -m 644 './man/idna_to_unicode_44i.3' '/home/milchstore/php5/share/man/man3/idna_to_unicode_44i.3'
```

```
 /usr/bin/install -c -m 644 './man/idna_to_ascii_4z.3' '/home/milchstore/php5/share/man/man3/idna_to_ascii_4z.3'
```

```
 /usr/bin/install -c -m 644 './man/idna_to_ascii_8z.3' '/home/milchstore/php5/share/man/man3/idna_to_ascii_8z.3'
```

```
are/man/man3/idna_to_ascii_lz.3'  
/usr/bin/install -c -m 644 './man/idna_to_unicode_4z4z.3' '/home/milchstore/php  
5/share/man/man3/idna_to_unicode_4z4z.3'  
/usr/bin/install -c -m 644 './man/idna_to_unicode_8z4z.3' '/home/milchstore/php  
5/share/man/man3/idna_to_unicode_8z4z.3'  
/usr/bin/install -c -m 644 './man/idna_to_unicode_8z8z.3' '/home/milchstore/php  
5/share/man/man3/idna_to_unicode_8z8z.3'  
/usr/bin/install -c -m 644 './man/idna_to_unicode_8zlj.3' '/home/milchstore/php  
5/share/man/man3/idna_to_unicode_8zlj.3'  
/usr/bin/install -c -m 644 './man/idna_to_unicode_lzlj.3' '/home/milchstore/php  
5/share/man/man3/idna_to_unicode_lzlj.3'  
/usr/bin/install -c -m 644 './man/stringprep_utf8_to_unichar.3' '/home/milchsto  
re/php5/share/man/man3/stringprep_utf8_to_unichar.3'  
/usr/bin/install -c -m 644 './man/stringprep_unichar_to_utf8.3' '/home/milchsto  
re/php5/share/man/man3/stringprep_unichar_to_utf8.3'  
/usr/bin/install -c -m 644 './man/stringprep_utf8_to_ucs4.3' '/home/milchstore/  
php5/share/man/man3/stringprep_utf8_to_ucs4.3'  
/usr/bin/install -c -m 644 './man/stringprep_ucs4_to_utf8.3' '/home/milchstore/  
php5/share/man/man3/stringprep_ucs4_to_utf8.3'  
/usr/bin/install -c -m 644 './man/stringprep_utf8_nfkc_normalize.3' '/home/milc  
hstore/php5/share/man/man3/stringprep_utf8_nfkc_normalize.3'  
/usr/bin/install -c -m 644 './man/stringprep_ucs4_nfkc_normalize.3' '/home/milc  
hstore/php5/share/man/man3/stringprep_ucs4_nfkc_normalize.3'  
/usr/bin/install -c -m 644 './man/pr29_4.3' '/home/milchstore/php5/share/man/ma  
n3/pr29_4.3'  
/usr/bin/install -c -m 644 './man/pr29_4z.3' '/home/milchstore/php5/share/man/m  
an3/pr29_4z.3'  
/usr/bin/install -c -m 644 './man/pr29_8z.3' '/home/milchstore/php5/share/man/m  
an3/pr29_8z.3'  
/usr/bin/install -c -m 644 './man/punycode_encode.3' '/home/milchstore/php5/sha  
re/man/man3/punycode_encode.3'  
/usr/bin/install -c -m 644 './man/punycode_decode.3' '/home/milchstore/php5/sha  
re/man/man3/punycode_decode.3'  
/usr/bin/install -c -m 644 './man/stringprep_4i.3' '/home/milchstore/php5/share  
/man/man3/stringprep_4i.3'  
/usr/bin/install -c -m 644 './man/stringprep_4zi.3' '/home/milchstore/php5/shar  
e/man/man3/stringprep_4zi.3'  
/usr/bin/install -c -m 644 './man/stringprep.3' '/home/milchstore/php5/share/ma  
n/man3/stringprep.3'  
/usr/bin/install -c -m 644 './man/stringprep_profile.3' '/home/milchstore/php5/  
share/man/man3/stringprep_profile.3'  
/usr/bin/install -c -m 644 './man/tld_get_table.3' '/home/milchstore/php5/share  
/man/man3/tld_get_table.3'  
/usr/bin/install -c -m 644 './man/tld_default_table.3' '/home/milchstore/php5/s  
hare/man/man3/tld_default_table.3'  
/usr/bin/install -c -m 644 './man/tld_get_4.3' '/home/milchstore/php5/share/man  
/man3/tld_get_4.3'  
/usr/bin/install -c -m 644 './man/tld_get_4z.3' '/home/milchstore/php5/share/ma  
n/man3/tld_get_4z.3'  
/usr/bin/install -c -m 644 './man/tld_get_z.3' '/home/milchstore/php5/share/man
```

```
/usr/bin/install -c -m 644 './man/tld_check_4t.3' '/home/milchstore/php5/share/
man/man3/tld_check_4t.3'
/usr/bin/install -c -m 644 './man/tld_check_4tz.3' '/home/milchstore/php5/share
/man/man3/tld_check_4tz.3'
/usr/bin/install -c -m 644 './man/tld_check_4.3' '/home/milchstore/php5/share/m
an/man3/tld_check_4.3'
/usr/bin/install -c -m 644 './man/tld_check_4z.3' '/home/milchstore/php5/share/
man/man3/tld_check_4z.3'
/usr/bin/install -c -m 644 './man/tld_check_8z.3' '/home/milchstore/php5/share/
man/man3/tld_check_8z.3'
/usr/bin/install -c -m 644 './man/tld_check_lz.3' '/home/milchstore/php5/share/
man/man3/tld_check_lz.3'
/usr/bin/install -c -m 644 './man/stringprep_locale_charset.3' '/home/milchstor
e/php5/share/man/man3/stringprep_locale_charset.3'
/usr/bin/install -c -m 644 './man/stringprep_convert.3' '/home/milchstore/php5/
share/man/man3/stringprep_convert.3'
/usr/bin/install -c -m 644 './man/stringprep_locale_to_utf8.3' '/home/milchstor
e/php5/share/man/man3/stringprep_locale_to_utf8.3'
/usr/bin/install -c -m 644 './man/stringprep_utf8_to_locale.3' '/home/milchstor
e/php5/share/man/man3/stringprep_utf8_to_locale.3'
/usr/bin/install -c -m 644 './man/stringprep_check_version.3' '/home/milchstore
/php5/share/man/man3/stringprep_check_version.3'
/usr/bin/install -c -m 644 './man/idna_strerror.3' '/home/milchstore/php5/share
/man/man3/idna_strerror.3'
/usr/bin/install -c -m 644 './man/pr29_strerror.3' '/home/milchstore/php5/share
/man/man3/pr29_strerror.3'
/usr/bin/install -c -m 644 './man/punycode_strerror.3' '/home/milchstore/php5/s
hare/man/man3/punycode_strerror.3'
/usr/bin/install -c -m 644 './man/stringprep_strerror.3' '/home/milchstore/php5
/share/man/man3/stringprep_strerror.3'
/usr/bin/install -c -m 644 './man/tld_strerror.3' '/home/milchstore/php5/share/
man/man3/tld_strerror.3'
make[4]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc'
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc'
make[1]: Leaving directory `/home/milchstore/source/libidn-0.6.14/doc'
Making install in tests
make[1]: Entering directory `/home/milchstore/source/libidn-0.6.14/tests'
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/tests'
make[2]: Nothing to be done for `install-exec-am'.
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/tests'
make[1]: Leaving directory `/home/milchstore/source/libidn-0.6.14/tests'
Making install in examples
make[1]: Entering directory `/home/milchstore/source/libidn-0.6.14/examples'
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/examples'
make[2]: Nothing to be done for `install-exec-am'.
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/examples'
make[1]: Leaving directory `/home/milchstore/source/libidn-0.6.14/examples'
```

```
make[1]: Entering directory `/home/milchstore/source/libidn-0.6.14/java'
Making install in gnu
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/gnu'
Making install in inet
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet
'
Making install in encoding
make[4]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet
/encoding'
make[5]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet
/encoding'
make[5]: Nothing to be done for `install-exec-am'.
make[5]: Nothing to be done for `install-data-am'.
make[5]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet/
encoding'
make[4]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet/
encoding'
make[4]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet
'
make[5]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet
'
make[5]: Nothing to be done for `install-exec-am'.
make[5]: Nothing to be done for `install-data-am'.
make[5]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet'
make[4]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet'
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/gnu/inet'
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/gnu'
make[4]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/gnu'
make[4]: Nothing to be done for `install-exec-am'.
make[4]: Nothing to be done for `install-data-am'.
make[4]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/gnu'
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/gnu'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/gnu'
Making install in .
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/java'
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/java'
make[3]: Nothing to be done for `install-exec-am'.
test -z "" || /bin/mkdir -p ""
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java'
Making install in misc
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/misc'
make[3]: Entering directory `/home/milchstore/source/libidn-0.6.14/java/misc'
make[3]: Nothing to be done for `install-exec-am'.
make[3]: Nothing to be done for `install-data-am'.
make[3]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/misc'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java/misc'
make[1]: Leaving directory `/home/milchstore/source/libidn-0.6.14/java'
Making install in csharp
make[1]: Entering directory `/home/milchstore/source/libidn-0.6.14/csharp'
```

```
make[2]: Nothing to be done for `install-exec-am'.
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14/csharp'
make[1]: Leaving directory `/home/milchstore/source/libidn-0.6.14/csharp'
make[1]: Entering directory `/home/milchstore/source/libidn-0.6.14'
make[2]: Entering directory `/home/milchstore/source/libidn-0.6.14'
make[2]: Nothing to be done for `install-exec-am'.
test -z "/home/milchstore/php5/lib/pkgconfig" || /bin/mkdir -p "/home/milchstore
/php5/lib/pkgconfig"
  /usr/bin/install -c -m 644 'libidn.pc' '/home/milchstore/php5/lib/pkgconfig/lib
idn.pc'
make[2]: Leaving directory `/home/milchstore/source/libidn-0.6.14'
make[1]: Leaving directory `/home/milchstore/source/libidn-0.6.14'
make sslnopwd
make[1]: Entering directory `/home/milchstore/source/imap-2004g'
+++++
+ Building in full compliance with RFC 3501 security
+ requirements:
++ TLS/SSL encryption is supported
++ Unencrypted plaintext passwords are prohibited
+++++
make[1]: Leaving directory `/home/milchstore/source/imap-2004g'
Applying an process to sources...
tools/an "ln -s" src/c-client c-client
tools/an "ln -s" src/ansilib c-client
tools/an "ln -s" src/charset c-client
tools/an "ln -s" src/osdep/unix c-client
tools/an "ln -s" src/mtest mtest
tools/an "ln -s" src/ipopd ipopd
tools/an "ln -s" src/imapd imapd
tools/an "ln -s" src/mailutil mailutil
tools/an "ln -s" src/mlock mlock
tools/an "ln -s" src/dmail dmail
tools/an "ln -s" src/tmail tmail
ln -s tools/an .
make build EXTRACFLAGS='' EXTRALDFLAGS='' EXTRADRIVERS='mbox' EXTRAAUTHENTICATOR
S='' PASSWDTYPE=std SSLTYPE=nopwd IP=4 EXTRASPECIALS='' BUILDTYPE=lnp \
    SPECIALS="GSSDIR=/usr SSLDIR=/usr SSLINCLUDE=/usr/include/openssl SSLCER
TS=/etc/ssl/certs SSLKEYS=/etc/ssl/private LOCKPGM=/usr/sbin/mlock"
make[1]: Entering directory `/home/milchstore/source/imap-2004g'
Building c-client for lnp...
echo `cat SPECIALS` > c-client/SPECIALS
cd c-client;make lnp EXTRACFLAGS='' \
    EXTRALDFLAGS='' \
    EXTRADRIVERS='mbox' \
    EXTRAAUTHENTICATORS='' \
    PASSWDTYPE=std SSLTYPE=nopwd IP=4 \
    GSSDIR=/usr SSLDIR=/usr SSLINCLUDE=/usr/include/openssl SSLCERTS=/etc/s
ssl/certs SSLKEYS=/etc/ssl/private LOCKPGM=/usr/sbin/mlock
make[2]: Entering directory `/home/milchstore/source/imap-2004g/c-client'
```

```

S='' PASSWDTYPE=std SSLTYPE=nopwd IP=4 `cat SPECIALS` OS=lnx \
    SIGTYPE=psx CHECKPW=pam CRXTYPE=nfs \
    SPOOLDIR=/var/spool \
    ACTIVEFILE=/var/lib/news/active \
    RSHPATH=/usr/bin/rsh \
    BASECFLAGS="-g -fno-omit-frame-pointer -O2" \
    BASELDFLAGS="-lpam -ldl"
make[3]: Entering directory `/home/milchstore/source/imap-2004g/c-client'
sh -c 'rm -rf auths.c crexcl.c nfstest.c linkage.[ch] siglocal.c osdep*.[ch] *.o
ARCHIVE *FLAGS *TYPE c-client.a || true'
Once-only environment setup...
echo cc > CCTYPE
echo -g -fno-omit-frame-pointer -O2 '' > CFLAGS
echo -DCREATEPROTO=unixproto -DEMPTYPROTO=unixproto \
    -DMAILSPOOL="/var/spool/mail\" \
    -DANONYMOUSHOME="/var/spool/mail/anonymous\" \
    -DACTIVEFILE="/var/lib/news/active\" -DNEWSSPOOL="/var/spool/news\" \
    -DRSHPATH="/usr/bin/rsh\" -DLOCKPGM="/usr/sbin/mlock\" > OSCFLAGS
echo -lpam -ldl > LDFLAGS
echo "ar rc c-client.a osdep.o mail.o misc.o newsrc.o smanager.o utf8.o siglocal
.o dummy.o pseudo.o netmsg.o flstring.o fdstring.o rfc822.o nntp.o smtp.o imap4r
1.o pop3.o unix.o mbx.o mmdf.o tenex.o mtz.o news.o phile.o mh.o mx.o;ranlib c-c
lient.a" > ARCHIVE
echo lnx > OSTYPE
./drivers mbox imap nntp pop3 mh mx mbx tenex mtz mmdf unix news phile dummy
./mkauths md5 pla log
make[4]: Entering directory `/home/milchstore/source/imap-2004g/c-client'
echo -DMD5ENABLE="/etc/cram-md5.pwd\" >> OSCFLAGS
make[4]: Leaving directory `/home/milchstore/source/imap-2004g/c-client'
ln -s os_lnx.h osdep.h
ln -s os_lnx.c osdepbas.c
ln -s log_std.c osdeplog.c
ln -s sig_psx.c siglocal.c
ln -s crx_nfs.c crexcl.c
ln -s ip4_unix.c ip_unix.c
sh -c '(test -f /usr/include/sys/statvfs.h -a lnx != sc5 -a lnx != sco) && ln -s
nfstnew.c nfstest.c || ln -s nfstold.c nfstest.c'
Standard password authentication
ln -s ckp_pam.c osdepckp.c
Building with SSL
ln -s ssl_unix.c osdepssl.c
echo -I/usr/include/openssl -I/usr/include/openssl/openssl -DSSL_CERT_DIRECTORY=
"/etc/ssl/certs\" -DSSL_KEY_DIRECTORY="/etc/ssl/private\" >> OSCFLAGS
echo " ssl_onceonlyinit ();" >> linkage.c
echo -L/usr/lib -lssl -lcrypto >> LDFLAGS
Building with SSL and plaintext passwords disabled unless SSL/TLS
echo " mail_parameters (NIL,SET_DISABLEPLAINTEXT,(void *) 2);" >> linkage.c
cat osdepbas.c osdepckp.c osdeplog.c osdepssl.c > osdep.c
Building OS-dependent module
If you get No such file error messages for files x509.h, ssl.h,

```

```
is not installed on your system. Either install OpenSSL first
or build with command: make lnx SSLTYPE=none
`cat CCTYPE` -c `cat CFLAGS` `cat OSCFLAGS` -c osdep.c
In file included from osdep.c:41:
env_unix.c: In function 'mm_blocknotify':
env_unix.c:1631: warning: cast to pointer from integer of different size
env_unix.c:1634: warning: cast from pointer to integer of different size
env_unix.c:1634: warning: cast from pointer to integer of different size
osdep.c:230:18: error: x509.h: No such file or directory
osdep.c:231:17: error: ssl.h: No such file or directory
osdep.c:233:17: error: pem.h: No such file or directory
osdep.c:234:20: error: buffer.h: No such file or directory
osdep.c:235:17: error: bio.h: No such file or directory
osdep.c:236:20: error: crypto.h: No such file or directory
osdep.c:237:18: error: rand.h: No such file or directory
osdep.c: At top level:
osdep.c:248: error: expected specifier-qualifier-list before 'SSL_CTX'
osdep.c:261: error: expected declaration specifiers or '...' before 'X509_STORE_
CTX'
osdep.c:265: error: expected '=', ',', ';', 'asm' or '__attribute__' before '*'
token
osdep.c: In function 'ssl_start_work':
osdep.c:411: error: 'BIO' undeclared (first use in this function)
osdep.c:411: error: (Each undeclared identifier is reported only once
osdep.c:411: error: for each function it appears in.)
osdep.c:411: error: 'bio' undeclared (first use in this function)
osdep.c:412: error: 'X509' undeclared (first use in this function)
osdep.c:412: error: 'cert' undeclared (first use in this function)
osdep.c:418: error: 'SSLSTREAM' has no member named 'context'
osdep.c:422: error: 'SSLSTREAM' has no member named 'context'
osdep.c:425: error: 'SSLSTREAM' has no member named 'context'
osdep.c:425: error: 'SSL_VERIFY_NONE' undeclared (first use in this function)
osdep.c:426: error: 'SSLSTREAM' has no member named 'context'
osdep.c:426: error: 'SSL_VERIFY_PEER' undeclared (first use in this function)
osdep.c:428: error: 'SSLSTREAM' has no member named 'context'
osdep.c:430: error: 'SSLSTREAM' has no member named 'con'
osdep.c:430: error: 'SSL' undeclared (first use in this function)
osdep.c:430: error: expected expression before ')' token
osdep.c:432: error: 'BIO_NOCLOSE' undeclared (first use in this function)
osdep.c:433: error: 'SSLSTREAM' has no member named 'con'
osdep.c:434: error: 'SSLSTREAM' has no member named 'con'
osdep.c:435: error: 'SSLSTREAM' has no member named 'con'
osdep.c:435: error: 'SSLSTREAM' has no member named 'con'
osdep.c:437: error: 'SSLSTREAM' has no member named 'con'
osdep.c:442: error: 'SSLSTREAM' has no member named 'con'
osdep.c: At top level:
osdep.c:467: error: expected declaration specifiers or '...' before 'X509_STORE_
CTX'
osdep.c: In function 'ssl_open_verify':
osdep.c:474: error: 'ctx' undeclared (first use in this function)
```

```
osdep.c: In function 'ssl_getline':
osdep.c:536: error: 'SSLSTREAM' has no member named 'iptr'
osdep.c:538: error: 'SSLSTREAM' has no member named 'ictr'
osdep.c:539: error: 'SSLSTREAM' has no member named 'iptr'
osdep.c:554: error: 'SSLSTREAM' has no member named 'iptr'
osdep.c:555: error: 'SSLSTREAM' has no member named 'iptr'
osdep.c:556: error: 'SSLSTREAM' has no member named 'ictr'
osdep.c: In function 'ssl_getbuffer':
osdep.c:583: error: 'SSLSTREAM' has no member named 'ictr'
osdep.c:585: error: 'SSLSTREAM' has no member named 'iptr'
osdep.c:587: error: 'SSLSTREAM' has no member named 'iptr'
osdep.c:589: error: 'SSLSTREAM' has no member named 'ictr'
osdep.c: In function 'ssl_getdata':
osdep.c:609: error: 'SSLSTREAM' has no member named 'con'
osdep.c:609: error: 'SSLSTREAM' has no member named 'con'
osdep.c:611: error: 'SSLSTREAM' has no member named 'ictr'
osdep.c:612: error: 'SSLSTREAM' has no member named 'con'
osdep.c:634: error: 'SSLSTREAM' has no member named 'con'
osdep.c:634: error: 'SSLSTREAM' has no member named 'ibuf'
osdep.c:636: error: 'SSLSTREAM' has no member named 'con'
osdep.c:636: error: 'SSL_ERROR_WANT_READ' undeclared (first use in this function
)
osdep.c:638: error: 'SSLSTREAM' has no member named 'iptr'
osdep.c:638: error: 'SSLSTREAM' has no member named 'ibuf'
osdep.c:639: error: 'SSLSTREAM' has no member named 'ictr'
osdep.c: In function 'ssl_sout':
osdep.c:668: error: 'SSLSTREAM' has no member named 'con'
osdep.c:673: error: 'SSLSTREAM' has no member named 'con'
osdep.c: In function 'ssl_abort':
osdep.c:698: error: 'SSLSTREAM' has no member named 'con'
osdep.c:699: error: 'SSLSTREAM' has no member named 'con'
osdep.c:700: error: 'SSLSTREAM' has no member named 'con'
osdep.c:701: error: 'SSLSTREAM' has no member named 'con'
osdep.c:703: error: 'SSLSTREAM' has no member named 'context'
osdep.c:704: error: 'SSLSTREAM' has no member named 'context'
osdep.c:705: error: 'SSLSTREAM' has no member named 'context'
osdep.c: In function 'ssl_server_init':
osdep.c:805: error: 'SSLSTREAM' has no member named 'context'
osdep.c:811: error: 'SSLSTREAM' has no member named 'context'
osdep.c:811: error: 'SSL_OP_ALL' undeclared (first use in this function)
osdep.c:813: error: 'SSLSTREAM' has no member named 'context'
osdep.c:817: error: 'SSLSTREAM' has no member named 'context'
osdep.c:821: error: 'SSLSTREAM' has no member named 'context'
osdep.c:822: error: 'SSL_FILETYPE_PEM' undeclared (first use in this function)
osdep.c:827: error: 'SSLSTREAM' has no member named 'context'
osdep.c:828: error: 'SSLSTREAM' has no member named 'context'
osdep.c:828: error: 'ssl_genkey' undeclared (first use in this function)
osdep.c:830: error: 'SSLSTREAM' has no member named 'con'
osdep.c:830: error: 'SSLSTREAM' has no member named 'context'
osdep.c:834: error: 'SSLSTREAM' has no member named 'con'
```



```
osdep.c: At top level:
osdep.c:869: error: expected '=', ',', ';', 'asm' or '__attribute__' before '*'
token
osdep.c: In function 'ssl_server_input_wait':
osdep.c:899: error: 'SSLSTREAM' has no member named 'ictr'
osdep.c:900: error: 'SSLSTREAM' has no member named 'con'
osdep.c:900: error: 'SSLSTREAM' has no member named 'con'
osdep.c:902: error: 'SSLSTREAM' has no member named 'con'
osdep.c:903: error: 'SSLSTREAM' has no member named 'con'
osdep.c:903: error: 'SSLSTREAM' has no member named 'ibuf'
osdep.c:904: error: 'SSLSTREAM' has no member named 'iptr'
osdep.c:904: error: 'SSLSTREAM' has no member named 'ibuf'
osdep.c:905: error: 'SSLSTREAM' has no member named 'ictr'
In file included from osdep.c:917:
sslstdio.c: In function 'PBIN':
sslstdio.c:30: error: 'SSLSTREAM' has no member named 'ictr'
sslstdio.c:31: error: 'SSLSTREAM' has no member named 'iptr'
sslstdio.c: In function 'PSIN':
sslstdio.c:49: error: 'SSLSTREAM' has no member named 'ictr'
sslstdio.c:50: error: 'SSLSTREAM' has no member named 'ictr'
sslstdio.c:52: error: 'SSLSTREAM' has no member named 'iptr'
make[3]: *** [osdep.o] Error 1
make[3]: Leaving directory `/home/milchstore/source/imap-2004g/c-client'
make[2]: *** [lnp] Error 2
make[2]: Leaving directory `/home/milchstore/source/imap-2004g/c-client'
make[1]: *** [OSTYPE] Error 2
make[1]: Leaving directory `/home/milchstore/source/imap-2004g'
make: *** [ldb] Error 2
[colts]$
```